

# setNum()

Stores a Float value in the Table's specified row and column. The row is specified by its ID, while the column may be specified by either its ID or title.

## Examples

```
// Given the CSV file "mammals.csv"
// in the project's "assets" folder:
//
// id,species,name
// 0,Capra hircus,Goat
// 1,Panthera pardus,Leopard
// 2,Equus zebra,Zebra

let table;

function preload() {
  //my table is comma separated value "csv"
  //and has a header specifying the columns labels
  table = loadTable('/assets/mammals.csv', 'csv', 'header');
}

function setup() {
  table.setNum(1, 'id', 1);

  print(table.getColumn(0));
  //["0", 1, "2"]

  describe('no image displayed');
}
```

## Syntax

```
setNum(row, column, value)
```

## Parameters

row	Integer: row ID
column	String Integer: column ID (Number) or title (String)
value	Number: value to assign

This page is generated from the comments in [src/io/p5.Table.js](#) . Please feel free to edit it and submit a pull request!

## Related References

### addColumn

Use `addColumn()` to add a new column to a `Table` object.

### addRow

Use `addRow()` to add a new row of data to a `p5.Table` object.

### clearRows

Removes all rows from a `Table`.

### columns

An array containing the names of the columns in the table, if the "header" the table is loaded with the "header" parameter.

### p5.js

### Resources

Reference  
Tutorials  
Examples  
Contribute  
Community  
About  
Start Coding  
Donate

### Information

Download  
Contact  
Copyright  
Privacy Policy  
Terms of Use

### Socials

GitHub ↗  
Instagram ↗  
X ↗  
YouTube ↗  
Discord ↗  
Forum ↗

