p5*js

Reference
Tutorials
Examples
Contribute
Community
About

</> Start Coding

♡ Donate

🌐 English ∨

Accessibility ∨

🔍 Search

hasClass()

Checks if a class is already applied to element.

Examples

```
let div;

function setup() {
  createCanvas(100, 100);

  background(200);

  // Create a div element.
  div = createDiv('div');

  // Add the class 'show' to the div.
  div.addClass('show');

  describe('A gray square.');
}

// Toggle the class 'show' when the mouse is pressed.
function mousePressed() {
  if (div.hasClass('show')) {
    div.addClass('show');
  } else {
    div.removeClass('show');
  }
}
```

Syntax

```
hasClass(c)
```

Parameters

c   String: name of class to check.

Returns

Boolean: a boolean value if element has specified class.

This page is generated from the comments in src/dom/dom.js . Please feel free to edit it and submit a pull request!

Related References

addClass
Adds a class to the element.

attribute
Adds an attribute to the element.

center
Centers the element either vertically, horizontally, or both.

child
Attaches the element as a child of another element.

p5.js

Resources
Reference
Tutorials
Examples
Contribute
Community
About
Start Coding
Donate

Information
Download
Contact
Copyright
Privacy Policy
Terms of Use

Socials
GitHub ↗
Instagram ↗
X ↗
YouTube ↗
Discord ↗
Forum ↗

Donate Today! Support p5.js and the Processing Foundation.   ✕