


# shininess()

Sets the amount of gloss ("shininess") of a `specularMaterial()`.

Shiny materials focus reflected light more than dull materials. `shininess()` affects the way materials reflect light sources including `directionalLight()`, `pointLight()`, and `spotLight()`.

The parameter, `shine`, is a number that sets the amount of shininess. `shine` must be greater than 1, which is its default value.

## Examples



```
function setup() {
  createCanvas(100, 100, WEBGL);

  describe(
    'Two red spheres drawn on a gray background. White light reflects from their surfaces as the mouse moves. The right sphere is shinier than the left sphere.'
  );
}

function draw() {
  background(200);

  // Turn on a red ambient light.
  ambientLight(255, 0, 0);


  // Get the mouse's coordinates.
  let mx = mouseX - 50;
  let my = mouseY - 50;

  // Turn on a white point light that follows the mouse.
  pointLight(255, 255, 255, mx, my, 50);

  // Style the sphere.
  noStroke();

  // Add a specular material with a grayscale value.
  specularMaterial(255);

  // Draw the left sphere with low shininess.
}
```



## Syntax

`shininess(shine)`



## Parameters

`shine` Number: amount of shine.

This page is generated from the comments in `src/webgl/material.js`. Please feel free to edit it and submit a pull request!

## Related References

### copyToContext

Copies the shader from one drawing context to another.

### inspectHooks

Logs the hooks available in this shader, and their current implementation.

### modify

Returns a new shader, based on the original, but with custom snippets of shader code replacing default behaviour.

### setUniform

Sets the shader's uniform (global) variables.

p5.js

Resources

Reference  
Tutorials  
Examples  
Contribute  
Community  
About

Start Coding

Donate

Information

Download  
Contact  
Copyright  
Privacy Policy  
Terms of Use

Socials

GitHub ↗  
Instagram ↗  
X ↗  
YouTube ↗  
Discord ↗  
Forum ↗

