

getString()

Retrieves a String value from the Table's specified row and column. The row is specified by its ID, while the column may be specified by either its ID or title.

Examples

```
// Given the CSV file "mammals.csv"
// in the project's "assets" folder:
//
// id,species,name
// 0,Capra hircus,Goat
// 1,Panthera pardus,Leopard
// 2,Equus zebra,Zebra

let table;

function preload() {
  // table is comma separated value "CSV"
  // and has specifying header for column labels
  table = loadTable('/assets/mammals.csv', 'csv', 'header');
}

function setup() {
  print(table.getString(0, 0)); // 0
  print(table.getString(0, 1)); // Capra hircus
  print(table.getString(0, 2)); // Goat
  print(table.getString(1, 0)); // 1
  print(table.getString(1, 1)); // Panthera pardus
  print(table.getString(1, 2)); // Leopard
  print(table.getString(2, 0)); // 2
  print(table.getString(2, 1)); // Equus zebra
}
```

Syntax

```
getString(row, column)
```

Parameters

row	Integer: row ID
column	String Integer: columnName (string) or ID (number)

Returns

String:

This page is generated from the comments in [src/io/p5.Table.js](#) . Please feel free to edit it and submit a pull request!

Related References

addColumn

Use `addColumn()` to add a new column to a Table object.

addRow

Use `addRow()` to add a new row of data to a p5.Table object.

clearRows

Removes all rows from a Table.

columns

An array containing the names of the columns in the table, if the "header" the table is loaded with the "header" parameter.

p5.js

Resources

Reference
Tutorials
Examples
Contribute
Community
About
Start Coding
Donate

Information

Download
Contact
Copyright
Privacy Policy
Terms of Use

Socials

GitHub ↗
Instagram ↗
X ↗
YouTube ↗
Discord ↗
Forum ↗

