

removeTokens()

Removes any of the specified characters (or "tokens").

If no column is specified, then the values in all columns and rows are processed. A specific column may be referenced by either its ID or title.

Examples

```
function setup() {
  let table = new p5.Table();

  table.addColumn('name');
  table.addColumn('type');

  let newRow = table.addRow();
  newRow.setString('name', '$Lion');
  newRow.setString('type', 'Mammal');

  newRow = table.addRow();
  newRow.setString('name', '$Snake');
  newRow.setString('type', 'Reptile');

  table.removeTokens(',$ ');
  print(table.toArray());
}

// prints:
// 0 "Lion" "Mammal"
// 1 "Snake" "Reptile"
```

Syntax

```
removeTokens(chars, [column])
```

Parameters

chars	String: String listing characters to be removed
column	String Integer: Column ID (number) or name (string)

This page is generated from the comments in [src/io/p5.Table.js](#). Please feel free to edit it and submit a pull request!

Related References

[addColumn](#)
Use `addColumn()` to add a new column to a Table object.

[addRow](#)
Use `addRow()` to add a new row of data to a `p5.Table` object.

[clearRows](#)
Removes all rows from a Table.

[columns](#)
An array containing the names of the columns in the table, if the "header" parameter is loaded with the "header" parameter.

p5.js

Resources

[Reference](#)
[Tutorials](#)
[Examples](#)
[Contribute](#)
[Community](#)
[About](#)
[Start Coding](#)
[Donate](#)

Information

[Download](#)
[Contact](#)
[Copyright](#)
[Privacy Policy](#)
[Terms of Use](#)

Socials

[GitHub ↗](#)
[Instagram ↗](#)
[X ↗](#)
[YouTube ↗](#)
[Discord ↗](#)
[Forum ↗](#)

