Dulux Promise Interior Emulsion



Product code F903

Usage Dulux Promise Interior has ChromaBrite Technology that keeps your

home looking fresh and new for longer. Dulux Promise Interior with Washable and Easy Wipe formulation, making wiping away common household stains easier. Dulux Promise Interior also has Antibacterial and Anti-Fungus properties inhibiting the growth of bacterial and developing mould and fungus on the wall. Dulux Promise Interior for your miraculously brighter, safer and cleaner walls that last longer.

Pack Size 1 Litre, 4 Litres and 16 Litres

Colour Range See Dulux Promise Interior shade card

FILM PROPERTIES

Water resistance Will tolerate the levels of atmospheric humidity present in normal

interior and exterior environments

Other Properties Chroma Brite Technology, EasyWipe, Anti-Bacterial, Anti-Fungus

and Anti-Mould, Anti-Chalking, Smooth Finish, High Opacity and Coverage, Low Odour and Low VOC, No Added Lead or Mercury,

Singapore Green Label Certified

COMPOSITION (NOMINAL) Pigment: Lightfast Non-Lead Pigments

Binder: Acrylic copolymer

Solvent: Water

VOLUME SOLIDS White 40% (nominal), other colours will vary.

FILM THICKNESS/ Wet: 60-70 micrometers
LITRE/COAT Dry: 25-30 micrometers

DRYING TIMESSingle coat at standard film thickness **Touch Dry**Dependent on temperature and humidity

Recoat 2-3 hours

PRACTICAL COVERAGE A guide to the practical coverage which can be achieved under

normal conditions is 13-15m²/litre /coat.

APPLICATION Brush Roller

THINNING

Brush For sealing new or bare surfaces thin with up to 3 parts of clean water

to 4 parts of paint (75%). For application with brush thinning should not exceed 2-3 parts of clean water to 4 parts of paint (60-75%).

For application with roller thinning should not exceed 0.5-0.75 parts Roller

of clean water to 4 parts of paint (10-15%)

CLEANING UP Clean all equipment with clean water immediately after use

SURFACE PREPARATION New surfaces must be clean, dry, free from all defective or poorly

adhering material, dirt, grease, wax etc. Treat any area affected by mould, lichens, algae or moss with Aquashield Pre Treatment Coat. Previously painted surfaces should be thoroughly rubbed down using

a suitable abrasive paper and then dust off.

FILLING NEW SURFACES After priming new surfaces with Dulux Promise Primer, fill the surface

with Promise Wall Putty. Please refer to SDS of Promise Wall Putty for correct application procedure and drying time properties. Third coat of Promise wall putty can be applied for extra smoothness. For best results apply one coat of Dulux Promise Primer again over wall

putty and dry overnight.

POWDRY, DUSTY SURFACES DEFECTS. **CRACKS AND OTHER SURFACES**

Repair minor defects in the wall using sand whereas for larger holes and cracks use cement mix. Allow the surface drying time. Prime surface with Promise Primer and then fill any surface

imperfections with the Promise Wall Putty. Scuff surface using

abrasive paper and dust off.

SYSTEM INFORMATION

Dulux Promise Primer(F912-9595) (1 New surfaces

Dulux Promise Putty (F962-9596) (2-3 Coats)

Dulux Promise Primer(F912-9595) (1

coat)

Dulux Promise Primer (F912-9595) **Powdery Surface**

(Apply 1 coat of putty if required)

Normal, sound surfaces No Primer required

(Previously painted)

(F903)

Dulux

Emulsion

Finish (3-4 coats)

Promise

interior

39

SAFETY, HEALTH AND ENVIRONMENT INFORMATION

Treatments such as sanding, burning off etc. of paint films may generate hazardous dust and/or fumes. Wet sanding/ flatting should be used wherever possible. Work in well ventilated areas. Use suitable personal protection equipment.



Lift with care – gross weight exceeds 10kg

Wear eye/ hand protection. Do not breathe vapors/spray. Use only in well-ventilated areas. Remove as much paints as possible from brushes and rollers before cleaning. Avoid release to the environment. Collect spillage. Keep away from food, drinks and animal feed. Store in a cool and shaded place. Container must be in a secure, upright position and be tightly closed. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. In case of contact with skin wash immediately with soap and water or a proprietary skin cleanser. Do not use solvents or thinners. Do not empty into water course. Safety data sheet available for professional/ user on request.



WARNING

Hazard Statements

May cause an allergic skin reaction.

Precautionary Statements

Keep out of reach of children. If medical advice is needed, have product container or label at hand. Do not get in eyes, on skin, or on clothing. Call a POISON CENTER or doctor if you feel unwell. Dispose of contents and container in accordance with all local, regional, national, or international regulations.