



## **N.C DUCO MASTER**

### **Material Safety Data Sheet**

N.C Duco Master is NC based gloss topcoat for furniture and where fast drying durable finish required for fast and efficient re-finishing. This product is recommended for all motor vehicles and wood or metal furniture.

**Research and Development Department**  
**Master Paint Industries (Pvt.) Ltd.**  
**Phone : 0 4 2 – 111 – 333 – 465,**  
**E-Mail : [info@masterpaints.com](mailto:info@masterpaints.com)**



[WWW.MASTERPAINTS.COM](http://WWW.MASTERPAINTS.COM)

## PRODUCT INFORMATION

**Description:** N.C Duco Master is NC based gloss topcoat for furniture and where fast drying durable finish required for fast and efficient re-finishing. This product is recommended for all motor vehicles and wood or metal furniture.

## TECHNICAL INFORMATION:

Colour	Standard Shade card
Finish	Semi Gloss
Generic Type	NC
Vol Solid	32 %
Spreading Rate	10.7 m <sup>2</sup> / L. @30 µm dft.
Drying Time	15 min. at 30 °C.
Recoating Time	1 hr.
Thinner / cleaner	NC Thinner
Weight / Litre	1.0 – 1.1 kg.
Flash Point	40 °F
Further coat	Coat on coat
Packing size	0.91 and 3.64 litres.

## APPLICATION DETAIL :

Conventional or airless spray.

## TYPICAL SURFACES :

Pre- primed and smooth surface. Ensure that surface is clean, dry and free from grease, oil and other contamination. Wood should be properly sanded and must be scuffed in the direction of metal or wood grains. Seal with N.C Putty or Maestro Putty.

### SAFETY AND ENVIRONMENTAL NOTES:

Ensure proper ventilation during application and drying of paint. Avoid inhalation of paint mist and vapours and skin contact. Spillage of paint on skin should immediately be removed with suitable cleanser soap and water. Eyes should be well flushed with water and immediate medical attention should be sought.

