



NIPPON WALL PUTTY

Water Based

Product Description:

Nippon Wall Putty (water based) is a high quality ready to use filler recommended for leveling uneven rough porous cement walls, plaster work, patching cracks and filling defective surfaces. With fast drying property and ease of application, it provides smooth finish for topcoat application. Nippon Wall Putty is not recommended on exterior.

Recommended Uses:

Nippon Wall Putty is recommended for use on masonry walls and ceiling.

Composition:

Pigments	: Mineral Extender.
Binder	: Poly Vinyl Acrylic Emulsion
Thinner	: Water

Properties:

Colour and Texture	: White, Flat Matt
---------------------------	--------------------

Number of coats	: 2-3
------------------------	-------

Drying Time

Touch Dry	: 15-30 minutes (Dependant on temperature and humidity)
Hard Dry	: 1 hour
Sanding	: 2-3 hours

Coverage	: 4-6m ² per Kg per coat (Coverage may vary depending on the substrate conditions)
-----------------	--

Application Methods:

Spatula, Trowel, Putty Applicator	: Spread PVA putty to get a smooth finish. Remove any dried putty from the applicator to achieve best performance.
--	--

Clean Up	: Clean up equipment with water immediately after use.
-----------------	--

Previously Painted Surfaces

Remove all unstable paint film, loose chalk, dust and foreign matter using suitable sanding paper or a stiff brush. Dust off properly. Apply NIPPON VINILEX 5100 WALL SEALER and allow thorough drying.

Surface Preparation:

All the surfaces must be thoroughly dry before putty application. Remove dust, grease, oil and other foreign matters from new masonry surface. Use a bleach solution to treat the surface affected by fungus or algae. Make the surface smooth before application of PVA Putty using sandstone or a coarse sanding paper. Dust off properly.

Allow all surfaces to dry completely prior to painting. Avoid painting when the moisture content and alkalinity of the walls is still high. (Recommended painting specification requires the moisture content of the walls to be below 16% measured by protimeter and alkalinity of the walls to be below pH9.)

Recommended Paint System**Type of Substrate:**

FOR BARE MASONRY, PREVIOUSLY PAINTED SOUND OR POWDERY MASONRY

Sequence	Product Name	No. of Coats	Remarks
Sealer	NIPPON VINILEX 5100 WALL SEALER	1	
Putty	NIPPON WALL PUTTY	2-3	

Standard Packing : 5 Kg, 20 Kg

Safety, Health and Environmental Information:

Keep out of reach of children and away from food and drink. Harmful if swallowed. If swallowed seek medical advice immediately. Ensure good ventilation during application and drying. Do not breathe in vapor or sanding dust. Avoid contact with eyes and skin. When applying putty it is advisable to wear eye protection. In case of contact with eyes rinse immediately with plenty of water and seek medical advice. Wear protective clothing and mask during application. Use soap and water to clean the splashes from skin. Putty must always be stored in a cool and dry place. Care must be taken during transportation. Always keep container in a secure upright position. Use sand to contain any spillage. Dispose of putty in accordance with the appropriate Environmental Quality Regulations. Do not discharge into drains or environment. Chemical Safety Data Sheet available on request.

Does not contain any added Lead, Mercury, Cadmium or Chromium compounds.

Note:

The above information is given to the best of our knowledge based on laboratory tests and practical experience.

However, since we cannot anticipate or control the many conditions under which our products may be used, we can only guarantee the quality of the product itself.

We reserve the right to alter the given data without prior notice.