

1 Preamble

- section name and its parents
- basic process header
- typed channel
- generic typed channels
- synchronisation channels
- various auxiliary declarations used

section *dot_field_multenv* **parents** *circus_toolkit*

channel *d, e*

channel *c : $\mathbb{N} \times \mathbb{N} \times \mathbb{N}$*

channel *[X, Y, Z]g : $X \times Y \times Z$*

process *DotTestMulti* $\hat{=}$ **begin**

$\left| \begin{array}{l} n1, n2 : \mathbb{N} \\ x?, y!, z? : \mathbb{N} \end{array} \right.$

$\left| \begin{array}{l} f : \mathbb{N} \rightarrow \mathbb{N} \times \mathbb{N} \end{array} \right.$

S $==$ $[y : \mathbb{N}]$

2 Example 1 — various simple patterns

- multiple actions in one environment
- tabs and various forms of new line
- multiple field patterns: in, out, dot
- field type directly mapped to channel type
- synchronisation channel d on chained prefixing

$Test0 \triangleq c?x?y?z \rightarrow Skip$

$Test1 \triangleq c?x!n1.n2 \rightarrow Skip$

$Test2 \triangleq c!n1?x.n2 \rightarrow Skip$

$Test3 \triangleq c.n1!n2?x \rightarrow d \rightarrow Skip$

$Test4 \triangleq d \rightarrow e \rightarrow Skip$

Description

Action	Communication pattern
$Test0$	$In(x, \mathbb{N}), In(y, \mathbb{N}), In(z, \mathbb{N})$
$Test1$	$In(x, \mathbb{N}), Out(n1), Dot(n2)$
$Test2$	$Out(n1), In(x, \mathbb{N}), Dot(n2)$
$Test3$	$Dot(n1), Out(n2), In(x, \mathbb{N}), Synch$
$Test4$	$Synch, Synch, Synch$

L^AT_EX

To avoid parsing the L^AT_EX markup within the `\begin{verbatim}` environment we omit the slash before the begin/end environment.

```
begin{circusaction}
\t1 Test0 \circdef c?x?y?z \then \Skip
\also
\t1 Test1 \circdef c?x!n1.n2 \then \Skip \\
\t1 Test2 \circdef c!n1?x.n2 \then \Skip
\also
\t1 Test3 \circdef c.n1!n2?x \then d \Skip
end{circusaction}
begin{circusaction}
\t1 Test4 \circdef d \then e \then \Skip
end{circusaction}
```

3 Example 2 — complex output expressions

- hard spaces - make no semantic difference
- application expressions on output fields
- parenthesised expressions form **one** field
- last fields get remainder type dimensions
- trickery to allow strokes on field expr — **mandatory** parenthesis
- schema binding selection as output ($S.y$) — **mandatory** parenthesis
- function application result as output — **mandatory** parenthesis

$$Test5 \hat{=} c ? i ! (f i) \rightarrow Skip$$

$$Test6 \hat{=} g[\mathbb{N}, \mathbb{N}, S] ? x ? y . (\theta S) \rightarrow Skip$$

$$Test7 \hat{=} c . (x ?) ! (y !) ! (z ?) \rightarrow Skip$$

Description

Action	Communication pattern
$Test5$	$\text{In}(i, \mathbb{N}), \text{Out}(\mathbb{N} \times \mathbb{N})$
$Test6$	$\text{Dot}(S.y), \text{In}(z, \mathbb{N} \times \mathbb{N})$
$Test4$	$\text{Out}(x?), \text{Out}(y!), \text{Out}(z?)$

* $S \in \mathbb{P}(\langle y == \mathbb{N} \rangle)$, hence $S.y \in \mathbb{N}$.

* $x?, y!, z?$ are decorated names; usually they appear in schemas.

L^AT_EX

```
begin{circusaction}
\t1 Test5 \circdef c~?i~!(f~i) \then \Skip
\also
\t1 Test6 \circdef c.(x.y)?z!w \then \Skip
\also
\t1 Test7 \circdef c.(x?)!(y!)!(z?) \then \Skip
end{circusaction}
```

4 Example 3 — complex input with restrictions

- input prefix restrictions — **mandatory** parenthesis
- prefix restrictions and complex expressions
- fields depending on previous value input
- chained expressions depending on previous input
- tuple selection within field restriction and output
- action broken across multiple lines

$$Test8 \triangleq c?x : (x > 1)!(f\ x) \rightarrow Skip$$

$$Test9 \triangleq c?x \rightarrow \\ c?z : (z > x.1).(f\ (x.2 + x.3)) \rightarrow Skip$$

Description

Action	Communication pattern
<i>Test8</i>	$\text{In}(x, \{v : \mathbb{N} \mid v > 1\}), \text{Out}(\mathbb{N} \times \mathbb{N})$
<i>Test9</i>	$\text{In}(x, \mathbb{N} \times \mathbb{N} \times \mathbb{N}); \text{In}(z, \{v : \mathbb{N} \mid v > x.1\}), \text{Out}(\mathbb{N} \times \mathbb{N})$

- * **type on inputs are restricted according to given predicate.**
- * *Test9* input on z is from “ $?z : (z > x.1)$ ”.

L^AT_EX

```
begin{circusaction}
  \t1 Test8 \circdef c?x \prefixcolon (x > 1)!(f~x) \then \Skip
\also
  \t1 Test9 \circdef c?x \then \\\
    \t4 c?z \prefixcolon (z > x.1).(f~(x.2+x.3)) \then \Skip
end{circusaction}
```

5 Example 4 — generic channels

- explicitly given generic actuals
- implicitly inferred generic actuals (?)

$Test10 \triangleq g[\mathbb{N}, \mathbb{N}, \mathbb{N}]?x!n1.n2 \rightarrow Skip$

$Test11 \triangleq g.n1.(f\ n1) \rightarrow Skip$

L^AT_EX

```
begin{circusaction}  
  \t1 Test10 \circdef g[\nat, \nat, \nat]?x!n1.n2 \then \Skip  
  \also  
  \t1 Test11 \circdef g.n1.(f~n1) \then \Skip  
end{circusaction}
```

6 (! Prolegomena) — basic process footer

It just terminates

- *Skip*

end