

3DF

Reactive Datalog for Datomic

by Nikolas Göbel

**“We want to make reactive systems that don't poll.
And we want those systems to get a consistent
view of the world.”**

– Rich Hickey, “Deconstructing the Database”

Nikolas Göbel

niko@clockworks.io


in collaboration with:

Frank McSherry (ETH)

David Bach (Clockworks)

Malte Sandstede (Clockworks)

ETH zürich



Systems Group



Reactive Systems?

- spreadsheets, chats, stock tickers, real-time dashboards
- alerting and rule engines
- collaboration tools
- stream processors

Reactive Principles

- data coordinates code
- change propagates
- a relationship, once established, is maintained
- results always reflect the current state of the domain

fx

=C4+C5

	A	B	C	D	E	F	G	
1								
2								
3								
4		A	12					
5		B	3					
6		(+ A B)	15					
7								
8								
9								
10								
11								
12								
13								
14								



Data coordinates code, not the other way around.

~~evaluating~~

subscribing to a query

~~re-computing from scratch~~

incrementally updating a previous result


<demo>

3DF (github.com/comnik/clj-3df)

- reactive Datalog queries
- feeds from durable sources (Datomic, Datahike, Kafka)
- scales from browsers to clusters

github.com/comnik/clj-3df

github.com/comnik/declarative-dataflow



Making Reactive Practical (I)

data coordinates code
work like a spreadsheet...

declarative
...without writing joins by hand


Making Reactive Practical (II)

transparent

notion of change shouldn't leak into Datalog...

efficient

...but update results incrementally



Computing with Snapshots

```
[:find ?device
```

```
  :where
```

```
    [?device :settings/speed ?target]
```

```
    [?device :device/speed ?speed]
```

```
    [(< ?speed ?target)]]
```



transparent



declarative



Computing with Differences

```
[ :find ?device  
  :in $ ?tx  
  :where  
    [$ ?device :settings/speed ?target]  
    [ ?tx ?device :device/speed ?speed]  
    [( < ?speed ?target) ] ]
```

✓ incremental

Differential Dataflow

github.com/TimelyDataflow/differential-dataflow

“a data-parallel programming framework designed to
quickly respond to arbitrary changes in input”

Time-varying Collections


:edge

(a b) +1 t0	
(c d) +1 t0	
(c d) -1 t1	← ({[a b] [c d]} t0)
(c e) +1 t1	← ({[a b] [c e]} t1)

Partially-ordered Times

(bfs :edge a)

(a b) +1 (t0 0)		
(c d) +1 (t0 0)		
(b c) +1 (t1 0)	(a c) +1 (t1 1)	(a d) +1 (t1 2)
(c d) -1 (t2 0)	-	(a d) -1 (t2 2)



Computing with Differences


Reactive Made Practical


- ✓ data coordinates code
- ✓ declarative joins, filters, and aggregations
- ✓ write Datalog without thinking about change
- ✓ all queries update incrementally / only propagate change

~~rule the world~~


Everybody wants to **be a database peer.**







Datomic: Broadcast All Novelty To All Peers



ions:

Move Consumers Into The DB



Selective Replication

multiple data sources?

Datomic shards, Kafka, external services...


only send relevant novelty to peers?

for browsers or mobile clients, a LRU cache is not enough

runtimes other than the JVM?

browsers, ML, data science...

3DF: Declarative Replication via Datalog



Selective Replication

- ✓ open to anyone who speaks Datalog
- ✓ only relevant novelty propagated to each consumer
- ✓ scales to deal with multiple sources

**“We want to make reactive systems that don't poll.
And we want those systems to get a consistent
view of the world.”**

– Rich Hickey, “Deconstructing the Database”

3DF lets you...

- ...leverage Datalog to build reactive systems
- ...treat data consumers as database peers
- ...scale queries beyond the limits of a single peer
- ...integrate with hand-written Differential Dataflow

Interested? Let's talk!

@NikolasGoebel | niko@clockworks.io