




Cross-cultural relationships between music, emotion, and visual imagery: A comparative study of Iran, Canada, and Japan [Stage 1 Registered Report]

Code and analyses: Simulation-based power analysis

Shafagh Hadavi ¹ Junji Kuroda² Taiki Shimozone² Juan David Leongómez ³
Patrick E. Savage ¹

14 July, 2023

¹ Graduate School of Media and Policy / Faculty of Environment and Information Studies, Keio University, Fujisawa, Japan.

² YAMAHA Corporation, Hamamatsu, Japan.

³ Human Behaviour and Evolution Lab, Faculty of Psychology, Universidad El Bosque, Bogota, Colombia.

Correspondence to: SH: shafagh@keio.jp. PES: psavage@sfc.keio.ac.jp.

Descripción

This document contains all code, and step by step explanations for the simulation-based power analysis (including supplementary figures and tables) for:

Hadavi, S., Kuroda, J., Shimozone, T., Leongómez, J. D., & Savage, P. E. (in prep). *Cross-cultural relationships between music, emotion, and visual imagery: A comparative study of Iran, Canada, and Japan* [Stage 1 Registered Report]. <https://doi.org/10.31234/osf.io/26yg5>

Data available from the *VisualEars* repository in GitHub: <https://github.com/comp-music-lab/VisualEars>. This document and its underlying code were created in R Markdown by Juan David Leongómez using L^AT_EX.

Contents

1	Preliminaries	2
1.1	Load packages	2
1.2	Custom functions	2
1.2.1	clmm_generate_data	2
1.2.2	pval.lev	2
1.2.3	summary.sig	3
1.2.4	contr.stars	3
1.2.5	tempo.contr	4
2	Data	5
2.1	Pilot data	5
2.2	Data simulation	6
2.2.1	Replication of the pilot data distribution	6
2.2.2	Simulation of data with a more conservative effect	9
2.3	Comparisons of the distribution of results between pilot and simulated data	12

3	Power analysis	13
3.1	Select random samples	14
3.2	Visual density power analysis	14
3.3	Arousal power analysis	15
3.4	Achieved power	15
4	Analysis script with example data	16
4.1	Visual density example model	18
4.2	Arousal example model	18
4.3	Estimated marginal means and confidence intervals for both models	19
4.4	Effect of Tempo	20
4.4.1	Visual density model	20
4.4.2	Arousal model	21
5	Session info (for reproducibility)	22
	Supplementary references	22

1 Preliminaries

1.1 Load packages

This file was created using **knitr** (Xie, 2014), mostly using **tidyverse** (Wickham et al., 2019) syntax. As such, data wrangling was mainly done using packages such as **dplyr** (Wickham et al., 2022), and most figures were created using **ggplot2** (Wickham, 2016). Tables were created using **knitr::kable** and **kableExtra** (Zhu, 2020).

Cumulative Link Mixed Models (CLMM) were fitted using **ordinal** (Christensen, 2022), and contrasts and interactions were explored using **emmeans** (Lenth, 2022). In all cases, threshold between levels of the dependent (ordinal) variable, were set as flexible.

All packages used in this file can be directly installed from the Comprehensive R Archive Network ([CRAN](https://cran.r-project.org/)). For a complete list of packages used to create this file, and their versions, see section 5, at the end of the document.

```
library(tidyverse)
library(ggpubr)
library(emmeans)
library(ordinal)
library(kableExtra)
library(performance)
```

1.2 Custom functions

1.2.1 clmm_generate_data

To simulate ordinal data with a specific distribution, we used the function **clmm_generate_data**, created by Borders et al. (2022) as part of their tutorial (<https://osf.io/e6usd/>). To run this function, a number of other custom functions need to be defined and implemented as well. The original code can be found in the **clmm-power-library.R** file (<https://osf.io/tjpkf/>). Here, it is run from source, but in a slightly modified version of the file in which we changed the **mc.cores** parameter to 1, to avoid errors.

```
source("clmm-power-library.R", local = knitr::knit_global())
```

1.2.2 pval.lev

The function **pval.lev** takes p-values and formats them in \LaTeX , highlighting significant results in bold.

```
pval.lev <- function(pvals) {
  ifelse(pvals < 0.0001,
```

```

    "\\textbf{< 0.0001}",
    ifelse(pvals < 0.001,
           "\\textbf{< 0.001}",
           ifelse(pvals < 0.05,
                  paste0("\\textbf{", round(pvals, 4), "}"),
                  round(pvals, 2))))
  }

```

1.2.3 summary.sig

The function `summary.sig` was created to bold significant p values from summary model tables. It highlights significant p values, and formats the output in L^AT_EX, ready to be used with `kable`.

```

summary.sig <- function(mod, custom_caption) {
  modTab <- data.frame(summary(mod)$coefficients) |>
  rownames_to_column() |>
  mutate_at("rowname", str_replace_all, ":", " × ") |>
  mutate_at("rowname", str_replace_all, "~", "") |>
  mutate("rowname" = str_replace_all(rowname,
                                     c("Tempo1" = "Tempo [Low]",
                                       "Solo.group1" = "Instrumentation [Group]",
                                       "Participant.country1" = "Participant country [Canada]",
                                       "Participant.country2" = "Participant country [Iran]",
                                       "Music.country1" = "Music country [Canada]",
                                       "Music.country2" = "Music country [Iran]"))) |>
  mutate(Pr...z... = pval.lev(Pr...z...)) |>
  kable(digits = 2,
        booktabs = TRUE,
        align = c("l", rep("c", 4)),
        linesep = "",
        caption = custom_caption,
        col.names = c("Effects",
                      "Estimate",
                      "Std. Error",
                      "$z$",
                      "$p$"),
        escape = FALSE) |>
  kable_styling(latex_options = c("HOLD_position", "scale_down")) |>
  pack_rows(group_label = "Thresholds",
            start_row = 1,
            end_row = 4,
            hline_after = TRUE,
            bold = TRUE) |>
  pack_rows(group_label = "Terms",
            start_row = 5,
            end_row = 39,
            hline_before = TRUE,
            hline_after = TRUE,
            bold = TRUE)
  return(modTab)
}

```

1.2.4 contr.stars

Function to create a data frame of model contrasts, representing significance levels from an `emmeans::emmeans` output. These data frames are formatted to be called by the `ggpubr::stat_pvalue_manual` function used in model figures.

```

contr.stars <- function(emms){
  require(emmeans)
  x <- tibble(as.data.frame(emms$contrasts))
  x <- separate(x,
    col = 1,
    into = c("group1", "group2"),
    sep = " - ",
    remove = TRUE)
  x$p.signif <- ifelse(x$p.value < 0.0001, "****",
    ifelse(x$p.value < 0.001, "***",
      ifelse(x$p.value < 0.01, "**",
        ifelse(x$p.value < 0.05, "*", NA))))
  x <- x |>
    mutate_at("group1", str_replace_all, "[()]", "") |>
    mutate_at("group2", str_replace_all, "[()]", "")
  return(x)
}

```

1.2.5 tempo.contr

This functions creates a table combining both estimated marginal means and contrasts between levels of Tempo, and formats the output in \LaTeX , ready to be used with `kable`.

```

tempo.contr <- function(mod){
  emms.mod <- emmeans(mod, pairwise~Tempo)
  emms.mod.tab <- tibble(data.frame(emms.mod$emmeans))
  t.mod <- contr.stars(emms.mod) |>
    mutate(p.value = pval.lev(p.value))
  emm.contr.tab <- merge(emms.mod.tab, t.mod, by = 0, all = TRUE) |>
    select(-c(1,5,12,15)) |>
    unite(Contrast, group1, group2, sep = " - ") |>
    mutate_at("Contrast", str_replace_all, "NA - NA", " ") |>
    kable(digits = 2,
      booktabs = TRUE,
      align = c("l", rep("c", 5), "l", rep("c", 5)),
      linesep = "",
      caption = "Estimated marginal means and contrasts between Tempo conditions",
      col.names = c("Tempo",
        "EMM",
        "$SE$",
        "$2.5\\% CI$",
        "$97.5\\% CI$",
        "Contrast",
        "Difference",
        "$SE$",
        "$z$",
        "$p$"),
      escape = FALSE) |>
    add_header_above(c(" " = 5, "Contrasts" = 5)) |>
    kable_styling(latex_options = c("HOLD_position")) |>
    footnote(general = "EMM = estimated marginal mean.",
      threeparttable = TRUE,
      footnote_as_chunk = TRUE,
      escape = FALSE)
  return(emm.contr.tab)
}

```

2 Data

2.1 Pilot data

To simulate data, first we looked at the distribution of the pilot data.

```
# Load data
sh1 <- read.csv("../sh1.csv") |>
  mutate(Tempo = str_replace(Tempo, "low", "Low")) |>
  mutate(Tempo = str_replace(Tempo, "high", "High")) |>
  mutate_if(is.character, as.factor) |>
  mutate(Tempo = fct_relevel(Tempo, c("Low", "High")))

# Assign unique id to pairs
uniqueval <- unique(sh1[, c("Participant", "Music.country", "Solo.group")])
sh1$groupid <- 0
for (i in 1:dim(uniqueval)[1]) {
  idx <- sh1$Participant == uniqueval$Participant[i] &
    sh1$Music.country == uniqueval$Music.country[i] &
    sh1$Solo.group == uniqueval$Solo.group[i]
  sh1$groupid[idx] <- i
}

# Select only relevant variables
data <- sh1 |>
  select(1:9, 20)

# Plot distribution of results for density ratings
p1a <- ggplot(data, aes(x = density.tempo, y = after_stat(density),
  fill = Tempo, color = Tempo)) +
  scale_fill_hue(direction = -1) + scale_colour_hue(direction = -1) +
  geom_histogram(alpha = 0.3, position = "identity", binwidth = 1) +
  labs(y= "Probability", x = "Rating", title = "Density") +
  geom_text(aes(label = format(after_stat(density), digits = 1), y= after_stat(density)),
    stat= "bin", binwidth = 1,
    vjust = -0.2,
    show.legend = FALSE) +
  facet_wrap(~Solo.group)

# Plot distribution of results for arousal ratings
p1b <- ggplot(data, aes(x = arousal.tempo, y = after_stat(density),
  fill = Tempo, color = Tempo)) +
  scale_fill_hue(direction = -1) + scale_colour_hue(direction = -1) +
  geom_histogram(alpha = 0.3, position = "identity", binwidth = 1) +
  labs(y= NULL, x = "Rating", title = "Arousal") +
  geom_text(aes(label = format(after_stat(density), digits = 1), y= after_stat(density)),
    stat= "bin", binwidth = 1,
    vjust = -0.2,
    show.legend = FALSE) +
  facet_wrap(~Solo.group)

# Arrange plots
p1 <- ggarrange(p1a, p1b,
  common.legend = TRUE,
  legend = "bottom",
  labels = "AUTO")
p1
```




Figure S1. Distribution of results from pilot data for ratings of both Density (A) and Arousal (B), by Instrumentation (Group, Solo), and Tempo (High, Low).

2.2 Data simulation

While basing a power analysis on pilot data is problematic and can bias the sample size estimation (see e.g., Albers & Lakens, 2018), we used this distribution as a starting point.

The `clmm_generate_data` function (Borders et al., 2022) allows to simulate data with random and fixed effects with an ordinal outcome. In this case, we simulated data for Tempo, the within-subject variable for which there was an *a-priori* prediction, replicating the distribution of the first level (Low) using a specified probability of each rating score (using the argument `control_distribution`). The second level of that within-subject variable (Tempo = High) is generated based on a hypothesized effect (using the argument `effect`). Other important factors such as participant country and music country were randomly assigned, as there are no *a-priori* predictions regarding these factors.

2.2.1 Replication of the pilot data distribution

To obtain distributions similar to the probabilities observed in the pilot data, we first simulated individual data for Density and Arousal ratings, separated by Instrumentation type (Group, Solo). In all cases, we simulated data from 10000 participants, and changed the value assigned to the `effect` argument until the distribution of the second level of the within-subject variable (Tempo = High) resembled the pilot data.

```
# Density ratings for group music
dat.den.gr.PILOT <- clmm_generate_data(n_participants = 10000,
  n_trials = 3,
  control_distribution = c(.04, .11, .59, .22, .04),
  effect = 3.2,
  participant_variation = 1,
  within_subject = TRUE,
  control_weight = .5) |>
mutate(group = ifelse(group == 0, "Low", "High")) |>
dplyr::rename(Density.tempo = pas) |>
dplyr::rename(Tempo = group) |>
dplyr::rename(Participant = id) |>
mutate(Participant = paste0("p", Participant)) |>
```

```

select(1:3) |>
mutate(pair = rep(1:3, times = 20000)) |>
mutate(Participant.country = rep(rep(c("Iran", "Canada", "Japan"), each = 10000), 2)) |>
mutate(Music.country = rep(c("Iran", "Canada", "Japan"), times = 20000)) |>
mutate(Solo.group = rep("Group", TIMES = 60000)) |>
select(c(1,6,5,2,7,3))

# Density ratings for solo music
dat.den.so.PILOT <- clmm_generate_data(n_participants = 10000,
                                     n_trials = 3,
                                     control_distribution = c(.55, .30, .04, .10, .01),
                                     effect = 1.2,
                                     participant_variation = 1,
                                     within_subject = TRUE,
                                     control_weight = .5) |>
mutate(group = ifelse(group == 0, "Low", "High")) |>
dplyr::rename(Density.tempo = pas) |>
dplyr::rename(Tempo = group) |>
dplyr::rename(Participant = id) |>
mutate(Participant = paste0("p", Participant)) |>
select(1:3) |>
mutate(pair = rep(1:3, times = 20000)) |>
mutate(Participant.country = rep(rep(c("Iran", "Canada", "Japan"), each = 10000), 2)) |>
mutate(Music.country = rep(c("Iran", "Canada", "Japan"), times = 20000)) |>
mutate(Solo.group = rep("Solo", TIMES = 60000)) |>
select(c(1,6,5,2,7,3))

# Arousal ratings for group music
dat.aro.gr.PILOT <- clmm_generate_data(n_participants = 10000,
                                     n_trials = 3,
                                     control_distribution = c(.11, .11, .52, .19, .07),
                                     effect = 3.1,
                                     participant_variation = 1,
                                     within_subject = TRUE,
                                     control_weight = .5) |>
mutate(group = ifelse(group == 0, "Low", "High")) |>
dplyr::rename(Arousal.tempo = pas) |>
dplyr::rename(Tempo = group) |>
dplyr::rename(Participant = id) |>
mutate(Participant = paste0("p", Participant)) |>
select(1:3) |>
mutate(pair = rep(1:3, times = 20000)) |>
mutate(Participant.country = rep(rep(c("Iran", "Canada", "Japan"), each = 10000), 2)) |>
mutate(Music.country = rep(c("Iran", "Canada", "Japan"), times = 20000)) |>
mutate(Solo.group = rep("Group", TIMES = 60000)) |>
select(c(1,6,5,2,7,3))

# Arousal ratings for solo music
dat.aro.so.PILOT <- clmm_generate_data(n_participants = 10000,
                                     n_trials = 3,
                                     control_distribution = c(.43, .41, .14, .01, .01),
                                     effect = 1.6,
                                     participant_variation = 1,
                                     within_subject = TRUE,
                                     control_weight = .5) |>
mutate(group = ifelse(group == 0, "Low", "High")) |>

```

```
dplyr::rename(Arousal.tempo = pas) |>
dplyr::rename(Tempo = group) |>
dplyr::rename(Participant = id) |>
mutate(Participant = paste0("p", Participant)) |>
select(1:3) |>
mutate(pair = rep(1:3, times = 20000)) |>
mutate(Participant.country = rep(rep(c("Iran", "Canada", "Japan"), each = 10000), 2)) |>
mutate(Music.country = rep(c("Iran", "Canada", "Japan"), times = 20000)) |>
mutate(Solo.group = rep("Solo", TIMES = 60000)) |>
select(c(1,6,5,2,7,3))
```

We then merged these four data frames to obtain a simulated data frame.

```
dat.sim.PILOT <- left_join(bind_rows(dat.den.gr.PILOT, dat.den.so.PILOT),
                           bind_rows(dat.aro.gr.PILOT, dat.aro.so.PILOT),
                           relationship = "many-to-many") |>
mutate(Tempo = fct_relevel(Tempo, c("Low", "High")))
```

The distribution of this replication of the pilot data distribution is represented in S2

```
# Plot distribution of results for density ratings
p2a <- ggplot(dat.sim.PILOT, aes(x = Density.tempo, y = after_stat(density),
                                fill = Tempo, color = Tempo)) +
  scale_fill_hue(direction = -1) + scale_colour_hue(direction = -1) +
  geom_histogram(alpha = 0.3, position = "identity", binwidth = 1) +
  labs(y= "Probability", x = "Rating") +
  geom_text(aes(label = format(after_stat(density), digits = 1), y= after_stat(density)),
            stat= "bin", binwidth = 1,
            vjust = -0.2,
            show.legend = FALSE) +
  facet_wrap(~Solo.group)

# Plot distribution of results for arousal ratings
p2b <- ggplot(dat.sim.PILOT, aes(x = Arousal.tempo, y = after_stat(density),
                                fill = Tempo, color = Tempo)) +
  scale_fill_hue(direction = -1) + scale_colour_hue(direction = -1) +
  geom_histogram(alpha = 0.3, position = "identity", binwidth = 1) +
  labs(y= NULL, x = "Rating") +
  geom_text(aes(label = format(after_stat(density), digits = 1), y= after_stat(density)),
            stat= "bin", binwidth = 1,
            vjust = -0.2,
            show.legend = FALSE) +
  facet_wrap(~Solo.group)

# Arrange plots
p2 <- ggarrange(p2a +
  labs(subtitle = "Density"),
  p2b +
  labs(subtitle = "Arousal"),
  common.legend = TRUE,
  legend = "bottom",
  labels = "AUTO")
p2
```





Figure S2. Distribution of results from a simulated replication of the pilot data distribution for ratings of both Density (A) and Arousal (B), by Instrumentation (Group, Solo), and Tempo (High, Low).

2.2.2 Simulation of data with a more conservative effect

While the data simulated in the previous section resembled the distribution of the pilot data, using these data would be problematic for at least two reasons:

First, the effects of Tempo were extremely large (3.2, 1.2, 3.1, 1.6), particularly for ratings of Group instrumentation (3.2, and 3.1). With such differences, a very high statistical power of about $1 - \beta = 0.95$ can be achieved with 2 or 3 participants. And second, as mentioned before, estimating effects from pilot data is problematic, as it biases the results (Albers & Lakens, 2018).

For this reason, we decided to maintain the distributions of probabilities for the first Tempo level (Low), as it is a good starting point to estimate the distribution of ratings that participants would assign, but simulated the second level (Tempo = High) with a much more conservative effect of 1 in all cases.

```
# Density ratings for group music
dat.den.gr <- clmm_generate_data(n_participants = 10000,
                                n_trials = 3,
                                control_distribution = c(.04, .11, .59, .22, .04),
                                effect = 1,
                                participant_variation = 1,
                                within_subject = TRUE,
                                control_weight = .5) |>
mutate(group = ifelse(group == 0, "Low", "High")) |>
dplyr::rename(Density.tempo = pas) |>
dplyr::rename(Tempo = group) |>
dplyr::rename(Participant = id) |>
mutate(Participant = paste0("p", Participant)) |>
select(1:3) |>
mutate(pair = rep(1:3, times = 20000)) |>
mutate(Participant.country = rep(rep(c("Iran", "Canada", "Japan"), each = 10000), 2)) |>
mutate(Music.country = rep(c("Iran", "Canada", "Japan"), times = 20000)) |>
mutate(Solo.group = rep("Group", TIMES = 60000)) |>
select(c(1,6,5,2,7,3))
```

```

# Density ratings for solo music
dat.den.so <- clmm_generate_data(n_participants = 10000,
                                n_trials = 3,
                                control_distribution = c(.55, .30, .04, .10, .01),
                                effect = 1,
                                participant_variation = 1,
                                within_subject = TRUE,
                                control_weight = .5) |>
mutate(group = ifelse(group == 0, "Low", "High")) |>
dplyr::rename(Density.tempo = pas) |>
dplyr::rename(Tempo = group) |>
dplyr::rename(Participant = id) |>
mutate(Participant = paste0("p", Participant)) |>
select(1:3) |>
mutate(pair = rep(1:3, times = 20000)) |>
mutate(Participant.country = rep(rep(c("Iran", "Canada", "Japan"), each = 10000), 2)) |>
mutate(Music.country = rep(c("Iran", "Canada", "Japan"), times = 20000)) |>
mutate(Solo.group = rep("Solo", TIMES = 60000)) |>
select(c(1,6,5,2,7,3))

# Arousal ratings for group music
dat.aro.gr <- clmm_generate_data(n_participants = 10000,
                                n_trials = 3,
                                control_distribution = c(.11, .11, .52, .19, .07),
                                effect = 1,
                                participant_variation = 1,
                                within_subject = TRUE,
                                control_weight = .5) |>
mutate(group = ifelse(group == 0, "Low", "High")) |>
dplyr::rename(Arousal.tempo = pas) |>
dplyr::rename(Tempo = group) |>
dplyr::rename(Participant = id) |>
mutate(Participant = paste0("p", Participant)) |>
select(1:3) |>
mutate(pair = rep(1:3, times = 20000)) |>
mutate(Participant.country = rep(rep(c("Iran", "Canada", "Japan"), each = 10000), 2)) |>
mutate(Music.country = rep(c("Iran", "Canada", "Japan"), times = 20000)) |>
mutate(Solo.group = rep("Group", TIMES = 60000)) |>
select(c(1,6,5,2,7,3))

# Arousal ratings for solo music
dat.aro.so <- clmm_generate_data(n_participants = 10000,
                                n_trials = 3,
                                control_distribution = c(.43, .41, .14, .01, .01),
                                effect = 1,
                                participant_variation = 1,
                                within_subject = TRUE,
                                control_weight = .5) |>
mutate(group = ifelse(group == 0, "Low", "High")) |>
dplyr::rename(Arousal.tempo = pas) |>
dplyr::rename(Tempo = group) |>
dplyr::rename(Participant = id) |>
mutate(Participant = paste0("p", Participant)) |>
select(1:3) |>
mutate(pair = rep(1:3, times = 20000)) |>
mutate(Participant.country = rep(rep(c("Iran", "Canada", "Japan"), each = 10000), 2)) |>

```

```
mutate(Music.country = rep(c("Iran", "Canada", "Japan"), times = 20000)) |>
mutate(Solo.group = rep("Solo", TIMES = 60000)) |>
select(c(1,6,5,2,7,3))
```

Again, we then merged these four data frames to obtain a final simulated data frame.

```
dat.sim <- left_join(bind_rows(dat.den.gr, dat.den.so),
                     bind_rows(dat.aro.gr, dat.aro.so),
                     relationship = "many-to-many") |>
mutate(Tempo = fct_relevel(Tempo, c("Low", "High")))

# Assign unique id to pairs
uniqueval <- unique(dat.sim[, c("Participant", "Music.country", "Solo.group")])
dat.sim$groupid <- 0
for (i in 1:dim(uniqueval)[1]) {
  idx <- dat.sim$Participant == uniqueval$Participant[i] &
    dat.sim$Music.country == uniqueval$Music.country[i] &
    dat.sim$Solo.group == uniqueval$Solo.group[i]
  dat.sim$groupid[idx] <- i
}
```

The distribution of these simulated data is represented in S3

```
# Plot distribution of results for density ratings
p3a <- ggplot(dat.sim, aes(x = Density.tempo, y = after_stat(density),
                          fill = Tempo, color = Tempo)) +
  scale_fill_hue(direction = -1) + scale_colour_hue(direction = -1) +
  geom_histogram(alpha = 0.3, position = "identity", binwidth = 1) +
  labs(y= "Probability", x = "Rating") +
  geom_text(aes(label = format(after_stat(density), digits = 1), y= after_stat(density)),
            stat= "bin", binwidth = 1,
            vjust = -0.2,
            show.legend = FALSE) +
  facet_wrap(~Solo.group)

# Plot distribution of results for arousal ratings
p3b <- ggplot(dat.sim, aes(x = Arousal.tempo, y = after_stat(density),
                          fill = Tempo, color = Tempo)) +
  scale_fill_hue(direction = -1) + scale_colour_hue(direction = -1) +
  geom_histogram(alpha = 0.3, position = "identity", binwidth = 1) +
  labs(y= NULL, x = "Rating") +
  geom_text(aes(label = format(after_stat(density), digits = 1), y= after_stat(density)),
            stat= "bin", binwidth = 1,
            vjust = -0.2,
            show.legend = FALSE) +
  facet_wrap(~Solo.group)

# Arrange plots
p3 <- ggarrange(p3a +
  labs(subtitle = "Density"),
  p3b +
  labs(subtitle = "Arousal"),
  common.legend = TRUE,
  legend = "bottom",
  labels = "AUTO")

p3
```




Figure S3. Distribution of results from a conservative simulated distribution for ratings of both Density (A) and Arousal (B), by Instrumentation (Group, Solo), and Tempo (High, Low).

2.3 Comparisons of the distribution of results between pilot and simulated data

```
p4 <- ggarrange(ggarrange(p1a + labs(title = "Pilot data"),
  p1b + labs(title = " "),
  legend = "none"),
  ggarrange(p2a + labs(title = "Simulation (pilot data replication)",
  p2b + labs(title = " "),
  legend = "none"),
  ggarrange(p3a + labs(title = "Final simulation (conservative effect)",
  p3b + labs(title = " "),
  common.legend = TRUE, legend = "bottom"),
  common.legend = TRUE,
  labels = "AUTO",
  nrow = 3,
  heights = c(1,1,1.1))
```

p4




Figure S4. Distribution of results of ratings of both Density and Arousal (**B**), by Instrumentation (Group, Solo), and Tempo (High, Low). **A** pilot data; **B** simulation replicating pilot data distribution; **C** simulation with a more conservative effect.

3 Power analysis

Using the final, simulated population ($N = 10000$ participants, with 6 paired observations per participant), we conducted a simulation-based power analysis. To do this, we first defined the desired number of simulations, the sample size (per country) of each simulation, and the α value (significance level) for all statistical tests:

```
# Number of simulations to run
num_sims.clmm = 1000

# Sample size for each simulation (number of participants per country)
```

```
sample_size.clmm = 30

# Significance level
alpha.clmm = 0.025
```

Then, models were fitted from the defined 1000 random samples extracted from the simulated population.

From each sample, two Cumulative Link Mixed Models (CLMM) were fitted (see e.g., Taylor et al., 2022): one for Density ratings, and one for arousal ratings. All models were fitted with the following call: `clmm(DV ~ Tempo * Solo.group * Participant.country * Music.country + (1 + Tempo | Participant))`.

This is, all models had the same structure, which included the main effects and all possible interactions between Tempo (Low, High), Instrumentation (Group, Solo), Participant country (Iran, Canada, Japan), and Music country (Iran, Canada, Japan) as fixed effects, as well as random intercepts and random slopes between Tempo conditions for each participant.

For each random sample, we adjusted the number of participants per country (in this case, $n = 30$) to achieve the target statistical power of at least $1 - \beta = 0.95$ for both the Density and Arousal models, for the contrast between Tempo levels (i.e., averaged over the levels of Instrumentation (`Solo.group`), participant country (`Participant.country`) and Music country (`Music.country`)).

3.1 Select random samples

```
# Get participant IDs
part <- dat.sim |>
  group_by(Participant.country) |>
  distinct(Participant) |>
  ungroup()

# Select samples of random participants
samples.clmm <- map_dfr(seq_len(num_sims.clmm), ~part |>
  sample_n(sample_size.clmm) |>
  mutate(sample.clmm = as.factor(.x)))

# Final data base of data for each participant selected for each sample
samples.clmm.long <- left_join(samples.clmm, dat.sim, by = c("Participant",
  "Participant.country"),
  relationship = "many-to-many") |>
  mutate(Density.tempo = as.factor(Density.tempo)) |>
  mutate(Arousal.tempo = as.factor(Arousal.tempo)) |>
  mutate(Tempo = as.factor(Tempo))
```

3.2 Visual density power analysis

```
# Create empty data frame
clmm.comps.den <- data.frame(Sample = 1:num_sims.clmm)

# Loop to fit a model for each random sample and extract the p-value of the Tempo contrasts
for (i in 1:num_sims.clmm){
  samp <- samples.clmm.long |>
    filter(sample.clmm == i)
  tryCatch(mod <- clmm(Density.tempo ~
    Tempo * Solo.group * Participant.country * Music.country +
    (1 + Tempo | Participant), data = samp),
    error = function(e) {})
  tryCatch(comp <- emmeans(mod, pairwise~Tempo),
    error = function(e) {})
```

```

clmm.comps.den$p[i] <- round(data.frame(comp$contrast)$p.value, 3)
clmm.comps.den$`Statistical significance`[i] <- ifelse(clmm.comps.den$p[i] <= alpha.clmm,
                                                       "Significant", "Non-significant")
}

# Calculate power (proportion of simulations in which the Tempo contrast was significant)
power.clmm.den <- sum(clmm.comps.den$`Statistical significance` == "Significant")/num_sims.clmm

```

3.3 Arousal power analysis

```

# Create empty data frame
clmm.comps.aro <- data.frame(Sample = 1:num_sims.clmm)

# Loop to fit a model for each random sample and extract the p-value of the Tempo contrasts
for (i in 1:num_sims.clmm){
  samp <- samples.clmm.long |>
    filter(sample.clmm == i)
  tryCatch(mod <- clmm(Arousal.tempo ~
                      Tempo * Solo.group * Participant.country * Music.country +
                      (1 + Tempo | Participant), data = samp),
            error = function(e) {})
  tryCatch(comp <- emmeans(mod, pairwise~Tempo),
            error = function(e) {})
  clmm.comps.aro$p[i] <- round(data.frame(comp$contrast)$p.value, 3)
  clmm.comps.aro$`Statistical significance`[i] <- ifelse(clmm.comps.aro$p[i] <= alpha.clmm,
                                                         "Significant", "Non-significant")
}

# Calculate power (proportion of simulations in which the Tempo contrast was significant)
power.clmm.aro <- sum(clmm.comps.aro$`Statistical significance` == "Significant")/num_sims.clmm

```

3.4 Achieved power

```

p5a <- ggplot(clmm.comps.den, aes(x = p, fill = `Statistical significance`)) +
  scale_fill_hue(direction = -1) +
  geom_histogram(bins = 1/alpha.clmm, breaks = seq(0, 1, alpha.clmm)) +
  labs(y = "Count", x = "p-value", title = "Density") +
  annotate("text", x = 0.5,
          y = sum(clmm.comps.den$`Statistical significance` == "Significant") * 0.9,
          label = paste0("Power = ", round(power.clmm.den, 3),
                        "\nSample size = ", sample_size.clmm,
                        " participants per country\n(6 paired responses per participant)"))

p5b <- ggplot(clmm.comps.aro, aes(x = p, fill = `Statistical significance`)) +
  scale_fill_hue(direction = -1) +
  geom_histogram(bins = 1/alpha.clmm, breaks = seq(0, 1, alpha.clmm)) +
  labs(y = "Count", x = "p-value", title = "Arousal") +
  annotate("text", x = 0.5,
          y = sum(clmm.comps.aro$`Statistical significance` == "Significant") * 0.9,
          label = paste0("Power = ", round(power.clmm.aro, 3),
                        "\nSample size = ", sample_size.clmm,
                        " participants per country\n(6 paired responses per participant)"))

p5 <- ggarrange(p5a, p5b,
               common.legend = TRUE,

```




Figure S5. Histogram of p -values for the contrasts between Tempo conditions (Low, High) for all simulations. The statistical power is the proportion of significant results. Significant results are in red.

4 Analysis script with example data

Here, using a randomly selected sample, we fit one model as if it was the data collected from the experiment. This is not only to make sure that the data are sufficient and the structure is adequate to fit the model, but to plan in advance all the code.

```

set.seed(2)
# Select a random sample
ex.data <- samples.clmm.long |>
  filter(sample.clmm == sample(1:num_sims.clmm, 1, replace = TRUE)) |>
  mutate_if(is.character, as.factor)

```

Because only the effect of Tempo was predicted and simulated *a-priori*, all other effects and interactions are completely random.

```

p6a <- ggplot(ex.data, aes(x = Tempo, y = Density.tempo,
  color = Participant.country, shape = Music.country)) +
  geom_violin(aes(group = Tempo), draw_quantiles = 0.5) +
  geom_point(position = position_dodge(0.3), size = 3) +
  geom_line(aes(group = factor(groupid)),
    linewidth = 0.5, linetype = "dashed", position = position_dodge(0.3), alpha = 0.5) +
  labs(y = "Density", x = "Tempo", title = "Density") +
  scale_x_discrete(limits = c("Low", "High")) +
  scale_size_discrete(breaks = c("Solo", "Group")) +
  theme(plot.title = element_text(face = "bold", hjust = 0.5)) +
  facet_wrap(~Solo.group)

p6b <- ggplot(ex.data, aes(x = Tempo, y = Arousal.tempo,

```



```

    color = Participant.country, shape = Music.country)) +
  geom_violin(aes(group = Tempo), draw_quantiles = 0.5) +
  geom_point(position = position_dodge(0.3), size = 3) +
  geom_line(aes(group = factor(groupid)),
    linewidth = 0.5, linetype = "dashed", position = position_dodge(0.3), alpha = 0.5) +
  labs(y= "Arousal", x = "Tempo", title = "Arousal") +
  scale_x_discrete(limits = c("Low", "High")) +
  scale_size_discrete(breaks = c("Solo", "Group")) +
  theme(plot.title = element_text(face = "bold", hjust = 0.5)) +
  facet_wrap(~Solo.group)

p6 <- ggarrange(p6a, p6b,
  common.legend = TRUE,
  legend = "bottom")
p6

```




Figure S6. Data for Density and Arousal ratings from a randomly selected, simulated sample. Dashed lines represent the within-subject effect of the Tempo manipulation.

We fitted the models with the same structure: `clmm(DV ~ Tempo * Solo.group * Participant.country * Music.country + (1 + Tempo | Participant))`. To obtain p -values that represent main effects and interactions in an ANOVA-type manner (i.e. the intercept is the grand mean of all cells, and estimates are differences between each category mean and the mean of all categories), we used *sum-to-zero* contrasts¹ (see e.g., Kaufman & Sweet, 1974; Keppel & Zedeck, 1989).

In all cases, results are for main effects and all possible interactions between Tempo (Low, High), Instrumentation (Group, Solo), Participant country (Iran, Canada, Japan), and Music country (Iran, Canada, Japan) as fixed effects, as well as random intercepts and random slopes between Tempo conditions for each participant. *High* was used as reference category for Tempo, and *Japan* for both participant and music country. Contrasted levels are in square brackets. Significant effects are in bold.

As pointed out by Lenth (2021), it is crucial to consider that ordinal models rely on estimates of a dependent

¹We did not do this for the models fitted for the power analysis, as it would not change the contrasts between Tempo conditions, but it is useful to display the full model results as we used `summary` (regression-type tables of estimates) instead on ANOVA-type tables (which are not available for models of `clmm` class).

variable (y) following a logistic distribution. However, y itself cannot be directly observed; rather, only the interval in which it lies is observable. Consequently, y is an unobserved latent variable. Thus, in order to interpret the estimates, the model also calculates the thresholds (cut points) for the ordinal levels of the dependent variable.

4.1 Visual density example model

```
# Fit Density model
options(contrasts = c("contr.sum", "contr.poly"))
model.den <- clmm(Density.tempo ~ Tempo * Solo.group * Participant.country * Music.country +
  (1 | Participant),
  data = ex.data)

# Summary table
summary.sig(model.den, "Visual density ratings model summary")
```

Table S1. *Visual density ratings model summary*

Effects	Estimate	Std. Error	z	p
Thresholds				
1 2	-2.09	0.19	-10.75	< 0.0001
2 3	-0.48	0.15	-3.16	0.0016
3 4	1.23	0.16	7.66	< 0.0001
4 5	3.38	0.26	13.02	< 0.0001
Terms				
Tempo [Low]	-0.52	0.10	-5.00	< 0.0001
Instrumentation [Group]	0.94	0.11	8.28	< 0.0001
Participant country [Canada]	0.28	0.19	1.47	0.14
Participant country [Iran]	-0.36	0.17	-2.08	0.0375
Music country [Canada]	0.09	0.14	0.65	0.51
Music country [Iran]	0.17	0.14	1.20	0.23
Tempo [Low] × Instrumentation [Group]	0.30	0.10	2.93	0.0033
Tempo [Low] × Participant country [Canada]	0.04	0.15	0.26	0.8
Tempo [Low] × Participant country [Iran]	-0.09	0.14	-0.69	0.49
Instrumentation [Group] × Participant country [Canada]	-0.45	0.15	-2.95	0.0032
Instrumentation [Group] × Participant country [Iran]	0.37	0.14	2.71	0.0068
Tempo [Low] × Music country [Canada]	-0.01	0.14	-0.07	0.95
Tempo [Low] × Music country [Iran]	0.06	0.14	0.44	0.66
Instrumentation [Group] × Music country [Canada]	0.10	0.14	0.70	0.48
Instrumentation [Group] × Music country [Iran]	0.05	0.14	0.37	0.71
Participant country [Canada] × Music country [Canada]	-0.20	0.22	-0.94	0.35
Participant country [Iran] × Music country [Canada]	-0.04	0.19	-0.21	0.83
Participant country [Canada] × Music country [Iran]	0.23	0.21	1.09	0.27
Participant country [Iran] × Music country [Iran]	-0.07	0.19	-0.35	0.73
Tempo [Low] × Instrumentation [Group] × Participant country [Canada]	-0.15	0.15	-1.02	0.31
Tempo [Low] × Instrumentation [Group] × Participant country [Iran]	0.01	0.14	0.05	0.96
Tempo [Low] × Instrumentation [Group] × Music country [Canada]	-0.06	0.14	-0.45	0.65
Tempo [Low] × Instrumentation [Group] × Music country [Iran]	-0.09	0.14	-0.64	0.52
Tempo [Low] × Participant country [Canada] × Music country [Canada]	-0.12	0.22	-0.55	0.59
Tempo [Low] × Participant country [Iran] × Music country [Canada]	-0.07	0.19	-0.36	0.72
Tempo [Low] × Participant country [Canada] × Music country [Iran]	-0.21	0.21	-0.99	0.32
Tempo [Low] × Participant country [Iran] × Music country [Iran]	-0.10	0.19	-0.53	0.59
Instrumentation [Group] × Participant country [Canada] × Music country [Canada]	-0.17	0.22	-0.80	0.42
Instrumentation [Group] × Participant country [Iran] × Music country [Canada]	0.04	0.19	0.19	0.85
Instrumentation [Group] × Participant country [Canada] × Music country [Iran]	-0.02	0.21	-0.11	0.92
Instrumentation [Group] × Participant country [Iran] × Music country [Iran]	0.05	0.19	0.27	0.79
Tempo [Low] × Instrumentation [Group] × Participant country [Canada] × Music country [Canada]	0.33	0.22	1.51	0.13
Tempo [Low] × Instrumentation [Group] × Participant country [Iran] × Music country [Canada]	-0.02	0.19	-0.09	0.93
Tempo [Low] × Instrumentation [Group] × Participant country [Canada] × Music country [Iran]	-0.59	0.21	-2.73	0.0063
Tempo [Low] × Instrumentation [Group] × Participant country [Iran] × Music country [Iran]	0.11	0.19	0.57	0.57

4.2 Arousal example model

```
# Fit Arousal model
options(contrasts = c("contr.sum", "contr.poly"))
model.aro <- clmm(Arousal.tempo ~ Tempo * Solo.group * Participant.country * Music.country +
  (1 | Participant),
```

```
data = ex.data)

# Summary table
summary.sig(model.aro, "Arousal ratings model summary")
```

Table S2. Arousal ratings model summary

Effects	Estimate	Std. Error	z	p
Thresholds				
1 2	-2.00	0.20	-9.79	< 0.0001
2 3	-0.28	0.18	-1.58	0.11
3 4	2.35	0.22	10.45	< 0.0001
4 5	4.14	0.31	13.24	< 0.0001
Terms				
Tempo [Low]	-0.37	0.10	-3.58	< 0.001
Instrumentation [Group]	1.60	0.14	11.58	< 0.0001
Participant country [Canada]	-0.30	0.22	-1.32	0.19
Participant country [Iran]	0.04	0.20	0.18	0.85
Music country [Canada]	-0.09	0.15	-0.62	0.54
Music country [Iran]	-0.13	0.15	-0.88	0.38
Tempo [Low] × Instrumentation [Group]	0.05	0.10	0.46	0.64
Tempo [Low] × Participant country [Canada]	-0.04	0.15	-0.28	0.78
Tempo [Low] × Participant country [Iran]	0.01	0.14	0.05	0.96
Instrumentation [Group] × Participant country [Canada]	-0.17	0.15	-1.09	0.28
Instrumentation [Group] × Participant country [Iran]	-0.04	0.14	-0.28	0.78
Tempo [Low] × Music country [Canada]	-0.09	0.15	-0.62	0.53
Tempo [Low] × Music country [Iran]	-0.12	0.15	-0.82	0.41
Instrumentation [Group] × Music country [Canada]	0.04	0.15	0.26	0.79
Instrumentation [Group] × Music country [Iran]	0.02	0.15	0.14	0.89
Participant country [Canada] × Music country [Canada]	0.37	0.22	1.68	0.09
Participant country [Iran] × Music country [Canada]	-0.33	0.20	-1.68	0.09
Participant country [Canada] × Music country [Iran]	-0.23	0.22	-1.07	0.29
Participant country [Iran] × Music country [Iran]	0.09	0.19	0.48	0.63
Tempo [Low] × Instrumentation [Group] × Participant country [Canada]	-0.22	0.15	-1.44	0.15
Tempo [Low] × Instrumentation [Group] × Participant country [Iran]	0.03	0.14	0.23	0.82
Tempo [Low] × Instrumentation [Group] × Music country [Canada]	0.23	0.15	1.58	0.11
Tempo [Low] × Instrumentation [Group] × Music country [Iran]	-0.39	0.15	-2.67	0.0076
Tempo [Low] × Participant country [Canada] × Music country [Canada]	-0.14	0.22	-0.63	0.53
Tempo [Low] × Participant country [Iran] × Music country [Canada]	-0.09	0.20	-0.47	0.64
Tempo [Low] × Participant country [Canada] × Music country [Iran]	0.10	0.22	0.44	0.66
Tempo [Low] × Participant country [Iran] × Music country [Iran]	0.11	0.19	0.58	0.56
Instrumentation [Group] × Participant country [Canada] × Music country [Canada]	0.42	0.22	1.90	0.06
Instrumentation [Group] × Participant country [Iran] × Music country [Canada]	-0.21	0.20	-1.04	0.3
Instrumentation [Group] × Participant country [Canada] × Music country [Iran]	-0.09	0.22	-0.42	0.67
Instrumentation [Group] × Participant country [Iran] × Music country [Iran]	0.11	0.19	0.58	0.56
Tempo [Low] × Instrumentation [Group] × Participant country [Canada] × Music country [Canada]	-0.03	0.22	-0.15	0.88
Tempo [Low] × Instrumentation [Group] × Participant country [Iran] × Music country [Canada]	-0.44	0.20	-2.24	0.0251
Tempo [Low] × Instrumentation [Group] × Participant country [Canada] × Music country [Iran]	0.24	0.22	1.09	0.28
Tempo [Low] × Instrumentation [Group] × Participant country [Iran] × Music country [Iran]	0.42	0.20	2.14	0.0324

4.3 Estimated marginal means and confidence intervals for both models

Estimated marginal means and confidence intervals for this simulation are represented in S7.

```
p7a <- emmip(model.den, Solo.group ~ Tempo | Participant.country + Music.country,
  CIs = TRUE) +
  labs(title = "Density")

p7b <- emmip(model.aro, Solo.group ~ Tempo | Participant.country + Music.country,
  CIs = TRUE) +
  labs(title = "Arousal")

p7 <- ggarrange(p7a, p7b,
  common.legend = TRUE,
  legend = "bottom")

p7
```




Figure S7. Estimated marginal means and confidence intervals for the within-subject effects of Tempo from a randomly selected, simulated sample. Columns represent data from simulated participants from each country, while rows represent the simulated response to music from each country.

4.4 Effect of Tempo

Estimated marginal mean and contrast between the levels of Tempo (Low, High) averaged over the levels of Instrumentation (`Solo.group`), participant country (`Participant.country`) and Music country (`Music.country`). To obtain the estimated distributions of the ordinal levels of the dependent variable, the argument `mode = "mean.class"` can be added to the `emmeans` function (see Lenth, 2021).

4.4.1 Visual density model

Table of estimated marginal means and contrasts between tempo conditions. All estimated marginal means and contrasts were calculated using the `emmeans` function from the `emmeans` package (Lenth, 2022).

```
tempo.contr(model.den)
```


Table S3. Estimated marginal means and contrasts between Tempo conditions

Tempo	EMM	SE	2.5%CI	97.5%CI	Contrasts				
					Contrast	Difference	SE	z	p
Low	-1.03	0.17	-1.37	-0.69	Low - High	-1.05	0.21	-5	< 0.0001
High	0.02	0.17	-0.31	0.35					

Note: EMM = estimated marginal mean.

Figure of estimated marginal means and contrasts between tempo conditions.

```
emmip(model.den, ~Tempo, CIs = TRUE)
```



4.4.2 Arousal model

Table of estimated marginal means and contrasts between tempo conditions. All estimated marginal means and contrasts were calculated using the `emmeans` function from the `emmeans` package (Lenth, 2022).

```
tempo.contr(model.aro)
```


Table S4. *Estimated marginal means and contrasts between Tempo conditions*

Tempo	EMM	SE	2.5%CI	97.5%CI	Contrasts				
					Contrast	Difference	SE	z	p
Low	-1.42	0.20	-1.81	-1.04	Low - High	-0.74	0.21	-3.58	< 0.001
High	-0.68	0.19	-1.05	-0.32					

Note: EMM = estimated marginal mean.

Figure of estimated marginal means and contrasts between tempo conditions.

```
emmip(model.aro, ~Tempo, CIs = TRUE)
```



5 Session info (for reproducibility)

```
library(pander)
pander(sessionInfo(), locale = FALSE)
```

R version 4.3.1 (2023-06-16 ucrt)

Platform: x86_64-w64-mingw32/x64 (64-bit)

attached base packages: stats, graphics, grDevices, utils, datasets, methods and base

other attached packages: pander(v.0.6.5), beepr(v.1.3), performance(v.0.10.4), kableExtra(v.1.3.4), ordinal(v.2022.11-16), emmeans(v.1.8.6), ggpubr(v.0.6.0), lubridate(v.1.9.2), forcats(v.1.0.0), stringr(v.1.5.0), dplyr(v.1.1.2), purrr(v.1.0.1), readr(v.2.1.4), tidyr(v.1.3.0), tibble(v.3.2.1), ggplot2(v.3.4.2), tidyverse(v.2.0.0) and knitr(v.1.43)

loaded via a namespace (and not attached): gtable(v.0.3.3), xfun(v.0.39), insight(v.0.19.2), rstatix(v.0.7.2), lattice(v.0.21-8), tzdb(v.0.4.0), numDeriv(v.2016.8-1.1), vctrs(v.0.6.3), tools(v.4.3.1), generics(v.0.1.3), parallel(v.4.3.1), fansi(v.1.0.4), highr(v.0.10), ucminf(v.1.2.0), pkgconfig(v.2.0.3), Matrix(v.1.5-4.1), webshot(v.0.5.4), lifecycle(v.1.0.3), farver(v.2.1.1), compiler(v.4.3.1), tinytex(v.0.45), munsell(v.0.5.0), codetools(v.0.2-19), carData(v.3.0-5), htmltools(v.0.5.5), yaml(v.2.3.7), pillar(v.1.9.0), car(v.3.1-2), MASS(v.7.3-60), abind(v.1.4-5), nlme(v.3.1-162), tidyselect(v.1.2.0), rvest(v.1.0.3), digest(v.0.6.31), mvtnorm(v.1.2-2), stringi(v.1.7.12), bookdown(v.0.34), labeling(v.0.4.2), cowplot(v.1.1.1), fastmap(v.1.1.1), grid(v.4.3.1), colorspace(v.2.1-0), cli(v.3.6.1), magrittr(v.2.0.3), utf8(v.1.2.3), broom(v.1.0.5), withr(v.2.5.0), scales(v.1.2.1), backports(v.1.4.1), timechange(v.0.2.0), estimability(v.1.4.1), rmarkdown(v.2.22), httr(v.1.4.6), audio(v.0.1-10), gridExtra(v.2.3), ggsignif(v.0.6.4), hms(v.1.1.3), evaluate(v.0.21), viridisLite(v.0.4.2), rlang(v.1.1.1), Rcpp(v.1.0.10), xtable(v.1.8-4), glue(v.1.6.2), xml2(v.1.3.4), svglite(v.2.1.1), rstudioapi(v.0.14), R6(v.2.5.1) and systemfonts(v.1.0.4)

Supplementary references

Albers, C., & Lakens, D. (2018). When power analyses based on pilot data are biased: Inaccurate effect size estimators and follow-up bias. *Journal of Experimental Social Psychology*, 74, 187–195. <https://doi.org/10.1016/j.jesp.2017.09.004>

Borders, J. C., Grande, A. A., & Troche, M. S. (2022). *Power Analysis with Ordinal Outcomes: A Tutorial*. <https://osf.io/8sc5e>

- Christensen, R. H. B. (2022). *Ordinal—regression models for ordinal data*. <https://CRAN.R-project.org/package=eordinal>
- Kaufman, D., & Sweet, R. (1974). Contrast Coding in Least Squares Regression Analysis. *American Educational Research Journal*, 11(4), 359–377. <https://doi.org/10.3102/00028312011004359>
- Keppel, G., & Zedeck, S. (1989). *Data analysis for research designs: Analysis of variance and multiple regression/correlation approaches*. W.H. Freeman.
- Lenth, R. V. (2021). *Interpreting the results of a clmm model with one independent variable - some questions*. Cross Validated. <https://stats.stackexchange.com/q/532079>
- Lenth, R. V. (2022). *Emmeans: Estimated marginal means, aka least-squares means*. <https://CRAN.R-project.org/package=emmeans>
- Taylor, J. E., Rousselet, G. A., Scheepers, C., & Sereno, S. C. (2022). Rating norms should be calculated from cumulative link mixed effects models. *Behavior Research Methods*. <https://doi.org/10.3758/s13428-022-01814-7>
- Wickham, H. (2016). *ggplot2: Elegant graphics for data analysis*. Springer-Verlag New York. <https://ggplot2.tidyverse.org>
- Wickham, H., Averick, M., Bryan, J., Chang, W., McGowan, L. D., François, R., Golemund, G., Hayes, A., Henry, L., Hester, J., Kuhn, M., Pedersen, T. L., Miller, E., Bache, S. M., Müller, K., Ooms, J., Robinson, D., Seidel, D. P., Spinu, V., ... Yutani, H. (2019). Welcome to the tidyverse. *Journal of Open Source Software*, 4(43), 1686. <https://doi.org/10.21105/joss.01686>
- Wickham, H., François, R., Henry, L., & Müller, K. (2022). *Dplyr: A grammar of data manipulation*. <https://CRAN.R-project.org/package=dplyr>
- Xie, Y. (2014). Knitr: A comprehensive tool for reproducible research in R. In V. Stodden, F. Leisch, & R. D. Peng (Eds.), *Implementing reproducible computational research*. Chapman and Hall/CRC. <https://doi.org/10.1201/9781315373461-1>
- Zhu, H. (2020). *kableExtra: Construct complex table with 'kable' and pipe syntax*. <https://CRAN.R-project.org/package=kableExtra>