

Midterm m02 Practice Exam

Created by Ajay Gandechea for
COMP 301: Foundations of Programming
Spring 2023, Section 001

March 23, 2023

Name: _____

We recommend that you set a timer for 75 minutes to complete this practice exam,
which consists of 65 points, 6 questions, and 13 pages.
Feel free to either complete this practice exam with or without the timer.
Note that on exam day, you will have 75 minutes.

BEWARE:

**This is practice exam is not comprehensive.
The structure, content, and type of questions
found on the actual exam may differ.**

**This practice exam was written *before* the actual exam was written.
This practice exam is meant to be a good study tool but not your
primary method of studying. Please make sure to study just as
you would if this practice exam did not exist.**

Good luck!

Question 1: True/False (20 points) Completely fill in the bubble next to your answer.

- | | |
|---|---|
| <p>1.1. (1 point) A subclass can implement multiple interfaces, while a subclass can only extend a single abstract class.
<input type="radio"/> True <input type="radio"/> False</p> <p>1.2. (1 point) Abstract classes can be instantiated directly, while interface cannot.
<input type="radio"/> True <input type="radio"/> False</p> <p>1.3. (1 point) Abstract classes allow for the use of access modifiers (public, private, etc.), while interfaces do not.
<input type="radio"/> True <input type="radio"/> False</p> <p>1.4. (1 point) Abstract classes can include fields and constructors, while interfaces cannot.
<input type="radio"/> True <input type="radio"/> False</p> <p>1.5. (1 point) An error can either be a compile time error or a runtime error, but not both.
<input type="radio"/> True <input type="radio"/> False</p> <p>1.6. (1 point) A program might terminate due to an uncaught checked exception.
<input type="radio"/> True <input type="radio"/> False</p> <p>1.7. (1 point) JUnit is a library to help write integration tests.
<input type="radio"/> True <input type="radio"/> False</p> <p>1.8. (1 point) The expression <code>assertEquals(a, b)</code> is always equal to <code>assertTrue(a == b)</code>.
<input type="radio"/> True <input type="radio"/> False</p> <p>1.9. (1 point) The finally block in a try-catch cannot execute unless an exception is caught.
<input type="radio"/> True <input type="radio"/> False</p> <p>1.10. (1 point) Only one catch block can be executed in a single try-catch block.
<input type="radio"/> True <input type="radio"/> False</p> | <p>1.11. (1 point) The for-each loop allows us to iterate over a collection in a more concise way than a traditional for loop.
<input type="radio"/> True <input type="radio"/> False</p> <p>1.12. (1 point) The for-each loop provides access to the current index of an iteration.
<input type="radio"/> True <input type="radio"/> False</p> <p>1.13. (1 point) Classes implementing the <i>Singleton</i> design pattern should include public constructors.
<input type="radio"/> True <input type="radio"/> False</p> <p>1.14. (1 point) We can traverse an iterable collection numerous times with different iterators.
<input type="radio"/> True <input type="radio"/> False</p> <p>1.15. (1 point) In order to create anonymous classes, we must create a new Java file.
<input type="radio"/> True <input type="radio"/> False</p> <p>1.16. (1 point) In the <i>Singleton</i> design pattern, a instance method calls on the Singleton constructor to run.
<input type="radio"/> True <input type="radio"/> False</p> <p>1.17. (1 point) Calling <code>.hasNext()</code> on an <code>Iterator<></code> object may result in a <code>NoSuchElementException</code> to be thrown.
<input type="radio"/> True <input type="radio"/> False</p> <p>1.18. (1 point) We can use the <i>Factory</i> design pattern to dynamically create instances of subclasses.
<input type="radio"/> True <input type="radio"/> False</p> <p>1.19. (1 point) In memory, the <i>Decorator</i> design pattern resembles a tree data structure.
<input type="radio"/> True <input type="radio"/> False</p> <p>1.20. (1 point) In the <i>Observer</i> design pattern, the subject maintains a list of observers.
<input type="radio"/> True <input type="radio"/> False</p> |
|---|---|

Question 2: Multiple Choice (5 points) Completely fill in the bubble next to your answer using a pencil. Each question should have exactly one filled-in bubble.

2.1. (1 point) Which of the following is a *compile-time error*?

- ☐ Running out of heap memory
- ☐ Returning a value in a `void` method
- ☐ Attempting to divide a number by 0
- ☐ Attempting to call a method on a field that is not initialized in the constructor

2.2. (1 point) Which of the following is NOT true about JUnit unit testing?

- ☐ We can run `assert` statements inside of `try/catch` blocks.
- ☐ We can use `assertArrayEquals` to easily compare two lists.
- ☐ We can test that a method returns a correct value, but not that a method throws an error.
- ☐ We should write small, specific tests that test specific functionality for a given class.

2.3. (1 point) Which of the following are true about dependency injection?

- ☐ It usually less code to write a structure that supports dependency injection compared to one that does not.
- ☐ Dependency injection supports tight coupling.
- ☐ Dependency injection allows dependencies to be changed at run-time.
- ☐ None of the above

2.4. (1 point) Which of the following structures allow us to concisely define an action without creating an explicitly-named method?

- ☐ Lambda expressions
- ☐ Factory design patterns
- ☐ Observer design patterns
- ☐ Abstract classes

2.5. (1 point) Which of the following would be a proper registration method for a class that is the subject of an observer that implements the interface `EventHandler<CreeperExplosion>`?

- ☐ `void register(CreeperExplosion ce)`
- ☐ `void register(EventHandler<CreeperExplosion> eh)`
- ☐ `void register(CreeperExplosion<EventHandler> ce)`
- ☐ `void EventHandler<CreeperExplosion> register()`
- ☐ `void CreeperExplosion register(EventHandler<CreeperExplosion> eh)`

Question 3: Fill-In-The-Blank and Long Answer (14 points) Complete the table and questions.

3.1. (6 points) Complete the following table by organizing the seven design patterns into the categories of design patterns:

Bank: *Multiton*, *Observer*, *Decorator*, *Singleton*, *Iterator*, *Factory*, *Strategy*

NOTE: Not all cells will be filled.

Creational Patterns	Structural Patterns	Behavioral Patterns
_____	_____	_____
_____	_____	_____
_____	_____	_____
_____	_____	_____
_____	_____	_____
_____	_____	_____

3.2. (4 points) List and briefly explain the four stages of software testing.

3.3. (2 points) Explain the goal of lamda expressions and anonymous classes.

3.4. (2 points) Provide a real-world example in which the Observer/Observable design pattern could be successfully used.

Question 4: Exception Code Tracing (3 points) Use the following `Exception` class definitions below to solve the following problems.

```
1 class ExA extends Exception {}
2 class ExB extends RuntimeException {}
3 class ExC extends IOException {}
4 class ExD extends ExA {}
5 class ExE extends ExC {}
6 class ExF extends ExB {}
7 class ExG extends ExE {}
8 class ExH extends ExG {}
```

4.1. (1 point) Write all of the subclasses are NOT subject to the “catch or specify” policy.

4.2. (2 points) Given `ExH`, write down all of the possible `catch` statements that could catch the exception if thrown within a `try` block.

Question 5: Code Completion (5 points) Fill in the blanks to complete the implementation of the Singleton design pattern:

```
1 public class Singleton {
2
3     /*__BLANK A__*/ Singleton instance;
4
5     /*__BLANK B__*/ Singleton() {
6         // Implementation not shown.
7     }
8
9     /*__BLANK C__*/ Singleton create() {
10         if(/*__BLANK D__*/) {
11             instance = new Singleton();
12         }
13         return /*__BLANK E__*/
14     }
15 }
```

Fill in the blanks below:

- 5.1. (1 point) Blank A: _____
- 5.2. (1 point) Blank B: _____
- 5.3. (1 point) Blank C: _____
- 5.4. (1 point) Blank D: _____
- 5.5. (1 point) Blank E: _____

Question 6: Free Response (18 points) *Minecraft*, coincidentally created in Java, is one of the most popular video games to date. This question involves implementing features for the Minecraft game.

In order to interact with blocks and creatures in a *Minecraft* world, players must use tools - including swords, pickaxes, axes, and more. For the purposes of this question, assume that we are focusing only on the *sword* tool.

Swords in Minecraft come in 6 different materials: wooden, stone, iron, gold, diamond, and netherite. Each type of sword has its own associated attack damage values and durability values. The values for each type of sword are shown below:

Sword Material	Attack Damage	Durability
Wooden	5.0	60.0
Gold	5.0	33.0
Stone	6.0	132.0
Iron	7.0	251.0
Diamond	8.0	1562.0
Netherite	9.0	2032.0

We can store the different types of swords using an **enumeration** structure with the name `ToolMaterial`, and we can represent a sword using a **class**. The implementations of this structure is shown below:

```
1  /** Enum that represents the different possible material tools. */
2  public enum ToolMaterial {
3      // TODO: Question 6.1
4  }
5
6  /** Class to model a Sword object. */
7  public class Sword implements SwordInterface {
8
9      // Material of the sword
10     private ToolMaterial toolMaterial;
11     // Damage dealt to an entity on use
12     private double attackDamage;
13     // Number of sword swings before the tool breaks
14     private double durability;
15
16     /* Initializes 'Sword' fields */
17     public Sword(ToolMaterial material, double atk, double dur) {
18         this.toolMaterial = material;
19         this.attackDamage = atk;
20         this.durability = dur;
21     }
22
23     /* GETTER Methods */
24     public ToolMaterial getMaterial() { return this.toolMaterial; }
25
26     public double getAttackDamage() { return this.attackDamage; }
27
28     public double getDurability() { return this.durability; }
29 }
```

- 6.1. (2 points) In the box below, complete the correct implementation of the `ToolMaterial` enum given the different sword materials referenced in the instructions.

- 6.2. (5 points) For the next part of this question, provide the correct implementation for a **SwordFactory** class which implements the factory design pattern. This class should provide methods to create swords of the six different types referenced in the instructions with the correct attack damage and durability values. You may name these methods whatever you like as long as they conform to the standards of the factory design pattern.

6.3. (5 points) Now that you have completed the implementation of `SwordFactory`, as any good software engineer should, you must now write tests to ensure that your class works effectively. For the sake of your wrists, you only have to write one unit test - one to test your factory's ability to create *diamond swords*.

Ensure to test for the following things:

- Ensure object was created and returned by the method.
- Ensure that the object types are correct.
- Ensure that the object field values are correct.

In the box below, complete the correct implementation of the test using `JUnit`. Assume all relevant import statements are provided.

- 6.4. (6 points) Minecraft tools are great by themselves. But, they are even better with *enchancements*. Enchantments added to tools *enhance* certain characteristics about that tool. For example, when we apply the *Sharpness* enchantment to a sword, we *increase the sword's attack damage*.

There are *five different levels* of the Sharpness Enchantment: Sharpness I - V. In game, each level becomes increasingly harder to obtain, but the reward is (usually) worth it.

In Minecraft, the formula $0.5 * \max(0, \text{level}-1) + 1.0$ specifies the **extra damage (i.e., new damage = original damage + the result of the formula)** that the sword inflicts. Assume that `level` as specified in the formula is an integer between 1 and 5.

There is also an **Unbreaking** enchantment with three levels: 1-3, which increases the *durability* of a sword. The formula for this is slightly more complex, so let's simplify it - for every level applied, the durability doubles. So, the new durability is the formula $\text{original} * (2^{\text{level}})$.

The final task of this question is to use the *Decorator* design patterns to implement two classes - **SharpnessSword** and **UnbreakingSword** respectively - which represent a sword with the enchantment applied.

For example, given a base sword `baseSword`, you can expect the following behavior:

```
1 // "Applies" the sharpness level 2 enchantment to the base sword
2 Sword sharpSword = new SharpnessSword(baseSword, 2);
3 // The following should output the adjusted attack damage
4 System.out.println(sharpSword.getAttackDamage());
5
6 // "Applies" the unbreaking level 3 enchantment to the base sword
7 Sword unbreakingSword = new UnbreakingSword(baseSword, 3);
8 // The following should output the adjusted durability (so, durability *
9   8)
9 System.out.println(unbreakingSword.getDurability());
10
11 // Sample code applying two enchantments at once
12 Sword verySharpSword = new SharpnessSword(baseSword, 5);
13 Sword opSword = new UnbreakingSword(verySharpSword, 3);
```

Hints:

- You can use `@Override` to override the respective getter methods.
- Assume the `Math` package is imported! Use `Math.max(a,b)` for max values and `Math.pow(base,exponent)` for exponents.
- In Minecraft, usually you cannot stack the same enchantment on an item (for example, applying two Unbreaking III enchantments on one item). Do not worry about implementing this protection.

*Provide the complete implementation for the **SharpnessSword** class below:*

*Provide the complete implementation for the **UnbreakingSword** class below:*

This box is ungraded. Use this as scratch paper: