



CompacOnline V2 API Quickstart

Version 1.8

Date: 13/03/2026

Compac Industries Ltd.
52 Walls Road. Penrose. Auckland 1061. New Zealand.
PO Box 12 417. Penrose. Auckland 1642. New Zealand.
Tel: +64 9 579 2094 Fax: +64 9 579 0635 info@compac.co.nz



Document Control

Revision History			
Version	Date	Author(s)	Revision Notes
1.0	6/11/2025	B Nixon	New Manual
1.1	13/11/2025	B Nixon	Corrected Authentication URL
1.3	18/11/2025	B Nixon	Updated Cards and Transaction URLs
1.5	20/11/2025	B Nixon	Added Card PIN Update
1.6	8/12/2025	B Nixon	Added Tank API
1.7	13/02/2026	I Laan	Updated Card API for Prepay Support
1.8	13/03/2026	I Laan	Amended Typos and Card Schemes

Contents

Getting started	5
Prerequisites	5
Authentication.....	5
Site ID.....	5
Organisation ID	5
Authentication Process	5
API Testing tools	5
Environments.....	5
API Headers	6
Endpoints	6
Authentication	6
Get access token.....	6
Cards.....	7
Get Cards	7
Get Card	8
Delete card	8
Create card.....	9
Update card	9
Get card pin	10
Update card pin.....	10
Delete card pin.....	11
Request card top-up	11
Get card balance transactions.....	12
Card schemas.....	12
Transactions.....	15
Get transactions.....	15
Get transaction	16
Transaction Schemas	17
Tanks	20
Get tanks	20
Get tank.....	20
Get tank statuses	21
Get tank status.....	21
Create delivery	22

Adjustment delivery	24
Get deliveries	26
Tank Schemas.....	27

Getting started

Prerequisites

Authentication

The authentication prerequisites below are required for being able to call Compac's API's:

- Client ID
- Client secret
- Subscription key

Site ID

The site ID is a required field for some API calls. It is currently not supported to be retrieved using API calls and each site will have its site ID communicated by Compac.

Organisation ID

The Organisation ID is a required field for all API calls. It is currently not supported to be retrieved using API calls and each organisation will have its organisation ID communicated by Compac.

Authentication, site and organisation information can be obtained by contacting techsupport@compac.co.nz

Authentication Process

1. The Client ID and Client secret is first used to acquire an access token
2. CompacOnline's API's can then be called using the received access token and the subscription key

API Fair Usage

There is no implemented rate limiting or throttling of requests in this service. Due to this, it is encouraged that best practices for API usage are followed, namely:

- An excessive number of requests are not sent
- The same type of data is not continually requested

The above points prevent abuse of the API, which otherwise leads to excessive resource consumption and negatively impacts system performance, slowing down the service.

API Testing tools

API testing tools are recommended to be used for validation as they have an intuitive interface and can quickly and easily post requests. Popular options include:

- Postman
- SoapUI

- Insomnia Core
- JMeter

Environments

Compac supports the following environments:

Environment	Environment specifier (ENV) for authentication (access token retrieval)	Environment specifier (ENV) for CompacOnline API's
QA	"qa"	"qa"
production	"prod"	N/A

Where the test and environments are convenient to test API functions without affecting production data. The request URL and scope (where required) feature the environment specifier. Replace "ENV" with the desired environment specifier in the documentation below.

API Headers

Except for the authentication get access token API, every API call requires the following information:

Information	Type	Key	Value	Description
Authorization	Authorization (Bearer token)	Authorization	<access token>	The access token received by the 'get access token' API
Subscription key	Header	Ocp-Apim-Subscription-Key	<subscription key>	The subscription key given by Compac

Endpoints

Unless specified below, the base URL (*BASEURL*) for end points is:

- <https://ENV.api.compaconline.com>

Note: endpoint URL's are subject to change

Authentication

Get access token	
Description	This function is given an API key and secret combination and returns a temporary access token which can be used for subsequent api calls.
URL(QA)	https://qa.accounts.compaconline.com/colqaadb2c.onmicrosoft.com/B2C_1A_SIGNIN_HRD/oauth2/v2.0/token
URL (Production)	https://accounts.compaconline.com/colprodadb2c.onmicrosoft.com/B2C_1A_SIGNIN_HRD/oauth2/v2.0/token
Method	GET

Inputs	Key	Key type	Relevance	Description
	client_id	Body (x-www-form-urlencoded)	<i>required</i>	Must contain the client ID given by Compac.
	client_secret		<i>required</i>	Must contain the client secret given by Compac.
	scope		<i>required</i>	Must contain the specified scope 'https://colENVadb2c.onmicrosoft.com/api/.default'
	grant_type		<i>required</i>	Must contain the value 'client_credentials'
Response code status	Status code			Description
	200			Access code returned okay

Cards

Card endpoints can be used to:

- Get cards associated with the organisation
- Delete cards associated with the organisation
- Update card status
- Change customer fields

Get Cards			
Description	This function returns the cards associated with the organisation		
URL	https://ENV.BASEURL/card-management/cards		
Method	GET		
Parameters			
Key	Relevance	Description	
organisationID <i>string(\$uuid)</i>	<i>required</i>	Must contain the fixed organisation identifier	
pan <i>string</i>	<i>optional</i>	Card PAN filter. Filters for the full PAN	
pan:contains <i>string</i>	<i>optional</i>	Card PAN filter. Filters for the full or partial PAN	
binRangeld <i>string(\$uuid)</i>	<i>optional</i>	Filter and retrieve cards given a specified BIN range	
siteld <i>string(\$uuid)</i>	<i>optional</i>	Filter and retrieve cards given a specified siteld	
enabled <i>boolean</i>	<i>optional</i>	Filter by enabled or disabled cards	
Responses			
Code	Description		
200	List of cards <i>itemList_cardDto</i>		
400	Invalid query (fail) <i>errorResult</i>		
401	Missing or invalid bearer token (fail) <i>errorResult</i>		
403	Insufficient permissions to perform the request (fail)		

	<i>errorResult</i>
--	--------------------

Get Card			
Description	This function returns the card associated with the organisation		
URL	https://ENV.BASEURL/card-management/cards/{id}		
Method	GET		
Parameters			
Key	Relevance	Description	
organisationID <i>string(\$uuid)</i>	<i>required</i>	Must contain the fixed organisation identifier	
Other inputs			
Path	Type	Description	
id <i>string(\$uuid)</i>	<i>URL input</i>	Card PAN filter. Filters for the full PAN. Include in URL {id} as above	
Responses			
Code	Description		
200	Card details <i>Card</i>		
400	Invalid query (fail) <i>errorResult</i>		
401	Missing or invalid bearer token (fail) <i>errorResult</i>		
403	Insufficient permissions to perform the request (fail) <i>errorResult</i>		
404	Card not found <i>errorResult</i>		

Delete card			
Description		This function deletes a card associated with the organisation	
URL		https://ENV.BASEURL/card-management/cards/{id}	
Method		DELETE	
Parameters			
Key		Relevance	Description
organisationID <i>string(\$uuid)</i>		<i>required</i>	Must contain the fixed organisation identifier
Other inputs			
Path		Type	Description
id <i>string(\$uuid)</i>		<i>URL input</i>	Must contain the card id. Include in URL {id} as above
Responses			
Code		Description	
204		The card deleted successfully	
400		Invalid card data (id/organisation id) <i>errorResult</i>	
401		Missing or invalid bearer token <i>errorResult</i>	
403		Insufficient permissions to perform the request <i>errorResult</i>	
404		Card not found	

	<i>errorResult</i>	
Create card		
Description	This function creates a card	
URL	https://ENV.BASEURL/card-management/cards	
Method	POST	
Request body		
Detail	Relevance	Description
card <i>card</i>	<i>required</i>	Must contain the card schema of the card to be created
Responses		
Code	Description	
201	The card created successfully <i>cardDto</i>	
400	Invalid card data (id/organisation id/payment plan) <i>errorResult</i>	
401	Missing or invalid bearer token <i>errorResult</i>	
403	Insufficient permissions to perform the request <i>errorResult</i>	
404	Card not found <i>errorResult</i>	

Update card		
Description	This function updates card details and can be used to enable/disable a card or change card details. Before calling, use get card (cards/{id}) to retrieve all card details and adjust details where necessary.	
URL	https://ENV.BASEURL/card-management/cards/{id}	
Method	PUT	
Request Body (JSON)		
Detail	Relevance	Description
Card card	required	The card schema containing details of the card to update
Other inputs		
Path	Type	Description
id string(\$uuid)	URL input	Must contain the card id. Include in URL {id} as above
Responses		
Code	Description	
200	The card updated successfully cardDto	
400	Invalid card data (id/organisation id) errorResult	
401	Missing or invalid bearer token errorResult	
403	Insufficient permissions to perform the request errorResult	

404	Card not found <i>errorResult</i>		
Get card pin			
Description	This function gets a card’s pin detail using its card id. While the pin itself is not returned and is replaced with “*****” for security reasons, it can be useful to check the date of the last pin change.		
URL	https://ENV.BASEURL/card-management/cards/{id}/pin		
Method	GET		
Other inputs			
Path	Type	Description	
id <i>string(\$uuid)</i>	URL input	Must contain the card id. Include in URL {id} as above	
Responses			
Code	<i>Description</i>		
200	Card pin information <i>(cardPinDto)</i>		
400	Invalid card pin data (id/organisation id) <i>errorResult</i>		
401	Missing or invalid bearer token <i>errorResult</i>		
403	Insufficient permissions to perform the request <i>errorResult</i>		
404	pin not found. <i>errorResult</i> <i>Note: This is returned after trying to call get card pin on a card which has just had its pin deleted with the delete pin API.</i>		

Update card pin			
Description	This function updates a card’s pin using its card id and desired pin. When the id is not known, first call the get cards API with an appropriate filter such as a complete PAN filter to return the cards details including id.		
URL	https://ENV.BASEURL/card-management/cards/{id}/pin		
Method	PUT		
Request Body (JSON)			
Detail		Relevance	Description
Card pin cardPinCreateUpdate		required	The card pin detail schema of the card to update
Other inputs			
Path		Type	Description
id string(\$uuid)		URL input	Must contain the card id. Include in URL {id} as above
Responses			
Code		Description	
200		The card pin updated successfully (No response body given, get card pin can later be called to check last updated time)	
400		Invalid card pin data (id/organisation id)	

	<i>errorResult</i>
401	Missing or invalid bearer token <i>errorResult</i>
403	Insufficient permissions to perform the request <i>errorResult</i>
404	Card not found <i>errorResult</i>

Delete card pin			
Description		This function deletes a card’s pin detail using its card id.	
URL		https://ENV.BASEURL/card-management/cards/{id}/pin	
Method		DELETE	
Other inputs			
Path		Type	Description
id <i>string(\$uuid)</i>		URL input	Must contain the card id. Include in URL {id} as above
Responses			
Code		<i>Description</i>	
204		Card pin deleted successfully <i>(No response body is given, if get card pin is subsequently called this will return code 404 – pin not found)</i>	
400		Invalid card pin data (id/organisation id) <i>errorResult</i>	
401		Missing or invalid bearer token <i>errorResult</i>	
403		Insufficient permissions to perform the request <i>errorResult</i>	
404		pin not found. <i>errorResult</i>	

Request card top-up			
Description	This function requests a top-up for a prepay card using its card id.		
URL	https://ENV.BASEURL/card-management/cards/{id}/balance/transactions		
Method	POST		
Request Body (JSON)			
Detail		Relevance	Description
Card Balance Transaction <code>cardBalanceTransactionCreate</code>		required	The card balance transaction detail schema of the card to update
Other inputs			
Path		Type	Description
id <i>string(\$uuid)</i>		URL input	Must contain the card id. Include in URL {id} as above
Responses			
Code		<i>Description</i>	
202		Top-up request accepted	

	<i>cardBalanceTransactionDto</i>
400	Invalid request (id/organisation id/payment plan) <i>errorResult</i>
401	Missing or invalid bearer token <i>errorResult</i>
403	Insufficient permissions to perform the request <i>errorResult</i>
404	Card not found <i>errorResult</i>

Get card balance transactions			
Description	This function returns the card associated with the organisation		
URL	https://ENV.BASEURL/card-management/cards/{id}/balance/transactions		
Method	GET		
Parameters			
Key	Relevance	Description	
organisationID <i>string(\$uuid)</i>	<i>required</i>	Must contain the fixed organisation identifier	
Other inputs			
Path	Type	Description	
id <i>string(\$uuid)</i>	<i>URL input</i>	Must contain the card id. Include in URL {id} as above	
Responses			
Code	Description		
200	List of transactions <i>itemList_cardBalanceTransactionDto</i>		
400	Invalid query <i>errorResult</i>		
401	Missing or invalid bearer token <i>errorResult</i>		
403	Insufficient permissions to perform the request <i>errorResult</i>		
404	Card not found <i>errorResult</i>		

Card schemas	
Schema	Detail
amount	<pre>amount{ value <i>number(\$double)</i> Where value string conforms to: • maximum: 99999 • minimum: 0.01 }</pre>
balanceAmount	balanceAmount{

	total <i>number(\$double)</i> available <i>number(\$double)</i> }
card	card { organisationId <i>string(\$uuid)</i> pan <i>string</i> enabled <i>boolean</i> binRangeId <i>string(\$uuid)</i> allowedOnAllSites <i>boolean</i> sites [<i>string(\$uuid)</i>] allowedAllProducts <i>boolean</i> products [<i>string(\$uuid)</i>] expiryDate <i>string</i> pin (<i>cardPin</i>) tags [<i>cardTag</i>] balance (<i>cardBalanceAmount</i>) paymentPlan <i>string</i> id <i>string(\$uuid)</i> createdDateTimeUtc <i>string(\$date-time)</i> lastUpdateDateTimeUtc <i>string(\$date-time)</i> } Note that the <i>paymentPlan</i> parameter is compulsory and sets the payment plan as either: • <i>postpay</i> if the string value is set to “<i>postpay</i>” • <i>prepay</i> if the string value is set to “<i>prepay</i>”
cardDto	cardDto { id <i>string(\$uuid)</i> organisationId <i>string(\$uuid)</i> pan <i>string</i> enabled <i>Boolean</i> binRangeId <i>string(\$uuid)</i> allowedOnAllSites <i>Boolean</i> sites [<i>string(\$uuid)</i>] allowedAllProducts <i>Boolean</i> products [<i>string(\$uuid)</i>] expiryDate <i>string</i> tags [<i>cardTag</i>] }
cardPin	cardPin { pin <i>string</i> resetRequiredOnNextUse <i>Boolean</i> lastUpdateDateTimeUtc <i>string(\$date-time)</i> }
cardTag	cardTag { key <i>string</i> value <i>string</i> } Where key and value string conform to:

	• <i>maxLength</i>: 50 • <i>minLength</i>: 1 • <i>pattern</i>: <i>^(?!)[0-9A-Za-z & _/.-]*(?<!)\$</i>
cardPinDto	<pre>cardPinDto { pin string resetRequiredOnNextUse Boolean lastUpdatedDateTimeUtc string(\$date-time) }</pre>
cardPinCreateUpdate	<pre>cardPinCreateUpdate { organisationId string(\$uuid) pin string resetRequiredOnNextUse Boolean }</pre>
cardBalanceAmount	<pre>cardBalanceAmount { total number(\$double) available number(\$double) currency (currency) lastUpdatedTimeUtc string(\$date-time) }</pre>
cardBalanceTransactionCreate	<pre>cardBalanceTransactionCreate { organisationId string(\$uuid) amount (amount) type string currency (currency) }</pre> Note that the type field is compulsory and will either: • Credit the card by the amount if set to “credit” • Debit the card by the amount if set to “debit”
cardBalanceTransactionDto	<pre>cardBalanceTransactionDto{ id string(\$uuid) organisationId string(\$uuid) cardId string(\$uuid) correlationId string(\$uuid) amount (amount) type integer(\$int32) state integer(\$int32) balance (balanceAmount) user (userInfo) currency (currency) lastUpdatedDateTimeUtc string(\$date-time) }</pre>
currency	<pre>currency { code string symbol string }</pre> Where code string conforms to: • <i>minLength</i>: 1 This is used to set currency type e.g. “AUD” for AUD, and “NZD” for NZD

	Where symbol string conforms to: • <i>minLength</i>: 1 • <i>maxLength</i>: 4 AUD and NZD use “\$”
itemList_cardBalanceTransactionDto	<pre>itemList_cardBalanceTransactionDto{ count integer(\$int32) items [cardBalanceTransactionDto] }</pre>
itemList_cardDto	<pre>itemList_cardDto { count integer(\$int32) items [cardDto] }</pre>
userInfo	<pre>userInfo{ id string(\$uuid) email string }</pre>

Transactions

Transactions endpoints can be used to:

- Download transactions for a given start-end date range.
- Download a single transaction
- Download a specified number of transactions

This functionality is achieved by calling the transactions API with varying optional parameters, acting as filters.

Get transactions		
Description	This function returns several transactions	
URL	https://ENV.BASEURL/payment-management/transactions	
Method	GET	
Parameters		
Key	Relevance	Description
organisationID <i>string(\$uuid)</i>	<i>required</i>	Must contain the fixed organisation identifier
siteID <i>string(\$uuid)</i>	<i>optional</i>	Filter by the site ID (currently given by Compac)
type <i>Integer(\$int32)</i>	<i>optional</i>	Filter by type of transaction: • 0 – Authorisation • 1 – Completion • 2 – Void
startDateTimeUtc <i>string(\$date-time)</i>	<i>optional</i>	Start time filter. Must be less than endDateTimeUtc
endDateTimeUtc <i>string(\$date-time)</i>	<i>optional</i>	End time filter. Must be greater than startDateTimeUtc

startCreatedDateTimeUtc <i>string(\$date-time)</i>	<i>optional</i>	Start time filter when transaction was first processed on CompacOnline. Must be less than endCreatedDateTime
endCreatedDateTimeUtc <i>string(\$date-time)</i>	<i>optional</i>	End time filter when transaction was first processed on CompacOnline. Must be greater than startCreatedDateTimeUtc
continuationToken <i>string</i>	<i>optional</i>	Retrieve next set of transactions not completed by the previous call. - This is required where multiple calls are required to retrieve a block of transactions. Keep consecutive calls identical, only changing the continuationToken.
limit <i>integer(\$int32)</i>	<i>optional</i>	Limit the number of transactions in the result
state <i>enum/integer(\$int32)</i>	<i>optional</i>	Filter transactions by state of the transaction: • 0 - Approved • 1 - Completed • 2 - CompletionFailed • 3 -Declined • 4 - Voided • 5 - VoidFailed
pan <i>string</i>	<i>optional</i>	Filter transactions by a given pan or card number
reference <i>string</i>	<i>optional</i>	Filter transactions by a given reference number
correlationId <i>string(\$uuid)</i>	<i>optional</i>	Filter transactions by a given correlationId to find related transactions
binRangeld <i>string(\$uuid)</i>	<i>optional</i>	Filter transactions by a given BIN range
Acquirer <i>integer(\$int32)</i>	<i>optional</i>	Filter transactions by a given acquirer • 0 - Windcave • 1 - Compac • 2 - Wex

Response code status

Status code	Description
200	List of transactions <i>paginatedList_transactionDto</i>
400	Invalid query <i>errorResult</i>
401	Missing or invalid bearer token <i>errorResult</i>
403	Insufficient permissions to perform the request <i>errorResult</i>

Get transaction

Description	This function returns a single transaction
-------------	--

URL	https://ENV.BASEURL/payment-management/transactions/{id}	
Method	GET	
Parameters		
Key	Relevance	Description
organisationID <i>string(\$uuid)</i>	<i>required</i>	Must contain the fixed organisation identifier
Other inputs		
Path	Type	Description
id <i>string(\$uuid)</i>	<i>URL input</i>	Must contain the site transaction identifier
Response code status		
Status code	Description	
200	Transaction details <i>transactionDto</i>	
400	Invalid query <i>errorResult</i>	
401	Missing or invalid bearer token <i>errorResult</i>	
403	Insufficient permissions to perform the request <i>errorResult</i>	
Transaction Schemas		
Schema	Detail	
acquirer	acquirer { name <i>integer(\$int32)</i> connecitonState <i>integer(\$int32)</i> correlationId <i>string</i> }	
amountDto	amountDto { value <i>number(\$double)</i> currentyCode <i>string</i> currency (<i>siteCurrencyDto</i>) }	
binRangeDto	binRangeDto { id <i>string(\$uuid)</i> name <i>string</i> }	
cardDto	cardDto { od <i>string(\$uuid)</i> binRange (<i>binRangeDto</i>) pan <i>string</i> type <i>integer(\$int32)</i> track2 <i>string</i> scheme <i>integer(\$int32)</i> tags (<i>cardTag</i>) }	
cardTag	cardTag { key <i>string</i> value <i>string</i> }	
errorDetail	errorDetail {	

	title <i>string</i> source <i>string</i> detail <i>string</i> }
errorResult	errorResult { statusCode <i>integer(\$int32)</i> message <i>string</i> correlationId <i>string(\$uuid)</i> dateTimeUtc <i>string(\$date-time)</i> errors (<i>errorDetail</i>) errorMessages [<i>string</i>] }
PaginatedList_transaction Dto	paginatedList_transactionDto { Count <i>integer(\$int32)</i> ContinuationToken <i>string</i> Items [<i>transactionDto</i>] }
productCodeDto	productCodeDto { internal <i>integer(\$int32)</i> }
productDto	productDto { id <i>string(\$uuid)</i> code (<i>productCodeDto</i>) name <i>string</i> hoseNumber <i>integer(\$int32)</i> amount <i>number(\$double)</i> quantity <i>number(\$double)</i> unitPrice <i>number(\$double)</i> tank (<i>tankDto</i>) unit (<i>productUnit</i>) }
<i>productUnit</i>	productUnit { name <i>string</i> symbol <i>string</i> }
<i>pumpDto</i>	PumpDto { Id <i>string(\$uuid)</i> Number <i>integer(\$int32)</i> Amount <i>number(\$double)</i> Products [<i>productDto</i>] }
siteCurrencyDto	siteCurrencyDto { code <i>string</i> symbol <i>string</i> }
siteDto	siteDto { id <i>string(\$uuid)</i> name <i>string</i> }
tankDto	tankDto {

	id <i>string(\$uuid)</i> number <i>string</i> }
<i>terminalDto</i>	TerminalDto { id <i>string(\$uuid)</i> number <i>integer(\$int32)</i> }
<i>transactionDto</i>	transactionDto { id <i>string(\$uuid)</i> messageId <i>string(\$uuid)</i> Type <i>integer(\$int32)</i> State <i>integer(\$int32)</i> OrganisationId <i>string(\$uuid)</i> Site (<i>siteDto</i>) Terminal (<i>terminalDto</i>) CorrelationId <i>string(\$uuid)</i> DateTimeUtc <i>string(\$date-time)</i> DateTimeSiteLocal <i>string(\$date-time)</i> - nullable CreateDateTimeSiteLocal <i>string(\$date-time)</i> - nullable Reference <i>string</i> Card (<i>cardDto</i>) Amount (<i>amountDto</i>) ResponseCode <i>string</i> ResponseText <i>string</i> Pumps [<i>pumpDto</i>] Receipt <i>string</i> Acquirer (<i>acquirer</i>) Odometer <i>integer(\$int32)</i> - nullable EngineHours <i>integer(\$int32)</i> - nullable OrderNumber <i>string</i> VehicleNumber <i>string</i> UserId <i>string(\$uuid)</i> Origin <i>integer(\$int32)</i> CreatedDateTimeUtc <i>string(\$date-time)</i> LastUpdatedDateTimeUtc <i>string(\$date-time)</i> }

Tanks

Tanks endpoints can be used to:

- Retrieve tanks for a given site or organisation
- Retrieve current and historical status of a specified tank
- Create or adjust tank deliveries

This functionality is achieved by calling the tanks API with varying optional parameters, acting as filters.

Get tanks		
Description	This function returns all tanks by an organisation or site	
URL	https://ENV.BASEURL/tank-management/tanks	
Method	GET	
Parameters		
Key	Relevance	Description
organisationID <i>string(\$uuid)</i>	<i>required</i>	Must contain the fixed organisation identifier
siteID <i>string(\$uuid)</i>	<i>optional</i>	Filter by the site ID (currently given by Compac)
Response code status		
Status code	Description	
200	Tank model <i>paginatedList_tankDto</i>	
400	Invalid query <i>errorResult</i>	
401	Missing or invalid bearer token <i>errorResult</i>	
403	Insufficient permissions to perform the request <i>errorResult</i>	

Get tank		
Description	This function returns tank details for a single tank given its tank Id	
URL	https://ENV.BASEURL/tank-management/tanks/{id}	
Method	GET	
Parameters		
Key	Relevance	Description
organisationID <i>string(\$uuid)</i>	<i>required</i>	Must contain the fixed organisation identifier
siteID <i>string(\$uuid)</i>	<i>optional</i>	Filter by the site ID (currently given by Compac)
Other inputs		
Path	Type	Description
id <i>string(\$uuid)</i>	<i>URL input</i>	Must contain the tank identifier
Response code status		
Status code	Description	

200	Tank model <i>paginatedList_tankDto</i>
400	Invalid query <i>errorResult</i>
401	Missing or invalid bearer token <i>errorResult</i>
403	Insufficient permissions to perform the request <i>errorResult</i>

Get tank statuses		
Description	This function returns the status of all tanks by an organisation or site	
URL	https://ENV.BASEURL/tank-management/tanks/status	
Method	GET	
Parameters		
Key	Relevance	Description
organisationID <i>string(\$uuid)</i>	<i>required</i>	Must contain the fixed organisation identifier
siteID <i>string(\$uuid)</i>	<i>optional</i>	Filter by the site ID (currently given by Compac)
continuationToken <i>string</i>	<i>optional</i>	Retrieve the next set of tank status not completed by the previous call. - This is required where multiple calls are required to retrieve a block of tank statuses. Keep consecutive calls identical, only changing the continuationToken.
Limit <i>Integer(\$int32)</i>	<i>optional</i>	Limit the number of statuses in a result
Response code status		
Status code	Description	
200	Tank statuses <i>paginatedList_tankStatusDto</i>	
400	Invalid query <i>errorResult</i>	
401	Missing or invalid bearer token <i>errorResult</i>	
403	Insufficient permissions to perform the request <i>errorResult</i>	

Get tank status		
Description	This function returns the current and historical statuses of a single tank by an organisation or site	
URL	https://ENV.BASEURL/tank-management/tanks/{id}/status	
Method	GET	
Parameters		
Key	Relevance	Description
organisationID <i>string(\$uuid)</i>	<i>required</i>	Must contain the fixed organisation identifier

continuationToken <i>string</i>	<i>optional</i>	Retrieve the next set of tank status not completed by the previous call. - This is required where multiple calls are required to retrieve a block of tank statuses. Keep consecutive calls identical, only changing the continuationToken.
Limit <i>Integer(\$int32)</i>	<i>optional</i>	Limit the number of statuses in a result
startDateTimeUtc <i>string(\$date-time)</i>	<i>optional</i>	Receive a status from a specified start time (UTC)
endDateTimeUtc <i>string(\$date-time)</i>	<i>optional</i>	Retrieve a status to a specified end time (UTC)
Other inputs		
Path	Type	Description
id <i>string(\$uuid)</i>	URL input	Must contain the tank identifier
Response code status		
Status code	Description	
200	Tank statuses <i>paginatedList_tankStatusDto</i>	
400	Invalid query <i>errorResult</i>	
401	Missing or invalid bearer token <i>errorResult</i>	
403	Insufficient permissions to perform the request <i>errorResult</i>	

Create delivery		
Description	This function creates a new tank delivery.	
URL	https://ENV.BASEURL/tank-management/tanks/{id}/deliveries	
Method	POST	
Parameters		
Key	Relevance	Description
organisationID <i>string(\$uuid)</i>	<i>required</i>	Must contain the fixed organisation identifier
Request body (JSON)		
Detail	Relevance	Description
Tank delivery details <i>tankDeliveryCreate</i>	<i>required</i>	The tankDeliveryCreate schema containing details of the tank delivery
Other inputs		
Path	Type	Description
id <i>string(\$uuid)</i>	<i>URL input</i>	Must contain the tank identifier
Response code status		
Status code	Description	
200	Tank delivery success. Returns the newly created delivery. <i>tankDeliveryDto</i>	
400	Invalid query <i>errorResult</i>	

401	Missing or invalid bearer token <i>errorResult</i>
403	Insufficient permissions to perform the request <i>errorResult</i>
404	Tank not found <i>errorResult</i>
Notes	
• A tank must first be configured with at least 1 gauge before being able to create deliveries. • The start volume must equal the current tank volume For example, to apply a +500L delivery, the start volume should equal the current volume and end volume the current volume + 500L.	
Example JSON body	
<pre>{ "organisationId": " *OID* ", "siteId": " *SID* ", "type": "Delivery", "start": { "dateTimeUtc": "2025-12-10T01:23:45.678Z", "product": { "volume": { "value": 1000, "unit": { "name": "litre", "symbol": "L" } } } }, "end": { "dateTimeUtc": "2025-12-10T01:23:45.789Z", "product": { "volume": { "value": 1200, "unit": { "name": "litre", "symbol": "L" } } } } }</pre>	

Adjustment delivery		
Description	This function can be used to manually adjust a tanks current volume.	
URL	https://ENV.BASEURL/tank-management/tanks/{id}/deliveries	
Method	POST	
Parameters		
Key	Relevance	Description
organisationID <i>string(\$uuid)</i>	<i>required</i>	Must contain the fixed organisation identifier
Request body (JSON)		
Detail	Relevance	Description
Tank delivery details <i>tankDeliveryCreate</i>	required	The tankDeliveryCreate schema containing details of the tank delivery
Other inputs		
Path	Type	Description
id <i>string(\$uuid)</i>	<i>URL input</i>	Must contain the tank identifier
Response code status		
Status code	Description	
200	Tank adjustment success. Returns the newly created adjustment. <i>tankDeliveryDto</i>	
400	Invalid query <i>errorResult</i>	
401	Missing or invalid bearer token <i>errorResult</i>	
403	Insufficient permissions to perform the request <i>errorResult</i>	
404	Tank not found <i>errorResult</i>	
Notes		
• A tank must first be configured with at least 1 gauge before being able to create deliveries. • The start volume must equal the current tank volume. • The end volume must equal the desired tank volume.		
Example JSON body		
<pre>{ "organisationId":"OID", "siteId":"SID", "type":"Adjustment", "start": { "dateTimeUtc":"2025-12-10T01:23:45.678Z", "product": { "volume": { "value":1200, "unit": { "name":"litre", "symbol":"L" } } } } }</pre>		

```
    },  
    "end": {  
      "dateTimeUtc": "2025-12-10T01:23:45.789Z",  
      "product": {  
        "volume": {  
          "value": 1300,  
          "unit": {  
            "name": "litre",  
            "symbol": "L"  
          }  
        }  
      }  
    }  
  }  
}
```

Get deliveries		
Description	This function returns tank deliveries for a single tank given its tank Id	
URL	https://ENV.BASEURL/tank-management/tanks/{id}/deliveries	
Method	GET	
Parameters		
Key	Relevance	Description
organisationID <i>string(\$uuid)</i>	<i>required</i>	Must contain the fixed organisation identifier
Other inputs		
Path	Type	Description
id <i>string(\$uuid)</i>	<i>URL input</i>	Must contain the tank identifier
Response code status		
Status code	Description	
200	Tank delivery details. <i>tankDeliveryDto</i>	
400	Invalid query <i>errorResult</i>	
401	Missing or invalid bearer token <i>errorResult</i>	
403	Insufficient permissions to perform the request <i>errorResult</i>	
404	Tank not found <i>errorResult</i>	

Tank Schemas	
Schema	Detail
capacityUnit	capacityUnit { name <i>integer(\$int32)</i> symbol <i>string</i> }
capacity	capacity { value <i>number(\$double)</i> unit <i>capacityUnit</i> }
safeFillCapacity	safeFillCapacity { value <i>number(\$double)</i> unit <i>capacityUnit</i> }
tankDto	tankDto { id <i>string(\$uuid)</i> organisationId <i>string(\$uuid)</i> siteId <i>string(\$uuid)</i> number <i>integer(\$int32)</i> productId <i>string(\$uuid)</i> capacity <i>capacity</i> safeFillCapacity <i>safeFillCapacity</i> gauges [<i>gauge</i>] }
PaginatedList_tankDto	paginatedList_tankDto { count <i>integer(\$int32)</i> continuationToken <i>string</i> items [<i>tankDto</i>] }
tankUpdate	tankUpdate { organisationId <i>string(\$uuid)</i> number <i>integer(\$int32)</i> productId <i>string(\$uuid)</i> capacity <i>capacity</i> safeFillCapacity <i>safeFillCapacity</i> gauges [<i>gauge</i>] }
calibrationPoint	calibrationPoint { current <i>number(\$double)</i> correspondingValue <i>number(\$double)</i> }
calibrationPointValueUnit	calibrationPointValueUnit { name <i>integer(\$int32)</i> correspondingValue <i>number(\$double)</i> }
calibration	calibration { currentUnit <i>currentUnit</i> correspondingValueUnit <i>calibrationPointValueUnit</i> points [<i>calibrationPoint</i>] }

sensorReadingUnit	sensorReadingUnit { name <i>integer(\$int32)</i> symbol <i>string</i> }
strappingPointValueUnit	strappingPointValueUnit { name <i>integer(\$int32)</i> symbol <i>string</i> }
Strapping	Strapping { sensorReadingUnit sensorReadingUnit correspondingValueUnit strappingPointValueUnit points [<i>strappingPoint</i> <i>Min=1, Max=50</i>]
gauge	gauge { type <i>integer(\$int32)</i> measuringCapabilities <i>integer(\$int32)</i> channel <i>integer(\$int32)</i> calibration <i>calibration</i> strapping <i>strapping</i> }
volumeUnit	volumeUnit { name <i>integer(\$int32)</i> symbol <i>string</i> }
Volume	Volume { Value <i>number(\$double)</i> temperatureCompensatedValue <i>number(\$double)</i> <i>nullable:true</i> unit <i>volumeUnit</i> }
heightUnit	heightUnit { name <i>integer(\$int32)</i> symbol <i>string</i> }
height	height { Value <i>number(\$double)</i> Unit <i>heightUnit</i> }
product	product { volume <i>volume</i> height <i>height</i> }
currentUnit	currentUnit { name <i>integer(\$int32)</i> symbol <i>string</i> }
temperatureUnit	temperatureUnit { name <i>integer(\$int32)</i> symbol <i>string</i> }
Temperature	Temperature { Value <i>number(\$double)</i>

	Unit <i>temperature</i> Unit }
current	Current { Value <i>number(\$double)</i> Unit <i>current</i> Unit }
water	water { volume <i>volume</i> height <i>height</i> }
tankStatusDto	tankStatusDto { id <i>string(\$uuid)</i> organisationId <i>string(\$uuid)</i> productId <i>string(\$uuid)</i> siteId <i>string(\$uuid)</i> number <i>integer(\$int32)</i> capacity <i>capacity</i> status <i>integer(\$int32)</i> gauges [<i>gauge</i>] product <i>product</i> water <i>water</i> ullage <i>volume</i> current <i>current</i> temperature <i>temperature</i> messages [<i>message</i>] dateTimeUtc <i>string(\$date-time)</i> }
PaginatedList_tankStatusD to	paginatedList_tankStatusDto { count <i>integer(\$int32)</i> continuationToken <i>string</i> items [<i>tankStatusDto</i>] }
Tank	Tank { organisationId <i>string(\$uuid)</i> siteId <i>string(\$uuid)</i> number <i>integer(\$int32)</i> productId <i>string(\$uuid)</i> capacity <i>capacity</i> safeFillCapacity <i>safeFillCapacity</i> gauges [<i>gauge</i>] id <i>string(\$uuid)</i> createdDateTimeUtc <i>string(\$date-time)</i> lastUpdatedDateTimeUtc <i>string(\$date-time)</i> _etag <i>string</i> (<i>nullable:true</i>) }
tankCreate	tankCreate { organisationId <i>string(\$uuid)</i> siteId <i>string(\$uuid)</i> number <i>integer(\$int32)</i> productId <i>string(\$uuid)</i>

	capacity <i>capacity</i> safeFillCapacity <i>safeFillCapacity</i> gauges [<i>gauge</i>] }
message	message { text <i>string</i> level <i>integer(\$int32)</i> }
errorDetail	errorDetail { title <i>string</i> source <i>string</i> detail <i>string</i> }
errorResult	errorResult { statusCode <i>integer(\$int32)</i> message <i>string</i> correlationId <i>string(\$uuid)</i> dateTimeUtc <i>string(\$date-time)</i> errors (<i>errorDetail</i>) errorMessages [<i>string</i>] }
deliveryPoint	deliveryPoint { dateTimeUtc <i>string(\$date-time)</i> product <i>product</i> water <i>water</i> temperature <i>temperature</i> }
tankDeliveryCreate	tankDeliveryCreate { organisationId <i>string(\$uuid)</i> siteId <i>string(\$uuid)</i> type <i>enum/integer(\$int32)</i> "delivery" start <i>deliveryPoint</i> end <i>deliveryPoint</i> }
tankDeliveryDto	tankDeliveryDto { id <i>string(\$uuid)</i> organisationId <i>string(\$uuid)</i> siteId <i>string(\$uuid)</i> tankId <i>string(\$uuid)</i> type <i>integer(\$int32)</i> source <i>integer(\$int32)</i> start <i>deliveryPoint</i> end <i>deliveryPoint</i> }
Enum definitions	
tankDeliveryCreate – "type"	type { "Delivery", "Adjustment" }

