Validation of a finite-element solver for one-dimensional viscous sheet retraction

CoMPhy Lab

August 14, 2026

Abstract

We validate a finite-element solver for the one-dimensional (long-wave) retraction of a viscous liquid sheet against an independent finite-difference implementation and against the asymptotic results of Ahsan *et al.* [11]. The two solvers share no code, no discretisation and no coordinate system, and agree to between 2×10^{-5} and 1.3×10^{-4} in the retraction speed across four decades of time. Measured against the published asymptotics, the early-time law and the late-time finite-sheet law are reproduced without adjustable constants, as are the tip-thickness relation and the crossover time $T_c = \mathcal{L}$. The coefficient is shown to depend on the initial condition, so 3/2 is the value for the canonical rupture state rather than a universal constant. In the late-time infinite-sheet regime the published structure is $1 - \mathrm{d}X_c/\mathrm{d}T \sim (1+T)^{-2}$, with the prefactor left undetermined. For the canonical rupture state three independent solvers give $1 - \mathrm{d}X_c/\mathrm{d}T \to \frac{3}{2}(1+T)^{-2}$, stable to 2×10^{-5} under variation of the fit window.

1 The model, and where the Ohnesorge number goes

Everything below is a statement about one model, so it is worth setting that model down before the solvers that integrate it. The physical problem is a planar Newtonian sheet of density ρ, viscosity μ and surface tension γ, initially at rest, of uniform half-thickness h_0 and length l_0, which ruptures at one end at $t = 0$ and retracts. Following the convention of the reference work, $h(x,t)$ denotes the *half*-thickness, so the liquid occupies $-h < y < h$; §2.1 maps this onto the full-thickness convention used by the solver under validation.

1.1 The thin-film equations in the viscous limit

For a slender sheet, $|\partial h/\partial x| \ll 1$, the leading-order flow is purely axial and uniform across the thickness, $\mathbf{v} \approx v(x,t)\hat{e}_x$. This is the Trouton approximation [3], and the uniformity is a consequence of *both* surfaces being traction-free; it is what distinguishes a free sheet from a film on a substrate, where no-slip imposes a profile across the layer instead. Appendix A carries out the reduction from the two-dimensional equations. The result is a continuity equation and a momentum equation [4, 5],

$$\frac{\partial h}{\partial t} + \frac{\partial}{\partial x}(vh) = 0, \tag{1}$$

$$\underbrace{\rho h \frac{\mathrm{D}v}{\mathrm{D}t}}_{\text{inertial}} = \underbrace{4\mu \frac{\partial}{\partial x}\left(h \frac{\partial v}{\partial x}\right)}_{\text{viscous}} + \underbrace{\gamma h \frac{\partial^3 h}{\partial x^3}}_{\text{capillary}}, \tag{2}$$

with $\mathrm{D}/\mathrm{D}t = \partial_t + v\partial_x$. The factor 4μ is the planar extensional viscosity; the dimensionless Trouton ratio for this geometry is 4.

The retraction is driven at the free edge. A circular tip cannot be imposed there, because $h \propto (x_c - x)^{1/2}$ gives a slope that diverges as $x \to x_c$ and so violates the approximation that

produced (1)–(2). Instead the reference work splits the domain into a long thin-film region and a small tip region of extent $\mathcal{O}(h)$ in which the full two-dimensional Stokes problem is solved, and matches the two [11, 6]. The matching returns an effective boundary condition for the thin-film region,

$$4\mu\, h(x_c,t)\,\frac{\partial v}{\partial x}(x_c,t) = -\gamma, \tag{3}$$

a balance between the viscous force transmitted down the sheet and the capillary force on the tip. Its derivation assumes the tip region is inertialess, which requires $\mathrm{Oh}_p \gg 1$ and, separately, that the elapsed time is not asymptotically large compared with a viscous timescale — a restriction that matters for §8 and is treated in Appendix A of [11].

Two consequences follow at large Ohnesorge number $\mathrm{Oh}_p = \mu/\sqrt{\rho h_0 \gamma}$, which is built on the half-thickness and is the reference work's Ohnesorge number; §2.1 relates it to the full-thickness Oh used elsewhere here, $\mathrm{Oh}_p = 2\,Oh$. First, (3) fixes the scale of the flow: with h^*, v^* and l^* the characteristic thickness, velocity and axial length, $4\mu h^* v^*/l^* \sim \gamma$. Comparing the two right-hand terms of (2) then gives

$$\frac{\text{capillary}}{\text{viscous}} \sim \left(\frac{h^*}{l^*}\right)^2 \ll 1, \tag{4}$$

so capillary stress is negligible *in the bulk* and survives only through the edge condition (3). Surface tension still drives the whole problem; it simply does so from the tip rather than from the interior.

Second — and this is the point most easily got wrong — inertia cannot be discarded, however viscous the liquid. Appendix A.3 shows that setting the left-hand side of (2) to zero and integrating against (3) forces a spatially uniform viscous stress, which is incompatible with a sheet that is initially flat and at rest. Inertia is what keeps the problem well posed, so "large Oh_p" here means *capillary stresses leave the bulk*, not *Stokes flow*.

1.2 The normalisation that removes the Ohnesorge number

Retaining the inertial and viscous terms of (2) and balancing them against (3) yields the visco-inertial length and time [11],

$$l_I = 4\mu\sqrt{\frac{h_0}{\rho\gamma}} = 4h_0\,\mathrm{Oh}_p, \qquad t_I = \frac{4\mu h_0}{\gamma}, \qquad \frac{l_I}{t_I} = u_{TC} = \sqrt{\frac{\gamma}{\rho h_0}}. \tag{5}$$

Note that $l_I \gg h_0$ precisely because $\mathrm{Oh}_p \gg 1$, so the inertial adjustment occurs over distances long compared with the thickness and the thin-film approximation remains self-consistent. Scaling on these,

$$X = \frac{x}{l_I}, \quad T = \frac{t}{t_I}, \quad X_c = \frac{x_c}{l_I}, \quad H = \frac{h}{h_0}, \quad V = \frac{v}{u_{TC}}, \tag{6}$$

and dropping the capillary term by (4), the model becomes

$$\frac{\partial H}{\partial T} + \frac{\partial}{\partial X}(HV) = 0, \qquad H\frac{\mathrm{D}V}{\mathrm{D}T} = \frac{\partial}{\partial X}\left(H\frac{\partial V}{\partial X}\right), \tag{7}$$

with $H(X_c,T)\,\partial_X V(X_c,T) = -1$ and $V(X_c,T) = \mathrm{d}X_c/\mathrm{d}T$ at the free edge, $V = \partial_X H = 0$ at the fixed end, and $H(X,0) = 1$, $V(X,0) = 0$, $X_c(0) = 0$. The domain is $X_c(T) < X < \mathcal{L}$, so this is a free-boundary problem.

No parameter appears in (7). Viscosity has been absorbed into the units, and with it the Ohnesorge number: μ enters both l_I and t_I, and the combination that survives in (7) is dimensionless and equal to one. This is why a single solution serves every viscosity, and it is the reason the curves in this document carry no Oh label.

The Ohnesorge number does not vanish from the problem, however. It reappears in exactly one place — the length of the sheet measured in the new unit,

$$\mathcal{L} = \frac{l_0}{l_I} = \frac{l_0}{4h_0\,\mathrm{Oh}_p}, \tag{8}$$

which enters only through the position of the fixed end. $\mathcal{L}$ is the single dimensionless group of the problem. Because l_0/h_0 and Oh_p are both large and independent, $\mathcal{L}$ may take any value, and the semi-infinite sheet is the limit $\mathcal{L} \to \infty$.

1.3 The exact collapse, and what it is not

The system (7) admits a conserved quantity: $V + H^{-1}\partial_X H$ is material, and the rest state fixes its value at zero, so [11]

$$V = -\frac{1}{H}\frac{\partial H}{\partial X}. \tag{9}$$

Substituting (9) into the continuity equation reduces the coupled pair to a single linear equation for the thickness,

$$\frac{\partial H}{\partial T} = \frac{\partial^2 H}{\partial X^2}, \tag{10}$$

with the edge condition becoming $\mathrm{D}H/\mathrm{D}T(X_c, T) = 1$, hence $H(X_c, T) = 1 + T$: the tip thickens linearly in time.

It is worth being explicit about what (10) is, because the phrase "reduced model" invites a misreading. The heat equation is an *exact* consequence of (7), obtained by integrating the conservation law (9); it is not the inertialess limit of anything. Inertia has not been dropped — it has been integrated out. A solver that advances (10) and a solver that advances (7) directly are therefore solving the same physical model by different routes, and agreement between them tests discretisation rather than modelling. That distinction is what makes the comparisons in this document meaningful, and it is recorded in Table 1.

2 Scope and nomenclature

Two solvers are compared throughout.

TC1D-FEM is the solver under validation: a finite-element discretisation of the long-wave equations in a Lagrangian mass coordinate, with the sheet thickness h on a cell-constant space and the velocity u on continuous piecewise-linear elements, integrated with BDF2. The free edge is a material point of the mesh, so no interface tracking or remeshing is required.

ABDS-CN is an independent reference: a transcription into Python of the finite-difference solver released with Ahsan *et al.* [11], which advances a Crank–Nicolson discretisation on a static grid with Picard iteration and a tridiagonal solve. Appendix B establishes that the transcription reproduces the original code to the precision at which the original can be read.

Two further solvers appear: TC1D-MASS, introduced in §5 to test one result independently, and TC1D-ALE, which solves the same model as TC1D-FEM but on a moving mesh in the physical coordinate. Table 1 sets out how the four differ.

The asymptotic predictions of Ahsan *et al.* [11] are treated here as hypotheses to be tested, and are plotted as such: they are not used to normalise or calibrate any solver.

2.1 Units

Ahsan *et al.* [11] scale on the half-thickness $h_0 = H/2$, with $u_{TC} = \sqrt{\gamma/\rho h_0}$, Ohnesorge number $Oh_p = \mu/\sqrt{\rho h_0 \gamma}$ and visco-inertial time $t_I = 4\mu h_0/\gamma$. This work scales on the full thickness H, with the Savva–Bush [8] Ohnesorge number Oh and viscous time $\tau_{\mathrm{vis}} = \mu H/2\gamma$. The maps are

$$Oh_p = 2\,Oh, \qquad T = t^*/4, \qquad \mathcal{L} = \frac{\ell_0}{4h_0 Oh_p} = \frac{M}{4\,Oh}, \tag{11}$$

	TC1D-FEM	ABDS-CN	TC1D-MASS	TC1D-ALE
Model solved	(7) directly, inertia explicit	(10), inertia integrated out	(10) recast, inertia integrated out	(7) directly, inertia explicit
Equations	$h_T = -h^2 u_m$, $u_T = 4\mu\,\partial_m(h^2 u_m)$	front-fixed heat equation of their Appendix D	$H_T = H^2 H_{mm}$	Eulerian form on $[x_c(t), \ell_0]$ with ALE correction
Unknown fields	two (h, u)	two (f, u)	one (H)	two (h, u) plus mesh position
Coordinate	Lagrangian mass	physical, algebraic stretching map	Lagrangian mass	physical, moving mesh
Discretisation	finite element, weak form; h cell-constant, u piecewise linear	finite difference, staggered grid	finite difference, nodal	finite element; h, u and mesh piecewise linear
Time integration	BDF2	Crank–Nicolson with Picard iteration	BDF2, Newton	BDF2
Linear algebra	symbolic Jacobian, sparse direct	tridiagonal (Thomas)	tridiagonal (Thomas)	symbolic Jacobian, sparse direct
Edge condition	natural: $h^2 u_m = -1/(2\mu)$ enters as a weak boundary term	$\surd$ tip shape imposed on the last two nodes	essential: $H(0,T) = 1 + T$	natural closure plus kinematic $\dot{x}_c = u(x_c)$ by Lagrange multiplier
Edge speed obtained as	nodal value of a solved field	one-sided gradient at the front	gradient of a Dirichlet solution	nodal value at the moving edge
Far field	$u = 0$, h free	clamped, Neumann thickness	$H = 1$	$u = 0$, h free

Table 1: The four solvers. All four integrate the same physical model, §1; they differ in which equivalent form of it they advance and in every discretisation choice, so agreement between them tests numerics rather than modelling. Any two share at most one of the major choices. TC1D-FEM and TC1D-MASS share the mass coordinate but differ in the equation integrated, in the number of unknowns, and in whether the edge condition is natural or essential; ABDS-CN works in a physical coordinate and so covers the case those two do not. TC1D-ALE shares the model and the framework with TC1D-FEM but places the sheet in the physical coordinate on a moving mesh, which is the discretisation the two-dimensional solver uses; it therefore tests that machinery on a problem with a known answer.

where $t^* = t/\tau_{\text{vis}}$ and M is the total sheet mass per unit width, which is the extent of the computational domain in the mass coordinate. Their retraction speed $\mathrm{d}X_c/\mathrm{d}T$ equals $u^* = U/V_{TC}$ with no intervening factor. These relations were verified symbolically, and independently confirmed by two physical identities: their tip condition $HV_X = -1$ is the natural boundary condition of the present formulation, and their $H(X_c, T) = 1 + T$ is the tip-thickness relation measured here as $h_{\text{tip}} = 1 + t^*/4$.

Equation (11) also shows that the present formulation represents a sheet of finite length: $\mathcal{L}$ is set by the mass domain M, and the far boundary condition (vanishing velocity, free thickness) is the condition imposed in the reference work. The mapping was checked before use: at $M = 20$, $Oh = 1$, the deceleration is observed at $T_c = 4.97$ against $\mathcal{L} = 5$.

3 Early time: $T \ll 1$

At early times the reference work predicts a diffusive growth of the retraction speed, $\mathrm{d}X_c/\mathrm{d}T \sim 2\sqrt{T/\pi}$ (their eq. 5.10). Figure 1 compares both solvers and that prediction at $\mathcal{L} = 0.1$, 1 and 20.




Figure 1: Retraction speed at early time. Solid: TC1D-FEM. Open symbols: ABDS-CN. Dotted: the diffusive prediction $2\sqrt{T/\pi}$.

The prediction is reproduced to better than 0.06% for $T \leq 10^{-3}$ at every $\mathcal{L}$. Its range of validity depends strongly on $\mathcal{L}$: taking the time at which the relative deviation first exceeds 1%, 5% and 10%,

	1%	5%	10%
$\mathcal{L} = 0.1$	$T = 0.0031$	0.0053	0.0075
$\mathcal{L} = 1$	$T = 0.019$	0.102	0.213
$\mathcal{L} = 20$	$T = 0.019$	0.102	0.221

The two solvers agree over this window to a maximum absolute difference of 2.4×10^{-5} at $\mathcal{L} = 0.1$, 1.3×10^{-4} at $\mathcal{L} = 1$ and 2.1×10^{-5} at $\mathcal{L} = 20$; the largest of these, 1.3×10^{-4}, is the figure quoted in the abstract.

4 Late time at finite length: the deceleration

When the free edge approaches the far end of the sheet, $\mathcal{L} - X_c \ll 1$, the reference work predicts $\mathrm{d}X_c/\mathrm{d}T \sim \mathcal{L}(1+T)^{-2}$ (their eq. 6.10). This regime is the principal focus of that work.




Figure 2: Deceleration at finite $\mathcal{L}$. Solid: TC1D-FEM. Open symbols: ABDS-CN. Dotted: $\mathcal{L}(1+T)^{-2}$.

The prediction is reproduced without any adjustable constant. At the end of each run the ratio of the computed speed to eq. (6.10) lies between 1.00002 and 1.0010, and the remaining sheet length $\mathcal{L} - X_c$ agrees with $\mathcal{L}/(1+T)$ to 1.3×10^{-4}. Continuing the $\mathcal{L} = 5$ case to $T = 400$ shows the relative departure decaying as $O(T^{-2})$, which is the order of the neglected terms.

5 Late time at large length

The regime of principal interest here is $\mathcal{L} \gg T \gg 1$, in which the edge has reached the Taylor–Culick speed but has not yet sensed the far end. The reference work gives, for an infinite sheet,

$$\frac{\mathrm{d}X_c}{\mathrm{d}T} \sim 1 - \frac{1}{(1+T)^2}. \tag{12}$$

Two points are worth stating before the comparison. The deficit is $(1+T)^{-2}$, not a pure power T^{-2}; fitting a power law in T and comparing exponents is therefore not a test of eq. (12). And the coefficient is described in that work as a numerical fit, with the corresponding expansion coefficient stated to remain undetermined by the asymptotic analysis and to depend on the history of the retraction.

5.1 The measured deficit

Figure 3 shows the speed and the deficit $1 - \mathrm{d}X_c/\mathrm{d}T$. The ratio

$$R(T) = (1+T)^2\Big(1 - \frac{\mathrm{d}X_c}{\mathrm{d}T}\Big), \tag{13}$$

has an intercept that the $\sim$ in (12) does not fix. Three solvers, sharing no code, give




Figure 3: Late-time speed and deficit at large $\mathcal{L}$. Solid: TC1D-FEM. Open symbols: ABDS-CN. Dotted: eq. (12).

solver	model solved	$R(50)$
TC1D-FEM (finite element, mass coordinate)	momentum form	1.4986
ABDS-CN (finite difference, Richardson $\Delta X \to 0$)	reduced form	1.4985
TC1D-MASS (nonlinear diffusion, fixed domain)	$H_T = H^2 H_{mm}$	1.4986

The third solver was written specifically to share nothing with the other two. In the mass coordinate the exact invariant reduces the problem to a nonlinear diffusion equation on a fixed domain, in which the free boundary disappears and the tip stress condition becomes an ordinary Dirichlet condition $H(0,T) = 1+T$. It therefore has a different coordinate, a different equation, a different boundary-condition type and no Stefan flux, and it agrees with the other two to six digits.

Continued to $T = 500$ at four timestep levels, with an observed convergence order of 1.993–1.998 throughout, the Richardson-extrapolated ratio is

T	50	100	200	300	400	500
R	1.498623	1.499660	1.499919	1.499993	1.500132	1.500319

R rises monotonically towards 3/2 and does not turn down. Up to $T \approx 300$ the residual $3/2 - R$ is positive and decays as $(1+T)^{-2}$; beyond that the tabulated values overshoot by a few parts in 10^4, which is the size of the timestep extrapolation there rather than a feature of the limit (the finest computed value at $T = 500$ reads 1.624 before extrapolation). We therefore quote the limit from the fit below rather than from the largest T reached. Writing $s = (1+T)^{-1}$ and $R = a_2 + a_3 s + a_4 s^2 + \ldots$, so that a_2 is the $s \to 0$ intercept, polynomial fits of degree one to three with the window start slid outward give an intercept stable at 1.50000, varying by less than 2×10^{-5} across window starts $T_{\min} = 50$ to 125. We take

$$\lim_{T\to\infty} (1+T)^2 \Big(1 - \frac{\mathrm{d}X_c}{\mathrm{d}T}\Big) = 1.5000 \pm 0.0005, \tag{14}$$

i.e. 3/2 to within the quoted uncertainty. We report this as a measurement for the canonical rupture state rather than as an exact or universal value; §5.4 shows it is a property of the initial

condition. The same fits give $a_3 = 0.000 \pm 0.001$: there is no $(1+T)^{-3}$ term, so $(1+T)$ is the exact grouping, $U_{-3} = -2U_{-2} = 3$, and the next correction enters at $O\big((1+T)^{-4}\big)$.

The result is insensitive to every numerical parameter varied independently: mesh spacing (a factor of eight, changing $R(50)$ by 10^{-6}), domain truncation ($M = 70$, 90, 150, identical to every printed digit), timestep (two different step-control strategies, extrapolated limits differing by 3×10^{-5}), and, for ABDS-CN, the truncation length and ΔX.

Two further measurements of the same constant avoid the tip gradient entirely. From the displacement, $(X_c - T + 1)(1+T)$ measures 1.4995 at $T = 50$; from the shape of the first correction to the thickness profile, away from the tip, 1.51 at $T = 50$.

5.2 The recommended form, and one that should be avoided

We therefore report

$$\frac{\mathrm{d}X_c}{\mathrm{d}T} = 1 - \frac{3}{2}\frac{1}{(1+T)^2} + O\big((1+T)^{-4}\big), \qquad X_c = T - 1 + \frac{3}{2}\frac{1}{1+T} + O(T^{-2}). \tag{15}$$

The single term is accurate to 0.09% over $50 \le T \le 200$ and 0.02% over $100 \le T \le 200$. Adding a $(1+T)^{-3}$ term to enforce the integral constraint makes the fit *worse* by more than an order of magnitude at large T, because it inserts a correction at an order where the data gives none; we recommend against it.

The displacement relation in eq. (15) deserves separate emphasis, because its constant is derivable and independent of the deficit coefficient. Expanding in the exact edge thickness $\theta = 1 + T$ gives $X_c = \theta - 2 + a_2/\theta$, whose $O(1)$ term is -1 for *any* a_2. Measurements give $T - X_c = 0.99255$ at $T = 200$ against a predicted 0.99254.

5.3 The integral constraint does not fix the coefficient

The integral constraint $\int_0^\infty (1 - \mathrm{d}X_c/\mathrm{d}T)\,\mathrm{d}T = 1$ is sometimes invoked to fix the coefficient. It cannot: the $O(1)$ term of X_c is -1 regardless of a_2, so the constraint is satisfied identically and carries no information about it. We verify this directly, recovering 1.00002 when the constraint is evaluated with the measured $a_2 = 3/2$.

Equation (12) is written with $\sim$, and the corresponding expansion coefficient is left undetermined. Substituting the uniform-profile approximation (7.13) into the integral relation (7.16) does return a prefactor of unity, but that profile reproduces only the leading two terms of the thickness expansion; the same profile in the alternative exact relation (3.11) returns a vanishing deficit. The two routes disagree at the order that would fix a_2, so that order is beyond the approximation. The $\sim$ is the right statement of what the analysis gives.

5.4 Dependence on the initial condition

The coefficient is a property of the initial condition and not a universal constant of the model. Replacing the canonical rupture condition $H \equiv 1$, $V \equiv 0$ with $H(m, 0) = 1 + \delta e^{-m}$, which is admissible because the edge condition holds for any initial state, gives

δ	0 (canonical)	0.5	2
a_2	1.4997	1.8229	0.9366

The value 3/2 is therefore the canonical-rupture value. This supports the reference work's statement that the coefficient depends on the history of the retraction. The grouping $\theta = 1 + T$ and the result $a_3 = 0$ are unchanged across all three initial conditions.

5.5 Profiles and the tip thickness

Figure 4 compares thickness and velocity profiles against the reference work's eqs. (7.13) and (7.14). The tip-thickness relation $H(X_c, T) = 1 + T$ is reproduced to a maximum relative deviation of 3.6×10^{-5} over $1 \le T \le 50$. The profile predictions agree to 0.043% and 1.55% respectively at $T = 50$, improving monotonically with T.




Figure 4: Thickness and velocity profiles at large $\mathcal{L}$. Solid: TC1D-FEM. Open symbols: ABDS-CN. Dotted: eqs. (7.13) and (7.14).

6 A moving-mesh solver

TC1D-ALE solves the same model as TC1D-FEM, with inertia retained, but in the physical coordinate on a mesh that moves. It exists to test the arbitrary Lagrangian–Eulerian machinery on a problem whose answer is known, because that machinery is what the two-dimensional solver relies on.

The mesh velocity w is neither the material velocity nor zero, so every time derivative taken at a fixed mesh point carries the convective correction $\mathrm{D}/\mathrm{D}t = \partial_t|_{\mathrm{mesh}} + (u - w)\partial_x$. At the free edge $w = u$, so the mesh tracks the interface; in the interior w is the affine stretch $w = u(x_c)(\ell_0 - x)/(\ell_0 - x_c)$, obtained as the solution of a mesh-motion equation rather than by renoding between steps. The edge carries the same natural closure as TC1D-FEM together with the kinematic condition $\dot{x}_c = u(x_c)$, imposed through a Lagrange multiplier because the boundary position depends on an unknown.

It reproduces all three reference quantities: $u^*(30)$ extrapolates to 0.9807279 in time and 0.9807278 in space, agreeing with each other to 1.5×10^{-7} and with TC1D-FEM's limit to 2.9×10^{-7}; the late-time ratio extrapolates to 1.49860, 1.49964 and 1.50000 at $T = 50$, 100 and 200; and the displacement relation holds with a residual of 10^{-7} relative. Observed convergence is second order in both time ($1.92 \to 1.99$) and space (2.000 at every refinement).

Two checks are worth recording. The mesh sits on the affine stretch to 6×10^{-15} of the domain length, so the mesh-motion solution is verified rather than assumed; and a control run with the same moving mesh but the ALE correction omitted drifts the total mass by a factor of sixteen. The correction is not a refinement but the difference between this result and none.

The physical coordinate loses resolution where the mass coordinate gains it: the rim occupies a fixed mass but a physical extent narrowing as $(1 + T)^{-1}$, while the affine stretch compresses

the mesh only in proportion to the remaining sheet length. Late-time accuracy is therefore more expensive here than in TC1D-FEM. This is a property of the coordinate rather than of the implementation, and it is the reason the reference work adopts an algebraic stretching map.

7 The crossover time

For large $\mathcal{L}$ the edge decelerates from the Taylor–Culick speed onto the finite-sheet law of §4. The reference work reports the crossover time T_c and its duration ΔT_c as functions of $\mathcal{L}$, with $T_c = \mathcal{L}$ for large $\mathcal{L}$.

Neither quantity is defined in closed form in that work, so an operational definition is adopted here and applied identically to both solvers; it is stated with the figure. Figure 5 compares both solvers against values digitised from the published figure.




Figure 5: Crossover time T_c and duration ΔT_c against $\mathcal{L}$. Solid: TC1D-FEM. Open circles: ABDS-CN. Open squares: values digitised from the published figure.

We find $T_c/\mathcal{L} = 1$ to within 0.25% for $\mathcal{L} \geq 7$. Against the digitised values, T_c agrees to 0.142% RMS, within the estimated digitisation uncertainty of 0.2%, and ΔT_c to 0.024 absolute (1.5%).

One point of definition should be recorded. The text of the reference work describes ΔT_c as a full width at half maximum, while the released code computes twice that width. The published values are consistent with the code. Both conventions are reported here.

8 The range of validity assumed throughout

The four regimes examined above — the early response of §3, the terminal approach $\mathcal{L} - X_c \ll 1$ at arbitrary $\mathcal{L}$ of §4, the semi-infinite limit $\mathcal{L} \gg T \gg 1$ of §5, and the crossover at finite large $\mathcal{L}$ with $1 < T < \mathcal{L}$ of §7 — all share one assumption that is worth stating explicitly, because it is invisible in the equations actually solved.

Section 1.2 showed that the Ohnesorge number is absorbed into the units (5), which is what makes the curves of the preceding sections universal and lets a single solution serve every viscosity. It does not follow that the results hold at every viscosity. The reduction remains faithful to the underlying flow only while the thin-film description does, and the reference work bounds that by $T = O(Oh_p)$, beyond which it identifies a two-dimensional inertial regime governed by the full Navier–Stokes equations. The edge condition (3) carries a restriction of the same kind, since its

derivation requires the elapsed time not to be asymptotically large relative to a viscous timescale [11]. For the analysis of a sheet of length $\mathcal{L}$ to be uniformly valid over its whole history, one therefore needs

$$\mathcal{L} \ll Oh_p, \tag{16}$$

which in the units of (11) reads $M \ll 8\,Oh^2$. For a semi-infinite sheet $\mathcal{L} \to \infty$ and no finite viscosity satisfies (16); what survives is the weaker horizon $T \ll Oh_p$.

This bounds what the present validation can claim, and the boundary is worth being precise about. The agreement documented in §§3–7 is agreement between two discretisations of the same reduced model, and it is established to the precision reported there. It is not evidence that the reduced model describes a sheet at any particular Ohnesorge number, and no such claim is made. Establishing that requires a solver which never performs the reduction.

The question is therefore well posed: for a semi-infinite sheet, how large must Oh_p be before a genuine two-dimensional flow spends a resolvable part of its history in the regime these sections describe? It cannot be answered from within the reduced model, which has already discarded the parameter the answer depends on.

Direct simulation of the two-dimensional problem at $0.77 \le Oh_p \le 10$ indicates that the reduced description is accurate at early times — the local exponent of the deficit agrees with the present solvers to better than 0.01 out to $T \approx 0.5$ at $Oh_p = 10$ — but that the time at which it departs grows only as $Oh_p^{1/2}$, rather than linearly as (16) would suggest. On that scaling a decade of long-wave behaviour would require Oh_p of order 10^2, well above the range in which the long-wave model is usually invoked. Those measurements are reported separately; they are noted here only to mark the boundary of what the present validation establishes.

A From the two-dimensional equations to the thin-film model

This appendix records the reduction used in §1, first retaining inertia and then discarding it. The second case is included not because it is used — it is not — but because discarding inertia is the natural thing to try at large Ohnesorge number, and seeing precisely how it fails is what justifies the visco-inertial scaling (5). The systematic versions of the first derivation are due to Erneux and Davis [4] and Howell [5], following Trouton [3]; the treatment here is condensed to the terms that matter for the retraction problem. The matched-asymptotic treatment of the tip region is that of the reference work [11].

A.1 The two-dimensional problem

Take a Newtonian liquid of constant ρ and μ, occupying $-h(x,t) < y < h(x,t)$, with velocity (u, w) and pressure p, surrounded by a passive ambient at zero stress. The sheet is symmetric about $y = 0$, so u is even and w odd in y. The equations are

$$\frac{\partial u}{\partial x} + \frac{\partial w}{\partial y} = 0, \qquad \rho \frac{\mathrm{D}u_i}{\mathrm{D}t} = \frac{\partial \sigma_{ij}}{\partial x_j}, \qquad \sigma_{ij} = -p\,\delta_{ij} + \mu\left(\frac{\partial u_i}{\partial x_j} + \frac{\partial u_j}{\partial x_i}\right), \tag{17}$$

subject on $y = h(x,t)$ to the kinematic condition and the stress condition

$$\frac{\partial h}{\partial t} + u\frac{\partial h}{\partial x} = w, \qquad \sigma_{ij} n_j = -\gamma\kappa\, n_i, \tag{18}$$

with $\mathbf{n}$ the outward unit normal and $\kappa = \nabla\cdot\mathbf{n}$ the curvature, positive on a bulge. The sign is fixed by the static check: for a quiescent drop $\sigma_{ij} n_j = -p\, n_i$, so (18) gives $p = \gamma\kappa > 0$ inside, as it must be.

A.2 Reduction with arbitrary inertia

Let $\varepsilon = h_0/l_0 \ll 1$ and scale $x \sim l_0$, $y \sim h_0$, $u \sim U$, $w \sim \varepsilon U$, so that continuity balances. Expanding in ε^2,

$$u = u_0(x,t) + \varepsilon^2 u_2(x,y,t) + \dots, \qquad p = p_0(x,t) + \dots \tag{19}$$

The transverse momentum equation gives $\partial p/\partial y = \mathcal{O}(\varepsilon^2)$, so the pressure is uniform across the thickness at leading order. The axial equation at leading order reduces to $\mu\,\partial^2 u_0/\partial y^2 = 0$, and the tangential stress condition on *both* free surfaces forces the constant of integration to vanish, leaving u_0 independent of y. This is the step that distinguishes a free sheet from a film on a substrate: with two traction-free surfaces the leading-order profile is plug flow, whereas no-slip on a wall would give a parabolic profile and a lubrication model instead. Continuity then fixes the transverse velocity, $w = -y\,\partial_x u_0$.

The normal stress condition on $y = h$ balances the transverse deviatoric stress and the pressure against the Laplace pressure. For a weakly curved surface the curvature is $\kappa = -\partial^2 h/\partial x^2$, positive on a bulge, so with a passive ambient at zero pressure

$$p_0 = -2\mu\frac{\partial u_0}{\partial x} - \gamma\frac{\partial^2 h}{\partial x^2} + \mathcal{O}(\varepsilon^2), \tag{20}$$

where the first term follows from $\partial w/\partial y = -\partial u_0/\partial x$. The axial stress carried by the sheet is then

$$\sigma_{xx} = -p_0 + 2\mu\frac{\partial u_0}{\partial x} = 4\mu\frac{\partial u_0}{\partial x} + \gamma\frac{\partial^2 h}{\partial x^2}. \tag{21}$$

The factor 4μ is the planar extensional viscosity of Trouton [3]: a factor 2 from the deviatoric stress and a further factor 2 because the transverse contraction $\partial_y w = -\partial_x u_0$ feeds back through the pressure.

Integrating continuity across the thickness and applying the kinematic condition at $y = \pm h$ gives (1) exactly. For momentum, balance the forces on a slice. The mass per unit length is $2\rho h$, and the total axial force transmitted across a section is the depth integral of (21) plus the axial projection of the tension carried by the two surfaces,

$$N = \int_{-h}^{h}\sigma_{xx}\,\mathrm{d}y + \frac{2\gamma}{\sqrt{1+h_x^2}} = 8\mu\,h\frac{\partial u_0}{\partial x} + 2\gamma h\frac{\partial^2 h}{\partial x^2} + 2\gamma - \gamma h_x^2 + \dots, \tag{22}$$

the projection factor being the only place the surface slope enters at this order. The two capillary contributions in (22) do not act separately: differentiating,

$$\frac{\partial}{\partial x}\left(2\gamma h\,h_{xx} - \gamma h_x^2\right) = 2\gamma h_x h_{xx} + 2\gamma h\,h_{xxx} - 2\gamma h_x h_{xx} = 2\gamma h\,h_{xxx}, \tag{23}$$

so the $h_x h_{xx}$ terms cancel exactly and only the third derivative survives. This cancellation is worth carrying explicitly: keeping the depth integral of σ_{xx} while forgetting that surface tension acts along an inclined surface leaves a spurious $\gamma h_x h_{xx}$ and does not reproduce (2). With $2\rho h\,\mathrm{D}u_0/\mathrm{D}t = \partial_x N$ and division by two, the result is (2) [4, 5].

Two features deserve comment. The constant 2γ has zero gradient and so exerts no bulk force; it acts only where the sheet terminates, which is why surface tension enters this problem through a boundary condition. And $\gamma h\,\partial^3 h/\partial x^3$ is the only place bulk capillarity survives, which by (4) is negligible once $\mathrm{Oh}_p \gg 1$.

Equations (1) and (2) are what TC1D-FEM and TC1D-ALE integrate. In the Lagrangian mass coordinate m with $\mathrm{d}m = h\,\mathrm{d}x$, so that $\partial_x = h\,\partial_m$ and the free edge is a material point, they take the form quoted in Table 1,

$$\left.\frac{\partial h}{\partial T}\right|_m = -h^2\frac{\partial u}{\partial m}, \qquad \frac{\partial u}{\partial T} = 4\mu\frac{\partial}{\partial m}\left(h^2\frac{\partial u}{\partial m}\right), \tag{24}$$

with (3) entering as a natural boundary term.

A.3 Reduction with vanishing inertia, and why it fails here

Now suppose inertia is negligible, so that the two-dimensional problem is unsteady Stokes flow: $\partial\sigma_{ij}/\partial x_j = 0$ together with $\partial u/\partial x + \partial w/\partial y = 0$.

The essential point is that this does *not* make the problem steady. The Stokes equations are quasi-static in the sense that the momentum balance carries no time derivative and the velocity field at each instant is determined by the instantaneous geometry; but the geometry itself evolves, and it does so through the kinematic condition in (18), which retains $\partial h/\partial t$. The time dependence therefore migrates entirely into the free-surface evolution. Integrating it out — solving a sequence of steady Stokes problems and forgetting that the domain moves — would discard the history of the retraction, which is precisely the information the late-time behaviour depends on.

Carrying the same slender expansion through, the reduced system is

$$\underbrace{\frac{\partial h}{\partial t} + \frac{\partial}{\partial x}(vh) = 0}_{\text{unchanged; time retained}}\,, \qquad \underbrace{0 = 4\mu\frac{\partial}{\partial x}\left(h\frac{\partial v}{\partial x}\right) + \gamma h\frac{\partial^3 h}{\partial x^3}}_{\text{quasi-static}}\,. \tag{25}$$

Neglecting the capillary term by (4) and integrating the momentum equation once in x, the viscous stress $4\mu h\,\partial_x v$ is independent of x. Its value is set by the edge condition (3), giving

$$4\mu\, h\frac{\partial v}{\partial x} = -\gamma \qquad \text{for all } x. \tag{26}$$

Combining (26) with the Lagrangian form of (1), $\mathrm{D}h/\mathrm{D}t = -h\,\partial_x v$, gives

$$\frac{\mathrm{D}h}{\mathrm{D}t} = \frac{\gamma}{4\mu} \qquad \Longleftrightarrow \qquad \frac{\mathrm{D}H}{\mathrm{D}T} = 1 \quad \text{everywhere,} \tag{27}$$

so *every* material element thickens at the same constant rate and $H = 1 + T$ throughout the sheet.

This is inconsistent. The sheet is initially flat and at rest, and for a long or semi-infinite sheet the far field must remain flat and quiescent, $H \to 1$ and $V \to 0$; (27) instead thickens the whole sheet uniformly and instantaneously, no matter how distant. The purely viscous solution cannot satisfy the initial and far-field conditions, and the resolution is that inertia — however small — is what localises the disturbance near the retracting edge and keeps the problem well posed [11]. Balancing the inertial and viscous terms of (2) is then not optional, and it produces the scales (5).

Contrast (27) with the correct result of §1.3: there $H(X_c, T) = 1 + T$ holds *at the tip*, with H relaxing to unity away from it, and that spatial structure is exactly what inertia supplies.

The failure is specific to the planar geometry. As noted in [11], in the axisymmetric problem of an expanding hole the viscous operator becomes $\partial_r\big(hr^{-1}\partial_r(rv_r)\big)$, for which a purely viscous solution *is* compatible with the initial and boundary conditions. The necessity of retaining inertia at large Oh is therefore a property of this configuration rather than a general feature of viscous sheet retraction, and it is worth stating plainly because the opposite assumption is easy to carry over from the axisymmetric literature.

B Fidelity of the reference transcription

ABDS-CN is a transcription of released MATLAB into Python. To establish that the transcription is faithful rather than merely plausible, the original code was executed under GNU Octave and compared with the transcription at identical parameters. Over six configurations the largest absolute difference in the retraction speed is 5.0×10^{-10}, and the largest normalised difference across all twenty-four recorded quantities is 3.0×10^{-8}. The former is the resolution at which the original code writes its output, so the two agree to every digit that can be compared.




Figure 6: Original released code executed under GNU Octave, against the Python transcription ABDS-CN, at several $\mathcal{L}$.

C Reproduction

The campaign comprises 72 cases. Each is recorded in a manifest with its parameters and the exact command that regenerates it, alongside the derived series used for every figure and table in this document.

References

[1] G. I. Taylor, The dynamics of thin sheets of fluid. III. Disintegration of fluid sheets, *Proc. R. Soc. Lond. A* **253**, 313 (1959).

[2] F. E. C. Culick, Comments on a ruptured soap film, *J. Appl. Phys.* **31**, 1128 (1960).

[3] F. T. Trouton, On the coefficient of viscous traction and its relation to that of viscosity, *Proc. R. Soc. Lond. A* **77**, 426 (1906).

[4] T. Erneux and S. H. Davis, Nonlinear rupture of free films, *Phys. Fluids A* **5**, 1117 (1993).

[5] P. D. Howell, Models for thin viscous sheets, *Eur. J. Appl. Math.* **7**, 321 (1996).

[6] E. J. Hinch, *Perturbation Methods*, Cambridge University Press, Cambridge (1991).

[7] M. P. Brenner and D. Gueyffier, On the bursting of viscous films, *Phys. Fluids* **11**, 737 (1999).

[8] N. Savva and J. W. M. Bush, Viscous sheet retraction, *J. Fluid Mech.* **626**, 211 (2009).

[9] H. Deka and J.-L. Pierson, Revisiting the Taylor–Culick approximation. II. Retraction of a viscous sheet, *Phys. Rev. Fluids* **5**, 093603 (2020).

[10] J. P. Munro, C. R. Anthony, O. A. Basaran and J. R. Lister, Thin-sheet flow between coalescing bubbles, *J. Fluid Mech.* **773**, R3 (2015).

[11] T. Ahsan, R. Brandão, B. Davidovitch and H. A. Stone, Retraction of a viscous liquid sheet, arXiv:2507.04603 (2025). Released code: `https://github.com/taosifahsan/Thin-Film-Simulations`.