szvz20rxp

May 7, 2023

1 Data cleaning for Algerian Forest Fire Dataset

[2]:
```
import numpy as np
import pandas as pd
import seaborn as sns
import matplotlib.pylab as plt
%matplotlib inline
```

[3]:
```
data = pd.read_csv(r"../Algerian_forest_fires_dataset_UPDATE.csv",header=1)
data
```

[3]:

	day	month	year	Temperature	RH	Ws	Rain	FFMC	DMC	DC	ISI	BUI	FWI	Classes
0	01	06	2012	29	57	18	0	65.7	3.4	7.6	1.3	3.4	0.5	not fire
1	02	06	2012	29	61	13	1.3	64.4	4.1	7.6	1	3.9	0.4	not fire
2	03	06	2012	26	82	22	13.1	47.1	2.5	7.1	0.3	2.7	0.1	not fire
3	04	06	2012	25	89	13	2.5	28.6	1.3	6.9	0	1.7	0	not fire
4	05	06	2012	27	77	16	0	64.8	3	14.2	1.2	3.9	0.5	not fire
..	..	…	…	…	..	..	…	…	…	…	…	…	…	…
241	26	09	2012	30	65	14	0	85.4	16	44.5	4.5	16.9	6.5	fire
242	27	09	2012	28	87	15	4.4	41.1	6.5	8	0.1	6.2	0	not fire
243	28	09	2012	27	87	29	0.5	45.9	3.5	7.9	0.4	3.4	0.2	not fire
244	29	09	2012	24	54	18	0.1	79.7	4.3	15.2	1.7	5.1	0.7	not fire
245	30	09	2012	24	64	15	0.2	67.3	3.8	16.5	1.2	4.8	0.5	not fire

[246 rows x 14 columns]

[3]:
```
data[data.isna().any(axis=1)]
data.iloc[121:125,:]
data.drop([122,123],inplace=True)
data.reset_index(inplace=True)
data.drop(['index',"day","month","year"],axis=1,inplace=True)
data["region"] = None
data.iloc[:122,-1] = "Bejaia"
data.iloc[122:,-1] = "Abbes"
data
```

[3]:

	Temperature	RH	Ws	Rain	FFMC	DMC	DC	ISI	BUI	FWI	Classes	\
0	29	57	18	0	65.7	3.4	7.6	1.3	3.4	0.5	not fire	
1	29	61	13	1.3	64.4	4.1	7.6	1	3.9	0.4	not fire	
2	26	82	22	13.1	47.1	2.5	7.1	0.3	2.7	0.1	not fire	
3	25	89	13	2.5	28.6	1.3	6.9	0	1.7	0	not fire	
4	27	77	16	0	64.8	3	14.2	1.2	3.9	0.5	not fire	
..	…	..	..	…	…	…	…	…	…	…	…	
239	30	65	14	0	85.4	16	44.5	4.5	16.9	6.5	fire	
240	28	87	15	4.4	41.1	6.5	8	0.1	6.2	0	not fire	
241	27	87	29	0.5	45.9	3.5	7.9	0.4	3.4	0.2	not fire	
242	24	54	18	0.1	79.7	4.3	15.2	1.7	5.1	0.7	not fire	
243	24	64	15	0.2	67.3	3.8	16.5	1.2	4.8	0.5	not fire	

	region
0	Bejaia
1	Bejaia
2	Bejaia
3	Bejaia
4	Bejaia
..	…
239	Abbes
240	Abbes
241	Abbes
242	Abbes
243	Abbes

[244 rows x 12 columns]

2 Data cleaning operations

[4]:
```
data.info()
```

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 244 entries, 0 to 243
```

```
Data columns (total 12 columns):
 #   Column       Non-Null Count  Dtype
---  ------       --------------  -----
 0   Temperature  244 non-null    object
 1    RH          244 non-null    object
 2    Ws          244 non-null    object
 3   Rain         244 non-null    object
 4   FFMC         244 non-null    object
 5   DMC          244 non-null    object
 6   DC           244 non-null    object
 7   ISI          244 non-null    object
 8   BUI          244 non-null    object
 9   FWI          244 non-null    object
 10  Classes      244 non-null    object
 11  region       244 non-null    object
dtypes: object(12)
memory usage: 23.0+ KB
```

Getting unique values from y data column:
* Getting unique values from a column involves identifying and selecting only the distinct or unique values in that column.

[5]:
```
data["Classes  "].unique()
```

[5]:
```
array(['not fire   ', 'fire   ', 'fire', 'fire ', 'not fire', 'not fire ',
       'not fire     ', 'not fire    '], dtype=object)
```

Apply `str.strip()` to clean the data:
* As we can see y data has some blank spaces so we need to remove then before use.
* I have used the `.strip()` method in Python to remove the leading and trailing spaces from the data in a column.

[6]:
```
data["Classes  "] = data["Classes  "].str.strip()
```

[7]:
```
data
```

[7]:

	Temperature	RH	Ws	Rain	FFMC	DMC	DC	ISI	BUI	FWI	Classes
0	29	57	18	0	65.7	3.4	7.6	1.3	3.4	0.5	not fire
1	29	61	13	1.3	64.4	4.1	7.6	1	3.9	0.4	not fire
2	26	82	22	13.1	47.1	2.5	7.1	0.3	2.7	0.1	not fire
3	25	89	13	2.5	28.6	1.3	6.9	0	1.7	0	not fire
4	27	77	16	0	64.8	3	14.2	1.2	3.9	0.5	not fire
..	…	..	..	…	…	…	…	…	…	…	…
239	30	65	14	0	85.4	16	44.5	4.5	16.9	6.5	fire
240	28	87	15	4.4	41.1	6.5	8	0.1	6.2	0	not fire
241	27	87	29	0.5	45.9	3.5	7.9	0.4	3.4	0.2	not fire
242	24	54	18	0.1	79.7	4.3	15.2	1.7	5.1	0.7	not fire
243	24	64	15	0.2	67.3	3.8	16.5	1.2	4.8	0.5	not fire

```
     region
0    Bejaia
1    Bejaia
2    Bejaia
3    Bejaia
4    Bejaia
..      …
239   Abbes
240   Abbes
241   Abbes
242   Abbes
243   Abbes

[244 rows x 12 columns]
```

[8]:
```
data["Classes  "].unique()
```

[8]:
```
array(['not fire', 'fire'], dtype=object)
```

Convert data type of all data column:
* In below code I am selecting all data which are intiger and making the column data type as float64

[9]:
```
columns = data.columns[:-2]
for i in columns:
    data[i] = data[i].astype("float64")
data.info()
```

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 244 entries, 0 to 243
Data columns (total 12 columns):
 #   Column       Non-Null Count  Dtype
---  ------       --------------  -----
 0   Temperature  244 non-null    float64
 1    RH          244 non-null    float64
 2    Ws          244 non-null    float64
 3   Rain         244 non-null    float64
 4   FFMC         244 non-null    float64
 5   DMC          244 non-null    float64
 6   DC           244 non-null    float64
 7   ISI          244 non-null    float64
 8   BUI          244 non-null    float64
 9   FWI          244 non-null    float64
 10  Classes      244 non-null    object
 11  region       244 non-null    object
dtypes: float64(10), object(2)
memory usage: 23.0+ KB
```