

Git Best practices

Jiří Jabůrek (jjaburek) Red Hat 2012

Basic credentials setup

- Name & email
 - Use full name
 - Use valid email address
 - (or <name@something.else>)

Example:

- More about git-config, config types
 - Global (per user) versus local (per repo)



- Descriptive header
 - Bad: "fixed the annoying bug"
 - Good: "fixed \$var shell escaping"
 - Examples all over tests/ repos
- Use commit message for details
 - Repository "documentation" versus code comments
 - Git commits are tied to history (timeline)
- Commit only relevant changes
 - Eliminate secondary unrelated code changes
 - One big versus multiple smaller commits (later)

- Always check diffs before commit/push
 - Uncommited changes (before commit)

```
git-diffgit-diff --cachedgit-diff HEADgit-gui
```

Given multiple commits (before push)

```
git-log -pgitktiggit-diff origin/master
```

- Watch for whitespace errors
 - Combined tabs and spaces
 - Tabs in a spaced file or vice versa
 - Trailing whitespaces
 - Empty lines with white characters
 - Solution?
 - git-diff --check
 - git-apply --whitespace=fix
 - has drawbacks



- Rebase before push
 - After committing your changes
 - git pull --rebase
 - With unstaged changes only
 - git stash ; git pull ; git stash apply

- Multiple smaller commits versus one big
 - Easier to review / document / bisect
 - Easier to revert / cherry-pick / export (diff)
 - One big disadvantage; added effort / time
 - Separation
 - per-file ; per-change ; ...?
 - Not that hard to manage in git
 - git-add --patch

- Subdirectory svn checkout versus Git
 - svn = different workflow, git unrelated
 - Management change
 - Git submodules



Questions?

Appendix: my ~/.gitconfig

```
[user]
    name = Jiri Jaburek
   email = jjaburek@redhat.com
    signingkey = 5C33C50A
[advice]
    pushNonFastForward = false
    statusHints = false
    commitBeforeMerge = false
    resolveConflict = false
    implicitIdentity = false
    detachedHead = false
[color]
    branch = auto
   diff = auto
   grep = auto
   interactive = auto
    showbranch = auto
   status = auto
   ui = auto
[color "diff"]
   whitespace = red reverse
[push]
   default = matching
```

```
[branch]
    autosetupmerge = false
[merge]
    stat = false
    tool = vimdiff
[rebase]
    stat = false
[sendemail]
    smtpserver = localhost
    smtpserverport = 25
    chainreplyto = false
[diff]
    renames = true
```

