

Objects

BLOB

- create: `hash-object -w <file>`
- show: `cat-file -p <hash>`

TREE

- create: `mktree`
 - see `ls-tree(1)`, "OUTPUT FORMAT"
- from idx: `write-tree`
- show: `ls-tree <tree>`

COMMIT

- create: `commit-tree <tree> < msg>`
 - from idx: `commit -m <msg>`
- show: `log -1 <commit>`
- or: `cat-file -p <commit>`

TAG

- create: `mktag < sig>`
- show: `cat-file -p <tag>`

Refs

LOCATIONS (in .git/)

- branches: `refs/heads/<name>`
- remotes: `refs/remotes/<name>/*`
- tags: `refs/tags/<name>`
- *: `refs/*`
- HEAD: `HEAD`

MODIFY

- update-ref: write dst hash
 - set: `update-ref <path> <dst>`
 - multiple lines via `--stdin`
- symbolic-ref: write dst pointer
 - create: `symbolic-ref <path> <dst>`

PACKED

- pack all: `pack-refs --all`
- update: `pack-refs`

Transfer

ENDPOINTS

- fetch
 - client: `fetch-pack <remote>`
 - server: `upload-pack <dir>`
- push
 - client: `send-pack <host>:<dir>`
 - server: `receive-pack <dir>`
- archive
 - client: `archive --remote=<host>`
 - server: `upload-archive <dir>`

PROTOCOLS

- `<proto>::<addr>` uses `remote-<proto>`
- `http::<url>` (`curl`)
- `ftp::<url>` (`curl`)
- `fd::<inf>[,<outfd>]`
- `ext::<cmd>` [`arg...`]
- see `man gitremote-helpers`

FETCH/PUSH REFSPEC

- format: `[+]<src>[:<dst>]`
 - where: `<src>` is any revspec, `<dst>` is ref + is force push / overwriting fetch
- rm ref: `:<ref>`

CLONE OPTS

- info/alternates: `--reference <repo>`
- rm alternates: `--dissociate`
- specific branch: `-b <name>`
 - only fetch one: `--single-branch`
- shallow clone: `--depth <nr>`

OFFLINE

- binary: `bundle create <file> <revlist>`
 - extract: `bundle unbundle` or `clone (!)`
- text: `fast-export <revlist>`
 - pipe to: `fast-import`

Index (stage/cache)

SHOW

- show: `ls-files --stage`
- diff/tree: `diff-index --cached <tree>`
- diff/wd: `diff-files`

LOAD

- from tree: `read-tree <tree> [tree]...`
- from wd: `add [-u] <path>`
 - or: `update-index --{add|..}`
 - no blobs: `update-index --info-only`
- raw: `update-index --cacheinfo`
 - or from stdin with `--index-info`

STORE

- to tree: `write-tree`
- to wd: `checkout-index`

Maintenance

EASY FIX

- do nothing - git has auto gc

LAZY SIMPLE

- just: `gc`
- minsize: `gc --aggressive`

MANUAL

- add pack: `repack`
- into one: `repack -a -d` or `-A -d`
 - c.ratio: `--window` and `--depth`
- rm loose: `prune [-n]`

MINIMUM SIZE (reasonably)

- rm reflog: `reflog expire \`
 - `--expire=now --all`
- do gc: `gc --aggressive --prune=all`

Pack

SHOW

- idx file: `verify-pack -v file.idx`
 - raw: `show-index < file.idx`
- extra: `pack-redundant --all`

MAKE

- pack+idx: `pack-objects < objlist`
 - lost idx?: `index-pack <pack>`

EXTRACT

- into repo: `unpack-objects < pack`

Recovery

FINDING LOST

- reflog: `reflog -10`
- dangling: `fsck`
 - w/ stage: `fsck --cache`
 - extract: `fsck --lost-found`
 - into `.git/lost-found/`
- bad pack: `unpack-objects -r`
- read: `git/howto/recover-corrupted*`

Merge

STRATEGIES

- merge-resolve / merge-recursive
 - recursive has additional -X opts
- merge-octopus
- merge-ours / merge-theirs
- merge-subtree

FLOW

- strategy: `merge-*`
- ancestor: `merge-base <commit> [commit]...`
- trivial: `read-tree -m`
- show: `ls-files --unmerged`
- external: `merge-index <prog> {-a|paths}`
- prog: `merge-one-file`
- uses: `merge-file <ours> <base> <theirs>`

CONFLICTS

- stages: `ls-files --unmerged`
- tofiles: `checkout-index --stage=all -a`
 - one: `checkout-index --stage=N <file>`
- markers: `merge-file <ours> <base> <theirs>`
 - if no base, touch empty file and use it as `<base>`

Documentation

MANPAGES

- per-command:
 - `man git-log`
 - `git log --help`
- `apropos -s7 ^git`
- gitrevisions
- gitglossary
- gitcore-tutorial
- ...

BOOKS

- Version Control with Git, 2nd Edition
 - reasonably thorough, in-depth
- ProGIT
 - `progit.org`
- (old) Git Community Book
 - `schacon.github.io/gitbook`

DOCS ONLINE

- `kernel.org/pub/software/scm/git/docs`

Extra

VARIABLES (just a few)

- `GIT_DIR`
 - main git metadata dir (ie. `.git/`)
- `GIT_EXEC_PATH`
 - where `git(1)` looks for subcommands
- `GIT_INDEX_FILE`
 - instead of `$GIT_DIR/index`
- `GIT_WORK_TREE`
 - for checkout, etc. - can point outside repo
- `GIT_OBJECT_DIRECTORY`
 - external actions on objects (ie. extracting packs)
- `GIT_ALTERNATE_OBJECT_DIRECTORIES`
 - for easy injections of extra objects into a repo
- `GIT_AUTHOR_{NAME,EMAIL,DATE}`
- `GIT_COMMITTER_{NAME,EMAIL,DATE}`
 - override config defaults for `git-commit(1)`
- `GIT_TRACE` or `GIT_TRACE_*`
 - enable git debugging (see `man git` for more)
- `GIT_NAMESPAC`
 - subst all refs/* for `refs/$GIT_NAMESPACE/*`

TIPS

- create permanently detached worktree with git commands working like in a normal one:
 - create file `.git in tld`, with
 - `gitdir: /absolute/path/to/git_dir`
- create url base aliases in local config
 - `[url "git://actual-url/"] \ insteadOf = work:`
 - `git clone work:somerepo // git-fetch(1)`
- search commits for
 - string in log message: `git log --grep=str`
 - string in modified code: `git log -Sstr`
- `git-interpret-trailers` for your Reviewed-by: