

Lecture 16:

Recurrent Neural Networks

Visual Question Answering



Q: What endangered animal is featured on the truck?

- A: A bald eagle.**
- A: A sparrow.
- A: A humming bird.
- A: A raven.



Q: Where will the driver go if turning right?

- A: Onto 24 3/4 Rd.**
- A: Onto 25 3/4 Rd.
- A: Onto 23 3/4 Rd.
- A: Onto Main Street.



Q: When was the picture taken?

- A: During a wedding.**
- A: During a bar mitzvah.
- A: During a funeral.
- A: During a Sunday church service





Q: Who is under the umbrella?


- A: Two women.**
- A: A child.
- A: An old man.
- A: A husband and a wife.

Agrawal et al, "VQA: Visual Question Answering", ICCV 2015
Zhu et al, "Visual 7W: Grounded Question Answering in Images", CVPR 2016
Figure from Zhu et al, copyright IEEE 2016. Reproduced for educational purposes.

Visual Question Answering: RNNs with Attention




What kind of animal is in the photo?
A **cat**.



Why is the person holding a knife?
To cut the **cake** with.


Zhu et al, "Visual 7W: Grounded Question Answering in Images", CVPR 2016
Figures from Zhu et al, copyright IEEE 2016. Reproduced for educational purposes.

Recurrent Networks offer a lot of flexibility:




↖ **Vanilla Neural Networks**

Recurrent Networks offer a lot of flexibility:



↖ e.g. **Image Captioning**
image -> sequence of words


Recurrent Networks offer a lot of flexibility:




e.g. **Sentiment Classification**
sequence of words -> sentiment

Recurrent Networks offer a lot of flexibility:


one to one




one to many




many to one



many to many




many to many




e.g. **Machine Translation**
seq of words -> seq of words

Recurrent Networks offer a lot of flexibility:


one to one




one to many




many to one



many to many




many to many




e.g. Video classification on frame level

Recurrent Neural Network



Recurrent Neural Network



Recurrent Neural Network


We can process a sequence of vectors \mathbf{x} by applying a recurrence formula at every time step:

$$\boxed{h_t} = \boxed{f_W}(\boxed{h_{t-1}}, \boxed{x_t})$$

new state / some function with parameters W

old state

input vector at some time step




Recurrent Neural Network

We can process a sequence of vectors \mathbf{x} by applying a recurrence formula at every time step:


$$h_t = f_W(h_{t-1}, x_t)$$

Notice: the same function and the same set of parameters are used at every time step.



(Vanilla) Recurrent Neural Network

The state consists of a single “hidden” vector \mathbf{h} :



$$h_t = f_W(h_{t-1}, x_t)$$




$$h_t = \tanh(W_{hh}h_{t-1} + W_{xh}x_t)$$

$$y_t = W_{hy}h_t$$

Character-level language model example

Vocabulary:
[h,e,l,o]


Example training
sequence:
“hello”



Character-level language model example

Vocabulary:
[h,e,l,o]

Example training
sequence:
“hello”




Character-level language model example

Vocabulary:
[h,e,l,o]

Example training
sequence:
“hello”

$$h_t = \tanh(W_{hh}h_{t-1} + W_{xh}x_t)$$



Character-level language model example

Vocabulary:
[h,e,l,o]

Example training
sequence:
“hello”





Image Captioning



Explain Images with Multimodal Recurrent Neural Networks, Mao et al.


Deep Visual-Semantic Alignments for Generating Image Descriptions, Karpathy and Fei-Fei

Show and Tell: A Neural Image Caption Generator, Vinyals et al.

Long-term Recurrent Convolutional Networks for Visual Recognition and Description, Donahue et al.

Learning a Recurrent Visual Representation for Image Caption Generation, Chen and Zitnick

Recurrent Neural Network



Convolutional Neural Network



test image

image

conv-64

conv-64

maxpool

conv-128

conv-128

maxpool

conv-256

conv-256

maxpool

conv-512

conv-512

maxpool

conv-512

conv-512

maxpool

FC-4096

FC-4096

FC-1000

softmax



test image

image

conv-64

conv-64

maxpool

conv-128

conv-128

maxpool

conv-256

conv-256

maxpool

conv-512

conv-512

maxpool

conv-512

conv-512

maxpool

FC-4096


FC-4096

FC-1000

softmax



test image



image

conv-64

conv-64

maxpool

conv-128

conv-128

maxpool

conv-256

conv-256

maxpool

conv-512

conv-512

maxpool

conv-512

conv-512

maxpool

FC-4096

FC-4096



test image


x0
<STA
RT>

<START>



V

W_{ih}



test image

before:

$$h = \tanh(W_{xh} * x + W_{hh} * h)$$

now:

$$h = \tanh(W_{xh} * x + W_{hh} * h + W_{ih} * v)$$

image

conv-64

conv-64

maxpool

conv-128

conv-128

maxpool

conv-256

conv-256

maxpool

conv-512

conv-512

maxpool

conv-512

conv-512

maxpool

FC-4096

FC-4096



test image

y0

h0

x0
<STA
RT>

straw

sample!

<START>

image

conv-64

conv-64

maxpool

conv-128

conv-128

maxpool

conv-256

conv-256

maxpool

conv-512

conv-512

maxpool

conv-512

conv-512


maxpool

FC-4096

FC-4096



test image



<START>

image

conv-64

conv-64

maxpool

conv-128

conv-128

maxpool

conv-256

conv-256

maxpool

conv-512

conv-512

maxpool

conv-512

conv-512

maxpool

FC-4096

FC-4096



test image

y0

y1

h0

h1

x0
<STA
RT>

straw

hat

sample!

<START>

image

conv-64

conv-64

maxpool

conv-128

conv-128

maxpool

conv-256

conv-256

maxpool

conv-512

conv-512

maxpool

conv-512

conv-512


maxpool

FC-4096

FC-4096



test image



image

conv-64

conv-64

maxpool

conv-128

conv-128

maxpool

conv-256

conv-256

maxpool

conv-512

conv-512

maxpool

conv-512

conv-512


maxpool

FC-4096

FC-4096



test image



<START>

sample
<END> token
=> finish.

Image Sentence Datasets

a man riding a bike on a dirt path through a forest.
bicyclist raises his fist as he rides on desert dirt trail.
this dirt bike rider is smiling and raising his fist in triumph.
a man riding a bicycle while pumping his fist in the air.
a mountain biker pumps his fist in celebration.



Microsoft COCO

[Tsung-Yi Lin et al. 2014]

mscoco.org

currently:

~120K images

~5 sentences each



"man in black shirt is playing guitar."



"construction worker in orange safety vest is working on road."



"two young girls are playing with lego toy."



"boy is doing backflip on wakeboard."



"man in black shirt is playing guitar."



"construction worker in orange safety vest is working on road."



"two young girls are playing with lego toy."



"boy is doing backflip on wakeboard."



"a young boy is holding a baseball bat."



"a cat is sitting on a couch with a remote control."



"a woman holding a teddy bear in front of a mirror."



"a horse is standing in the middle of a road."


RNN:

$$h_t^l = \tanh W^l \begin{pmatrix} h_t^{l-1} \\ h_{t-1}^l \end{pmatrix}$$

$h \in \mathbb{R}^n$

$W^l [n \times 2n]$

depth



time

Recurrent Neural Networks have loops




Figure credit: [Understanding LSTM Networks](#) on colah's blog

Subhransu Maji, Chuang Gan and TAs

Some slides kindly provided by Fei-Fei Li, Jiajun Wu, Erik Learned-Miller

An unrolled recurrent neural network




Figure credit: [Understanding LSTM Networks](#) on colah's blog

Subhransu Maji, Chuang Gan and TAs

Some slides kindly provided by Fei-Fei Li, Jiajun Wu, Erik Learned-Miller

Problem of Long-Term Dependencies

“the clouds are in the *sky*”




Figure credit: [Understanding LSTM Networks](#) on colah's blog

Subhransu Maji, Chuang Gan and TAs

Some slides kindly provided by Fei-Fei Li, Jiajun Wu, Erik Learned-Miller

Problem of Long-Term Dependencies

“I grew up in France... I speak fluent *French*.”




Figure credit: [Understanding LSTM Networks](#) on colah's blog

Subhransu Maji, Chuang Gan and TAs

Some slides kindly provided by Fei-Fei Li, Jiajun Wu, Erik Learned-Miller

RNN:

$$h_t^l = \tanh W^l \begin{pmatrix} h_t^{l-1} \\ h_{t-1}^l \end{pmatrix}$$

$h \in \mathbb{R}^n$, $W^l [n \times 2n]$

LSTM:


$W^l [4n \times 2n]$

$$\begin{pmatrix} i \\ f \\ o \\ g \end{pmatrix} = \begin{pmatrix} \text{sigm} \\ \text{sigm} \\ \text{sigm} \\ \text{tanh} \end{pmatrix} W^l \begin{pmatrix} h_t^{l-1} \\ h_{t-1}^l \end{pmatrix}$$

$$c_t^l = f \odot c_{t-1}^l + i \odot g$$

$$h_t^l = o \odot \tanh(c_t^l)$$

depth



Summary


- RNNs allow a lot of flexibility in architecture design
- Vanilla RNNs are simple but don't work very well
- Common to use LSTM or GRU: their additive interactions improve gradient flow
- Backward flow of gradients in RNN can explode or vanish. Exploding is controlled with gradient clipping. Vanishing is controlled with additive interactions (LSTM)
- Better/simpler architectures are a hot topic of current research
- Better understanding (both theoretical and empirical) is needed.

Sequence to Sequence with RNNs

Input: Sequence x_1, \dots, x_T

Output: Sequence y_1, \dots, y_T

Encoder: $h_t = f_W(x_t, h_{t-1})$




Sequence to Sequence with RNNs

Input: Sequence x_1, \dots, x_T

Output: Sequence y_1, \dots, y_T

Encoder: $h_t = f_W(x_t, h_{t-1})$ From final hidden state predict:
Initial decoder state s_0
Context vector c (often $c=h_T$)



Sequence to Sequence with RNNs

Input: Sequence x_1, \dots, x_T

Output: Sequence y_1, \dots, y_T


Decoder: $s_t = g_U(y_{t-1}, s_{t-1}, c)$

Encoder: $h_t = f_W(x_t, h_{t-1})$

From final hidden state predict:

Initial decoder state s_0

Context vector c (often $c=h_T$)



Sequence to Sequence with RNNs

Input: Sequence x_1, \dots, x_T

Output: Sequence y_1, \dots, y_T


Decoder: $s_t = g_U(y_{t-1}, s_{t-1}, c)$

Encoder: $h_t = f_W(x_t, h_{t-1})$

From final hidden state predict:

Initial decoder state s_0

Context vector c (often $c=h_T$)



Sequence to Sequence with RNNs

Input: Sequence x_1, \dots, x_T

Output: Sequence y_1, \dots, y_T


Decoder: $s_t = g_U(y_{t-1}, s_{t-1}, c)$

Encoder: $h_t = f_W(x_t, h_{t-1})$

From final hidden state predict:

Initial decoder state s_0

Context vector c (often $c=h_T$)



Sequence to Sequence with RNNs

Input: Sequence x_1, \dots, x_T

Output: Sequence y_1, \dots, y_T


Decoder: $s_t = g_U(y_{t-1}, s_{t-1}, c)$

Encoder: $h_t = f_W(x_t, h_{t-1})$

From final hidden state predict:

Initial decoder state s_0

Context vector c (often $c=h_T$)



Problem: Input sequence bottlenecked through fixed-sized vector.

Sequence to Sequence with RNNs

Input: Sequence x_1, \dots, x_T

Output: Sequence y_1, \dots, y_T


Decoder: $s_t = g_U(y_{t-1}, s_{t-1}, c)$

Encoder: $h_t = f_W(x_t, h_{t-1})$

From final hidden state predict:

Initial decoder state s_0

Context vector c (often $c=h_T$)



Problem: Input sequence bottlenecked through fixed-sized vector.


Idea: use new context vector at each step of decoder!

Sequence to Sequence with RNNs and Attention

Input: Sequence x_1, \dots, x_T

Output: Sequence $y_1, \dots, y_{T'}$


Encoder: $h_t = f_W(x_t, h_{t-1})$ From final hidden state:
Initial decoder state s_0




Sequence to Sequence with RNNs and **Attention**

Compute (scalar) **alignment scores**

$$e_{t,i} = f_{\text{att}}(s_{t-1}, h_i) \quad (f_{\text{att}} \text{ is an MLP})$$



Sequence to Sequence with RNNs and Attention




Compute (scalar) **alignment scores**

$$e_{t,i} = f_{\text{att}}(s_{t-1}, h_i) \quad (f_{\text{att}} \text{ is an MLP})$$

Normalize alignment scores
to get **attention weights**

$$0 < a_{t,i} < 1 \quad \sum_i a_{t,i} = 1$$

Sequence to Sequence with RNNs and **Attention**




Compute (scalar) **alignment scores**
 $e_{t,i} = f_{\text{att}}(s_{t-1}, h_i)$ (f_{att} is an MLP)

Normalize alignment scores to get **attention weights**
 $0 < a_{t,i} < 1 \quad \sum_i a_{t,i} = 1$


Compute context vector as linear combination of hidden states
 $c_t = \sum_i a_{t,i} h_i$

estamos



[START]

Sequence to Sequence with RNNs and Attention



Compute (scalar) **alignment scores**
 $e_{t,i} = f_{\text{att}}(s_{t-1}, h_i)$ (f_{att} is an MLP)


Normalize alignment scores to get **attention weights**
 $0 < a_{t,i} < 1 \quad \sum_i a_{t,i} = 1$

Compute context vector as linear combination of hidden states

$$c_t = \sum_i a_{t,i} h_i$$

Use context vector in decoder: $s_t = g_U(y_{t-1}, s_{t-1}, c_t)$

Sequence to Sequence with RNNs and Attention



Compute (scalar) **alignment scores**
 $e_{t,i} = f_{\text{att}}(s_{t-1}, h_i)$ (f_{att} is an MLP)

Normalize alignment scores to get **attention weights**
 $0 < a_{t,i} < 1 \quad \sum_i a_{t,i} = 1$

Compute context vector as linear combination of hidden states


$$c_t = \sum_i a_{t,i} h_i$$

Use context vector in decoder: $s_t = g_U(y_{t-1}, s_{t-1}, c_t)$


This is all differentiable! No supervision on attention weights – backprop through everything

Sequence to Sequence with RNNs and Attention


Repeat: Use s_1 to compute new context vector c_2



Sequence to Sequence with RNNs and Attention




Sequence to Sequence with RNNs and Attention



Sequence to Sequence with RNNs and Attention

Use a different context vector in each timestep of decoder

- Input sequence not bottlenecked through single vector
- At each timestep of decoder, context vector “looks at” different parts of the input sequence




Sequence to Sequence with RNNs and Attention

Example: English to French translation

Input: “The agreement on the European Economic Area was signed in August 1992.”

Output: “L’accord sur la zone économique européenne a été signé en août 1992.”

Visualize attention weights $a_{t,i}$



Sequence to Sequence with RNNs and Attention

Example: English to French translation


Input: “**The agreement on the** European Economic Area was signed **in August 1992.**”

Output: “**L'accord sur la** zone économique européenne a été signé **en août 1992.**”

Diagonal attention means words correspond in order

Diagonal attention means words correspond in order

Visualize attention weights $a_{t,i}$



Sequence to Sequence with RNNs and Attention

Example: English to French translation

Input: “The agreement on the European Economic Area was signed in August 1992.”


Output: “L’accord sur la zone économique européenne a été signé en août 1992.”

Diagonal attention means words correspond in order

Attention figures out different word orders

Diagonal attention means words correspond in order


Visualize attention weights $a_{t,i}$





Sequence to Sequence with RNNs and Attention

The decoder doesn't use the fact that h_i form an ordered sequence – it just treats them as an unordered set $\{h_i\}$


Can use similar architecture given any set of input hidden vectors $\{h_i\}$!



Visual Question Answering: RNNs with Attention



What kind of animal is in the photo?
A **cat**.



Why is the person holding a knife?
To cut the **cake** with.

Zhu et al, "Visual 7W: Grounded Question Answering in Images", CVPR 2016
Figures from Zhu et al, copyright IEEE 2016. Reproduced for educational purposes.