

Introduction to group activity on surveys

Matthew J. Salganik
Department of Sociology
Princeton University



Online, Opt-in Surveys: Fast and Cheap, but are they Accurate?

Sharad Goel
Stanford University
scgoel@stanford.edu

Adam Obeng
Columbia University
adam.obeng@columbia.edu

David Rothschild
Microsoft Research
davidmr@microsoft.com

<https://5harad.com/papers/dirtysurveys.pdf>

ABSTRACT

It is increasingly common for government and industry organizations to conduct online, opt-in surveys, in part because they are typically fast, inexpensive, and convenient. Online polls, however, attract a non-representative set of respondents, and so it is unclear whether results from such surveys generalize to the broader population. These non-representative surveys stand in contrast to probability-based sampling methods, such as random-digit dialing (RDD) of phones, which are a staple of traditional survey research. Here we investigate the accuracy of non-representative data by administering an online, fully opt-in poll of social and political attitudes. Our survey consisted of 49 multiple-choice attitudinal questions drawn from the probability-based, in-person 2012 General Social Survey (GSS) and select RDD phone surveys by the Pew Research Center. To correct for the inherent biases of non-representative data, we statistically adjust estimates via model-based poststratification, a classic statistical tool but one that is only infrequently used for bias correction. Our online survey took less than one-twentieth the time and money of traditional RDD polling, and less than one-hundredth the time and money of GSS polling. After statistical correction, we find the median absolute difference between the non-probability-based online survey and the probability-based GSS and Pew studies is 7 percentage points. This difference is considerably larger than if the surveys were all perfect simple random samples drawn from the same population; the gap, however, is comparable to that between the GSS and Pew estimates themselves. Our results suggest that with proper statistical adjustment, online, non-representative surveys are a valuable tool for practitioners in varied domains.

Activity:

- ▶ Design a questionnaire using questions already asked on a high-quality survey

Activity:

- ▶ Design a questionnaire using questions already asked on a high-quality survey
- ▶ Recruit participants from Amazon Mechanical Turk (MTurk) and have them complete your questionnaire

Activity:

- ▶ Design a questionnaire using questions already asked on a high-quality survey
- ▶ Recruit participants from Amazon Mechanical Turk (MTurk) and have them complete your questionnaire
- ▶ Compare results from your survey to the results from the high-quality survey

Activity:

- ▶ Design a questionnaire using questions already asked on a high-quality survey
- ▶ Recruit participants from Amazon Mechanical Turk (MTurk) and have them complete your questionnaire
- ▶ Compare results from your survey to the results from the high-quality survey
- ▶ Try different approaches to weighting and see how the change the estimates

Activity:

- ▶ Design a questionnaire using questions already asked on a high-quality survey
- ▶ Recruit participants from Amazon Mechanical Turk (MTurk) and have them complete your questionnaire
- ▶ Compare results from your survey to the results from the high-quality survey
- ▶ Try different approaches to weighting and see how the change the estimates
- ▶ Ideal but not possible because of time constraints: De-identify and “open-source” data by sending to your local organizer (but remember to think about the end at the beginning)

This activity will give you practice:

- ▶ Designing questionnaires

This activity will give you practice:

- ▶ Designing questionnaires
- ▶ Deploy jobs to MTurk

This activity will give you practice:

- ▶ Designing questionnaires
- ▶ Deploy jobs to MTurk
- ▶ Analyzing survey data (data wrangling and post-stratification)

This activity will give you practice:

- ▶ Designing questionnaires
- ▶ Deploy jobs to MTurk
- ▶ Analyzing survey data (data wrangling and post-stratification)
- ▶ Using the total survey error framework to consider and discuss errors in estimates

Remember: This is a learning activity so try whatever you want and don't expect perfection in just a few hours.

Our recommended work flow:

- ▶ Create a short write-up that describes what data you will be collecting, why, and how it will be shared with others (for tips, see [Meyer \(2018\)](#)); this will be presented to your survey participants

Our recommended work flow:

- ▶ Create a write-up that describes what data you will be collecting, why, and how it will be shared with others (for tips, see [Meyer \(2018\)](#))
- ▶ Create survey on Google Forms (we have a [template](#))

If you were making up the budget for the federal government this year, would you increase spending, decrease spending, or keep spending the same for the following issues?

	Increase spending	Decrease spending	Keep spending the same
Military Defense	<input type="radio"/>	<input type="radio"/>	<input checked="" type="radio"/>
Economic assistance to needy people in the U.S.	<input type="radio"/>	<input checked="" type="radio"/>	<input type="radio"/>
Education	<input type="radio"/>	<input checked="" type="radio"/>	<input type="radio"/>
Environmental Protection	<input type="radio"/>	<input checked="" type="radio"/>	<input type="radio"/>
Economic assistance to needy people around the world	<input type="radio"/>	<input checked="" type="radio"/>	<input type="radio"/>
Health care	<input type="radio"/>	<input checked="" type="radio"/>	<input type="radio"/>
Rebuilding highways, bridges and roads	<input type="radio"/>	<input checked="" type="radio"/>	<input type="radio"/>
Scientific Research	<input type="radio"/>	<input checked="" type="radio"/>	<input type="radio"/>
Social Security	<input type="radio"/>	<input checked="" type="radio"/>	<input type="radio"/>

If you were making up the budget for the federal government this year, would you increase spending, decrease spending, or keep spending the same for: Military defense?

- Increase spending
- Decrease spending
- Keep spending the same

If you were making up the budget for the federal government this year, would you increase spending, decrease spending, or keep spending the same for: Economic assistance to needy people in the U.S.

- Increase spending
- Decrease spending
- Keep spending the same

If you were making up the budget for the federal government this year, would you increase spending, decrease spending, or keep spending the same for: Education?

- Increase spending
- Decrease spending
- Keep spending the same

If you were making up the budget for the federal government this year, would you increase spending, decrease spending, or keep spending the same for: Environmental protection?

- Increase spending
- Decrease spending
- Keep spending the same

Or

Collect the information that you will need for post-stratification:

Collect the information that you will need for post-stratification:

- ▶ gender
- ▶ age
- ▶ state of residence
- ▶ race/ethnicity

How should you ask these questions?

Collect the information that you will need for post-stratification:

- ▶ gender
- ▶ age
- ▶ state of residence
- ▶ race/ethnicity

How should you ask these questions? You should copy from the American Community Survey.

Our recommended work flow:

- ▶ Create a write-up that describes what data you will be collecting, why, and how it will be shared with others (for tips, see [Meyer \(2018\)](#))
- ▶ Create survey on Google Forms (we have a [template](#))

Our recommended work flow:

- ▶ Create a write-up that describes what data you will be collecting, why, and how it will be shared with others (for tips, see [Meyer \(2018\)](#))
- ▶ Create survey on Google Forms (we have a [template](#))
- ▶ Deploy to MTurk



Last year, every group made at least one error deploying their relatively simple survey.

https://en.wikipedia.org/wiki/Failure#/media/File:Train_wreck_at_Montparnasse_1895.jpg

Our recommended work flow:

- ▶ Create a write-up that describes what data you will be collecting, why, and how it will be shared with others (for tips, see [Meyer \(2018\)](#))
- ▶ Create survey on Google Forms (we have a [template](#))
- ▶ Deploy to MTurk

Our recommended work flow:

- ▶ Create a write-up that describes what data you will be collecting, why, and how it will be shared with others (for tips, see [Meyer \(2018\)](#))
- ▶ Create survey on Google Forms (we have a [template](#))
- ▶ Deploy to MTurk
- ▶ Take a break



Allison Morgan
@alliecmorgan

Following



Just wrapped up the first week of
#SICSS2017! On Thursday, we got 50+
online survey responses, all while frolicking in
a fountain.



3:24 PM - 24 Jun 2017

Our recommended work flow:

- ▶ Create a write-up that describes what data you will be collecting, why, and how it will be shared with others (for tips, see [Meyer \(2018\)](#))
- ▶ Create survey on Google Forms
- ▶ Deploy to MTurk
- ▶ Take a break

Our recommended work flow:

- ▶ Create a write-up that describes what data you will be collecting, why, and how it will be shared with others (for tips, see [Meyer \(2018\)](#))
- ▶ Create survey on Google Forms
- ▶ Deploy to MTurk
- ▶ Take a break
- ▶ Validate and pay workers

Our recommended work flow:

- ▶ Create a write-up that describes what data you will be collecting, why, and how it will be shared with others (for tips, see [Meyer \(2018\)](#))
- ▶ Create survey on Google Forms
- ▶ Deploy to MTurk
- ▶ Take a break
- ▶ Validate and pay workers
- ▶ Analyze the much larger sample that we have collected for you

A quick and dirty tour of the post-stratification methods we will use

Use this estimator in three steps:

1. Chop up the sample into groups

Use this estimator in three steps:

1. Chop up the sample into groups
2. Estimate the mean in each group

Use this estimator in three steps:

1. Chop up the sample into groups
2. Estimate the mean in each group
3. Combine the estimates for each group into an overall estimate

Use this estimator in three steps:

1. Chop up the sample into groups
2. Estimate the mean in each group
3. Combine the estimates for each group into an overall estimate

$$\hat{\bar{y}}_{post} = \sum_{h=1}^H \frac{N_h}{N} \hat{\bar{y}}_h$$

where

- ▶ N : size of the population
- ▶ N_h : size of group h
- ▶ $\hat{\bar{y}}_h$: estimated average outcome for group h

Techniques vary in how they estimate the average outcome for group h : $\hat{\bar{y}}_h$

Cell-based Poststratification

“Response Homogeneity Group Model” (RHG Model), see Sarndal et al. (1992) Sec 15.6.2 (“A Useful Response Model”) Assumptions:

- ▶ The realized sample s is partitioned into H groups, s_1, s_2, \dots, s_H
- ▶ Given s , all elements in s_k are assumed to have the same response probability; different groups can have different response probabilities
- ▶ Equivalent to data is missing completely at random (MCAR) within each group

If RHG model holds (and some other minor technical conditions), then the poststratification estimator is unbiased. See Sarndal et al. (1992) Result 15.6.1

Bias of cell-based poststratification estimator from non-response

If RHG does not hold and if the original sample is simple random sampling without replacement, then (Bethlehem, Cobben, and Schouten 2011, sec. 8.2.1):

$$bias(\hat{y}_{post}) = \frac{1}{N} \sum_{h=1}^H \frac{cor(\phi_i, y_i)^{(h)} S(\phi_i)^{(h)} S(y_i)^{(h)}}{\bar{\phi}^{(h)}}$$

So, how should we create the H groups?

Bias of cell-based poststratification estimator from non-response

If RHG does not hold and if the original sample is simple random sampling without replacement, then (Bethlehem, Cobben, and Schouten 2011, sec. 8.2.1):

$$bias(\hat{y}_{post}) = \frac{1}{N} \sum_{h=1}^H \frac{cor(\phi_i, y_i)^{(h)} S(\phi_i)^{(h)} S(y_i)^{(h)}}{\bar{\phi}^{(h)}}$$

So, how should we create the H groups?

- ▶ form homogeneous groups where there is little variation in response propensity ($S(\phi_i)^{(h)} \approx 0$) and the outcome ($S(y_i)^{(h)} \approx 0$)

Bias of cell-based poststratification estimator from non-response

If RHG does not hold and if the original sample is simple random sampling without replacement, then (Bethlehem, Cobben, and Schouten 2011, sec. 8.2.1):

$$bias(\hat{y}_{post}) = \frac{1}{N} \sum_{h=1}^H \frac{cor(\phi_i, y_i)^{(h)} S(\phi_i)^{(h)} S(y_i)^{(h)}}{\bar{\phi}^{(h)}}$$

So, how should we create the H groups?

- ▶ form homogeneous groups where there is little variation in response propensity ($S(\phi_i)^{(h)} \approx 0$) and the outcome ($S(y_i)^{(h)} \approx 0$)
- ▶ form groups where the people that you see are like the people that you don't see ($cor(\phi_i, y_i)^{(h)} \approx 0$)

In practice this can be difficult because you want to form many groups, but then you have noisy estimates for each group.

Note:

- ▶ Horvitz-Thompson estimation is individual-based weight
- ▶ Poststratification can better be understood as a group-based weight

Three increasingly sophisticated ways to make group estimate \hat{y}_h . You won't have time to do all of these:

- ▶ simple cell-based poststratification
- ▶ model-based poststratification
- ▶ multilevel regression poststratification (Mr. P)

Data

- ▶ The data that we are providing you for analysis comes from a survey we deployed on MTurk recently
- ▶ We will compare to high-quality telephone surveys from the Pew Research Center (links to [questionnaires](#))
- ▶ To poststratify our survey data, we will use data from the American Community Survey about the population of the United States
- ▶ We use multiple questions because estimates are also a property of a question not just a sample.

Simple cell-based poststratification

Let's do lots of groups.

- ▶ gender (2 groups)
- ▶ age (4 groups)
- ▶ race (5 groups)
- ▶ region (4 groups)
- ▶ Makes $160 (2 \times 4 \times 5 \times 4)$ groups

Simple cell-based poststratification

$$\hat{y}_h = \frac{\sum_{i \in h} y_i}{n_h}$$

h is a group described by a unique combination of gender (2 groups) \times age (4 groups) \times race (5 groups) \times region (4 groups)

Simple cell-based poststratification



- ▶ We can't make an estimate for each group. For example, we don't have any female, 65+, Hispanic living in the South.

Simple cell-based poststratification



- ▶ We can't make an estimate for each group. For example, we don't have any female, 65+, Hispanic living in the South.
- ▶ This problem can arise if you have too many cell. We have a crude work-around in the code we provide.

For the activity, it would be great if you could complete doing simple cell-based poststratification. The following slides are if you have extra time and want to try other methods.

Model-based poststratification

$$\hat{\bar{y}}_{post} = \sum_{h=1}^H \frac{N_h}{N} \hat{\bar{y}}_h$$

where $\hat{\bar{y}}_h$ comes from an individual-level model

$$\begin{aligned} Pr(y_i = 1) = & \text{logit}^{-1}(\beta_0 + \\ & \beta_{male} \cdot male_i + \\ & \beta_{30-49} \cdot 30 - 49_i + \beta_{50-64} \cdot 50 - 64_i + \beta_{65+} \cdot 65_i + \\ & \beta_{afr-am} \cdot afam_i + \beta_{as-am} \cdot asam_i + \beta_{hispanic} \cdot hisp_i + \beta_{other} \cdot other_i + \\ & \beta_{midwest} \cdot midwest_i + \beta_{south} \cdot south_i + \beta_{west} \cdot west_i) \end{aligned}$$

Bayesian Multilevel Estimation with Poststratification: State-Level Estimates from National Polls

David K. Park

*Department of Political Science and Applied Statistics,
Washington University, St. Louis, MO 63130
e-mail: dpark@artsci.wustl.edu*

Andrew Gelman

*Departments of Statistics and Political Science, Columbia University,
New York, NY 10027
e-mail: gelman@stat.columbia.edu*

Joseph Bafumi

Department of Political Science, Columbia University, New York, NY 10027

<https://www.jstor.org/stable/25791784>

See also Gelman and Hill (2007), Chapter 14 ("Multilevel logistic regression")

We fit a multilevel logistic regression model for the mean of a binary response variable conditional on poststratification cells. This approach combines the modeling approach often used in small-area estimation with the population information used in poststratification (see Gelman and Little 1997, *Survey Methodology* 23:127–135). To validate the method, we apply it to U.S. preelection polls for 1988 and 1992, poststratified by state, region, and the usual demographic variables. We evaluate the model by comparing it to state-level election outcomes. The multilevel model outperforms more commonly used models in political science. We envision the most important usage of this method to be not forecasting elections but estimating public opinion on a variety of issues at the state level.

<https://www.jstor.org/stable/25791784>

See also Gelman and Hill (2007), Chapter 14 (“Multilevel logistic regression”)

Mr. P.

\hat{y}_h comes from an individual-level model

$$\begin{aligned} Pr(y_i = 1) = & \text{logit}^{-1}(\beta_0 + \\ & \beta_{\text{male}} \cdot \text{male}_i + \\ & \alpha_{k[i]}^{\text{age}} + \\ & \alpha_{k[i]}^{\text{race}} + \\ & \alpha_{k[i]}^{\text{region}}) \end{aligned}$$

$$\alpha_k^{\text{age}} \sim N(0, \sigma_{\text{age}}^2) \text{ for } k = 1, \dots, 4$$

$$\alpha_k^{\text{race}} \sim N(0, \sigma_{\text{race}}^2) \text{ for } k = 1, \dots, 5$$

$$\alpha_k^{\text{region}} \sim N(0, \sigma_{\text{region}}^2) \text{ for } k = 1, \dots, 4$$

Priors determined by RStanarm (<https://cran.r-project.org/web/packages/rstanarm/vignettes/priors.html>)

To learn more about Mr. P.

Generally optimistic:

- ▶ Park, Gelman, and Bafumi. 2004. “[Bayesian Multilevel Estimation with Poststratification: State-Level Estimates from National Polls](#).” *Political Analysis*.
- ▶ Lax and Phillips. 2009. “[How should we estimate public opinion in the states?](#)” *American Journal of Political Science*.
- ▶ Ghitza and Gelman. 2013. “[Deep Interactions with MRP: Election Turnout and Voting Patterns Among Small Electoral Subgroups](#).” *American Journal of Political Science*.
- ▶ Warshaw and Rodden. 2012. “[How should we measure district-level public opinion on individual issues?](#)” *Journal of Politics*.
- ▶ Downs et al. 2018. “[Multilevel Regression and Poststratification: A Modelling Approach to Estimating Population Quantities From Highly Selected Survey Samples](#).” *American Journal of Epidemiology*.

Generally cautious:

- ▶ Buttice and Highton. 2013. “[How Does Multilevel Regression and Poststratification Perform with Conventional National Surveys?](#)” *Political Analysis*.

Our recommended work flow:

- ▶ Create a write-up that describes what data you will be collecting, why, and how it will be shared with others (for tips, see [Meyer \(2018\)](#))
- ▶ Create survey on Google Forms
- ▶ Deploy to MTurk
- ▶ Take a break
- ▶ Validate and pay workers
- ▶ Analyze the much larger sample that we have collected for you
- ▶ Ideal but not possible because of time constraints: De-identify and “open-source” data by sending to your local organizer (but remember to think about the end at the beginning)



https://www.youtube.com/watch?v=66oNv_DJuPc

YouTube search: “Data Sharing and Management Snafu in 3 Short Acts”

When you start your projects next week

- ▶ plan to release your data
- ▶ plan to release your code

Our recommended work flow:

- ▶ Create a write-up that describes what data you will be collecting, why, and how it will be shared with others (for tips, see [Meyer](#))
- ▶ Create survey on Google Forms
- ▶ Deploy to MTurk
- ▶ Take a break
- ▶ Validate and pay workers
- ▶ Analyze the much larger sample that we have collected for you
- ▶ Ideal but not possible because of time constraints: De-identify and “open-source” data by sending to your local organizer (but remember to think about the end at the beginning)