

# Predictive Coding

Computational Psychiatry Course  
03.09.2019

Lilian A. Weber  
Translational Neuromodeling Unit  
University of Zurich & ETH Zurich

# I. The idea: an algorithmic motif

From redundancy reduction in signal processing to approximate Bayesian inference in the visual cortex: *Rao & Ballard, 1999*



University of  
Zurich<sup>UZH</sup>

**ETH**

Eidgenössische Technische Hochschule Zürich  
Swiss Federal Institute of Technology Zurich



Translational Neuromodeling Unit

# Predictive coding algorithm(s)

Linear predictive coding

O'Shaughnessy 1988 *IEEE Potentials*

Spatial decorrelation in the retina

Srinivasan et al. 1982 *Proc R Soc London Ser B*,  
Hosoya et al. 2005 *Nature*



Special Invited Review

A review of predictive coding algorithms

M.W. Spratling \*



(a)



University of  
Zurich<sup>UZH</sup>

**ETH**

Eidgenössische Technische Hochschule Zürich  
Swiss Federal Institute of Technology Zurich



Translational Neuromodeling Unit

Kersten 1987 *J Opt Soc Am A*

# Predictive coding algorithm(s)

Linear predictive coding

O'Shaughnessy 1988 *IEEE Potentials*

Spatial decorrelation in the retina

Srinivasan et al. 1982 *Proc R Soc London Ser B*,  
Hosoya et al. 2005 *Nature*

Predictive coding in visual cortex

Rao & Ballard 1999 *Nat Neurosci*

Free-energy formulation of predictive coding

Friston 2005 *Phil Trans Royal Soc B*




ELSEVIER

Special Invited Review

A review of predictive coding algorithms

M.W. Spratling \*




Stefanics et al. 2014 *Front Hum Neurosci*

### III. Predictive coding as approximate inference

Firing rates/  
Pixel values      Model (possible  
patterns)      noise

$$\mathbf{I} = f(\mathbf{U}\mathbf{r}) + \mathbf{n}$$

$$\begin{bmatrix} i_1 \\ i_2 \\ i_3 \\ \vdots \\ i_K \end{bmatrix} = f\left(\begin{bmatrix} u_{1,1} & u_{1,2} & \cdots & u_{1,N} \\ u_{2,1} & u_{2,2} & \cdots & u_{2,N} \\ u_{3,1} & u_{3,2} & \cdots & u_{3,N} \\ \vdots & \ddots & & \vdots \\ u_{K,1} & u_{K,2} & \cdots & u_{K,N} \end{bmatrix} \begin{bmatrix} r_1 \\ r_2 \\ \vdots \\ r_N \end{bmatrix}\right) + \begin{bmatrix} n_1 \\ n_2 \\ n_3 \\ \vdots \\ n_K \end{bmatrix}$$



University of  
Zurich<sup>uzh</sup>

**ETH**

Eidgenössische Technische Hochschule Zürich  
Swiss Federal Institute of Technology Zurich



Translational Neuromodeling Unit

Rao & Ballard 1999 Nat Neurosci


# III. Predictive coding as approximate inference

Introducing hierarchy

$$\mathbf{r} = \mathbf{r}^{\text{td}} + \mathbf{n}^{\text{td}}$$

$$= f(U^h \mathbf{r}^h) + \mathbf{n}^{\text{td}}$$

$$\mathbf{I} = f(U\mathbf{r}) + \mathbf{n}$$



Rao & Ballard 1999 *Nat Neurosci*



University of  
Zurich<sup>UZH</sup>

**ETH**

Eidgenössische Technische Hochschule Zürich  
Swiss Federal Institute of Technology Zurich



Translational Neuromodeling Unit

### III. Predictive coding as approximate inference


Implementation

$$\mathbf{r} = \mathbf{r}^{\text{td}} + \mathbf{n}^{\text{td}}$$

$$= f(\mathbf{U}^{\text{h}} \mathbf{r}^{\text{h}}) + \mathbf{n}^{\text{td}}$$

$$\mathbf{I} = f(\mathbf{U} \mathbf{r}) + \mathbf{n}$$

Question: How to find  $\mathbf{r}$  and  $\mathbf{U}$ ?



University of  
Zurich<sup>UZH</sup>

ETH

Eidgenössische Technische Hochschule Zürich  
Swiss Federal Institute of Technology Zurich



Translational Neuromodeling Unit

Rao & Ballard 1999 Nat Neurosci


# Predictive coding as approximate inference

Optimization: Finding causes and associations

$$E = E_1 - \log p(\mathbf{r}) - \log p(U)$$

$$E_1 = \frac{1}{\sigma^2} (\mathbf{I} - f(U\mathbf{r}))^\top (\mathbf{I} - f(U\mathbf{r})) + \frac{1}{\sigma_{\text{td}}^2} (\mathbf{r} - \mathbf{r}^{\text{td}})^\top (\mathbf{r} - \mathbf{r}^{\text{td}})$$

(precision-weighted) sum of squared  
prediction errors



University of  
Zurich<sup>UZH</sup>

**ETH**

Eidgenössische Technische Hochschule Zürich  
Swiss Federal Institute of Technology Zurich



Translational Neuromodeling Unit

# Predictive coding as approximate inference

**Inference:** Estimating the causes based on inputs and expectations

**Learning:** Improving the model to reflect the statistics of the environment


$$\frac{d\mathbf{r}}{dt} = -\frac{k_1}{2} \frac{\partial E}{\partial \mathbf{r}}$$

$$= \frac{k_1}{\sigma^2} U^T \frac{\partial f}{\partial U \mathbf{r}}^\top (\mathbf{I} - f(U\mathbf{r})) + \frac{k_1}{\sigma_{td}^2} (\mathbf{r}^{td} - \mathbf{r}) - k_1 \alpha \mathbf{r}$$

Inputs                      Expectations  
precision-weighting

$$\frac{dU}{dt} = -\frac{k_2}{2} \frac{\partial E}{\partial U} = \frac{k_2}{\sigma^2} \frac{\partial f}{\partial U \mathbf{r}}^\top (\mathbf{I} - f(U\mathbf{r}))\mathbf{r} - \frac{k_2}{2} \lambda U$$

Hebbian learning



Rao & Ballard 1999 Nat Neurosci



University of  
Zurich

**ETH**

Eidgenössische Technische Hochschule Zürich  
Swiss Federal Institute of Technology Zurich



Translational Neuromodeling Unit

# Predictive coding as approximate inference

**Inference:** Estimating the causes based on inputs and expectations

**Learning:** Improving the model to reflect the statistics of the environment

$$\frac{d\mathbf{r}}{dt} = -\frac{k_1}{2} \frac{\partial E}{\partial \mathbf{r}}$$


**Inputs**                    **Expectations**

$$= \frac{k_1}{\sigma^2} U^\top \frac{\partial f}{\partial U \mathbf{r}}^\top (\mathbf{I} - f(U \mathbf{r})) + \frac{k_1}{\sigma_{\text{td}}^2} (\mathbf{r}^{\text{td}} - \mathbf{r}) - k_1 \alpha \mathbf{r}$$

precision-weighting

$$\frac{dU}{dt} = -\frac{k_2}{2} \frac{\partial E}{\partial U} = \frac{k_2}{\sigma^2} \frac{\partial f}{\partial U \mathbf{r}}^\top (\mathbf{I} - f(U \mathbf{r})) \mathbf{r} - \frac{k_2}{2} \lambda U$$

Hebbian learning



Rao & Ballard 1999 Nat Neurosci



University of  
Zurich

**ETH**

Eidgenössische Technische Hochschule Zürich  
Swiss Federal Institute of Technology Zurich



Translational Neuromodeling Unit

# Predictive coding as approximate inference

**Inference:** Estimating the causes based on inputs and expectations

**Learning:** Improving the model to reflect the statistics of the environment


$$\frac{d\mathbf{r}}{dt} = -\frac{k_1}{2} \frac{\partial E}{\partial \mathbf{r}}$$

$$= \frac{k_1}{\sigma^2} U^\top \frac{\partial f}{\partial U \mathbf{r}}^\top (\mathbf{I} - f(U \mathbf{r})) + \frac{k_1}{\sigma_{\text{td}}^2} (\mathbf{r}^{\text{td}} - \mathbf{r}) - k_1 \alpha \mathbf{r}$$

Inputs                      Expectations  
precision-weighting

$$\frac{dU}{dt} = -\frac{k_2}{2} \frac{\partial E}{\partial U} = \frac{k_2}{\sigma^2} \frac{\partial f}{\partial U \mathbf{r}}^\top (\mathbf{I} - f(U \mathbf{r})) \mathbf{r} - \frac{k_2}{2} \lambda U$$

Hebbian learning



University of  
Zurich<sup>uzh</sup>

**ETH**

Eidgenössische Technische Hochschule Zürich  
Swiss Federal Institute of Technology Zurich




Translational Neuromodeling Unit

Rao & Ballard 1999 Nat Neurosci

# Predictive coding as approximate inference

## Summary

- A hierarchy of causes (predictive estimators and PE units)
- **Recurrent message passing:** PEs are signaled upwards (bottom-up) and predictions are signaled top-down
- **Inference:** finding the most appropriate causes to describe the data
- **Learning:** finding the most appropriate model to describe the data
- Both involve **minimizing precision-weighted prediction errors**
- (This looks like Bayesian inference for finding the most likely causes of sensory inputs (MAP estimates) and like Hebbian learning, respectively)




Rao & Ballard 1999 *Nat Neurosci*

# The main ingredients of predictive coding (from a computational point of view)

- A hierarchical generative model of sensory inputs
- The estimates of the causes generate predictions of sensory input
- The estimates of causes are updated in response to prediction errors (mismatches)
- The relative influence of PEs and predictions is determined by their relative precision (certainty)
- These computations underlie both perception (inference) and learning (model update)

$$\Delta \text{belief} \sim \text{precision} \times \text{PE}$$



Adapted from Stephan et al. 2016 *Brain*



University of  
Zurich<sup>UZH</sup>

**ETH**

Eidgenössische Technische Hochschule Zürich  
Swiss Federal Institute of Technology Zurich



Translational Neuromodeling Unit

## II. Implementing (and testing) PC

Mapping the ingredients of predictive coding onto neuroanatomy and  
neurophysiology



University of  
Zurich<sup>UZH</sup>

**ETH**


Eidgenössische Technische Hochschule Zürich  
Swiss Federal Institute of Technology Zurich



Translational Neuromodeling Unit

# Mapping predictive coding onto the brain

- A hierarchical generative model of sensory inputs
- The estimates of the causes generate predictions of sensory input
- The estimates of causes are updated in response to prediction errors (mismatches)
- The relative influence of PEs and predictions is determined by their relative precision (certainty)
- These computations underlie both perception (inference) and learning (model update)



University of  
Zurich<sup>UZH</sup>

ETH

Eidgenössische Technische Hochschule Zürich  
Swiss Federal Institute of Technology Zurich



Translational Neuromodeling Unit


Felleman & Van Essen 1991 Cereb Cortex

15

# Mapping predictive coding onto the brain

- A hierarchical generative model of sensory inputs
- The estimates of the causes generate predictions of sensory input
- The estimates of causes are updated in response to prediction errors (mismatches)
- The relative influence of PEs and predictions is determined by their relative precision (certainty)
- These computations underlie both perception (inference) and learning (model update)

1. The source populations of forward and backward pathways should be completely separate, given their functional distinction.



University of  
Zurich<sup>UZH</sup>

ETH

Eidgenössische Technische Hochschule Zürich  
Swiss Federal Institute of Technology Zurich





Translational Neuromodeling Unit

Berezovskii et al. 2011 *J Comp Neurol*

# Mapping predictive coding onto the brain

- A hierarchical generative model of sensory inputs
- The estimates of the causes generate predictions of sensory input
- The estimates of causes are updated in response to prediction errors (mismatches)
- The relative influence of PEs and predictions is determined by their relative precision (certainty)
- These computations underlie both perception (inference) and learning (model update)

1. The source populations of forward and backward pathways should be completely separate, given their functional distinction.



Markov et al. 2014 *J Comp Neurol*



University of  
Zurich<sup>UZH</sup>

ETH

Eidgenössische Technische Hochschule Zürich  
Swiss Federal Institute of Technology Zurich




Translational Neuromodeling Unit

# Mapping predictive coding onto the brain

- A hierarchical generative model of sensory inputs
- The estimates of the causes generate predictions of sensory input
- The estimates of causes are updated in response to prediction errors (mismatches)
- The relative influence of PEs and predictions is determined by their relative precision (certainty)
- These computations underlie both perception (inference) and learning (model update)

2. Backward connections encode predictions and expected precision, so they should be more divergent.



Zeki & Shipp 1988 *Nature*

3. Causes interact non-linearly to generate data, so backward connections should be more modulatory.

Self et al. 2012 *PNAS*  
Olsen et al. 2012 *Nature*  
Zilles et al. 2004 *J Anat*

4. Predictions are generated more slowly than prediction errors, suggesting a spectral asymmetry.

Roopun 2006 *PNAS*  
Roopun et al. 2008  
*Front. Cell. Neurosci*

Buffalo et al. 2011 *PNAS*  
Bosman et al. 2012 *Neuron*  
Bastos et al. 2015 *NeuroImage*



University of  
Zurich<sup>UZH</sup>

**ETH**


Eidgenössische Technische Hochschule Zürich  
Swiss Federal Institute of Technology Zurich



Translational Neuromodeling Unit

# Mapping predictive coding onto the brain

- A hierarchical generative model of sensory inputs
- The estimates of the causes generate predictions of sensory input
- The estimates of causes are updated in response to prediction errors (mismatches)
- **The relative influence of PEs and predictions is determined by their relative precision (certainty)**
- These computations underlie both perception (inference) and learning (model update)



Adapted from Iglesias et al. 2017 *WIRE Cogn Sci*



University of  
Zurich<sup>UZH</sup>

**ETH**


Eidgenössische Technische Hochschule Zürich  
Swiss Federal Institute of Technology Zurich





Translational Neuromodeling Unit

# Mapping predictive coding onto the brain

- A hierarchical generative model of sensory inputs
- The estimates of the causes generate predictions of sensory input
- The estimates of causes are updated in response to prediction errors (mismatches)
- **The relative influence of PEs and predictions is determined by their relative precision (certainty)**
- These computations underlie both perception (inference) and learning (model update)



Fiorillo et al. 2003 *Science*



Tobler et al. 2005 *Science*

Achieved via cholinergic modulation?  
Naudé et al. 2018 *bioRxiv*



University of  
Zurich<sup>UZH</sup>

ETH


Eidgenössische Technische Hochschule Zürich  
Swiss Federal Institute of Technology Zurich



Translational Neuromodeling Unit

# Mapping predictive coding onto the brain

- A hierarchical generative model of sensory inputs
- The estimates of the causes generate predictions of sensory input
- The estimates of causes are updated in response to prediction errors (mismatches)
- The relative influence of PEs and predictions is determined by their relative precision (certainty)
- These computations underlie both perception (inference) and learning (model update)



University of  
Zurich<sup>UZH</sup>

**ETH**

Eidgenössische Technische Hochschule Zürich  
Swiss Federal Institute of Technology Zurich



Translational Neuromodeling Unit

Stephan et al. 2016 *Brain*



# Is predictive coding theory articulated enough to be testable?

*Naoki Kogo \* and Chris Trengove*



University of  
Zurich<sup>uzh</sup>


**ETH**

Eidgenössische Technische Hochschule Zürich  
Swiss Federal Institute of Technology Zurich




Translational Neuromodeling Unit

Haeusler and Maass (2007)




Bastos et al. 2012 *Neuron*

Canonical microcircuit for predictive coding



# Mapping predictive coding onto the brain ... advanced



University of  
Zurich<sup>UZH</sup>

ETH

Eidgenössische Technische Hochschule Zürich  
Swiss Federal Institute of Technology Zurich




Translational Neuromodeling Unit

Shipp 2016 *Frontiers in Psychology*

# Testing the *relevant* predictions

- locomotion is sufficient to drive activity in mouse V1, even in the complete absence of visual input (**Keller et al., 2012, Saleem et al., 2013**)
- layer 2/3 of sensory cortices signals a mismatch between predicted and actual sensory feedback (**Eliades and Wang, 2008, Keller et al., 2012**)
- this results from a comparison of an excitatory motor-related input and an inhibitory visual input (**Attinger et al., 2017, Zmarz and Keller, 2016**)
- A24b/M2 provides a strong and dense projection to V1, which conveys motor-related signals that depend on the mouse's visuomotor experience. This projection fulfills all the criteria necessary to be interpreted as a prediction of visual flow given a motor output (**Leinweber et al., 2017**)



University of  
Zurich<sup>UZH</sup>


**ETH**

Eidgenössische Technische Hochschule Zürich  
Swiss Federal Institute of Technology Zurich



Translational Neuromodeling Unit

# Testing the *relevant* predictions



University of  
Zurich<sup>UZH</sup>

**ETH**

Eidgenössische Technische Hochschule Zürich  
Swiss Federal Institute of Technology Zurich



Translational Neuromodeling Unit

Heilbron & Chait 2018 Neurosci

26

# III. The computational goal

From representing probability distributions (and uncertainty) and the Laplace assumption to predictions on cortical infrastructure and plasticity: *Friston, 2005*



University of  
Zurich<sup>UZH</sup>

**ETH**

Eidgenössische Technische Hochschule Zürich  
Swiss Federal Institute of Technology Zurich



Translational Neuromodeling Unit



Available online at [www.sciencedirect.com](http://www.sciencedirect.com)

**ScienceDirect**

Current Opinion in  
**Neurobiology**

## **With or without you: predictive coding and Bayesian inference in the brain**

Laurence Aitchison<sup>1</sup> and Máté Lengyel<sup>1,2</sup>



CrossMark

## **What does the free energy principle tell us about the brain?**

Samuel J. Gershman

[arXiv:1901.07945v1](https://arxiv.org/abs/1901.07945v1)



**University of  
Zurich**<sup>uzh</sup>

**ETH**

Eidgenössische Technische Hochschule Zürich  
Swiss Federal Institute of Technology Zurich



Translational Neuromodeling Unit

# Predictive coding as approximate inference: Rao and Ballard

Optimization: Finding causes and associations


$$E = E_1 - \log p(\mathbf{r}) - \log p(U)$$

$$E_1 = \underbrace{\frac{1}{\sigma^2}(\mathbf{I} - f(U\mathbf{r}))^\top(\mathbf{I} - f(U\mathbf{r})) + \frac{1}{\sigma_{\text{td}}^2}(\mathbf{r} - \mathbf{r}^{\text{td}})^\top(\mathbf{r} - \mathbf{r}^{\text{td}})}_{-\log p(\mathbf{I}|\mathbf{r}, U) + C}$$


$$E = -\log p(\mathbf{I}|\mathbf{r}, U) - \log p(\mathbf{r}) - \log p(U)$$

$$= -\log(p(\mathbf{I}|\mathbf{r}, U) p(\mathbf{r}) p(U))$$

Optimization looks like finding the most likely cause (MAP estimate) in Bayesian inference.



# The Bayesian Brain



University of  
Zurich<sup>UZH</sup>

ETH

Eidgenössische Technische Hochschule Zürich  
Swiss Federal Institute of Technology Zurich



Translational Neuromodeling Unit

$$p(x|y) = \frac{p(x)p(y|x)}{p(y)} \quad p(y) = \int p(x)p(y|x) \, dx$$

# Representing uncertainty

So far, we've only computed the MAP.  
To be fully Bayesian: care about your uncertainty!




$q(x)$ : our best guess about  $p(x|y)$

$$\begin{aligned} \text{KL}(q(x), p(x|y)) &= \ln p(y) - \int q(x) \ln \frac{p(y, x)}{q(x)} \, dx \\ &= \ln p(y) - F \end{aligned}$$

$$\ln p(y|m) = \text{KL}(q(x), p(x|y, m)) + F(q(x), p(x, y|m))$$

$$F = \int q(x) \ln \frac{p(y, x)}{q(x)} \, dx$$



University of  
Zurich

**ETH**

Eidgenössische Technische Hochschule Zürich  
Swiss Federal Institute of Technology Zurich



Translational Neuromodeling Unit

Bishop, 2008; Friston et al. 2007 *NeuroImage*

# 'Fristonian' PC

The free energy formulation of predictive coding

$$F = \int q(x) \ln \frac{p(y, x)}{q(x)} dx$$

**Inference:** maximizing F to find the approximate posterior


**Learning:** maximizing F to improve the model and thereby reduce average surprise over time.

Additional assumption:  $q(x)$  is a Gaussian.

We only need to represent the mean and the variance.

→ *precision-weighted prediction errors*

Predictive Coding can be viewed as the implementation of a particular scheme of approximate Bayesian inference in the brain.



Predictive Coding



University of  
Zurich<sup>UZH</sup>

**ETH**

Eidgenössische Technische Hochschule Zürich  
Swiss Federal Institute of Technology Zurich



Translational Neuromodeling Unit

# IV. PC in CP

Stratifying psychiatric diseases using hierarchical Bayesian models



University of  
Zurich<sup>UZH</sup>

**ETH**

Eidgenössische Technische Hochschule Zürich  
Swiss Federal Institute of Technology Zurich



Translational Neuromodeling Unit


# Hierarchical Bayesian Inference in Computational Psychiatry

Possible primary disruption at:


1. Sensory inputs (sensations)
2. Inference (perception)
3. Forecasting
4. Control (action)
5. Metacognition

At any of these, possible disturbance of:

- Prediction error (PE) computation
- Predictions/Expectations
- Estimation of their precision.



Stephan et al. 2016 *Brain*



Petzschnier et al. 2017 *Biol Psychiatry*



University of  
Zurich<sup>UZH</sup>

ETH

Eidgenössische Technische Hochschule Zürich  
Swiss Federal Institute of Technology Zurich



Translational Neuromodeling Unit


# Precision: The right balance

Schizophrenia/Psychosis

Sterzer et al. 2018 *Biol Psychiatry*; Adams et al. 2013 *Front Psychiatry*; Corlett et al. 2011 *NPP*; Stephan et al. 2006 *Biol Psychiatry*; 2009; Powers et al. 2017 *Science*

Autism spectrum disorder

Pellicano & Burr 2012 *TiCS*; Van de Cruys et al. 2014 *Psychol Rev*; Lawson et al. 2014 *Front Hum Neurosci*; Lawson et al. 2017 *Nat Neurosci*



University of  
Zurich<sup>UZH</sup>

**ETH**

Eidgenössische Technische Hochschule Zürich  
Swiss Federal Institute of Technology Zurich



Translational Neuromodeling Unit

Sterzer et al. 2018 *Biol Psychiatry*

# A role for interoception


Seth 2013 *TiCS*

Barrett & Simmons 2015 *Nature Rev Neurosci*

Seth & Friston 2016 *Phil Trans Royal Soc B*

**Stephan et al. 2016 *Front Hum Neurosci***

Petzschnier et al. 2017 *Biol Psychiatry*



University of  
Zurich<sup>UZH</sup>

**ETH**

Eidgenössische Technische Hochschule Zürich  
Swiss Federal Institute of Technology Zurich



Translational Neuromodeling Unit

PREDICTIVE CODING

## Does predictive coding have a future?

In the 20th century we thought the brain extracted knowledge from sensations. The 21st century witnessed a 'strange inversion', in which the brain became an organ of inference, actively constructing explanations for what's going on 'out there', beyond its sensory epithelia. One paper played a key role in this paradigm shift.

Karl Friston

## V. THE FUTURE OF PC

Tests and extensions



University of  
Zurich<sup>UZH</sup>

ETH

Eidgenössische Technische Hochschule Zürich  
Swiss Federal Institute of Technology Zurich



Translational Neuromodeling Unit

# I. Testing further

- Sources of modulatory (precision) signals
  - Neuromodulators and how they interact
- Separate error units and prediction (representation) units
  - Laminar resolution, especially in the auditory domain (vision: Kok et al. 2016 *Curr Biol*)
  - High temporal resolution (predictions can precede a stimulus, PEs can only follow)
- Computationally explicit analyses ('model-based')
  - to test crucial theoretical distinctions, e.g. PEs vs. precision-weighted PEs
  - e.g., Iglesias et al. 2013 *Neuron*; Sedley et al. 2016 *eLife*; Bell et al. 2016 *Curr Biol*



University of  
Zurich<sup>UZH</sup>

**ETH**


Eidgenössische Technische Hochschule Zürich  
Swiss Federal Institute of Technology Zurich




Translational Neuromodeling Unit

## II. PC and ANNs

- A predictive coding network can perform supervised learning autonomously using simple Hebbian learning and approximates the backpropagation algorithm (Whittington & Bogacz 2017 *Neural Computation*)
- A single pyramidal neuron can implement predictive coding via its apical dendrites (Urbanczik & Senn 2014 *Neuron*; Sacramento et al. 2018 *NIPS*) which can help to solve the credit assignment problem... (Guergiev et al. 2017 *eLife*)



B Segregated dendrites solution



University of  
Zurich<sup>UZH</sup>

**ETH**

Eidgenössische Technische Hochschule Zürich  
Swiss Federal Institute of Technology Zurich



Translational Neuromodeling Unit


# Thank you



Translational Neuromodeling Unit

Rick Adams

Rafal Bogacz



$$\Delta \text{belief} \sim \text{precision} \times \text{PE}$$