

Machine Learning I: basics

Andre F. Marquand

a.marquand@donders.ru.nl



- Pattern Recognition (PR) is a subfield of machine learning, which relates to the automatic discovery of patterns of statistical regularity in data
- Aim to learn from empirical data rather than following fixed rules
- **Learn by example**
- Increasingly used in computational psychiatry for:



- Pattern Recognition (PR) is a subfield of machine learning, which relates to the automatic discovery of patterns of statistical regularity in data
- Aim to learn from empirical data rather than following fixed rules
- **Learn by example**
- Increasingly used in computational psychiatry for:
 - ① Predicting clinical variables (diagnosis or treatment response)
 - ② Stratifying psychiatric disorders



- 1 Introduction to Machine Learning
- 2 Basics of Pattern Recognition Analyses
- 3 Applications in Psychiatry
- 4 Conclusions



1 Introduction to Machine Learning

2 Basics of Pattern Recognition Analyses

3 Applications in Psychiatry

4 Conclusions



Historically, has been applied in many application domains:


Example Applications

- Speech Recognition
- Automatic Character recognition / handwriting recognition
- Document classification (e.g. spam filters)
- Analysis of genetic microarray data
- Self-driving cars
- Recommender systems / online shopping
- ...

Types of pattern recognition




Supervised learning involves learning a mapping between input and output:



Types of pattern recognition




Supervised learning involves learning a mapping between input and output:




Types of pattern recognition



Supervised learning involves learning a mapping between input and output:




In **Unsupervised** learning, algorithms are not provided with output labels and must learn to structure the data by applying heuristics




Types of pattern recognition



Supervised learning involves learning a mapping between input and output:




In **Unsupervised** learning, algorithms are not provided with output labels and must learn to structure the data by applying heuristics




Types of pattern recognition



Supervised learning involves learning a mapping between input and output:




In **Unsupervised** learning, algorithms are not provided with output labels and must learn to structure the data by applying heuristics






Mass univariate association testing (SPM, GWAS)






Mass univariate association testing (SPM, GWAS)



- Useful for understanding mechanisms



Mass univariate association testing (SPM, GWAS)




- Useful for understanding mechanisms
- For clinical decision making this does not suffice. It is necessary to make predictions about individuals


Predicting disease state



Making subject level predictions of diagnosis and outcome



Class 1
("patients")




Class 2
("controls")

Predicting disease state




Making subject level predictions of diagnosis and outcome



Predicting disease state




Making subject level predictions of diagnosis and outcome



Predicting disease state




Making subject level predictions of diagnosis and outcome



Predicting disease state




Making subject level predictions of diagnosis and outcome



Predicting disease state




Making subject level predictions of diagnosis and outcome



Predicting disease state



Making subject level predictions of diagnosis and outcome




Useful to find a measure of overall group separation

Machine Learning in Psychiatry: Stratification



Tackling the clinical and biological heterogeneity of psychiatric disorders



Insel et al. (2015)



1 Introduction to Machine Learning

2 Basics of Pattern Recognition Analyses

3 Applications in Psychiatry

4 Conclusions

Encoding and Decoding



Cognitive state

- Response to stimulus
- Cognitive scores
- Diagnostic label
- Symptom scores
- ...

Encoding model

$$Y = f(X)$$



Brain activity (e.g. BOLD)



Encoding and Decoding



*Which brain regions are activated
in a certain task condition?*

Cognitive state

- Response to stimulus
- Cognitive scores
- Diagnostic label
- Symptom scores
- ...

Encoding model

$$Y = f(X)$$




Brain activity (e.g. BOLD)




Encoding and Decoding




*Which brain regions are activated
in a certain task condition?*



Encoding and Decoding



Encoding and Decoding




- Also called Generative/Recognition models
- \neq Generative/Discriminative models in machine learning
- This distinction relates to the brain, not to the methods

Multivariate models



Sensitivity for spatially distributed (or multivariate) effects:



Haynes and Rees (2006)



Stages of supervised pattern recognition analysis



1. Feature extraction and/or feature selection




2. Classification / Regression using cross-validation



3. Performance evaluation

$$acc = \frac{1}{K} \sum_{i=1}^K acc_i$$



Feature selection and feature construction



Whole Brain




Feature selection and feature construction



Whole Brain




Region of Interest




Feature selection and feature construction




Whole Brain



Region of Interest



Searchlight




Feature selection and feature construction




Whole Brain




Region of Interest



Searchlight



Feature selection




Feature selection and feature construction




Whole Brain




Region of Interest



Searchlight



Feature selection



- Can also construct features (e.g. using ICA/ PCA,...)


Feature selection and feature construction




Whole Brain




Region of Interest



Searchlight



Feature selection



- Can also construct features (e.g. using ICA/ PCA,...)
- Feature selection should be performed on training data only!



Notation

$\mathcal{D} = \{\mathbf{X}, \mathbf{y}\}$ or $\{\mathbf{X}, \mathbf{Y}\}$ Dataset

$\mathbf{X}_{N \times D} = [\mathbf{x}_1, \dots, \mathbf{x}_N]^T$ N samples, D features

$\mathbf{y} = [y_1, \dots, y_N]^T$ Targets

$\mathbf{w} = [w_1, \dots, w_D]^T$ Weights



A smorgasbord of different approaches

- Regularisation methods (Penalized linear models, support vector machines, ...)
- Probabilistic approaches (Linear discriminant analysis, Gaussian processes, ...)
- Ensemble methods (Random forests, boosting, ...)
- Neural networks (multi-layer perceptrons, deep learning, ...)



A smorgasbord of different approaches

- Regularisation methods (Penalized linear models, support vector machines, ...)
- Probabilistic approaches (Linear discriminant analysis, Gaussian processes, ...)
- Ensemble methods (Random forests, boosting, ...)
- Neural networks (multi-layer perceptrons, deep learning, ...)

Most methods aim to trade-off data fit with complexity

$$f(\mathbf{x}_i, \mathbf{w}) = f_i = \mathbf{x}_i^T \mathbf{w}$$



A smorgasbord of different approaches

- Regularisation methods (Penalized linear models, support vector machines, ...)
- Probabilistic approaches (Linear discriminant analysis, Gaussian processes, ...)
- Ensemble methods (Random forests, boosting, ...)
- Neural networks (multi-layer perceptrons, deep learning, ...)

Most methods aim to trade-off data fit with complexity

$$f(\mathbf{x}_i, \mathbf{w}) = f_i = \mathbf{x}_i^T \mathbf{w} \quad \Rightarrow \hat{\mathbf{w}} = \min_{\mathbf{w}} \sum_{i=1}^n \ell(y_i, f_i) + \lambda J(\mathbf{w})$$




A smorgasbord of different approaches

- Regularisation methods (Penalized linear models, support vector machines, ...)
- Probabilistic approaches (Linear discriminant analysis, Gaussian processes, ...)
- Ensemble methods (Random forests, boosting, ...)
- Neural networks (multi-layer perceptrons, deep learning, ...)

Most methods aim to trade-off data fit with complexity


$$\begin{aligned} f(\mathbf{x}_i, \mathbf{w}) = f_i = \mathbf{x}_i^T \mathbf{w} \quad \Rightarrow \hat{\mathbf{w}} &= \min_{\mathbf{w}} \sum_{i=1}^n \ell(y_i, f_i) + \lambda J(\mathbf{w}) \\ \Rightarrow \hat{\mathbf{w}} &= \min_{\mathbf{w}} -\ln p(\mathbf{w}|\mathbf{y}) \\ &= \min_{\mathbf{w}} \sum_{i=1}^n \ln p(y_i|f_i) + \ln p(\mathbf{w}|\boldsymbol{\theta}) \end{aligned}$$

Choice of pattern recognition algorithm






Ashburner and Klöppel (2011)

Choice of pattern recognition algorithm






Ashburner and Klöppel (2011)

Choice of pattern recognition algorithm



Maximise between to
Within class variance

Choice of pattern recognition algorithm




Maximise between to
Within class variance



Linear discriminant
Analysis (LDA)




Ashburner and Klöppel (2011)

Choice of pattern recognition algorithm



Ashburner and Klöppel (2011)

Choice of pattern recognition algorithm






Maximise the margin
Between classes



Support vector
machine (SVM)

Ashburner and Klöppel (2011)




Choice of pattern recognition algorithm



Model log-odds
ratio between classes

Ashburner and Klöppel (2011)

Choice of pattern recognition algorithm






Model log-odds
ratio between classes



Logistic regression




Ashburner and Klöppel (2011)

Choice of pattern recognition algorithm



Integrate over all
Possible decision functions

Choice of pattern recognition algorithm






Integrate over all
Possible decision functions



Gaussian process
Classification (GPC)

Ashburner and Klöppel (2011)

Choice of pattern recognition algorithm



Integrate over all
Possible decision functions



Gaussian process
Classification (GPC)


All methods make assumptions!

Ashburner and Klöppel (2011)

Support Vector Machines




- Finds a separating hyperplane that is “optimal” in that it leads to the largest margin between classes (γ)
- Based on the assumption that each point is bounded by unknown noise (ρ)
- New points will be well classified if $\gamma > \rho$
- The hyperplane is uniquely defined by a subset of the most ambiguous data points (“support vectors”)



Support Vector Machines




- Finds a separating hyperplane that is “optimal” in that it leads to the largest margin between classes (γ)
- Based on the assumption that each point is bounded by unknown noise (ρ)
- New points will be well classified if $\gamma > \rho$
- The hyperplane is uniquely defined by a subset of the most ambiguous data points (“support vectors”)



Support Vector Machines



- Finds a separating hyperplane that is “optimal” in that it leads to the largest margin between classes (γ)
- Based on the assumption that each point is bounded by unknown noise (ρ)
- New points will be well classified if $\gamma > \rho$
- The hyperplane is uniquely defined by a subset of the most ambiguous data points (“support vectors”)



$$\begin{aligned} & \min_{\mathbf{w}, \xi, b} -\gamma + C \sum_{i=1}^N \xi_i \\ \text{s.t.: } & y_i(\mathbf{w}^T \phi(\mathbf{x}) + b) > \gamma - \xi_i \\ & \xi_i > 0 \\ & \|\mathbf{w}\|^2 = 1 \end{aligned}$$



- 'Deep' neural networks have seen an enormous surge in popularity over the last few years
- Extend 1950s-era neural networks to have many hidden layers
- Now provide state of the art performance in many domains, e.g. computer vision, game playing and perception

LETTER

doi:10.1038/nature14296

Human-level control through deep reinforcement learning

Volodymyr
Martin R.
Helen K.

ARTICLE

doi:10.1038/nature16961

Mastering the game of Go with deep neural networks and tree search

David Silver¹, Julian Schrittwieser¹, John Narine¹, Thore Graepel¹

npj | Digital Medicine


www.nature.com/npjdigitalmed

ARTICLE


OPEN

Scalable and accurate deep learning with electronic health records


Alvin Rajkomar^{1,2}, Eyal Oren¹, Kai Chen¹, Andrew M. Dai¹, Nissan Hajaj¹, Michaela Hardt¹, Peter J. Liu¹, Xiaobing Liu¹, Jake Marcus¹, Mimi Sun¹, Patrik Sundberg¹, Hector Yee¹, Kun Zhang¹, Yi Zhang¹, Gerardo Flores³, Gavin E. Duggan¹, Jamie Irvine¹, Quoc Le¹, Kurt Litsch¹, Alexander Mossin¹, Justin Tanuswanan¹, De Wang¹, James Wexler¹, Jimbo Wilson¹, Dana Ludwig¹, Samuel L. Volchenboum¹, Katherine Chou¹, Michael Pearson¹, Srinivasan Madabushi¹, Nigam H. Shah¹, Atul J. Butte¹, Michael D. Howell¹, Claire Cui¹, Greg S. Corrado¹ and Jeffrey Dean¹




Deep Learning




Deep Learning



"Non-deep" feedforward neural network



Deep neural network



- Many variants but “convolutional” networks are popular
- Predominantly supervised learning
- Usually many parameters to optimise (more in lecture 2)




ImageNet Classification with Deep Convolutional Neural Networks

Alex Krizhevsky
University of Toronto
kriz@cs.utoronto.ca

Ilya Sutskever
University of Toronto
ilya@cs.utoronto.ca

Geoffrey E. Hinton
University of Toronto
hinton@cs.utoronto.ca




- 7 layer network that won 2012 ImageNet large-scale visual recognition challenge by 10%
- Trained the network on 15 million annotated images from over 22,000 categories
- more than 45,000 citations since 2012!

Overfitting




- Occurs when a model performs well on the data that it was estimated or trained on, but poorly on new data
- Can arise in very many ways including improper parameter optimisation or feature selection



Cross-validation




- Testing on unseen data is essential to assess generalizability
- Cross-validation is the standard way to do this
- 'K-fold CV': split the data into K approximately equal chunks
- 'Leave-one-out': one sample is left out at a time ($K = N$)



Cross-validation



- Testing on unseen data is essential to assess generalizability
- Cross-validation is the standard way to do this
- 'K-fold CV': split the data into K approximately equal chunks
- 'Leave-one-out': one sample is left out at a time ($K = N$)



Parameter optimisation



- Most approaches depend on multiple (hyper)parameters
- e.g. regularization parameters in penalized linear models

$$\hat{\mathbf{w}} = \min_{\mathbf{w}} \sum_{i=1}^n \ell(y_i, f_i) + \lambda J(\mathbf{w})$$


Parameter optimisation



- Most approaches depend on multiple (hyper)parameters
- e.g. regularization parameters in penalized linear models

$$\hat{\mathbf{w}} = \min_{\mathbf{w}} \sum_{i=1}^n \ell(y_i, f_i) + \lambda J(\mathbf{w})$$

- Standard approach is *nested* cross-validation with a grid search




Parameter optimisation



- Bayesian models also depend on multiple variance/noise hyperparameters

$$p(\mathbf{w}|\mathbf{y}, \theta, \sigma) = \frac{p(\mathbf{y}|\mathbf{w}, \sigma)p(\mathbf{w}|\theta)}{p(\mathbf{y}|\theta, \sigma)}, \quad p(\mathbf{y}|\theta, \sigma) = \int p(\mathbf{y}|\mathbf{w}, \sigma)p(\mathbf{w}|\theta)d\mathbf{w}$$

- Many approaches: nested CV, Empirical Bayes, MCMC ...




Parameter optimisation



- Bayesian models also depend on multiple variance/noise hyperparameters

$$p(\mathbf{w}|\mathbf{y}, \theta, \sigma) = \frac{p(\mathbf{y}|\mathbf{w}, \sigma)p(\mathbf{w}|\theta)}{p(\mathbf{y}|\theta, \sigma)}, \quad p(\mathbf{y}|\theta, \sigma) = \int p(\mathbf{y}|\mathbf{w}, \sigma)p(\mathbf{w}|\theta)d\mathbf{w}$$

- Many approaches: nested CV, Empirical Bayes, MCMC ...




Parameter optimisation



- Bayesian models also depend on multiple variance/noise hyperparameters

$$p(\mathbf{w}|\mathbf{y}, \theta, \sigma) = \frac{p(\mathbf{y}|\mathbf{w}, \sigma)p(\mathbf{w}|\theta)}{p(\mathbf{y}|\theta, \sigma)}, \quad p(\mathbf{y}|\theta, \sigma) = \int p(\mathbf{y}|\mathbf{w}, \sigma)p(\mathbf{w}|\theta)d\mathbf{w}$$

- Many approaches: nested CV, Empirical Bayes, MCMC ...




Parameter optimisation



- Bayesian models also depend on multiple variance/noise hyperparameters

$$p(\mathbf{w}|\mathbf{y}, \theta, \sigma) = \frac{p(\mathbf{y}|\mathbf{w}, \sigma)p(\mathbf{w}|\theta)}{p(\mathbf{y}|\theta, \sigma)}, \quad p(\mathbf{y}|\theta, \sigma) = \int p(\mathbf{y}|\mathbf{w}, \sigma)p(\mathbf{w}|\theta)d\mathbf{w}$$

- Many approaches: nested CV, Empirical Bayes, MCMC ...




Parameter optimisation



- Bayesian models also depend on multiple variance/noise hyperparameters

$$p(\mathbf{w}|\mathbf{y}, \theta, \sigma) = \frac{p(\mathbf{y}|\mathbf{w}, \sigma)p(\mathbf{w}|\theta)}{p(\mathbf{y}|\theta, \sigma)}, \quad p(\mathbf{y}|\theta, \sigma) = \int p(\mathbf{y}|\mathbf{w}, \sigma)p(\mathbf{w}|\theta)d\mathbf{w}$$

- Many approaches: nested CV, Empirical Bayes, MCMC ...




Parameter optimisation



- Bayesian models also depend on multiple variance/noise hyperparameters

$$p(\mathbf{w}|\mathbf{y}, \theta, \sigma) = \frac{p(\mathbf{y}|\mathbf{w}, \sigma)p(\mathbf{w}|\theta)}{p(\mathbf{y}|\theta, \sigma)}, \quad p(\mathbf{y}|\theta, \sigma) = \int p(\mathbf{y}|\mathbf{w}, \sigma)p(\mathbf{w}|\theta)d\mathbf{w}$$

- Many approaches: nested CV, Empirical Bayes, MCMC ...





- Aims to determine if accuracy exceeds “chance” (e.g. 50%)

Statistical tests for binary classification

- ① Binomial test
- ② T-test based on individual subject accuracies
- ③ Permutation test



- Aims to determine if accuracy exceeds “chance” (e.g. 50%)

Statistical tests for binary classification

- ① Binomial test
 - ② T-test based on individual subject accuracies
 - ③ Permutation test
- Cross-validation induces dependency between the folds
 - The assumptions of the first two methods (e.g. normality) are also usually not met by neuroimaging data



Statistical inference and multiple testing correction in classification-based multi-voxel pattern analysis (MVPA): Random permutations and cluster size control

Johannes Stelzer ^{a,b}, Yi Chen ^{a,b}, Robert Turner ^a



1 Introduction to Machine Learning

2 Basics of Pattern Recognition Analyses

3 Applications in Psychiatry

4 Conclusions

Supervised learning for automated diagnosis and prognosis



Neuroscience and Biobehavioral Reviews 57 (2015) 328–349

Contents lists available at ScienceDirect

Neuroscience and Biobehavioral Reviews

journal homepage: www.elsevier.com/locate/neubiorev

ELSEVIER

Review

From estimating activation locality to predicting disorder: A review of pattern recognition for neuroimaging-based psychiatric diagnostics

Thomas Wolfers^{a,b,*}, Jan K. Buitelaar^{c,d}, Christian F. Beckmann^{b,c,e}, Barbara Franke^{a,f}, Andre F. Marquand^{b,g}

NeuroImage 145 (2017) 137–165

Contents lists available at ScienceDirect

NeuroImage

journal homepage: www.elsevier.com/locate/ynimrg

ELSEVIER

Single subject prediction of brain disorders in neuroimaging:
Promises and pitfalls

Mohammad R. Arbabshirani^{a,b,*}, Sergey Plis^a, Ling Sui^{a,c}, Vince D. Calhoun^{a,d}

nature
neuroscience


Building better biomarkers: brain models
in translational neuroimaging

Choong-Wan Woo^{1–4}, Luke J Chang⁵, Martin A Lindquist⁶ & Tor D Wager^{3,4}

Supervised learning for depression diagnosis




This study was an early application of Pattern recognition to predict disease state in major depression



Fu et al. (2008)




This study was an early application of Pattern recognition to predict disease state in major depression



- Patients could be discriminated from controls with 87% accuracy
- Patients who responded well to fluoxetine could be discriminated from non-responders with 67% accuracy

Fu et al. (2008)

Where are we now?







- 116 studies
- Most disorders
- Many data modalities

- Moderate accuracy, highly variable across studies
- Mostly small samples, minimal validation across cohorts
- Accuracy in small samples is extremely variable
- **Heterogeneity** is a major challenge in clinical cohorts


Wolfers et al. (2015)

Cross-validation with small samples



Varoquaux (2017)


Research Domain Criteria



National Institute
of Mental Health




Insel and Cuthbert (2015)



Insel and Cuthbert (2015)

Research Domain Criteria



National Institute
of Mental Health




RDoC
Research Domain Criteria Initiative



Research Domain Criteria



Precision Medicine comes to Neuro-symptomatics



Review

Beyond Lumping and Splitting: A Review of Computational Approaches for Stratifying Psychiatric Disorders

André F. Marquand, Thomas Wölfers, Maarten Minnes, Jan Buitelaar, and Christian F. Beckmann

- Subtyping has been done since the 1970s (100s of studies)
- Still no consistent subtypes for any disorder

Insel and Cuthbert (2015)

Subtyping psychiatric disorders



PNAS

Distinct neuropsychological subgroups in typically developing youth inform heterogeneity in children with ADHD

Damien A. Fair^{a,b,c,1}, Deep...

Departments of ^aBehavioral Neurology and ^bDepartment of Computer Science, University of Iowa, Iowa City, IA

The American Journal of Psychiatry

Current Issue | Archive ▾ | About | Residents' Journal | AIP In Advance | Podcast | CME | Author Resources

Back to table of contents

Previous Next

Articles

Identification of Distinct Psychosis Biotypes Using Brain-Based Biomarkers

ARTICLES

Brett A. Clementz[✉], Ph.D.,
Godfrey D. Pearlson, M.D., M...

Published Online: 7 Dec 2...

nature medicine

Resting-state connectivity biomarkers define neurophysiological subtypes of depression

Andrew T Drysdale^{1–3}, Logan Greenenick^{4,5}, Jonathan Donnar⁶, Katherine Dunlop⁶, Farrokh Mansouri⁶, Yux Meng¹, Robert N Fethko¹, Benjamin Zelby⁷, Desmond J Oathes⁸, Amit Etkin^{8,9}, Alan F Schatzberg⁹, Keith Sudheimer⁹, Jennifer Keller⁹, Helen S Mayberg¹¹, Faith M Gunning^{2,12}, George S Alexopoulos^{2,12}, Michael D Fox¹³, Alvaro Pascual-Leone¹², Henning U Voss¹⁴, BJ Casey¹⁵, Marc J Dublin^{1–2} & Conor Liston^{1–3}

Subtyping psychiatric disorders



Distinct neuropsychological subgroups in typically developing youth inform heterogeneity in children with ADHD

The American Journal of Psychiatry Current Issue | Archive | About | Residents' Journal | AIP In Advance | Podcast | CME | Author Resources

Back to table of contents Previous Next Full Access

Articles Identification of Distinct Psychosis Biotypes Using Brain-Based Biomarkers

Brett A. Clementz¹, Ph.D., Godfrey D. Pearlson, M.D., M

Published Online: 7 Dec 2013

ARTICLES


nature medicine

Resting-state connectivity biomarkers define neurophysiological subtypes of depression

Andrew T Drysdale^{1,2}, Logan Greenstick^{4,5}, Jonathan Donzar⁶, Katherine Dunlop⁶, Farrokh Mansouri⁶, Yux Meng¹, Robert N Fetsch¹, Benjamin Zelby⁷, Desmond J Oathes⁸, Amit Etkin^{1,9}, Alan F Schatzberg⁹, Keith Sudheimer¹⁰, Jennifer Keller⁷, Helen S Mayberg¹¹, Faith M Gunning^{1,12}, George S Alexopoulos^{1,12}, Michael D Fox¹³, Alvaro Pascual-Leone¹², Henning U Voss¹⁴, BJ Casey¹⁵, Marc J Dublin^{1,2} & Conor Liston^{1–3}


- Generally minimal validation or replication
- Do not test against the ‘null’ hypothesis that there are no clusters in the data
- Clustering on the basis of symptoms may not map onto the underlying biology

Stratification of major depression




Drysdale et al. (2017)

Stratification of major depression




- Extensive validation
- Predict treatment response (TMS)




Drysdale et al. (2017)


Stratification of major depression



- Extensive validation
- Predict treatment response (TMS)



- Cut across diagnoses



- Sounds good, but we will examine some problems with this study in lecture 2

Drysdale et al. (2017)



1 Introduction to Machine Learning

2 Basics of Pattern Recognition Analyses

3 Applications in Psychiatry

4 Conclusions



- PR is a powerful tool to perform single subject inference and detect spatially distributed effects
- Useful in clinical neuroscience for:
 - ① Making predictions at the subject level (e.g. prognosis)
 - ② Stratifying psychiatric disorders
- Validation of models is extremely important to ensure generalisability

References



- J. Ashburner and S. Klöppel. Multivariate models of inter-subject anatomical variability. *NeuroImage*, 56(2):422–439, 2011.
- Richard Dinga, Lianne Schmaal, Brenda W.J.H. Penninx, Marie Jose van Tol, Dick J. Veltman, Laura van Velzen, Maarten Mennes, Nic J.A. van der Wee, and Andre F. Marquand. Evaluating the evidence for biotypes of depression: Methodological replication and extension of drysdale et al. (2017). *NeuroImage: Clinical*, 22:101796, 2019. ISSN 2213-1582. doi: <https://doi.org/10.1016/j.nicl.2019.101796>. URL <http://www.sciencedirect.com/science/article/pii/S2213158219301469>.
- Andrew T Drysdale, Logan Grosenick, Jonathan Downar, Katharine Dunlop, Farrokh Mansouri, Yue Meng, Robert N Fetcho, Benjamin Zebley, Desmond J Oathes, Amit Etkin, Alan F Schatzberg, Keith Sudheimer, Jennifer Keller, Helen S Mayberg, Faith M Gunning, George S Alexopoulos, Michael D Fox, Alvaro Pascual-Leone, Henning U Voss, BJ Casey, Marc J Dubin, and Conor Liston. Resting-state connectivity biomarkers define neurophysiological subtypes of depression. *Nature Medicine*, (23):28–38, 2017.
- C. H. Fu, J. Mourao-Miranda, S. G. Costafreda, A. Khanna, A. F. Marquand, S. C. Williams, and M. J. Brammer. Pattern classification of sad facial processing: toward the development of neurobiological markers in depression. *Biol Psychiatry*, 63(7):656–62, 2008.
- J. D. Haynes and G. Rees. Decoding mental states from brain activity in humans. *Nat Rev Neurosci*, 7(7):523–34, 2006.
- Thomas R. Insel and Bruce N. Cuthbert. Brain disorders? precisely. *Science*, 348(6234):499–500, 2015. ISSN 0036-8075.
- Gael Varoquaux. Cross-validation failure: Small sample sizes lead to large error bars. *Neuroimage*, (In press), 2017.
- T. Wolfers, J. K. Buitelaar, C. F. Beckmann, B. Franke, and A. F. Marquand. From estimating activation locality to predicting disorder: A review of pattern recognition for neuroimaging-based psychiatric diagnostics. *Neuroscience and Biobehavioral Reviews*, in press, 2015.