




Predictive Coding


Computational Psychiatry Course

15.09.2021





Lilian A. Weber



Translational Neuromodeling Unit



Levels of analysis



“Bayesian predictive coding”

Aitchison & Lengyel 2017 *Curr Op Neurobiol*

Structure of this talk

- | | |
|---|-----------------------------|
| 1. What is predictive coding? | ← neural networks |
| 2. What is Bayesian predictive coding? | ← maths, Bayesian inference |
| 3. Can and does the brain use predictive coding? | ← neurobiology/neuroscience |
| 4. Why is it useful for computational psychiatry? | ← psychiatry |


What is predictive coding?

$$\text{prediction error} = \boxed{\text{prediction}} - \text{input}$$

(a)




(b)



What is predictive coding?


$$\text{prediction error} = \text{prediction} - \text{input}$$



$$\mathbf{I} = f(U\mathbf{r}) + \mathbf{n}$$

What is predictive coding?



prediction error = **prediction** - input



$$\mathbf{I} = f(U\mathbf{r}) + \mathbf{n} \quad \mathbf{r} = f(U^h\mathbf{r}^h) + \mathbf{n}^{\text{td}}$$


What is predictive coding?

$$\text{prediction error} = \text{prediction} - \text{input}$$




What is predictive coding?

$$\text{prediction error} = \text{prediction} - \text{input}$$



- Recurrent neural networks outperform purely feedforward networks in the presence of noise (e.g., **Alamia et al. 2021 arXiv**)
- Predictive coding networks can approximate the backpropagation of error algorithm (**Whittington & Bogacz 2017 *Neural Comput***; **Song et al. 2020 *Adv Neural Inf Process Syst***)



What is Bayesian (about) predictive coding?


1. The architecture represents a hierarchical generative model of how sensory inputs are caused.

$$\mathbf{I} = f(U\mathbf{r}) + \mathbf{n}$$

$$\rightarrow p(\mathbf{I}|\mathbf{r}, U)$$

2. The cost function is the negative log joint: maximising the joint means finding the MAP estimates in Bayesian inference.


$$\begin{aligned} E &= -\log p(\mathbf{I}|\mathbf{r}, U) - \log p(\mathbf{r}) - \log p(U) \\ &= -\log(p(\mathbf{I}|\mathbf{r}, U) p(\mathbf{r}) p(U)) \end{aligned}$$



Bayes' Rule

$$\text{posterior} \sim \text{likelihood} \cdot \text{prior}$$

$$p(\mathbf{x}|\mathbf{y}, \mathbf{m}) \sim p(\mathbf{y}|\mathbf{x}, \mathbf{m}) p(\mathbf{x}|\mathbf{m})$$



What is Bayesian (about) predictive coding?

3. The prediction errors that update the estimate causes are weighted by their inverse variance.


$$\frac{d\mathbf{r}}{dt} = -\frac{k_1}{2} \frac{\partial E}{\partial \mathbf{r}}$$

$$= \underbrace{\frac{k_1}{\sigma^2} U^\top \frac{\partial f^\top}{\partial U \mathbf{r}}}_{\text{precision-weighting}} \underbrace{(\mathbf{I} - f(U\mathbf{r}))}_{\text{Inputs}} + \underbrace{\frac{k_1}{\sigma_{td}^2} (\mathbf{r}^{td} - \mathbf{r})}_{\text{Expectations}} - k_1 \alpha \mathbf{r}$$

4. A single cost function accounts for inference (updating \mathbf{r}) and learning (updating U)

$$\frac{dU}{dt} = -\frac{k_2}{2} \frac{\partial E}{\partial U} = \frac{k_2}{\sigma^2} \frac{\partial f^\top}{\partial U \mathbf{r}} (\mathbf{I} - f(U\mathbf{r})) \mathbf{r} - \frac{k_2}{2} \lambda U$$



Hebbian learning




Predictive coding as approximate inference

Summary

- A hierarchy of causes (predictive estimators and PE units)
- **Recurrent message passing**: PEs are signaled upwards (bottom-up) and predictions are signaled top-down
- **Inference**: finding the most appropriate causes to describe the data
- **Learning**: finding the most appropriate model to describe the data
- Both involve **minimizing precision-weighted prediction errors**
- This looks like **Bayesian inference** for finding the most likely causes of sensory inputs (**MAP estimates**) and like Hebbian learning, respectively



The Bayesian Brain



Representing uncertainty

$$p(x|y) = \frac{p(x)p(y|x)}{p(y)} \quad p(y) = \int p(x)p(y|x) dx$$

So far, we've only computed the MAP.
To be fully Bayesian: care about your uncertainty!




$q(x)$: our best guess about $p(x|y)$

$$\begin{aligned} \text{KL}(q(x), p(x|y)) &= \ln p(y) - \int q(x) \ln \frac{p(y, x)}{q(x)} dx \\ &= \ln p(y) - F \end{aligned}$$

$$\ln p(y|m) = \text{KL}(q(x), p(x|y, m)) + F(q(x), p(x, y|m))$$

$$F = \int q(x) \ln \frac{p(y, x)}{q(x)} dx$$



'Fristonian' PC

Predictive Coding can be viewed as the implementation of a particular scheme of approximate Bayesian inference in the brain.

The free energy formulation of predictive coding

$$F = \int q(x) \ln \frac{p(y, x)}{q(x)} dx$$


Inference: maximizing F to find the approximate posterior

Learning: maximizing F to improve the model and thereby reduce average surprise over time.

Additional assumption: $q(x)$ is a Gaussian.
We only need to represent the mean and the variance.

→ *precision-weighted prediction errors*


→ *learning about the **precision** of beliefs*



The main ingredients of predictive coding (from a computational point of view)


- A hierarchical generative model of sensory inputs
- The estimates of the causes generate predictions of sensory input
- The estimates of causes are updated in response to prediction errors (mismatches)
- The relative influence of PEs and predictions is determined by their relative precision (certainty)
- These computations underlie both perception (inference) and learning (model update)

$$\Delta \text{belief} \sim \text{precision} \times \text{PE}$$



Mapping predictive coding onto the brain



- **A hierarchical generative model of sensory inputs**
- The estimates of the causes generate predictions of sensory input
- The estimates of causes are updated in response to prediction errors (mismatches)
- The relative influence of PEs and predictions is determined by their relative precision (certainty)
- These computations underlie both perception (inference) and learning (model update)



Mapping predictive coding onto the brain

- A hierarchical generative model of sensory inputs
- **The estimates of the causes generate predictions of sensory input**
- **The estimates of causes are updated in response to prediction errors (mismatches)**
- The relative influence of PEs and predictions is determined by their relative precision (certainty)
- These computations underlie both perception (inference) and learning (model update)



1. The source populations of forward and backward pathways should be completely separate, given their functional distinction.



Mapping predictive coding onto the brain


- A hierarchical generative model of sensory inputs
- **The estimates of the causes generate predictions of sensory input**
- **The estimates of causes are updated in response to prediction errors (mismatches)**
- The relative influence of PEs and predictions is determined by their relative precision (certainty)
- These computations underlie both perception (inference) and learning (model update)

1. The source populations of forward and backward pathways should be completely separate, given their functional distinction.




Mapping predictive coding onto the brain

- A hierarchical generative model of sensory inputs
- **The estimates of the causes generate predictions of sensory input**
- **The estimates of causes are updated in response to prediction errors (mismatches)**
- The relative influence of PEs and predictions is determined by their relative precision (certainty)
- These computations underlie both perception (inference) and learning (model update)



Translational Neuromodeling Unit

2. Backward connections encode predictions and expected precision, so they should be more divergent.



Zeki & Shipp 1988 *Nature*

3. Causes interact non-linearly to generate data, so backward connections should be more modulatory.

Self et al. 2012 *PNAS*

Olsen et al. 2012 *Nature*

Zilles et al. 2004 *J Anat*

4. Predictions are generated more slowly than prediction errors, suggesting a spectral asymmetry.

Roopun 2006 *PNAS*

Roopun et al. 2008

Front. Cell. Neurosci


Buffalo et al. 2011 *PNAS*

Bosman et al. 2012 *Neuron*

Bastos et al. 2015 *NeuroImage*

Mapping predictive coding onto the brain

- A hierarchical generative model of sensory inputs
- The estimates of the causes generate predictions of sensory input
- The estimates of causes are updated in response to prediction errors (mismatches)
- **The relative influence of PEs and predictions is determined by their relative precision (certainty)**
- These computations underlie both perception (inference) and learning (model update)



Mapping predictive coding onto the brain

- A hierarchical generative model of sensory inputs
- The estimates of the causes generate predictions of sensory input
- The estimates of causes are updated in response to prediction errors (mismatches)
- **The relative influence of PEs and predictions is determined by their relative precision (certainty)**
- These computations underlie both perception (inference) and learning (model update)


Dopamine
Fiorillo et al. 2003 *Science*
Tobler et al. 2005 *Science*

see also:

Fiorillo et al. 2005 *Behav Brain Func*
Bunzeck et al. 2010 *Hum. Brain. Map.*

Diederer et al. 2016 *Neuron*
Diederer et al. 2017 *J Neurosci*


Noradrenalin



Lawson et al. 2021 *Curr Biol*


Mapping predictive coding onto the brain

- A hierarchical generative model of sensory inputs
- The estimates of the causes generate predictions of sensory input
- The estimates of causes are updated in response to prediction errors (mismatches)
- The relative influence of PEs and predictions is determined by their relative precision (certainty)
- **These computations underlie both perception (inference) and learning (model update)**





Mapping predictive coding onto the brain ... *advanced*

Haeusler and Maass (2007)



Bastos et al. 2012 *Neuron*

Canonical microcircuit for predictive coding




Shipp 2016 *Frontiers in Psychology*

... and testing it: Walsh et al. 2020 *Ann N Y Acad Sci*

Does the brain use PC?

- locomotion is sufficient to drive activity in mouse V1, even in the complete absence of visual input (**Keller et al., 2012**, **Saleem et al., 2013**)
- layer 2/3 of sensory cortices signals a mismatch between predicted and actual sensory feedback (**Eliades and Wang, 2008**, **Keller et al., 2012**)
- this results from a comparison of an excitatory motor-related input and an inhibitory visual input (**Attinger et al., 2017**, **Zmarz and Keller, 2016**)
- A24b/M2 provides a strong and dense projection to V1, which conveys motor-related signals that depend on the mouse's visuomotor experience. This projection fulfills all the criteria necessary to be interpreted as a prediction of visual flow given a motor output (**Leinweber et al., 2017**)




Hierarchical Bayesian Inference in Computational Psychiatry

Possible primary disruption at:


1. Sensory inputs (sensations)
2. Inference (perception)
3. Forecasting
4. Control (action)
5. Metacognition

At any of these, possible disturbance of:

- Prediction error (PE) computation
- Predictions/Expectations
- Estimation of their precision.



Stephan et al. 2016 *Brain*



Petzschner et al. 2017 *Biol Psychiatry*


Precision: The right balance

Schizophrenia/Psychosis

Sterzer et al. 2018 *Biol Psychiatry*; Adams et al. 2013 *Front Psychiatry*; Corlett et al. 2011 *NPP*; Stephan et al. 2006 *Biol Psychiatry*; 2009; Powers et al. 2017 *Science*

Autism spectrum disorder

Pellicano & Burr 2012 *TiCS*; Van de Cruys et al. 2014 *Psychol Rev*; Lawson et al. 2014 *Front Hum Neurosci*; Lawson et al. 2017 *Nat Neurosci*



Interoceptive predictive coding


Seth 2013 *TiCS*

Barrett & Simmons 2015 *Nature Rev Neurosci*

Seth & Friston 2016 *Phil Trans Royal Soc B*


Stephan et al. 2016 *Front Hum Neurosci*

Petzschner et al. 2017 *Biol Psychiatry*



Building a model with PC

1. **Predict the input**
 - **generative model of the sensory inputs**
2. **Invert the model**
 - **gradient descent on the neg. log joint**
 - **or: be fully Bayesian and use F**
3. **Simulate!**
4. **Fitting: Be the scientist**
 1. **Specify a mapping to observable data**
 2. **Write down the likelihood, specify your priors**
 3. **Acquire data & invert your model**




Thank you



Translational Neuromodeling Unit

Rick Adams

Rafal Bogacz



$$\Delta \text{belief} \sim \text{precision} \times \text{PE}$$

Resources

- *all things PC (very comprehensive):*
 - Millidge, Seth, Buckley 2021 *arXiv:2107.12979*
- *evidence for PC in the brain:*
 - Walsh et al. 2020 *Ann N Y Acad Sci*
 - Keller & Mrosovsky 2018 *Neuron*
 - Heilbron & Chait 2018 *Neurosci*
- *tutorials on the free energy formulation of PC*
 - Bogacz 2017 *J Math Psychol*
 - Buckley et al. 2017 *J Math Psychol*
- *further thoughts on precision*
 - Yon & Frith 2021 *Curr Biol*
- *Recent PC perspectives on delusions and hallucinations*
 - Corlett & Fletcher 2021 *Cogn Neuropsych* (delusions)
 - Corlett et al. 2019 *TICS* (hallucinations)