# Performance Analysis for Projection-Correction Methods in Motion Deblurring Problems

Sara Casadio, Enrico Ferraiolo, Giovanni Maria Savoca

Alma Mater Studiorum - University of Bologna Master's Degree in Computer Science

June 4, 2025

## Problem Description

- The project analyzes the performance of two Projection-Correction algorithms for reconstructing medical images affected by motion blur.
- The studied algorithms are:
  - Diffusion Posterior Sampling (DPS)
  - Regularization by Denoising with Diffusion (RED-Diff)
- Both methods are based on pre-trained diffusion models.
- Objective: evaluate the effectiveness of these methods in recovering degraded images.

## Approach to the Problem

- Objective: Analyze the performance of Projection-Correction methods
   DPS and RED-Diff for motion blur removal on medical images
- Phase 1: Dataset preprocessing (128x128)
- Phase 2: Data augmentation to increase dataset diversity
- Phase 3: Training a DDIM diffusion model on medical data
- Phase 4: Simulation of motion blur and its removal
- Phase 5: Implementation and comparison of Projection-Correction methods: DPS and RED-Diff
- Phase 6: Quantitative evaluation of performance using metrics such as PSNR and SSIM

#### Dataset

- We use the "Mayo Clinic CT Dataset" of low-dose CT scans, available via the link provided in this report.
- It contains a total of 6,400 2D slices in PNG format, extracted from 20 different patients.
- The images are organized into:
  - raw\_data/train/: 5,120 slices for training (80% of the dataset)
  - raw\_data/test/: 1,280 slices for testing (20% of the dataset)




Figure: Examples of CT slices from the Mayo Clinic dataset

## Conversion Pipeline

Before applying augmentations, each image is converted using:

- Grayscale: single channel via transforms.Grayscale(num\_output\_channels=1)
- ② Resize: to  $128 \times 128$  pixels using bicubic interpolation
- **Output** Normalization: values scaled to [-1, 1] using mean 0.5 and std 0.5

```
base_transform = transforms.Compose([
    transforms.Grayscale(1),
    transforms.Resize((128,128), interpolation=Image.BICUBIC),
    transforms.ToTensor(),
    transforms.Normalize([0.5], [0.5]),
])
```

### Data Augmentation: Types

For each clean image, we apply the following transformations:

- Fixed rotations: ±5° via rotate\_fixed()
- Horizontal flip: horizontal\_flip()
- Gaussian noise: mean 0, std 10 via add\_gaussian\_noise()
- Salt-and-pepper noise: probability 2% via add\_salt\_pepper()
- Brightness adjustment: factor 1.2 via change\_brightness()
- Contrast adjustment: factor 1.3 via change\_contrast()

## Repository Organization

- raw\_data/: directory containing CT slice images (train/, test/)
- checkpoints/: saved model weights (\*.pth)
- scripts/: main scripts for training and evaluation
- utils.py: module with utility functions (dataset, model, checkpoint I/O)
- notebooks/: exploratory and prototyping notebooks
- result/: output images, plots, and metrics
- report/: report materials (media/, capitoli/)

#### Diffusion Model Architecture

- Model Type: UNet2DModel from HuggingFace Diffusers library
- Task: Denoising diffusion probabilistic model for grayscale image generation
- Input/Output:
  - Input channels: 1
  - Output channels: 1
  - Sample size:  $128 \times 128$  pixels

## **UNet Architecture Configuration**

#### Block Configuration:

- Layers per block: 2
- Block output channels: (64, 128, 256)
- Dropout rate: 0.1

#### Downsampling Path:

- DownBlock2D  $\rightarrow$  DownBlock2D  $\rightarrow$  AttnDownBlock2D
- Progressive feature extraction with attention in the deepest layer

#### Upsampling Path:

- AttnUpBlock2D  $\rightarrow$  UpBlock2D  $\rightarrow$  UpBlock2D
- Symmetric architecture with attention mechanism

#### Diffusion Schedulers

- Training Scheduler: DDPMScheduler
  - Number of timesteps: 1000
  - Used for forward diffusion process during training
  - Adds noise progressively over 1000 steps
- Inference Scheduler: DDIMScheduler
  - Number of timesteps: 1000
  - Deterministic sampling process
  - Used for image generation and inverse problems
  - Shares beta schedule with DDPM scheduler

## Model Optimization

- Optimizer: Adam
  - Learning rate:  $1 \times 10^{-4}$ • Weight decay:  $1 \times 10^{-5}$
- Loss Function: Mean Squared Error MSE
  - Compares predicted noise with actual noise
  - Standard objective for diffusion models
- Performance Optimizations:
  - Model compilation with torch.compile
  - Mixed precision training with GradScaler
  - Cosine annealing learning rate scheduler

## Architecture Summary

- Total Parameters: 15.722.625
- Key Features:
  - Attention mechanisms in deepest layers for better feature learning
  - Symmetric U-Net design for optimal information flow
  - Dropout regularization to prevent overfitting
  - Grayscale-optimized with single channel processing

## Training Pipeline

- Objective: Train a denoising diffusion model (DDIM U-Net) on grayscale images
- Main Components:
  - Oata Augmentation
  - OataLoader
  - Model Compilation
  - Training loop with mixed-precision

## Data Augmentation

- Base Dataset: Dataset Mayo
  - ullet Grayscale o 1 channel
  - ullet Resize images to 128 imes 128
- Augmentations (8 types):
  - None: no transformation
  - Rotation ±5° (rotation + centering)
  - Flip horizontal
  - Gaussian noise (mean=0, std=10)
  - Salt and pepper noise (prob=2%)
  - Brightness (factor=1.2)
  - Contrast (factor=1.3)

#### Schedulers for Diffusion

- DDPMScheduler for training diffusion process
  - Timesteps 1000
- DDIMScheduler for sampling
  - Timesteps 1000

## Compiling the Model

- Why: optimize the model for better performance
- Usage:

```
model = torch.compile(model)
```

• Benefits: improved batch throughput

#### Mixed-Precision with AMP

- GradScaler amd autocast:
  - GradScaler for scaling gradients
  - autocast for automatic mixed precision
- Reduce memory usage and speed up training

## Training Loop

- Loss function: MSE
- Start the training model.train()
- For each epoch:
  - Move images to GPU (if available)
  - Generate noise and timesteps
  - Compute noise prediction on the input data
  - Prediction + MSE loss
  - Optimization + scheduler.step()
- Save validation samples to visualize the model performance during training
- Compute and log average losses
- Save model weights each epoch

## Checkpointing

- Validation:
  - model.eval() to set the model to evaluation mode
  - MSE loss on validation set
- Checkpoint:
  - Save the model weights to a .pth file
  - Update loss, PSNR and SSIM history in history.txt
- Monitor train vs validation loss over epochs aswell as PSNR and SSIM between the generated and original images
  - For each epoch sample 10 images from the validation set and compute the metrics

## **Epoch Validation**

#### Metrics:

- PSNR: Peak Signal-to-Noise Ratio
- SSIM: Structural Similarity Index

#### Sample Generation:

- Pure noise sampling using DDIM scheduler
- Validation reconstruction:
  - Add noise to clean validation images
  - Model predicts and removes the noise

#### • Quality Assessment:

- PSNR range: 20-40 dB (higher = better reconstruction)
- SSIM range: 0-1 (closer to 1 = better similarity)
- Average metrics computed over 5-10 validation samples

## Monitoring Produced Samples

#### • Pure Noise Sampling:

- Tests model's ability to generate realistic images
- Uses DDIM scheduler for iterative denoising
- Saves generated images as generated\_epoch\_{epoch}.png

#### Validation Reconstruction:

- Adds noise to clean validation images
- Model predicts and removes the noise
- Direct assessment of denoising performance

#### History Tracking:

- All metrics saved to history.txt
- Enables trend analysis and model comparison

#### Plots

- Loss Monitoring:
  - Training vs Validation Loss curves over epochs
  - MSE loss
- Quality Metrics Visualization:
  - PSNR trends with average values
  - SSIM trends with average values
  - Both metrics computed on validation reconstructions
  - Useful to track model performance

## Comprehensive Monitoring

#### Comprehensive Monitoring:

- Three-panel subplot: Loss, PSNR, SSIM (as shown in the Figure 2)
- Data read from history.txt file
- Enables performance trend analysis




Figure: Training Loss, PSNR, and SSIM trends over epochs

## **Loading Checkpoints**

#### Checkpoint Structure:

- Model state dictionary
- Optimizer state dictionary
- Current epoch number for resuming training
- Naming: ddim\_unet\_epoch81.pth
- load\_checkpoint() utility function

## DPS: Diffusion Posterior Sampling

- DPS is a method for solving inverse problems using pre-trained diffusion models
- Key idea: combine data fidelity with diffusion model prior during reverse sampling
- Modifies the standard DDIM reverse process to incorporate measurement consistency

#### DPS - Overview

#### Algorithm Overview:

- **③** Start with noisy initialization  $x_T \sim \mathcal{N}(0, I)$
- ② For each timestep t: predict  $x_0$  using UNet
- **3** Apply posterior correction:  $x_0^{post} = x_0^{pred} + \gamma_t \cdot K^T(y Kx_0^{pred})$
- Continue DDIM step with corrected  $x_0^{post}$

#### Posterior Correction Weight:

$$\gamma_t = \frac{\sigma_{prior}^2}{\sigma_y^2 + \sigma_{prior}^2}$$

where  $\sigma_{prior}^2 = 1 - lpha_t$  and  $\sigma_y$  is measurement noise

## Implementation of DPS

#### Algorithm Steps:

- $\bigcirc$  Initialize  $x_t$  with random noise
- 2 Predict noise  $\epsilon_{\theta}(x_t, t)$  using UNet
- **3** Compute  $x_0^{pred} = \frac{x_t \sqrt{1 \alpha_t} \epsilon_{\theta}}{\sqrt{\alpha_t}}$
- Apply DPS correction with gradient step
- Update to next timestep using DDIM

## RED-Diff: Regularization by Denoising Diffusion

- RED-Diff is an optimization-based method for solving inverse problems using diffusion models
- Key idea: combine data fidelity loss with regularization from denoising diffusion priors
- Uses gradient-based optimization to reconstruct images by minimizing combined objective

#### RED-Diff - Overview

#### Algorithm Overview:

- **1** Initialize reconstruction  $\mu$  from adjoint operation:  $\mu = K^T(y)$
- ② For each timestep t: sample noise and create noisy version  $x_t$
- **②** Compute data fidelity loss:  $\mathcal{L}_{obs} = rac{1}{2\sigma_{v}^{2}} \|K(\mu) y\|^{2}$
- Compute regularization loss using diffusion model guidance
- $\odot$  Update  $\mu$  using gradient descent on combined loss

#### Combined Objective:

$$\mathcal{L} = \mathcal{L}_{obs} + \lambda \cdot w_t \cdot \mathcal{L}_{reg}$$

where  $w_t$  is a time-dependent weighting strategy

## Implementation of RED-Diff

#### Algorithm Steps:

- Initialize  $\mu \leftarrow K^T(y)$  with gradient enabled
- ② Sample noise  $\epsilon \sim \mathcal{N}(\mathsf{0},\mathit{I})$  and create  $x_t = \sqrt{lpha_t} \mu + \sqrt{1-lpha_t} \epsilon$
- **9** Predict noise  $\epsilon_{\theta}(x_t, t)$  using UNet
- **o** Compute regularization loss:  $\mathcal{L}_{reg} = w_t \cdot \|\epsilon_{\theta} \epsilon\|^2$
- ullet Update  $\mu$  using Adam optimizer on total loss
- Repeat for all timesteps in reverse order

Weighting Strategies: linear, sqrt, square, log, clip, const

## Sottosezione 2.1

## Sottosezione 2.1

## Conclusions

## Thank you for your attention