

# Intro to Python (Class 5)

Ben Bettisworth

- 1 Recursion
- 2 Files
- 3 Imports
- 4 General Advice

## Section 1

# Recursion

# Recursion

When working with certain structures (particularly trees) it is often easiest to express the logic using *recursion*.

## Definition

A ***recursive function*** is a function which calls itself.

# Example

## Code

```
def factorial(n):  
    if n == 0:  
        return 1  
    else:  
        return n * factorial(n-1)  
  
print(factorial(5))
```

## Output

120

# Recursive Functions

In order to not run forever, every recursive function *must have*:

- A base case, where recursion *does not happen*.
- A recursive case, where recursion does happen.

In order to prevent infinite recursion, you must ensure that the base case is hit eventually.

# Example

## Code

```
def factorial(n):  
    if n == 0: # Base Case  
        return 1  
    else: # Recursive Case  
        return n * factorial(n-1)
```

# Graded Exercise

The Fibonacci has a pair of rabbits. Every month, they have 2 baby rabbits. In a month, these baby rabbits will become adults. Every adult pair of rabbits produces a new pair baby rabbits every month.

## Example

- At month 1, Fibonacci has 1 pair.
- At month 2, Fibonacci still has 1 pair.
- At month 3, Fibonacci has 2 pairs.
- At month 4, Fibonacci has 3 pairs.
- At month 5, Fibonacci has 5 pairs.



# Graded Exercise

The formula for Fibonacci's rabbits is given by

$$F(1) = 1$$

$$F(2) = 1$$

$$F(n) = F(n - 1) + F(n - 2)$$

Write a function that outputs the pairs of rabbits that Fibonacci has at month  $n$ .

# Exercise

## Code

```
def fibo(n):  
    if n == 0 or n == 1: # Base Case  
        return 1  
    else: # Recursive Case  
        return fibo(n-1) + fibo(n-2)
```

# Recursion as a Tree




Figure 1: The call tree for fibo

# Recursion as a Tree




Figure 2: Return tree for fibo

# Recursion on Phylogenetic Trees




Figure 3: Return tree for fibo

# Recursion on Phylogenetic Trees

## Code

```
def phylo_recurse(PhyloNode):  
    for c in PhlyoNode.children:  
        phylo_recurse(PhyloNode)  
    do_something(PhyloNode)
```

## Section 2

### Files

# Files

At the beginning of the course, we defined a file as:

## Definition

*Files are chunks of memory stored in a file system*



# Practical Files

But practically, files are almost always *serialized*. This means that files have a *file format*, which governs their layout.

```
example.json
```

```
{  
  "foo": 3.14,  
  "bar": "hello world"  
}
```

File formats are a compromise between how the computer sees data, and how humans read data. This means that often the file format naturally fits into a `list` or `dict`.

# File systems

There are (seemingly) a billion different file systems out there. But, they all identify files with a *path*.

## Definition

*A path is a **ordered** series of directories and a final filename which identifies a file*

## Example

Windows: C:\Users\Docs\Final.docx

Unix: /home/user/Final.docx

# Opening a File

Files need to be *opened* before they can be read. This tells the Operating System (OS) to read the file from disk, and give it to the program.

## Code

```
f = open("my_super_cool_file.txt")  
print(f)
```

## Output

```
<_io.TextIOWrapper name='my_super_cool_file.txt'  
  mode='r' encoding='UTF-8'>
```

# Reading a File

Normally when reading files in Python, we use a `with` guard.

## Code

```
with open("my_super_cool_file.txt") as my_file:  
    print(my_file.readline())
```

## Output

```
Lorem ipsum dolor sit amet, consectetur adipiscing elit,  
sed do eiusmod tempor
```

# Reading Lines Iteratively

Lines of a file can be read one-by-one until the file is over with a `for` loop.

## Code

```
with open("my_super_cool_file.txt") as my_file:
    for line in my_file:
        print(line)
```

# Exercise

Read the lines of the file `my_super_cool_file.txt` and place them into a `list`.

Extension: Find the lines which contain a comma (,) and reverse those lines.

# Exercise

## (A Possible) Solution

```
lines = []  
with open("my_super_cool_file.txt") as my_file:  
    for line in my_file:  
        lines.append(line)
```

# File Formats

As mentioned before, files generally have a *format*. Examples of file formats include:

- .docx (Word Files)
- .pdf (Portable Document Format)
- .fasta (FASTA)
- .nwk (Newick)
- .bam (Binary Alignment Map)
- .zip (Zip Archive)



# Text vs Binary files

There are two ways that a file can be stored on disk:

- Binary, where the files require a special program to read them, and
- Text, which can be read in a text editor (Vscode, emacs, vim, etc.)

In Python, these files are treated differently.

# Opening Binary Files

## Code

```
with open("my_secret_binary_file.bin", 'rb')\n    as my_binary:\n    print(my_binary)
```

## Output

```
<_io.BufferedReader name='my_secret_binary_file.bin'>
```

# Exercise

Parse a fasta file into a dictionary, such that the key is the taxa name, and the value is the sequence. Use the file `data/tree1.fasta` to test your code.

Extension: Convert the fasta file into `phylip`.

# Exercise

```
1 sequences = {}
2 with open("data/tree1.fa") as fa_file:
3     taxa_line = None
4     sequence_line = None
5     for line in fa_file:
6         line = line.strip()
7         if line[0] == ">":
8             taxa_line = line[1:]
9         else:
10            sequence_line = line
11    if taxa_line is not None and \
12        sequence_line is not None:
13        sequences[taxa_line] = sequence_line
14        taxa_line, sequence_line = None, None
15
```

# Writing Files

Files are opened in read mode by default. To write a file, you must open the file in write mode. To do this, we pass "w" as the second argument of `open`.

## Example

```
with open("my_file.txt", "w") as outfile:  
    outfile.write("apples have a good flavor")
```

This will create a file with the name `my_file.txt`, and write the text "apples have a good flavor" to the file.

# Creating Files

Opening a file in in write mode *creates* the file. Even if there is already a file there.

## Example

```
with open("my_file.txt", "w") as outfile:
    outfile.write("pears have a sweet flavor\n")
with open("my_file.txt", "w") as outfile:
    outfile.write("but I prefer a banana\n")
```

## Result

```
> cat my_file.txt
but I prefer a banana
```

# Writing to an Existing File

To write to an existing file, the “append” mode must be used. A file can be opened in append mode by passing "a" as the second argument to `open`.

## Example

```
with open("my_file.txt", "a") as outfile:  
    outfile.write("only if the banana is ripe though.\n")
```

## Result

```
> cat my_file.txt  
but I prefer a banana  
only if the banana is ripe though
```

# Exercise

Write a  $n$  by  $m$  box to a file named `my_box.txt`.



## Section 3

### Imports

# Imports

Importing in python is the way that programmers include other people's code in their projects. It uses the `import`.

## Example

```
import math
```

# Imports

Once a *module* is imported, its contents can be accessed with the `.` operator.

## Example

```
import math
print(math.exp(3))
```

# Exercise

Write a function that computes the probability of getting a flush in a poker hand. As a reminder, a flush is a hand all of the same suit. Use the `math.comb` function.

# Exercise

## (A Possible) Solution

```
import math

def p_flush():
    denom = math.comb(52,5)

    numer = math.comb(4,1) * math.comb(13, 5)
    return numer / denom
```

# Example

Imports can be done to do much of the heavy lifting for you.

## Example

```
import csv
with open("cleaned-example.csv") as csv_file:
    csv_reader = csv.DictReader(csv_file)
    for row in csv_reader:
        print(row)
```

## Output

```
{'software': 'baseline', 'error': '0.0', ... }
{'software': 'baseline', 'error': '0.011103817', ...}
...
```

# Exercise

Write a program that finds the software with largest error in `cleaned-example.csv`.

Extension: Write a program that computes the average error for each different software in the CSV file.

# Exercise

## (A Possible) Solution

```
import csv
max_err = float("-inf")
max_software = None
with open("test.csv") as csv_file:
    csv_reader = csv.DictReader(csv_file)
    for row in csv_reader:
        err = float(row['error'])
        if err > max_err:
            max_err = err
            max_software = row['software']
```



## Third Party Libraries

In addition to the standard libraries, there are *thousands* of third party libraries. These need to be downloaded, but once downloaded<sup>1</sup>, then they can be imported just like any other library.

### Example

```
import seaborn
import matplotlib.pyplot as plt
tips = seaborn.load_dataset("tips")
seaborn.boxplot(data = tips, x = "day",
                 y = "total_bill")
```

---

<sup>1</sup>It's actually super complicated how you download the libraries. Commonly you might use: pip, conda, or uv.

# Exercise

Plot something. Anything. Here is some example code if you need something (taken from the seaborn examples).

## Example

```
import seaborn as sns
tips = sns.load_dataset("tips")

sns.violinplot(data=tips, x="day", y="total_bill",
               hue="smoker", split=True,
               inner="quart", fill=False,
               palette={"Yes": "g", "No": ".35"})
```

# Useful Libraries

- File format parsers: `csv`, `json`, `yaml`.
- Specialized scientific libraries: `numpy`, `scipy`.
- Even more specialized libraries: `ete3`, `BioPython`.
- Plotting libraries: `matplotlib`, `seaborn`, `plotly`.
- Utility libraries: `argparse`.

## Section 4

### General Advice

# General Advice

The remainder of the slides just contain general advice, from somebody who has been doing this a while.

# Version Control Systems

You should learn a version control system. This includes any of

- git
- mercurial
- fossil

# Version Control Systems

A version control system will:

- Save your work for you.
- Allow you revert changes easily.
- Help you find bugs.
- Make it easy to share code.

# Version Control System Example

## Example

```
git init .  
git add .  
git commit -m "initial commit"
```



# Structuring Code

In general, you should use functions whenever you have duplicated code.

Example