



SAVEETHA SCHOOL OF ENGINEERING
SAVEETHA INSTITUTE OF MEDICAL AND TECHNICAL SCIENCES
CHENNAI-602105

Submitted By

K Thilagavathi (192312301)

FINAL CODE:

```
#include<stdio.h>

#include<string.h>

#define MAX 100

struct ServiceRecord
{
    char vehicleNo[20];
    char customerName[30];
    char model[30];
    char serviceType[30];
    float partsCost;
    float labourCost;
    float totalCost;
};

void calculateCost(struct ServiceRecord *s)
{
    s->totalCost = s->partsCost + s->labourCost;
}

int searchVehicle(char vehicleNo[], struct ServiceRecord s[], int count)
{
    for(int i=0;i<count;i++)
    {
        if(strcmp(s[i].vehicleNo,vehicleNo)==0)
            return i;
    }
}
```

```
    return -1;
}
int main()
{
    struct ServiceRecord s;
    printf("Enter Vehicle Number: ");
    scanf("%s",s.vehicleNo);
    printf("Enter Parts Cost: ");
    scanf("%f",&s.partsCost);
    printf("Enter Labour Cost: ");
    scanf("%f",&s.labourCost);
    calculateCost(&s);
    printf("Total Service Cost = %.2f",s.totalCost);
    return 0;
}
```