

DA\CS1\Examples\HELLO\embedded18.c - uVision

File Edit View Project Flash Debug Peripherals Tools SVCS Window Help

Registers

Register	Value
r0	0x0a
r1	0x00
r2	0x00
r3	0x00
r4	0x00
r5	0x00
r6	0x01
r7	0x00
sys	
a	0x00
b	0x00
sp	0x09
sp_max	0x0d
dptr	0x08ce
PC	0x08C6
states	7789403
sec	3894.701...
pew	0x00

Logic Analyzer

Setup Load Save Min Time Max Time Grid Zoom Min/Max Update Screen Transition Jump to Signal Info Amplitude Tristatepin Enable

1 0

125.3502s 3988.149 3988.461s d 3863.07s 3985.445

embedded18.c STARTUP.A51

Disassembly

```
34: while(1);
35: 0x08C6 80FE SJMP C:08C6
36: 0x08C8 0108 AJMP C:0808
37: 0x08CB 0000 MOV
```

23
24 void main(void)
25 {
26 TMOD = 0x01; // Timer0 Mode 1 (16-bit)
27
28 TH0 = 0xFC; // 1 ms preload value
29 TL0 = 0x66;
30
31 IE = 0x82; // EA = 1, ET0 = 1
32 TR0 = 1; // Start Timer0
33
34 while(1);
35 }

Parallel Port 0

Port 0: 7 Bits 0

P0: 0xFF 7 Bits 0

Pins: 0xFF 7 Bits 0

Command

Load "D:\CS1\Examples\HELLO\Objects\embedded18"

LA 'pwm'

Call Stack - Locals

Name	Location/Value	Type
MAIN	C:0x08B8	

ASM ASSIGN BreakDisable BreakEnable BreakKill BreakList BreakSet BreakAccess COVERAGE COVTOFILE

Simulation

11: 4632.78819600 sec L:34 C:1 CAP NUM SCRL OVR R/W

34°C Partly sunny

Search

ENG IN 1423 14-08-2026