

DA\CS1\Examples\HELLO\embedded17.c - uVision

File Edit View Project Flash Debug Peripherals Tools SVCS Window Help

Registers

Register	Value
r0	0x00
r1	0x00
r2	0x00
r3	0x00
r4	0x00
r5	0x00
r6	0x00
r7	0x00
Sys	0x00
a	0x00
b	0x00
ap	0x07
sp_max	0x07
dptr	0x0000
PC	0x0800
status	389
sec	0.000194...
prw	0x00

Disassembly

```
12: void main()
13: {
14:     TMOD = 0x20;
15:     TH1 = 0xFD;
16:     SCON = 0x50;
17:     TR1 = 1;
18:     ES = 1;
19:     EA = 1;
20:     while(1);
21: }
```

embedded17.c

```
2
3 void serial_ISR(void) interrupt 4
4 {
5     if(RI)
6     {
7         P1 = SBUF;
8         RI = 0;
9     }
10 }
11
12 void main()
13 {
14     TMOD = 0x20;
15     TH1 = 0xFD;
16     SCON = 0x50;
17     TR1 = 1;
18     ES = 1;
19     EA = 1;
20     while(1);
21 }
```

Interrupt System

Int Source	Vector	Mode	Req	Ena	Pin
P3.2/Int0	0003H	0	0	0	0
Timer 0	000BH	0	0	0	0
P3.3/Int1	0013H	0	0	0	0
Timer 1	001BH	1	0	0	0
Serial Rcvr	0023H	0	1	0	0
Serial Xmt	002BH	0	1	0	0

Serial Channel

Mode: 8-Bit var.Baudrate

SCON: 0x50 SBUF: 0x00

Baudrate: 20833

Parallel Port 0

Port 0: 0x61

Command

Running with Code Size Limit: 2K

Load "D:\CS1\Examples\HELLO\Objects\embedded17"

Call Stack + Locals

Name	Location/Value	Type
MAIN	C:\0x0800	

Simulation

11: 851.67114100 sec L14 C:1 CAP NUM SCRL OVR: R AV

34°C Partly sunny

Search

ENG IN 14:10 14-08-2026