STAFF REVIEW · H446 132 source models

Separate from the eight-page pupil workbook. This copy is in a public repository and is NOT access controlled. Check technical correctness before use.

Printed question mapping: Booklet Q1 = original online Q1; Booklet Q2 = original online Q2; Booklet Q3 = original online Q3

Do Now — source answers

1. The corresponding trusted public key.

2. RAM.

3. First in, first out.

4. Linear/sequential search in the worst case.

I Do — source worked steps

1. Check server certificate — Predict the first step from the prompt.

2. Derive symmetric traffic key — Explain the intermediate result or decision.

3. Encrypt application data — Modern secure connections typically authenticate with public-key credentials, establish shared session keys (often via ephemeral key agreement) and use efficient symmetric encryption for bulk traffic. Identity checks guard against impostors.

We Do — guided CHECK

1. HTTPS is encrypted
Predict the first step from the prompt.
Check actual domain
Explain the intermediate result or decision.
Assess site legitimacy
No. HTTPS can establish an encrypted connection even with a harmful operator. Verify the domain and service, not just the presence of encrypted transport; a certificate proves control of an identity/domain to varying levels.

You Do — source mark schemes

1. Key establishment/authentication [3], efficient symmetric bulk encryption [3].

2. Temporary symmetric traffic key [2], derived/established for session [2], distinct from asymmetric identity/public-key material [2].

3. Encrypted in transit [2], does not certify honesty/safety of destination [2], phishing/endpoint compromise possible [2], domain checks and practical conclusion [2].

Exit Ticket — source answer

1. False. Encryption does not guarantee the operator's intentions.