STAFF REVIEW · H446 148 source models

Separate from the eight-page pupil workbook. This copy is in a public repository and is NOT access controlled. Check technical correctness before use.

Printed question mapping: Booklet Q1 = original online Q1; Booklet Q2 = original online Q2; Booklet Q3 = original online Q3

Do Now — source answers

1. A policy of rules, for example addresses, ports or connection state.

2. A queue.

3. 0.

4. Referencing a candidate key in another relation.

I Do — source worked steps

1. Laptop and switch — Identify the facts and make an initial prediction.

2. Router/default gateway — Explain the mechanism or trace the intermediate stage.

3. Remote network — Within the LAN, NICs form frames and the switch forwards using MAC addresses. To reach another IP network, traffic is sent to a router/default gateway that forwards packets. The gateway rewrites the link framing per next hop.

We Do — guided CHECK

1. Wired LAN works
Identify the facts and make an initial prediction.
Install suitable Wi-Fi AP
Explain the mechanism or trace the intermediate stage.
Clients join same LAN
Use a correctly connected wireless access point to extend radio coverage onto the existing LAN. An extra NAT router may create an unwanted separate network; plan channels, capacity and placement.

You Do — source mark schemes

1. Switch forwards LAN frames via MAC [2], router forwards IP packets among networks [2], AP connects wireless clients onto LAN [2].

2. IP identifies destination and enables routing [3]; MAC delivers frames on local link/next hop [3].

3. Switches/local ports [2], suitable access points [2], router/gateway [2], justified end-to-end path and coverage [2].

Exit Ticket — source answer

1. False. Switches forward local frames; routers forward between IP networks.