STAFF REVIEW · H446 149 source models

Separate from the eight-page pupil workbook. This copy is in a public repository and is NOT access controlled. Check technical correctness before use.

Printed question mapping: Booklet Q1 = original online Q1; Booklet Q2 = original online Q2; Booklet Q3 = original online Q3

Do Now — source answers

1. A wireless access point.

2. RAM.

3. The internet layer.

4. A queue.

I Do — source worked steps

1. Teachers send requests — Identify the facts and make an initial prediction.

2. Central marks database — Explain the mechanism or trace the intermediate stage.

3. Access control + backup — Client–server suits managed central data, controlled permissions, auditing and backups. A server failure can affect many clients, so redundancy and resilient backups matter. Peer-to-peer file sharing is harder to manage consistently.

We Do — guided CHECK

1. Peers hold file blocks
Identify the facts and make an initial prediction.
Peers share download load
Explain the mechanism or trace the intermediate stage.
Verify authentic file
A P2P distribution model can share upload load among peers, reducing demand on one central server. Clients must verify file authenticity with trusted signatures/hashes; peers may be untrusted or offline.

You Do — source mark schemes

1. Client requests services [2]; server provides managed services [2]; peer can act as client/provider [2].

2. Centralised data/controls [2], easier backups/updates [2], single service outage/cost [2].

3. P2P resource sharing [2], client-server central control [2], availability/scalability [2], trustworthy verification/justified recommendation [2].

Exit Ticket — source answer

1. False. Hybrid architectures can use multiple patterns.