STAFF REVIEW · H446 225 source models

Separate from the eight-page pupil workbook. This copy is in a public repository and is NOT access controlled. Check technical correctness before use.

Printed question mapping: Booklet Q1 = original online Q1; Booklet Q2 = original online Q2; Booklet Q3 = original online Q3

Do Now — source answers

1. As the right child of 10.

2. A value that identifies an object rather than copying the object itself.

3. A variable declared inside a method or block with limited scope.

4. 25.

I Do — source worked steps

1. Predict first — The local newScore becomes 10, but the field Score remains 7.

2. Model the reasoning — Replace the local-only calculation with Score += points;.

3. Model the reasoning — Retest: after AddPoints(3), Score should equal 10.

We Do — guided CHECK

1. Model the reasoning
Correct it to Count++; or Count += 1;. With Count=2, the resulting Count is 3.

You Do — source mark schemes

1. [4] 5 after first [1], 6 after second [1], 7 after third [1]; each call updates the same object's field [1].

2. [6] `int Age` declares a new local variable [2], shadowing rather than updating the member [1]; use `this.Age = age;` [2]; test SetAge(16) sets property to 16 [1].

3. [6] Reject amount<=0 [1] and amount>Balance [1]; valid update Balance-=amount [1].
Boundary tests: Withdraw(50) gives 0 [1], Withdraw(51) is rejected [1], Withdraw(0) is rejected [1].

Exit Ticket — source answer

1. True. A missing assignment can leave object state unchanged.