STAFF REVIEW · H446 228 source models

Separate from the eight-page pupil workbook. This copy is in a public repository and is NOT access controlled. Check technical correctness before use.

Printed question mapping: Booklet Q1 = original online Q1; Booklet Q2 = original online Q2; Booklet Q3 = original online Q3

Do Now — source answers

1. Step Into enters the called method; Step Over executes it without stopping inside.

2. Controlling how an object's internal state can be accessed or changed.

3. For example List<Book>, a collection holding Book references.

4. Set OnLoan=true, call Borrow, expect false and OnLoan to stay true.

I Do — source worked steps

1. Predict — Initial Reserved is false, so Reserve sets it to true and returns true.

2. Model response — The second call detects Reserved already true; it returns false and leaves state unchanged.

We Do — guided CHECK

1. Model response
The second call returns false without changing Occupied.

You Do — source mark schemes

1. [4] A class is a blueprint/type [1] that defines attributes/methods [1]; an object is a particular instance [1], e.g. a Book for one title [1].

2. [6] public bool ReturnBook(){ if(!OnLoan)return false; OnLoan=false; return true; } [4]; test after a successful Borrow, ReturnBook returns true [1] and OnLoan becomes false [1].

3. [6] Store Book objects in a Dictionary<string,Book> keyed by ISBN [2]; unique ISBN maps to one Book [1]; look up the selected object [1]; borrow once succeeds [1], borrowing again returns false and state remains on loan [1].

Exit Ticket — source answer

1. False. Each object maintains its own state.