STAFF REVIEW · H446 230 source models

Separate from the eight-page pupil workbook. This copy is in a public repository and is NOT access controlled. Check technical correctness before use.

Printed question mapping: Booklet Q1 = original online Q1; Booklet Q2 = original online Q2; Booklet Q3 = original online Q3

Do Now — source answers

1. OOP groups state and behaviour into objects; procedural code is organised around procedures/functions.

2. A variable accessible only within its declaration's scope.

3. Through public methods/property logic defined by the class.

4. The return is discarded and a value-type parameter is a copy; the caller must assign the returned result.

I Do — source worked steps

1. Predict — Account a's Balance becomes 12.

2. Model response — Account b remains at 20 because its state is separate.

We Do — guided CHECK

1. Model response
The caller's balance remains 7. Assign balance=Deposit(balance,3) to store 10.

You Do — source mark schemes

1. [3] Function returns 7 [1]; caller does not assign it [1]; x remains 2 [1].

2. [6] A=17 [1], B=32 [1]; each is a separate instance [2], each method changes only its own state [2].

3. [6] Procedures can be individually reused/tested [1] but shared mutable data can create coupling [2]; OOP encapsulates per-book state [1] and validation in methods [1], but excessive class complexity can make a small solution harder to follow [1].

Exit Ticket — source answer

1. False. The caller must assign the returned value unless code uses a ref parameter or other shared state.