EXIT TICKET / REFLECTION

Check your understanding

Complete the actual lesson Exit Ticket before checking the answer.

An O(2^n) approach grows only twice as much when n doubles.

How confident are you? Circle one: Confident / Getting there / Need help

Explain your choice, identifying one concept you can now use independently.

GREEN PEN — Correct and explain

Choose one mistake from your independent work. Write the correct method and explain precisely why your original answer was wrong.

Next step: revisit the model or a relevant revision-guide section if needed.

DO NOW — RECALL

Lesson 075 · Big O: Quadratic, Exponential and Growth

Name: _____ Class: _____ Date: _____

1. How does O(n) differ from O(1)?

2. How many halvings 32→1?

3. Which algorithm naturally explores include/exclude branches?

4. A rectangular 4×3 zero-indexed array holds how many elements? Give its last valid index pair.

DO NOW — CHECK / OBJECTIVES

Correct and improve

Check page 1 in GREEN PEN. Write corrections in full.

1. Model answer

One grows with n; the other does not.

2. Model answer

Five.

3. Model answer

Subset backtracking or exhaustive enumeration.

4. Model answer

12 elements; last index (3,2).

By the end, you can…

• Two nested n loops perform n×n operations, producing $O(n^2)$ time when each inner operation is constant.

• A binary decision at each of n positions can create 2^n possibilities. This exponential growth quickly outruns polynomial methods.

• Big O ignores constants and lower-order terms; compare classes by input growth while acknowledging memory, workload and implementation detail.

Vocabulary — know these terms

quadratic — Growth proportional to n^2.

exponential — Growth like 2^n.

pruning — Avoid exploring impossible branches.

scalability — Handling larger inputs feasibly.

YOU DO — INDEPENDENT PRACTICE

Questions · Part 2

Answer independently. Show code, calculations, a trace or justified reasoning as appropriate.

Question 3

A problem has 30 binary choices. Evaluate full subset enumeration and one way to reduce exploration. [6]

YOU DO — INDEPENDENT PRACTICE

Questions · Part 1

Answer independently. Show code, calculations, a trace or justified reasoning as appropriate.

Question 1

For n=5 and n=10, calculate n^2 and 2^n values. [6]

Question 2

Explain time growth of a nested n×n loop and classify. [6]

NEW LEARNING

Read, annotate and explain

Observe

Two nested n loops perform n×n operations, producing $O(n^2)$ time when each inner operation is constant.

Explain

A binary decision at each of n positions can create 2^n possibilities. This exponential growth quickly outruns polynomial methods.

Evaluate

Big O ignores constants and lower-order terms; compare classes by input growth while acknowledging memory, workload and implementation detail.

Explain one step in your own words, using the correct technical terms.

I DO — WORKED EXAMPLE

Follow the worked method

For n=6, calculate total iterations of two independent nested n loops.

Explain

Each of the six outer iterations runs six inner iterations.

WE DO — GUIDED PRACTICE

Try → Discuss → Improve