EXIT TICKET / REFLECTION

Check your understanding

Complete the actual lesson Exit Ticket before checking the answer.

Reducing a time quantum to an extremely small value always improves performance.

How confident are you? Circle one: Confident / Getting there / Need help

Explain your choice, identifying one concept you can now use independently.

GREEN PEN — Correct and explain

Choose one mistake from your independent work. Write the correct method and explain precisely why your original answer was wrong.

Next step: revisit the model or a relevant revision-guide section if needed.

DO NOW — RECALL

Lesson 110 · Round Robin and Multilevel Feedback Queu

Name: _____ Class: _____ Date: _____

1. Which scheduler preempts a running task when a shorter one arrives?

2. Why can an array provide direct indexed access?

3. A full adder receives A=1, B=1 and carry-in=0. What are sum and carry-out?

4. For the binary value 1010, what is its decimal value?

DO NOW — CHECK / OBJECTIVES

Correct and improve

Check page 1 in GREEN PEN. Write corrections in full.

1. Model answer

Shortest remaining time (SRT).

2. Model answer

Its element locations can be calculated from base address and index.

3. Model answer

Sum 0 and carry-out 1.

4. Model answer

10.

By the end, you can…

- Ready processes receive a time quantum in cyclic order.
- Expired slices trigger a switch; very small slices create overhead.
- Queues with differing priorities/quanta adapt to process behaviour.

Vocabulary — know these terms

time quantum — Maximum continuous CPU interval per RR turn.

round robin — Preemptive cyclic scheduling.

context switch — Saving/restoring CPU state when changing process.

MLFQ — Multilevel feedback queue scheduling.

YOU DO — INDEPENDENT PRACTICE

Questions · Part 2

Answer independently. Show code, calculations, a trace or justified reasoning as appropriate.

Question 3

Explain how MLFQ responds to CPU-bound and interactive tasks and evaluate a very short quantum. [8]

YOU DO — INDEPENDENT PRACTICE

Questions · Part 1

Answer independently. Show code, calculations, a trace or justified reasoning as appropriate.

Question 1

Describe the round-robin algorithm, including the purpose of the time quantum. [6]

Question 2

RR quantum 2: A burst 3, B burst 4, both arrive 0. Produce a Gantt timeline. [6]

NEW LEARNING

Read, annotate and explain

Round robin

Ready processes receive a time quantum in cyclic order.

Context switching

Expired slices trigger a switch; very small slices create overhead.

MLFQ

Queues with differing priorities/quanta adapt to process behaviour.

Explain one step in your own words, using the correct technical terms.

I DO — WORKED EXAMPLE

Follow the worked method

RR with quantum 2: P1 burst 5, P2 burst 3; both arrive at t=0. Trace completion.

Model answer

P1 runs 0–2, P2 2–4, P1 4–6, P2 6–7 (finishes), P1 7–8 (finishes). Completion times: P2 7, P1 8.

Check: link each claim to the scenario and use precise OCR terminology.

WE DO — GUIDED PRACTICE

Try → Discuss → Improve