EXIT TICKET / REFLECTION

Check your understanding

Complete the actual lesson Exit Ticket before checking the answer.

Standard ASCII provides 128 character codes.

How confident are you? Circle one: Confident / Getting there / Need help

Explain your choice, identifying one concept you can now use independently.

GREEN PEN — Correct and explain

Choose one mistake from your independent work. Write the correct method and explain precisely why your original answer was wrong.

Next step: revisit the model or a relevant revision-guide section if needed.

DO NOW — RECALL

Character sets: ASCII & Unicode

Name: _____ Class: _____ Date: _____

1. Which data type should store a telephone number beginning with 0? Explain briefly.

2. Convert 41_{16} to denary and eight-bit binary.

3. Apply AND 00001111 to 10100101. Explain which bits the mask preserves.

4. In 6+4 two's-complement floating-point format, subtract 010000 0010 from 011000 0010. Give a normalised result.

DO NOW — CHECK / OBJECTIVES

Correct and improve

Check page 1 in GREEN PEN. Write corrections in full.

1. Model answer

String: preserve the leading zero; it is an identifier, not a quantity for arithmetic.

2. Model answer

65; 01000001.

3. Model answer

00000101. The low four bits are preserved; the high four are cleared.

4. Model answer

3 − 2 = 1 → 010000 0001.

By the end, you can…

- explain how character codes represent text;
- compare ASCII and Unicode and choose an appropriate encoding;
- apply character-code calculations and calculate storage using stated encoding rules.

Vocabulary — know these terms

Recall the term — Character set

Recall the term — Code point

Recall the term — Encoding

Recall the term — ASCII

Recall the term — Unicode

Recall the term — UTF-8

Recall the term — Control character

Recall the term — Repertoire

YOU DO — INDEPENDENT PRACTICE

Questions · Part 2

Answer independently. Show code, calculations, a trace or justified reasoning as appropriate.

Question 4

Question 4 · ORIGINAL CAPACITY QUESTION · [3]
State how many codes standard seven-bit ASCII provides [1]. Calculate the minimum number of bits needed for a fixed-width character set containing 300 distinct codes, showing why the next smaller width is insufficient. [2]

Question 5

Question 5 · ORIGINAL ENCODING APPLICATION · [4]
A UTF-8 string contains 20 ASCII code points, three euro-sign code points and two emoji code points. The byte widths are 1, 3 and 4 respectively. Ignore metadata. Calculate bytes [2] and bits [1]. Explain why multiplying the number of code points by 2 bytes is not valid here. [1]

YOU DO — INDEPENDENT PRACTICE

Questions · Part 1

Answer independently. Show code, calculations, a trace or justified reasoning as appropriate.

Question 1

Question 1 · ADAPTED OCR PROGRAMMING TASK · [3]
Complete the three gaps to count uppercase ASCII letters. asc returns a character’s code. A = 65 and Z = 90. The loop examines each character once.
CODE:

```
function countCapitals(text)
count = 0
for each character in text
code = asc(character)
if code >= 65 _____ code <= 90 then
count = _____
endif
next character
return _____
endfunction
```

Adapted from OCR June 2022 Q5(e)(i): simplified loop and changed gaps; classroom allocation of one mark per gap. OCR June 2022, Q5(e), page 24

Question 2

Question 2 · ADAPTED EXAM COMPARISON · [4]
A school app must store English and Chinese messages. Explain why standard ASCII is unsuitable [1], why Unicode is suitable [1], give one similarity between them [1], and explain why the receiver must know the encoding [1].
Contextual adaptation of OCR June 2022 Q5(e)(ii–iii); classroom marks.

Question 3

Question 3 · ORIGINAL EXAM-STYLE CALCULATIONS · [6]
Use A = 65, a = 97 and 0 = 48. Show a code calculation and an eight-bit byte for each: (a) C, (b) c, (c) the digit character 5. [2 each]

NEW LEARNING

Read, annotate and explain

Useful ASCII anchors

'A' = 65 'Z' = 90
'a' = 97 'z' = 122
'0' = 48 '9' = 57
space = 32

Standard ASCII uses 7 bits → 128 possible codes.

A character code represents text. The character '7' is not the same value as the integer 7 .

Characters need agreed codes

A character set defines characters and their assigned numeric codes. An encoding specifies how those codes are represented as bytes.

Standard ASCII is limited

Seven bits provide $2^7 = 128$ codes for letters, digits, punctuation and control characters.

Eight-bit extensions can provide 256 values, but different extensions may map the extra codes differently.

Unicode supports a much larger repertoire

Unicode assigns code points to characters from many writing systems and symbols. Its first 128 code points match ASCII.

Use the encoding stated in storage questions

Storage depends on the number of code points and the number of bytes used for each one. Do not assume every Unicode character uses the same width.

Explain one step in your own words, using the correct technical terms.

I DO — WORKED EXAMPLE

Follow the worked method

Encode the text “AB”

Start with the character codes

```
A = 65
B = 66
```

ASCII assigns a numeric code to each character.

Write the 7-bit ASCII values

```
A = 1000001
B = 1000010
```

Add a leading zero

```
A → 01000001
B → 01000010

AB → 01000001 01000010
```

The leading zero lets each 7-bit ASCII code sit inside an 8-bit byte; it does not expand the standard ASCII repertoire.

Repeat the method with different inputs in your notebook. Check every intermediate value.

WE DO — GUIDED PRACTICE

Try → Discuss → Improve

1. 2. Character versus quantity

Use the I Do method and build the answer before checking.

Method / working:

2. 3. Use a code range

Use the I Do method and build the answer before checking.

Method / working:

3. 4. Choose an encoding

Use the I Do method and build the answer before checking.

Method / working:

4. 5. Calculate storage from stated widths

Use the I Do method and build the answer before checking.

Method / working:

5. OCR JUNE 2022 · Q5(e)(ii–iii) · [3]

Use the I Do method and build the answer before checking.

Method / working: