DO NOW — RECALL

Arrays in C#

Name: _____ Class: _____ Date: _____

1. For a 3 × 3 array called board , what do GetLength(0) and GetLength(1) return?

2. What is the difference between a function and a procedure?

3. Convert hexadecimal 2F to denary.

4. Why must every value in a C# string[,] array be stored as a string?

DO NOW — CHECK / OBJECTIVES

Correct and improve

Check page 1 in GREEN PEN. Write corrections in full.

1. Model answer

3 and 3. Dimension 0 is rows; dimension 1 is columns.

2. Model answer

A function returns a value; a procedure does not.

3. Model answer

47. 2 × 16 + 15 = 47 .

4. Model answer

An array has one declared element type, so every element must be compatible with that type.

By the end, you can…

• declare and access one-, two- and three-dimensional arrays;

• use zero-based indexes and GetLength() correctly;

• traverse arrays using loops and choose suitable dimensions for stored data.

Vocabulary — know these terms

Recall the term — Array

Recall the term — Element

Recall the term — Index

Recall the term — Dimension

Recall the syntax — []

Recall the syntax — [,]

Recall the syntax — [,,]

Recall the method — GetLength()

NEW LEARNING

Read, annotate and explain

Arrays up to 3 dimensions

string[] names;
string[,] results;
int[,,] readings;

Core rule: one array has one element type. More dimensions mean more indexes are needed to locate one element.

1D · one index

Indexes start at 0, so students[2] is Charlie .

2D · row and column

[0,0] means row 0, column 0. It outputs Amelia .

GetLength() names the dimension

For the array above, the answers are 3 and 2 .

3D · layer, row, column

Read the indexes as layer → row → column . A 3D array is easiest to visualise as several 2D tables stacked together.

Explain one step in your own words, using the correct technical terms.

I DO — WORKED EXAMPLE

Follow the worked method

Build studentResults

Rows are students · columns are fields

```
row 0 → Amelia | 72
row 1 → Ben    | 65
row 2 → Charlie| 81
```

We need 3 rows and 2 columns.

Create the 2D array

```
string[,] studentResults =
{
    { "Amelia", "72" },
    { "Ben", "65" },
    { "Charlie", "81" }
};
```

Both columns use strings in this teaching example.

Use row, then column

```
Console.WriteLine(studentResults[0,0]);
Console.WriteLine(studentResults[0,1]);
```

The outputs are Amelia and 72 .

Visit every row

```
for (int row = 0;
     row < studentResults.GetLength(0);
     row++)
{
    Console.WriteLine(
        studentResults[row,0] + " " +
        studentResults[row,1]);
}
```

Think in layers

```
LAYER 0
          col 0  col 1  col 2  col 3
row 0       12     15     18     20
row 1       21     24     27     30
row 2       32     35     38     40

LAYER 1
          col 0  col 1  col 2  col 3
row 0       42     45     48     50
row 1       51     54     57     60
row 2       62     65     68     70
```

Worked example: find scores[1,2,1] .

Three dimensions need three loops

I DO — WORKED EXAMPLE

Follow the worked method · continued

```
for (int layer = 0;
     layer < scores.GetLength(0);
     layer++)
{
    for (int row = 0;
         row < scores.GetLength(1);
         row++)
    {
        for (int column = 0;
             column < scores.GetLength(2);
             column++)
        {
            Console.WriteLine(
                scores[layer,row,column]);
        }
    }
}
```

WE DO — GUIDED PRACTICE

Try, discuss and improve

1. Read an indexed value

What is stored at index 2, and how many elements are in the array?

Method / working:

2. Read row and column

Find studentResults[2,1] and the two dimension lengths.

Method / working:

3. Find the address

The value 57 is in layer 1. What complete array reference accesses it?

Method / working:

4. Declare towns

OCR describes a 2D array called towns with 8 rows and 3 columns. Write a suitable declaration.

Method / working:

YOU DO — INDEPENDENT PRACTICE

Questions · Part 1

Answer independently. Show code, calculations or a justified explanation.

Question 1

Find 24

Using the supplied scores array, change the Console.WriteLine statement so the program outputs 24 .

Question 2

Find 38

Write a Console.WriteLine statement that outputs the value 38 .

Question 3

Find the last value

Output the last value in the array without changing the array.

Question 4

Change a value

Change the value 35 to 99 , then output it to prove that the value has changed.

Question 5

Measure the array

Output the size of all three dimensions using scores.GetLength(0) , scores.GetLength(1) and scores.GetLength(2) .

YOU DO — INDEPENDENT PRACTICE

Questions · Part 2

Answer independently. Show code, calculations or a justified explanation.

Question 6

Output one row

Use a for loop to output 12, 15, 18 without writing three separate Console.WriteLine statements.

Question 7

Output the first layer

Use two nested loops to output all six values in the first layer: scores[0, ... , ...] .

Question 8

Traverse the whole array

Use three nested loops and GetLength() to output every value in the 3D array.

Question 9

Calculate the total

Adapt your three nested loops to calculate and display the total of every value in scores .

Question 10

Find the largest value

Use three nested loops to find and display the largest value in the entire 3D array.

Do not assume 48 is the largest. Your algorithm must still work if the values in the array are changed.

EXIT TICKET / REFLECTION

Check your understanding

Complete the actual lesson Exit Ticket before checking.

int[,,] data = new int[2,3,4]; declares a three-dimensional array.

Circle: Confident / Getting there / Need help

Explain what you can now do independently.

GREEN PEN — Correct and explain

Choose one error. Write the correct method and explain precisely why your first response was wrong.