## Review & Improve · GREEN PEN

Now change to GREEN PEN. Find each original question. Tick correct answers; read the model and rewrite mistakes.

### Page 1 onwards · Do Now

Q1. They shift one position right to make space.

Q2. [1,3,4].

Q3. 4.

Q4. The input is already correctly ordered; comparisons find no element greater than the key.

### You Do pages · Independent questions

Q1. [1,2,5,6].

Q2. Merge pairs → [2,6] and [1,5]; merge both → [1,2,5,6].

Q3. There are about $\log_2 n$ merge levels, and each level processes n elements → O(n log n) time, with O(n) extra array storage for this implementation.

### Exit Ticket · Model answer

False. Both input runs must already be sorted.

## Try the question again

Choose one question you got wrong. All correct? Choose the hardest.

**1. Copy the whole original question:**

**2. Write a complete new answer in GREEN PEN. Show working if needed:**



RHS COMPUTING / OCR H446 / mixed LESSON 186 · DRAFT

BLACK PEN Answer all questions first. GREEN PEN Then: tick and rewrite mistakes.

# LESSON 186 · Merge sort: trace and implement

Name: _____ Class: _____ Date: _____

Work through the pages in order. Answer in BLACK PEN first. Check in GREEN PEN only after the Exit Ticket.

## Do Now · Recall previous learning

Q1. In insertion sort, what happens to values greater than the key in the sorted prefix?

Q2. After one ascending bubble-sort pass on [4,1,3], what remains?

Q3. What is the length of int[] a={8,5,2,1}?

Q4. Why is swapping not needed to place key 6 into already sorted [2,4,6,8]?

BLACK PEN Answer all questions first. GREEN PEN Then: tick and rewrite mistakes.

## I Do · Read new knowledge

### Key vocabulary

run — A consecutive sorted block.

merge — Combine sorted sequences while preserving order.

pointer — Position of the next candidate in a run.

bottom-up — Build sorted runs iteratively from small to large.

O(n log n) — Common time bound for comparison-based merge sort.

### New learning

Start with ordered runs — At each merge stage, both input runs must already be sorted.

Compare front values — Append the smaller current value, then advance that run's pointer.

Copy the remainder — When one run finishes, copy all remaining values from the other run; repeated merging doubles run size.

### Worked example

Merge the sorted runs [1,8] and [4,5].

1. Predict first — Compare the two current front values at every step.

2. Model solution — Choose 1, then 4, then 5, then copy the remaining 8 → [1,4,5,8].

## We Do · Practise with guidance

Merge [2,9] and [3,7] without sorting the runs again.

Predict first

Which value enters the output first?

Model solution

2, then 3, then 7, then 9: [2,3,7,9].





BLACK PEN Answer all questions first. GREEN PEN Then: tick and rewrite mistakes.

## You Do · Work independently

BLACK PEN: Write your own answers. Do not look at the Review & Improve pages yet.

### Question 1

Merge [2,6] with [1,5].

### Question 2

Bottom-up merge sort [6,2,5,1]: show the size-two runs then final result.

### Question 3

Explain the O(n log n) time complexity of merge sort.

## Exit Ticket · Answer before checking

Two unsorted arrays can be passed to the standard merge step and always yield sorted output.