STAFF REVIEW · H446 236 source models

Separate from the eight-page pupil workbook. This copy is in a public repository and is NOT access controlled. Check technical correctness before use.

Printed question mapping: Booklet Q1 = original online Q1; Booklet Q2 = original online Q2; Booklet Q3 = original online Q3

Do Now — source answers

1. −1 or 101.

2. Passes a function's result back to the caller.

3. 3.

4. Index 0 does not exist, causing an out-of-range error.

I Do — source worked steps

1. Predict first — Start best at first element 4; 2 does not replace it.

2. Model and explain — 9 is larger so best becomes 9; return 9.

We Do — guided CHECK

1. Predict first
11 replaces initial best 8; neither 6 nor 10 exceeds 11.
Model and explain
The output is 11; the required precondition is a nonempty array.

You Do — source mark schemes

1. [4] Starts best=2 [1]; 5 greater so best=5 [1]; 1 ignored [1]; returns 5 [1].

2. [6] Set smallest=values[0] [1]; loop over remaining items [1]; if item<smallest [1] then smallest=item [1]; return smallest [1]; array must be nonempty [1].

3. [6] Original best=−4 [1]; update to −2 [1]; ignores −9 [1]; returns −2 [1]; initialising to zero would incorrectly return 0 [1] even though zero is absent [1].

Exit Ticket — source answer

1. False. Arrays containing only negative values would produce an incorrect result.