STAFF REVIEW · H446 279 source models

Separate from the eight-page pupil workbook. This copy is in a public repository and is NOT access controlled. Check technical correctness before use.

Printed question mapping: Booklet Q1 = original online Q1; Booklet Q2 = original online Q2; Booklet Q3 = original online Q3

Do Now — source answers

1. Uniqueness of row identifier.

2. Return all columns.

3. Links a row to a related key.

4. $A \vee (\neg A \wedge B) = (A \vee \neg A) \wedge (A \vee B) = 1 \wedge (A \vee B) = A \vee B$.

I Do — source worked steps

1. Predict — DELETE with a key-based WHERE targets that record

2. Check the answer — DROP TABLE would remove the entire table.

We Do — guided CHECK

1. Predict
Jo, John and Joanne match
Check the answer
a name not starting Jo does not. The % wildcard may match zero or more characters.

You Do — source mark schemes

1. INSERT INTO Student [1] (ID,Name) [1] VALUES (7,'Elena') [2];

2. Without WHERE all rows removed [2]; DELETE FROM Student [1] WHERE ID=7 [2]; check key/transaction/backups first [1].

3. SELECT * returns all columns [2]; LIKE A% filters strings starting A [2]; DROP TABLE removes table structure and data [2].

Exit Ticket — source answer

1. False. Standard SQL LIKE uses %, while SELECT * selects all columns.