

# Senegalese License Plate Detection System

## Manual Parsing and Regex Approaches

Group 11: A. Irigena, M. Y. Mohamed, O. T. Ogundepo, J. B. Habineza

AIMS Rwanda

October 8, 2025

# Agenda

- 1 Problem Overview
- 2 Objectives
- 3 Manual Parsing Approach
- 4 Regex Approach
- 5 Testing and Results
- 6 Limitations and Improvements
- 7 Conclusion

# Motivation

- Extract structured information (license plates) from plain text.
- Useful for logs, reports, monitoring, and preprocessing.
- Focus: Senegalese vehicle plate formats only.
- Two complementary methods: manual parser and regex pattern.

Accepted canonical patterns (letters A–Z, digits 0–9):

- XY-1234-T
- XY-1234-ZT

Separators may be hyphen or single space in input: XY 1234 T.

# Rules Recap

- 2 starting letters
- Separator: - or space
- 4 digits
- Separator: - or space
- 1 or 2 trailing letters
- Not embedded inside longer alphanumeric strings
- Case-insensitive input; uppercase normalized output

# Core Objectives

- Detect all valid plates in arbitrary text.
- Print normalized unique results in order.
- Report when none are found.
- Provide simple, readable logic.

# Extended Objectives

- Allow punctuation around plates.
- Interactive menu (manual testing).
- Provide alternative regex method.
- Keep code dependency-free (core version).

# Why Manual Parsing?

- Educational transparency.
- Fine control over each rule.
- Easy to extend for new patterns.
- Avoids reliance on regex engine.



# Pseudocode (High-Level)

```
UPPER = text uppercased
plates = empty list
i = 0
while i < length - minimal_length:
    if next 2 chars not letters: i++ ; continue
    if next sep not '-' or ' ': i++ ; continue
    if next 4 chars not digits: i++ ; continue
    if next sep not '-' or ' ': i++ ; continue
    read 1 or 2 letters as end_part
    if none: i++ ; continue
    check boundary before and after
    if ok:
        plate = canonical form with hyphens
        store if new
        i = end of match
```

- Ensure no letter/digit directly touches start or end of detected pattern.
- Prevents false matches inside longer tokens (e.g. AAXY-1234-T).
- Accepts punctuation (comma, period) near plates.

# Regex Pattern

Core pattern (case-insensitive):

## Pattern

```
(?i)(?<![A-Z0-9])([A-Z]{2})[- ](\d{4})[- ]([A-Z]{1,2})(?![A-Z0-9])
```

## Pattern Components

- `(?i)` Case-insensitive matching
- `(?<![A-Z0-9])` Left boundary (no letter/digit before)
- `([A-Z]{2})` Two letters
- `[- ]` Separator (hyphen or space)
- `(\d{4})` Four digits
- `([A-Z]{1,2})` One or two letters
- `(?![A-Z0-9])` Right boundary (no letter/digit after)
- Lookbehind / lookahead enforce clean boundaries.
- Captures letter block, digits, ending letters.
- Short, expressive, fast.

# Manual vs Regex

## Manual

- Stepwise logic
- Easy to tweak mid-steps
- Verbose
- Didactic

## Regex

- Compact expression
- Faster to write
- Dense syntax
- Concise

Mixed sample paragraph included:

- Valid plates with hyphens and spaces.
- Single-letter and two-letter endings.
- Mixed casing.
- Near-miss invalid patterns.

# Observed Outcomes

- All expected valid plates detected.
- No false positives in sample.
- Output normalized consistently.
- Order preserved; duplicates removed.

# Current Limitations

- No fuzzy/typo tolerance.
- Only Senegal formats covered.
- Pattern validity only (not real issuance).

# Potential Enhancements

- Add fuzzy (edit-distance) matching.
- Multi-country format registry.
- Batch file / dataset scanning.
- JSON / CSV export.
- Performance benchmarking.



# Conclusion

- Two clear methods implemented: manual parser and regex.
- Both meet detection, normalization, and uniqueness goals.
- Manual path aids learning; regex path aids brevity.
- Solid base for future extensions (fuzzy logic, more formats).

# Key Takeaways

- Keep patterns explicit when teaching.
- Normalize early for consistency.
- Enforce boundaries to avoid false positives.
- Provide alternative implementations for flexibility.

# Thank You!

Questions / Feedback?