Designing Production Agentic Systems
Lecture 5: The Model Context Protocol and attacks on tool-using agents

Rahul Krishna
Columbia University, COMS E6998-019, Fall 2026

Revised October 16, 2026, as reading for the midterm and the final, from the lecture of October 9, 2026

Abstract

These notes are the reading for Lecture 5, written for students preparing for the midterm and the final, and each numbered section ends with Key points for revision. Lecture 4 kept every tool of `mini-swe-agent`, the course's running example, inside its harness, where the dispatcher checks each call before the tool runs. This lecture moves tools into separate processes with the Model Context Protocol (MCP), which divides the work of a tool call among a host, its clients and its servers, and asks which parts of a tool's contract the protocol enforces and which it leaves to trust. We then study how tool-using agents are attacked and what defenses are recorded, through a published vulnerability in the MCP Inspector, the risks of the OWASP MCP Top 10, and the techniques and mitigations of MITRE ATLAS. Two documented attacks on the OpenClaw assistant close the notes: in both, an attacker who reached the agent's settings or its inputs switched off or got past a control that lived inside the agent's own process and configuration.

Contents

Recap of Lecture 4 1

1 The Model Context Protocol 2
1.1 Checks inside the agent's process . . . 2
1.2 What MCP standardizes . . . 3
1.3 Tools, resources and prompts . . . 3
1.4 One request from the user to the server . . . 3
1.5 The server . . . 3
1.6 The host and its clients . . . 4
1.7 Messages and methods . . . 5
1.8 From MCP tools to native tool definitions . . . 6
1.9 The path of one tool call . . . 6
1.10 Tool results and errors . . . 6
1.11 Who performs each operation . . . 7

2 MCP tool definitions, enforcement and transports 8
2.1 The SDK generates the tool definition . . . 8
2.2 Which parts of the contract MCP enforces . . . 9
2.3 Annotations are hints . . . 9
2.4 Every request stands on its own . . . 10
2.5 The stdio transport . . . 10
2.6 The Streamable HTTP transport . . . 11
2.7 Progress and cancellation over server-sent events . . . 11
2.8 A broken stream forces a new request . . . 11
2.9 Who validates arguments and who resends a request 12

3 The MCP Inspector and its published vulnerability 12
3.1 A host with no model . . . 13
3.2 Errors and timeouts in the Inspector . . . 13
3.3 What the Inspector cannot show . . . 13
3.4 A vulnerability in the Inspector's proxy . . . 13
3.5 The fix and the trust boundary . . . 15

4 Threat catalogs: the OWASP MCP Top 10 and MITRE ATLAS 15
4.1 From a design smell to a threat . . . 16
4.2 The OWASP MCP Top 10 . . . 16
4.3 Documented cases of the risks . . . 17
4.4 One incident read through both catalogs . . . 17
4.5 MITRE ATLAS and its terms . . . 19
4.6 The ATLAS matrix . . . 20
4.7 Agentic AI coverage in ATLAS . . . 20

5 Attacks on tool-using agents 21
5.1 Tool poisoning: definition, implementation and response . . . 21
5.2 The sub-techniques and the tool contract . . . 22
5.3 A supply-chain attack on a tool . . . 22
5.4 The postmark-mcp attack in ATLAS . . . 23
5.5 Credentials in the agent's configuration . . . 24
5.6 Exfiltration through an authorized call . . . 25
5.7 Escape from the sandbox . . . 26
5.8 Instructions in persistent memory . . . 27
5.9 Spending the agent's budget . . . 27
5.10 Assets exposed through tool access . . . 28

6 Mitigations and where they act 28
6.1 Mitigations in ATLAS . . . 28
6.2 Which techniques have mitigations . . . 28
6.3 Where each family acts along a tool call . . . 29
6.4 Controls on agent authority . . . 30
6.5 Validation and containment controls . . . 31
6.6 Tool vetting, logging and human approval . . . 32
6.7 Where a control is enforced . . . 32

7 Case study: attacks on OpenClaw 33
7.1 OpenClaw and its Gateway . . . 34
7.2 OpenClaw's case studies in ATLAS . . . 34
7.3 Remote code execution from one click . . . 35
7.4 Command and control through a web page . . . 36
7.5 The controls that failed . . . 37

Recap of Lecture 4

Lecture 4 opened the tools node of `mini-swe-agent`, the node of the course's running agent that runs the tools the model requests. It studied the harness, the program that runs the model loop and executes tool calls for the model. This recap restates the parts of that lecture on which this lecture builds: the tool contract, the dispatcher, the guarantees of the harness, and the integration problem that the Model Context Protocol (MCP) addresses. The Lecture 4 notes, *Tool calls, contracts and execution boundaries*, give the full treatment.

A tool contract is the written specification of a tool, and Lecture 4 divided it into five parts:

- **Purpose.** The contract states what the tool does.
- **Arguments.** The contract lists the arguments that the tool accepts, with the constraints on their values.
- **Results and errors.** The contract states what a successful call returns and how a failed call is reported.
- **Side effects.** The contract states the changes a call makes besides returning its result, such as changes to files.
- **Execution constraints.** The contract limits where and how the tool may operate, for example by requiring that every file the tool writes lies inside the run's own copy of the code base.

`mini-swe-agent` has three tools. `read_file` and `search` only read, and `edit` is the only tool that writes files.

The model receives only part of the contract, the tool definition. It consists of the tool's name, a description of its purpose, and the argument schema, which gives the names and types of the arguments and the constraints on their values. The tool's

implementation and the dispatcher, the component of the harness that executes each tool call, define the rest of the contract: the results, the errors, the side effects and the execution constraints.

A description is text that the model reads. It can state a rule, but nothing in it stops a call that breaks the rule, so a description alone enforces nothing. A constraint holds only where code in the implementation or in the dispatcher checks it. Section 2 returns to the five parts of the contract and asks which of them MCP enforces, and Section 5 uses the same parts to describe what an attacker alters in a tool.

The workspace is the disposable copy of the code base that one run may read and edit. The dispatcher receives each tool request, executes it against the workspace, and returns an observation to the model. An observation is the tool's result as the harness records it.

The dispatcher holds the registry, the workspace root and the trace, and the model never touches any of them. The registry maps each tool name to the function that implements the tool. The workspace root is the path of the workspace, and the trace is the log of events that the harness writes during a run.

The tools node passes each tool call in the model's reply to the dispatcher. The dispatcher finds the tool in the registry, binds the model's arguments to the parameters of the tool function, and calls the function with the workspace root, which it supplies itself. It records the request and its result in the trace and returns the observation, which the tools node turns into a tool message, the message that carries one tool result back to the model. The model never calls a tool function directly. It can only ask for a call, and the dispatcher decides whether and how the call runs.

In `mini-swe-agent`, the dispatcher, the tool functions and their checks all run in the agent's own process. Section 1 begins by explaining why a check that runs inside that process can be switched off or avoided.

A guarantee is a property that the harness promises for every run, such as that only registered tools run. Lecture 4 asked which component enforces each guarantee, and Table 1 collects the answers. The row to look at is the one about reads, the only guarantee that no component enforces.

Table 1: The guarantees of the harness of `mini-swe-agent` and where each is enforced. Reads are not confined to the workspace.

Guarantee	Where it is enforced
Only registered tools run	The dispatcher checks the registry before calling a tool.
Arguments match the tool's parameters	The dispatcher binds the arguments and converts unambiguous type mismatches.
Writes stay inside the workspace	The `edit` tool, the only writer, checks paths with the path check.
Reads stay inside the workspace	Not enforced. The glob of `search` bypasses the path check.
No model call after the budget is exhausted	Each model node checks the budget before calling the model.

The path check, through which `edit` enforces the guarantee about writes, accepts a path only if it resolves to a location inside the workspace root. The model nodes are the nodes that call the model. Each of them checks the budget, the limit on the number of model calls in a run, before it calls the model. Every enforcer in the table is code that runs before the effect it protects.

Reads are not confined, because `search` skips the path check. The model may supply `search` with a glob, a file pattern with wildcards that selects the files to search. `search` applies the glob to the workspace root and opens every file that the glob matches, so a glob that climbs out of the root lets the tool read files outside the workspace. The path check itself is correct. `search` is a route to the files that does not pass through it.

Native tool calling, studied in Lecture 4, makes the tool call part of the model API, with one format per vendor. It standardizes the exchange between a model and an application, and it leaves the integration between an application and a tool to each application. An integration is the code that lets one application use one tool: the tool's definition in the application's format, and the code that carries out the five operations of a tool call. That code finds the tool, binds the arguments, checks policy (the rules that decide whether a requested call is allowed), runs the tool and observes the result. The work multiplies for the following reasons:

- **Vendor formats.** Each vendor defines its own format, so every application converts between formats. Each vendor's strict mode, which makes the model's arguments match the argument schema, accepts a different subset of JSON Schema, so even the argument schema must be adapted for each vendor.
- **Repeated operations.** Each application re-implements the five operations for every tool it uses.
- **Place and language.** Tools live in the process and language of the application that uses them, so a tool written as a Python function cannot serve an application written in TypeScript.

As a result, N applications and M tools need $N \times M$ integrations, one for each pair, which is the $N \times M$ integration problem. A shared protocol reduces the count to $N + M$, because each application and each tool implements the protocol once. For three applications and three tools, the count falls from nine to six. MCP, which Lecture 4 introduced briefly, is such a protocol for the tool side, and Section 1 studies it in full.

This lecture reads Table 1 from the attacker's side, where each unenforced row marks a fault that an adversary can use (Section 4), and it moves the tools out of the harness.

1 The Model Context Protocol

The recap showed that in `mini-swe-agent` every check on a tool call runs inside the harness, in the agent's own process (Recap of Lecture 4). A check that runs inside the agent's own process can be switched off or avoided, and the rest of this lecture studies that limitation from the attacker's side. This section first explains the limitation, then introduces the Model Context Protocol (MCP), which moves tools into separate programs and divides the work of a tool call among a host, its clients and its servers. We follow one tool call through the protocol and ask which component performs each of Lecture 4's five operations: find, bind, check, run and observe.

1.1 Checks inside the agent's process

A rule enforced inside the agent's own process can be disabled or bypassed by the agent. The limitation matters because the guarantees of a tool call rest on such rules. They come from the tool contract and from the harness. None of them comes from the model.

The guarantees of Lecture 4 (Table 1) include that only registered tools run, that the arguments match the tool's parameters, and that writes stay inside the workspace. The model only proposes a call. Code that the harness runs after the model has replied decides whether the call is allowed, whether its arguments fit and where it may write.

A process is a running program, to which the operating system gives its own memory and the permissions of the user who started it. In `mini-swe-agent`, the agent's own code shares one process and one set of permissions with the dispatcher. Every check between them, such as the path check that keeps writes inside the workspace, runs in that process too.

Code that runs in a process can do whatever the process is permitted to do. It can change the settings that switch a check on. It can also reach a file by a route that never passes through the check.

Code actions, introduced in Lecture 4, take the second route. A code action is an action written as a program that the harness runs in an interpreter, and the program executes with every right of the harness process. A program that writes a file directly never calls `edit`. None of the dispatcher's checks applies to it, and the path check inside `edit` never runs.

An agent misled by text in its inputs, or an attacker who reaches its settings, can take either route. OpenClaw, an open-source personal AI assistant, is the case study that closes this lecture. In both documented attacks on it, an attacker who reached the agent's settings or its inputs switched off or got past a control that lived inside the agent's own process and configuration (Section 7).

MITRE ATLAS, a catalog of adversary techniques against AI-enabled systems (Section 4), records the techniques by which such rules are disabled or bypassed. Lecture 6 studies enforcement outside the agent with NVIDIA OpenShell, a system that moves enforcement to the operating-system kernel and to a separate supervising process that the agent cannot reach.

Before studying attacks, we study the protocol through which an agent reaches tools that run outside its harness. When a tool moves into another program, the dispatcher's checks are divided among several components. For each rule, we must then ask which component enforces it.

1.2 What MCP standardizes

MCP is an open standard for connecting AI applications to external systems. Through MCP, an application connects to data sources such as local files and databases, to tools such as search engines and calculators, and to workflows such as specialized prompts. Lecture 4 introduced MCP briefly as a response to the $N \times M$ integration problem. This section and Section 2 study the protocol itself, in revision 2026-07-28 of its specification. Definition 1.1 defines MCP by comparison with a familiar connector.

Definition 1.1 (Model Context Protocol)**.** "MCP (Model Context Protocol) is an open-source standard for connecting AI applications to external systems. [. . .] Think of MCP like a USB-C port for AI applications. Just as USB-C provides a standardized way to connect electronic devices, MCP provides a standardized way to connect AI applications to external systems." [29]

The comparison describes one standard port in place of a different cable for every device. An application that implements MCP can use any MCP server, and a tool offered through an MCP server works with any application that implements MCP. The applications that support MCP include Claude, ChatGPT, Visual Studio Code and Cursor. Anthropic introduced the protocol in November 2024 [1].

MCP is the shared protocol that reduces the $N \times M$ integrations of the recap to $N+M$. Each application implements the protocol once, and each tool is offered once, through a server.

The name states what the protocol standardizes. A model's context, as Lecture 2 defined it, is the input that the model receives in one call. MCP standardizes how an application brings into that input the data and the actions that external systems offer. MCP provides "a standardized way to connect LLMs with the context they need" [32].

1.3 Tools, resources and prompts

An MCP server offers tools, resources and prompts [32]. A tool is a function that the model can ask to execute. It is the tool of Lecture 2: an action that the agent requests by name, with arguments, and that another program carries out. A **resource** is data that a server makes available for the user or the model to use, such as the text of a file. An **MCP prompt** is a templated message or workflow that a server offers to users. We add "MCP" to its name because "prompt" alone could mean the model's input. Table 2 gives one example of each from our running task.

Table 2: The features that an MCP server can offer, with an example of each from the running task.

Feature	What it is	Example
Tool	A function for the model to execute	`edit(path, old, new)`
Resource	Data for the user or the model to use	The text of `src/parse.py`
MCP prompt	A templated message or workflow for users	A template that asks for a review of a change

This lecture uses only tools, because tools are the features through which a model acts on the world. Resources and MCP prompts travel over the same connection as tools and in the same message format.

A server states which features it offers by declaring capabilities. A **capability** is a feature that a server declares it supports, so that a client knows what it can ask for. A server that offers tools, for example, must declare the tools capability. A client therefore learns from the server itself whether to ask it for tools, resources or MCP prompts. It asks the server through `server/discover`, a request that Section 1.7 describes.

1.4 One request from the user to the server

A request from a user crosses several components, and MCP covers the exchange between two of them, the MCP client and the MCP server. Each exchange between two neighboring components is a **hop**, and each hop can follow its own standard. Figure 1 follows a request in the constructed example of Lecture 4. The user asks an AI application to fix an off-by-one error in `src/parse.py`, and an MCP server offers the `edit` tool. The numbers in the figure mark the following steps:

1. The user asks the application to fix the off-by-one error.
2. The application sends the question to the model, together with the list of tools that its servers offer, written in the model vendor's native format.
3. The model replies with a call to `edit`.
4. The application's MCP client sends the edit request to the MCP server, and later receives the result.
5. Before it returns the result, the server changes the file.
6. The application returns the model's answer to the user.

The hop to the model, steps 2 and 3, uses the native tool calling of Lecture 4, in which the request to the model API lists the tools and the reply returns each tool call in a structured field. An application that uses MCP therefore still uses native tool calling. The MCP components of the request are the server, the client, and the application that contains the client, which MCP calls the host.

1.5 The server

An MCP **server** is a separate program, written once by the owner of a tool, that offers tools, resources and MCP prompts [32]. Any application that implements MCP can use it, so servers are the M side of the $N+M$ count. The term keeps its meaning




Figure 1: One request in an application that uses MCP, with steps numbered as in the text. Only the hop between the MCP client and the MCP server, drawn in color, uses MCP. The hop to the model uses the vendor's native tool calling.

from Lecture 4, where a server is a separate program that offers tools and runs them. The MCP project maintains reference servers, among them a Filesystem server and a Git server [31], and companies publish official servers for their own products.

A server runs as a separate process. It is either a subprocess that the application starts on the same machine, or a service that the application reaches over HTTP, on another machine or on the user's own machine. The mechanism that carries messages between a client and a server is the transport, a term that keeps its meaning from Lecture 4. MCP defines stdio and Streamable HTTP as its standard transports:

- **stdio.** The application starts the server as a subprocess, and the two exchange messages over the subprocess's standard streams. The client writes each message to the server's standard input and reads the replies from its standard output, one message per line.
- **Streamable HTTP.** The server runs as a web service, and the client sends each message as one HTTP POST request to a single address on the server, its endpoint. This transport suits a server on another machine.

Section 2 describes how each transport marks where a message ends and how a reply can stream.

Our illustrative edit server moves the course's `edit` tool into an MCP server written with the official Python SDK [30]. An SDK (software development kit) is a library that implements the protocol, so that the server's author writes only the tool. Listing 1 shows the server in outline.

Listing 1: Illustrative code for the edit server, written with the official Python SDK.

```
from typing import TypedDict
from mcp.server import MCPServer

mcp = MCPServer("workspace")

class EditResult(TypedDict):
    path: str
    replaced: int

@mcp.tool()
def edit(path: str, old: str, new: str) -> EditResult:
    """Replace one exact occurrence of old with new."""
    ...
```

The listing has the following parts:

- **The server object.** `MCPServer("workspace")` creates a server named `workspace`.
- **The result type.** `EditResult` names the fields of a successful result: the path of the edited file and the number of replacements made.
- **The decorator.** `@mcp.tool()` registers the function as a tool of the server, much as Lecture 4's registry maps a tool's name to its function.
- **The function.** Its body, elided here, is the course's `edit` tool. The server holds its workspace and refuses any path outside it.

From the decorated function, the SDK derives the tool definition, the part of the tool contract that the model receives (Recap of Lecture 4). It takes the name from the function's name, the description from its docstring, and the input schema from the type hints of its parameters. The **input schema** (`inputSchema`) is MCP's name for Lecture 4's argument schema. It is a JSON Schema, a description in a standard language of the shape that JSON data must have, and it gives the names and types of the arguments and says which are required. The server's author writes no schema by hand. Section 2 shows the whole definition that the SDK generates. It also includes an output schema, a JSON Schema that the data in the tool's result must match, which the SDK derives from `EditResult`.

1.6 The host and its clients

The application that the user runs is the **host**. It may be a chat application such as Claude Desktop, an IDE or an agent harness. A harness like ours, built with LangGraph [11], takes the host role when it connects to MCP servers. Product documentation often calls the whole application the client. In MCP's terms, the application is the host, and a client is one of its components.

For each server, the host creates one **client**, a component that starts or connects to that server and sends it requests. The relation is one to one: each client communicates with exactly one server. In code, a client is an object that holds the connection to one server. Lecture 4 called the client the part of the harness that exchanges messages with a server. When a harness like ours takes the host role, its clients are that part.

Claude Desktop, for example, reads a list of servers from its configuration and starts each listed server whenever it launches [27]. With the official Python SDK, the host's code opens a client on a server and calls a tool by its name with a dictionary of arguments [30]. Each such call sends one request to the server.

Figure 2 shows a host with two clients. Client A starts the illustrative edit server as a subprocess and talks to it over stdio. Client B reaches a remote server on another machine over Streamable HTTP. The host's model loop exchanges messages with the model API. The host coordinates its clients and holds what they share:




Figure 2: A host with two clients. Client A runs the edit server as a subprocess over stdio, and client B reaches a remote server over Streamable HTTP. The host holds the conversation, the user's consent and the policy, and each server sees only its own requests.

- **Clients.** The host creates and manages its clients, one for each server.
- **Conversation.** The host keeps the full conversation and combines the context gathered through all its clients.
- **Policy and consent.** The host enforces security policies and consent requirements, and it handles the user's decisions about what to authorize. Policy keeps its meaning from Lecture 4: the rules that decide whether a requested call is allowed. **Consent** is the user's approval, which the host obtains before it invokes a tool (Section 1.9).

Servers are kept apart from the conversation and from each other. One design principle of MCP is that "servers should not be able to read the whole conversation, nor 'see into' other servers", and that the full conversation history stays with the host [32]. Each server receives only the requests that its client sends, so it learns only what the host chooses to put in them. The edit server sees edit requests and their arguments. It sees the user's other questions only if the host puts them into a request. It does not see the traffic of the remote server, which passes through another client. This matters because a server is written by the tool's owner, who may be someone other than the author of the host, and the host need not trust it with the whole conversation.

In Lecture 4, every operation of a tool call took place inside the harness's process. Under MCP, the dispatcher's work is split: the host keeps the conversation and the policy, and the server runs the tool. Section 1.11 sets out the split operation by operation.

1.7 Messages and methods

Every MCP message is a **JSON-RPC** message [32]. JSON-RPC is a standard format, written in JSON, for remote procedure calls, the calls to a procedure in another process or on another machine that Lecture 4 described. A JSON-RPC message is a request, a response or a notification:

- **Request.** A request names a **method**, the action it asks the receiver to perform, such as `tools/call`. It carries a **request ID**, a string or an integer chosen by the sender, and the method's parameters.
- **Response.** A response repeats the request ID and carries either a result or an error. The ID lets the sender match each reply to its request. A sender never reuses the ID of a request that is still waiting for its response.
- **Notification.** A **notification** names a method but carries no ID, and its receiver sends no response.

MCP defines each kind of request as a method. Table 3 lists the methods that this lecture uses and the party that sends each one. The client sends every request in the table. The last row is a kind of result, which the server returns inside a reply when it needs more input from the client.

Table 3: The MCP methods that this lecture uses, with the party that sends each one and its purpose.

Method	Sent by	Purpose
`server/discover`	Client	Returns the server's protocol versions, capabilities and identity.
`tools/list`, `tools/call`	Client	List the server's tools, and call one of them.
`resources/list`, `resources/read`	Client	List the server's resources, and read one.
`prompts/list`, `prompts/get`	Client	List the server's MCP prompts, and fetch one.
`completion/complete`	Client	Suggests completions for an argument's value.
`subscriptions/listen`	Client	Opens one stream for the server's change notifications.
An `input_required` result	Server	Asks for more input. The client retries the request with that input.

An `input_required` result is the only entry in the table that the server sends. A server sends responses and notifications, and it never sends a request of its own. When it needs more input to finish a request, it returns a result of the type `input_required`. The client then sends the request again as a new request, with a new request ID, that carries the input the server asked for.

What a server must support follows from its capabilities. A server implements only the features that it declares as capabilities. Every server must also implement `server/discover`, which a client may call before any other request to learn the protocol versions that the server supports, its capabilities and its identity. MCP defines a few further messages, such as the progress notifications that a server sends before a result. Section 2 covers them, together with the cancellation of a request.

A message names its method in its body, so both transports carry every method in the same way. Over stdio, each message is one line of text. Over Streamable HTTP, each message from the client is one POST to the server's single endpoint, and the server's messages return in the HTTP response.

1.8 From MCP tools to native tool definitions

The host translates every MCP tool into the format of the model API, so no MCP message reaches the model. It converts each tool that a server lists into a **native tool definition**, a tool definition in Lecture 4's sense written in the format of one model vendor, and sends these definitions to the model API. Listing 2 shows the illustrative edit server's answer to `tools/list`, shortened to the fields that the model needs. Listing 3 shows host code that converts each listed tool into the native format of OpenAI's Chat Completions API.

Listing 2: Illustrative answer of the edit server to `tools/list`, shortened to the fields that the model receives.

```
{"tools": [{
   "name": "edit",
   "description": "Replace one exact occurrence of old with new.",
   "inputSchema": {
     "type": "object",
     "properties": {"path": {"type": "string"},
                    "old":  {"type": "string"},
                    "new":  {"type": "string"}},
     "required": ["path", "old", "new"]}}]}
```

Listing 3: Illustrative host code that builds one native tool definition for each listed tool.

```
tools = [{"type": "function",
          "function": {"name": t["name"],
                       "description": t["description"],
                       "parameters": t["inputSchema"]}}
         for t in listed["tools"]]
```

In Listing 3, the variable `listed` holds the answer to `tools/list`. Each native tool definition is an object whose `type` is `function` and whose `function` field holds the tool's fields, as OpenAI's format requires. The conversion copies three fields. The tool's `name` and `description` keep their names, and the MCP field `inputSchema` becomes the vendor's `parameters`. For Anthropic's API, the same schema becomes `input_schema`. The model therefore receives the name, the description and the input schema, which are the parts of Lecture 4's tool definition.

An MCP tool definition can carry more fields than the host passes to the model: a display title, an output schema for the result's data, annotations that hint at the tool's side effects, icons, and a `_meta` field for further metadata (Section 2). The answer to `tools/list` also carries `ttlMs`, the time in milliseconds for which the client may cache the list [32].

MCP messages travel both before and after the call to the model API. Before the call, the client lists the server's tools. After the model has replied, the client sends the tool call to the server and receives the result. Native tool calling covers the call to the model API itself. The two standards therefore work together: each covers its own hop, and an application uses both. A server written once can serve a model from any vendor, because the host translates its definitions into the format that the vendor's API expects.

1.9 The path of one tool call

Figure 3 follows one call of `edit` from the first listing of tools to the model's next input. It draws a vertical line, called a lifeline, for each party: the model API, the host, the client and the edit server. Time runs downward, and each arrow is a message between two parties. The call takes these steps:

1. **List.** The client sends `tools/list`, and the server returns its tool definitions.
2. **Ask the model.** The host sends the model API the conversation's messages and the native tool definitions.
3. **Receive the call.** The model API returns a tool call in the vendor's format.
4. **Map and approve.** The host maps the call to a server and a tool, and it obtains the user's consent.
5. **Send.** The client sends `tools/call` with the tool's name and arguments.
6. **Validate and run.** The server validates the arguments and then runs `edit`.
7. **Return.** The result travels back through the client to the host, with its content and its `isError` flag, which is true when the tool failed (Section 1.10).
8. **Feed back.** The host adds the result to the messages of the next model call.

The steps belong to different hops. Steps 1, 5 and 7 are MCP messages between the client and the server. Steps 2, 3 and 8 use native tool calling between the host and the model API. Steps 4 and 6 are local work: the host decides whether to send the call, and the server checks the arguments before it runs the tool. The host and its client run in one process, and the server runs in another.

Step 4 is where the user's consent enters the call. Hosts "must obtain explicit user consent before invoking any tool", and there should always be a human in the loop who can deny an invocation [32]. This is the human-in-the-loop pattern of Lecture 2, in which a person approves an action before it takes effect.

User consent is one of MCP's security principles, and MCP itself "cannot enforce these security principles at the protocol level". The `tools/call` request that reaches the server in step 5 carries no record of the user's approval, so the server cannot check whether consent was obtained. Consent is therefore a duty of the host's code. It holds only as long as that code runs as intended, which is the limitation described in Section 1.1.

1.10 Tool results and errors

A tool call under MCP ends either in a result, which reports success or a failure of the tool, or in a JSON-RPC error. Listing 4 shows a `tools/call` request for the off-by-one fix and its successful result. It also shows the result of a second request, which asked to edit a file outside the workspace and is not shown. That result carries ID 3, the ID of the second request, because a response repeats the ID of the request that it answers.

Listing 4: Illustrative `tools/call` request with its successful result, and a tool execution error returned for a second request (ID 3), which is not shown.

```
// request
{"jsonrpc": "2.0", "id": 2, "method": "tools/call",
 "params": {"name": "edit",
            "arguments": {"path": "src/parse.py",
                          "old": "i <= n", "new": "i < n"},
            "_meta": {...}}}

// result: success
{"jsonrpc": "2.0", "id": 2, "result": {
   "resultType": "complete",
   "content": [{"type": "text", "text":
     "{\"path\": \"src/parse.py\", \"replaced\": 1}"}],
   "structuredContent": {"path": "src/parse.py",
                         "replaced": 1},
   "isError": false}}

// result: tool execution error
{"jsonrpc": "2.0", "id": 3, "result": {
   "resultType": "complete",
   "content": [{"type": "text", "text":
     "refused: ../config.yaml is outside the workspace"}],
   "isError": true}}
```

The request names the method `tools/call`, carries the request ID 2, and gives the tool's name and its arguments as parameters. Every request also carries a `_meta` field with the protocol version and the client's capabilities, shortened here. Section 2 explains why it is needed.

A **tool result** is the result of a `tools/call` request [32]. It has the following fields:




Figure 3: The path of one MCP tool call, with steps numbered as in the text. Steps 2, 3 and 8 use the model vendor's native format, and steps 1, 5 and 7 are MCP messages. The host and its client run in one process, and the server runs in another.

- **`content`.** A list of content items, here one item of text, that reports the outcome.
- **`structuredContent`.** An optional JSON value that gives the result as data. A tool that returns **structured content** should also return the same JSON as text in `content`. This is why the success result carries the path and the count twice.
- **`isError`.** A flag that is true when the tool failed.

Every result also carries `resultType`. The value `complete` means that the request has finished. The value `input_required` means that the server needs more input first (Table 3).

MCP reports failures on two separate channels:

- **Tool execution error.** A **tool execution error** is a failure reported as a normal result with `isError` set to true. It covers failures of an API that the tool calls, input validation errors such as a missing or ill-typed argument, and refusals by the tool's own logic. The second result in Listing 4 is one: the server refuses a path outside its workspace. Clients should pass tool execution errors to the model, so that it can correct its request.
- **Protocol error.** A **protocol error** is a failure of the request itself, such as a call to an unknown tool or a request that does not fit the format of a `tools/call` request. It is reported as a JSON-RPC error: in place of a result, the response carries an error object with a numeric code and a message. Clients may pass protocol errors to the model, but the model is less likely to recover from them.

MCP's tool execution error covers two outcomes that Lecture 4 kept apart. One is the refusal, in which the dispatcher declines to run a request. The other is the tool error, a failure inside the tool function after it was called. Under MCP, both take the same form, a result with `isError` set to true, which the model can read. The refusal in Listing 4 mirrors the dispatcher's refusal of a path outside the workspace in Lecture 4.

1.11 Who performs each operation

Under MCP, the operations of a tool call are divided among the host, the client and the server. Lecture 4 divided the handling of a call into five operations: find the tool by its name, bind the arguments, check policy, run the tool, and observe the result. The harness performed all of them except running the tool, and the tool function ran inside the harness's own process when the dispatcher called it. Table 4 assigns each operation to the three parties of MCP.

The cells of the table keep the verbs of the MCP specification. A "must" in a server cell is a requirement of the specification, and a "should" in a client cell is a recommendation [32]. The host's "must" states user consent, one of MCP's security principles, which the protocol itself cannot enforce (Section 1.9). The rows read as follows:

- **Find.** The server advertises its tools, the client fetches the list and may cache it, and the host decides which of the listed tools the model will see.
- **Bind.** The host matches the model's call to a server and a tool, and the client sends it. The server must validate every input, whatever the host has checked before.
- **Check.** The host must obtain the user's consent. The client should set a timeout, a limit on how long it waits for a reply. The server must implement access controls, which decide which callers may do what, and rate limits, which cap the number of calls accepted in a period.
- **Run.** Only the server runs the tool. Neither the host nor the client executes it.
- **Observe.** The server must sanitize its outputs, removing or neutralizing content that the receiver should not process. The client should validate results and pass tool execution errors to the model. The host decides what enters the model's context.

Policy is checked twice, once by the host and once by the server, and the two do not trust each other. The server cannot see the conversation, and the request carries no proof that the user consented, so the server cannot rely on the host's check. The host cannot see inside the server, so it cannot rely on the server's check. Each side therefore enforces its own rules. The illustrative edit server refuses a path outside its workspace even when the host has approved the call. The host asks the user before it sends a call, even to a server that validates its inputs.

The host's check is code in the host's process, which is the agent's own process, so it has the limitation described at the start of this

Table 4: Lecture 4's five operations under MCP, with the part that the host, the client and the server each perform.

Operation	Host	Client	Server
Find	The host chooses which listed tools the model sees.	The client sends `tools/list` and may cache the list for `ttlMs`.	The server advertises its tools.
Bind	The host maps the model's call to a server and a tool.	The client sends the call as a `tools/call` request.	The server must validate all tool inputs.
Check	The host must obtain the user's consent before invoking any tool.	The client should set timeouts for tool calls.	The server must implement access controls and rate limits.
Run	The host does not run the tool.	The client does not run the tool.	The server executes the tool.
Observe	The host decides what enters the model's context.	The client should validate results and pass tool execution errors to the model.	The server must sanitize tool outputs.

section (Section 1.1). The server's check runs inside a program that the host cannot inspect, so the host must trust the server to perform it. The rest of this lecture shows how attackers exploit both: through tools whose definitions or code are poisoned (Section 5) and through settings that an attacker can reach (Section 7).

Key points

- A rule enforced inside the agent's own process can be disabled or bypassed, because the agent's code, the dispatcher's code and every check between them share one process and its permissions.
- MCP is an open standard that connects AI applications to external systems through one shared protocol, so N applications and M tools need $N+M$ integrations rather than $N \times M$.
- An MCP server is a separate program, written once by a tool's owner, that offers tools, resources and MCP prompts, declares them as capabilities, and exchanges JSON-RPC messages with its client over stdio or Streamable HTTP.
- The host is the application the user runs: it creates one client per server, keeps the conversation, enforces policy and obtains the user's consent, while each server sees neither the whole conversation nor the other servers.
- Only the hop between client and server uses MCP: the host converts each MCP tool definition into a native tool definition, and the model receives only its name, description and input schema.
- A failure of the tool, including a refusal or an invalid argument, returns as a result with `isError` true that the model should see, and an unknown tool or a malformed request returns as a JSON-RPC protocol error.
- Only the server runs the tool, and policy is checked by both the host and the server, because the `tools/call` request carries no record of the user's consent and the host cannot see inside the server.

2 MCP tool definitions, enforcement and transports

Section 1 followed one tool call from the user to an MCP server and back. This section reads the tool definition that a server publishes and asks which parts of Lecture 4's tool contract MCP enforces and which it leaves to trust. The distinction matters because a hostile server can falsify any part that rests on trust (Section 5). The section then follows the messages over stdio and Streamable HTTP and asks what happens when a reply never arrives, the failure that Lecture 4 studied as a retried request.

2.1 The SDK generates the tool definition

A server's author writes an ordinary typed Python function, and the official Python SDK, the library introduced in Section 1, generates the whole MCP tool definition from it [30]. The course's `edit` tool replaces one exact occurrence of the text `old` with the text `new` in the file at `path`. It refuses the call when `old` does not appear exactly once.

Listing 5 shows `edit` from the edit server of Section 1. In Section 1, the SDK's tool decorator took no arguments. In Listing 5, it receives arguments that set the tool's name, title, description and annotations, and one that requires an output schema.

Listing 5: Illustrative server code: the `edit` tool with explicit arguments to the SDK's tool decorator.

```
mcp = MCPServer("workspace")

class EditResult(TypedDict):
    path: str
    replaced: int

@mcp.tool(
    name="edit",
    title="Edit a workspace file",
    description="Replace one exact occurrence "
                "of old with new.",
    annotations=ToolAnnotations(
        read_only_hint=False, destructive_hint=True,
        idempotent_hint=False, open_world_hint=False),
    structured_output=True,
)
def edit(path: str, old: str, new: str) -> EditResult:
    """Replace one exact occurrence of old with new."""
    ...
```

The object `mcp` is the server, and its `tool` decorator registers the function below it as a tool. The body of the function, left out of the listing, performs the edit. The SDK reads each part of the definition from a part of this code:

- **Name, title and description.** The decorator's `name`, `title` and `description` set them. When the name or the description is omitted, the SDK takes the name from the function's name and the description from its docstring.
- **Input schema.** The SDK builds the input schema from the type hints of the parameters. Each parameter becomes a property with its type, and a parameter without a default value becomes a required property.
- **Output schema.** An **output schema** is a JSON Schema that the tool's structured content (`structuredContent`, Section 1) must match. The SDK builds it from the function's return type. For `edit`, the return type is `EditResult`, a typed dictionary with a string `path` and an integer `replaced`, so the output schema describes an object with those two fields. A typed dictionary, a Pydantic model or a dataclass becomes an object schema in this way. A scalar type such as `int`, or a list, is wrapped in an object with a single field, `result`.
- **Annotations.** The `ToolAnnotations` object carries the **tool annotations**, four optional true-or-false hints about the tool's side effects, which Section 2.3 defines one by one. Python spells their names in snake case (`read_only_hint`), and the definition sent to clients spells them in camel case (`readOnlyHint`).

The output schema is optional. With `structured_output=True`, as here, the SDK reports an error when it registers a tool whose return type yields no schema. With `structured_output=False`, it publishes no output schema.

Listing 6 shows the definition that the server returns when a client sends `tools/list`. The server's author wrote none of this JSON. The decorator can also attach display icons and a `_meta` object of further metadata, which both listings leave out.

Listing 6: The tool definition that the SDK generates from the code of Listing 5, abridged by leaving out the titles that the SDK adds to each schema and to every property.

```
{
  "name": "edit",
  "title": "Edit a workspace file",
  "description":
    "Replace one exact occurrence of old with new.",
  "inputSchema": {
    "type": "object",
    "properties": {"path": {"type": "string"},
                   "old":  {"type": "string"},
                   "new":  {"type": "string"}},
    "required": ["path", "old", "new"]},
  "outputSchema": {
    "type": "object",
    "properties": {"path": {"type": "string"},
                   "replaced": {"type": "integer"}},
    "required": ["path", "replaced"]},
  "annotations": {
    "readOnlyHint": false, "destructiveHint": true,
    "idempotentHint": false, "openWorldHint": false}
}
```

Most fields of the definition carry one of the five parts of the tool contract (Recap of Lecture 4), and the rest serve display:

- **Purpose.** The `title` is a human-readable name for display, and the `description` tells the model what the tool does.
- **Arguments.** The `inputSchema` lists the arguments, their types and which of them are required.
- **Results and errors.** The `outputSchema` describes the structured content of a result. A failure is reported in the result itself through `isError` (Section 1).
- **Side effects.** The `annotations` hold the four side-effect hints.
- **Display and metadata.** The `icons` are images that a client can show in its user interface, and `_meta` holds any further metadata. Neither describes what the tool does when it runs.

The host obtains this definition through `tools/list` and only reads it. Nothing in the definition lets the host check that the code behind it does what the definition says. The host also passes on only part of it. The model receives the name, the description and the input schema, converted into a native tool definition (Section 1). The title, the output schema, the annotations, the icons and `_meta` stay with the host.

2.2 Which parts of the contract MCP enforces

MCP gives an enforcer only to the shapes of a tool's arguments and results. Table 5 places each of the five parts of the tool contract next to the MCP field that carries it and the party that the specification makes responsible for it [32]. The rows for purpose and for side effects name no enforcer, and the row for execution constraints names no field.

Table 5: The parts of a tool contract, the MCP fields that carry them, and who enforces each part. Only the input schema and the output schema have an enforcer.

Contract part	MCP field	Who enforces it
Purpose	`description`, `title`	No one. The model reads it.
Arguments	`inputSchema`	The server, which must validate all tool inputs.
Results and errors	`outputSchema`, `content`, `structuredContent`, `isError`	The server must return structured content that conforms to the output schema, and the client should validate it. No one checks meaning.
Side effects	`annotations`	No one. They are hints, untrusted unless the server is trusted.
Execution constraints	No field	The code of the host and the server.

Each row has the following meaning:

- **Purpose.** The description is text that the model reads when it chooses a tool. No party checks that it is true, and the host forwards it as the server's author wrote it.
- **Arguments.** The server must validate all tool inputs, whose shape the input schema describes. A call with a missing or ill-typed argument returns a tool execution error, a result with `isError` set to true (Section 1).
- **Results and errors.** When a tool declares an output schema, the server must return structured content that conforms to it, and the client should validate it. These checks cover only the shape of a result. A result can report one replacement in the correct format even when the tool edited the wrong line, just as Lecture 4 found that a call can match its argument schema and still name the wrong file.
- **Side effects.** The annotations are hints. Clients must treat them as untrusted unless they come from a trusted server.
- **Execution constraints.** The specification has no field for constraints such as timeouts, quotas or confinement to a directory. The code of the host and the server enforces them. In our example, the edit server's own code refuses paths outside its workspace. A client should set its own timeout for each request it sends.

MCP thus divides a tool's contract into checked parts and trusted parts. Code checks the shapes of arguments and results. The description and the annotations are statements by the server's author, which the host must take on trust. Execution constraints hold only where someone wrote code to enforce them, and the definition does not tell the host whether anyone did.

The trusted parts matter because the model reads one of them. A host that connects to a server it does not trust passes the model a description that no one has verified, and the model treats it as an account of the tool. Section 5 studies attacks that place instructions in this text.

2.3 Annotations are hints

Tool annotations describe a tool's side effects, but nothing binds a server to them, so a client may rely on them only when it trusts the server. Each of the four hints has a meaning and a default that applies when the server omits it:

- **`readOnlyHint`.** If true, the tool does not modify its environment. The default is false.
- **`destructiveHint`.** If true, the tool may perform destructive updates. If false, it performs only additive updates. The default is true.
- **`idempotentHint`.** If true, calling the tool repeatedly with the same arguments has no additional effect on its environment. The default is false.
- **`openWorldHint`.** If true, the tool may interact with an open world of external entities. The default is true.

Each default assumes the riskier behavior. A tool that declares nothing is treated as one that may modify its environment, destroy data, repeat its effect when called again, and reach outside systems.

The annotations of Listing 6 fit `edit`. The tool modifies files, so `readOnlyHint` is false. It overwrites text instead of only adding text, so `destructiveHint` is true. It reaches no system outside the workspace, so `openWorldHint` is false.

Because the server's author chooses the hints and nothing checks them, a hint can misdescribe the tool. The same holds for the display `title` that the annotations may also carry.

Definition 2.1 (Tool annotations are hints)**.** "[A]ll properties in `ToolAnnotations` are hints. They are not guaranteed to provide a faithful description of tool behavior (including descriptive properties like `title`). Clients should never make tool use decisions based on `ToolAnnotations` received from untrusted servers." [32]

A tool use decision is any choice a client makes about calling a tool. A host could, for example, ask for the user's consent before every call to a destructive tool but only once for a tool marked read-only. With an untrusted server it should not do so, because a hostile server can mark a destructive tool as read-only.

Even an honest hint can be too coarse. Lecture 4 called a request idempotent when repeating it has the same effect as executing it once. The hint `idempotentHint` is one flag for the whole tool, whereas whether a repeated call has an additional effect can depend on the arguments. Listing 7 shows two pairs of identical calls to `edit` on constructed files. Each file contains the text to be replaced exactly once before the first call of its pair.

Listing 7: Illustrative calls: the same `edit` call made twice, for two sets of arguments.

```
# src/parse.py contains "i <= n" once
edit("src/parse.py", "i <= n", "i < n")
    # changes the file
edit("src/parse.py", "i <= n", "i < n")
    # refused: old no longer appears

# src/limit.py contains "count" once
edit("src/limit.py", "count", "count + 1")
    # changes the file
edit("src/limit.py", "count", "count + 1")
    # changes it again
```

In the first pair, the first call replaces `i <= n` with `i < n`. The repeated call finds no `i <= n` in the file, so `edit` refuses it, and the file does not change again. For these arguments, `edit` behaves idempotently.

In the second pair, the new text `count + 1` contains the old text `count`. After the first call, `count` still appears exactly once, inside `count + 1`. The repeated call therefore succeeds, and the file then contains `count + 1 + 1`. For these arguments, `edit` is not idempotent.

A single flag cannot describe both cases. The server marks `edit` with `idempotentHint` false, which is correct for the tool as a whole. The flag says nothing about whether one particular repeated call is safe, and that is the question a client faces when it sends a request again (Section 2.8).

2.4 Every request stands on its own

MCP is a **stateless protocol**: every request carries everything needed to process it, so a server may not rely on earlier requests.

Definition 2.2 (Stateless protocol)**.** "The Model Context Protocol (MCP) is a stateless protocol: all the information needed to process a request is contained in the request itself. A server processes each request independently; no state should be inferred from previous requests, even those on the same connection or stream." [32]

Every request therefore carries its protocol version and the client's capabilities, the optional features that the client itself supports. Listing 8 shows where they travel: in a `_meta` object inside the parameters of the request, one key for each value. The protocol version and the client capabilities are required on every request. The client's name and version are optional, although clients should send them.

Listing 8: The metadata carried in the parameters of every request, as in the specification's own example.

```
"_meta": {
  "io.modelcontextprotocol/protocolVersion": "2026-07-28",
  "io.modelcontextprotocol/clientCapabilities": {},
  "io.modelcontextprotocol/clientInfo":
     {"name": "ExampleClient", "version": "1.0.0"}
}
```

A server must not use earlier requests on the same connection to learn any of these values. Earlier revisions of MCP exchanged them once, in an opening handshake that started a protocol session, a context on which later requests relied. Revision 2026-07-28 has no handshake and no session. The server accepts or rejects each request on its own, according to the protocol version that the request names. An open connection, such as the standard streams of a server process, may carry unrelated requests one after another, and the server must not treat it as one conversation.

Some tools need state that spans several calls, such as a shopping basket that one call creates and later calls fill. Such state travels as a **handle**: an explicit identifier that one call returns and later calls pass back as an ordinary argument. A call that creates a basket, for example, returns an identifier such as `basket_id`, and each later call that adds an item passes it. The server stores the basket under that identifier and looks it up on each call, so the state lives with the handle. The connection plays no part in it.

Statelessness has a consequence for failures. Because each request is complete in itself, a client can send any request again, to the same server process or to a new one, and the server processes the copy as an independent request. The protocol also gives the server nothing with which to recognize the copy as a repeat (Section 2.8).

2.5 The stdio transport

Over stdio, each message is one line of JSON, and the newline at the end of the line ends the message. As in Section 1, stdio is the transport in which the client starts the server as a subprocess and the two exchange messages over the subprocess's standard input and output. Any transport that sends messages over a stream of bytes needs **framing**, a rule by which the receiver finds where one message ends and the next begins. On stdio, the rule is the newline [32]:

- **Requests.** The client writes each request to the server's standard input as JSON containing no raw newline, followed by one newline.
- **Replies.** The server writes each response to its standard output in the same way, and the client reads one line per message. All replies arrive on this one stream, so the client matches each response to its request by the request ID.
- **Newlines in values.** A line break inside a string value is written as the escape sequence `\n`, a backslash followed by the letter n. The newline after a message is therefore the only raw newline it contains.
- **Logs.** The server may write log messages to its standard error stream. It must not write anything to standard output that is not a valid MCP message.

The rule about logs follows from the framing. The client reads every line on standard output as a message, so a line of debugging out-

put printed there would reach the client as a malformed message.

The framing rule uses only the newline, so it does not depend on the standard streams. The same format works over any reliable two-way stream of bytes, such as a Unix socket or a TCP connection.

2.6 The Streamable HTTP transport

Over Streamable HTTP, every message from the client is a new HTTP POST request to the server's endpoint, the single URL path at which it accepts MCP messages (Section 1). The body of each POST is one JSON-RPC message, and its headers repeat the parts of the message that matter for routing [32]. Listing 9 shows the request line and headers of a `tools/call` request for `edit`.

Listing 9: The request line and headers of a `tools/call` request over Streamable HTTP. The body, not shown, is the JSON-RPC request.

```
POST /mcp HTTP/1.1
Content-Type: application/json
Accept: application/json, text/event-stream
MCP-Protocol-Version: 2026-07-28
Mcp-Method: tools/call
Mcp-Name: edit
```

The headers have the following roles:

- **`Accept`.** The client must list both `application/json` and `text/event-stream`, because the server may answer in either form.
- **`MCP-Protocol-Version`.** Every POST must carry this header, and its value must match the protocol version in the request's `_meta`.
- **`Mcp-Method` and `Mcp-Name`.** `Mcp-Method` repeats the method and is required on all requests. `Mcp-Name` repeats the name of the tool or MCP prompt, or the URI of the resource, and is required on `tools/call`, `resources/read` and `prompts/get`.

The headers repeat what the body already says so that intermediaries such as load balancers can route and inspect a request without parsing its body.

The server answers a request in one of two forms, and the client must support both. It returns either a single JSON object, marked `Content-Type: application/json`, or a stream of **server-sent events** (SSE), an HTTP response that stays open and delivers a sequence of events, marked `Content-Type: text/event-stream` (Section 2.7). A reply as one JSON object is the JSON-RPC response itself, with the same request ID as the request.

The server must also validate the `Origin` header on every incoming connection. A browser adds this header to many of the requests that a web page sends, including every POST request, and it names the origin of that page: the scheme, host and port of its address. The check prevents DNS rebinding, an attack through which a public web page reaches a server running on the user's own machine. Section 3 studies a local component that lacked such checks.

2.7 Progress and cancellation over server-sent events

When the server answers with a stream of events, it can report progress before it sends the result. In the replies of the official Python SDK, each SSE event consists of an event line (`event: message`), a data line that carries one JSON-RPC message, and a blank line that ends the event (Listing 10). The specification itself does not require the event line.

Listing 10: The shape of an SSE reply to a `tools/call` request: a progress notification, then the result. The angle brackets stand for the JSON-RPC messages.

```
HTTP/1.1 200 OK
Content-Type: text/event-stream

event: message
data: <notifications/progress message>

event: message
data: <JSON-RPC response with id 2>
```

A **progress notification** is a notification, sent on the stream before the result, that reports how far the work on a request has come. A client asks for such reports by placing a **progress token** in the request's `_meta`. The token is an identifier that each progress notification repeats, so that the client knows which request a report describes. In Listing 10, the first event carries a progress notification and the second carries the result.

The specification sets the following rules for such a stream [32]:

- **Related notifications only.** The server may send notifications before the final response, and they must relate to the request that opened the stream.
- **No requests.** The server must not send requests of its own on the stream.
- **End of the stream.** The final response should end the stream.
- **Closing means cancelling.** If the stream closes before the final response, the server must treat the closing as cancellation of the request.

Cancellation means abandoning a request before its result arrives. On Streamable HTTP, a client cancels a request by closing the request's stream, and the server should then stop the work. The server treats a closed stream as cancellation whether the client closed it on purpose or the connection broke. In either case, the server may already have finished the work. On stdio, which has no stream per request, the client instead sends a `notifications/cancelled` notification that names the request's ID.

2.8 A broken stream forces a new request

A response stream that breaks before the result arrives loses the request, and the client must send it again: "A broken response stream loses the in-flight request; clients MUST re-issue it as a new request with a new request ID" [32]. An in-flight request is one that has been sent and not yet answered. Because every request is self-contained (Section 2.4), the client can send it again in full.

Streams cannot be resumed, and the server does not redeliver a result once the stream that should have carried it is gone. On stdio, the same loss happens when the server process exits unexpectedly. The requests in flight are lost, and the client can send them again to a new server process.

The protocol's own repeats of a request also use new IDs. When a server needs more input before it can finish, it answers with an `input_required` result (Section 1). The client then sends the original request again with the answer added, and the request ID of the repeat must differ from that of the first request. Every repeat of a request, whether the protocol's own or one after a broken stream, therefore carries a new ID. The ID cannot tell the server that two requests ask for the same operation.

MCP also lacks the means by which a server could recognize a repeat or bound the work it does:

- **No idempotency key.** Lecture 4 defined an idempotency key as an identifier that a request carries so that the receiver can detect a duplicate and decline to repeat its effect. MCP defines no such field for `tools/call`. The only related field is




Figure 4: A broken response stream and the request sent again. The first call appends a line, its response stream breaks, and the client re-issues the call with a new request ID, so the server appends the line a second time. The tool `append_line` is illustrative.

`idempotentHint`, which is untrusted and covers the whole tool (Section 2.3).

- **No deduplication.** The server is not required to detect that two requests ask for the same operation.
- **No deadline.** A **deadline** is a time limit carried in the request, after which the work is no longer wanted. MCP requests carry none. The specification asks implementations to set timeouts for all the requests they send, so each side keeps its own timeout. A server therefore learns that a client has stopped waiting only if the client cancels the request, and it may finish work after the client has given up.

The request ID therefore cannot serve as an idempotency key. An ID only has to differ from the IDs of the sender's other requests that are still awaiting a reply.

Figure 4 shows what follows for a tool that is not idempotent. The illustrative tool `append_line` adds one line to a file. The client calls it with request ID 7, and the server appends the line. The response stream breaks before the result reaches the client. The client cannot tell whether the line was appended, and the rule requires it to re-issue the call with a new ID, 8. The server sees an ordinary new request and appends the line a second time.

This is the failure that Lecture 4 studied as a retried request. There, the request with ID 7 applied a patch, its reply was lost, and the retry with ID 8 applied the patch again. Lecture 4 named the mechanism that prevents the second effect, the idempotency key. Under MCP, a tool that needs one can declare it as an ordinary argument in its input schema, so the protection is left to each tool's designer.

The protocol thus tells the client to send the request again and gives the server no way to recognize the repeat. MCP therefore does not provide exactly-once semantics, in Lecture 4's sense of a side effect that occurs once despite lost requests, lost replies or duplicate delivery.

2.9 Who validates arguments and who resends a request

The server must validate a tool's arguments, and the client must resend a request after a broken stream. The reasons are as follows:

- **Validating arguments.** The server must validate all tool inputs [32]. The host may check the arguments too, but the server cannot rely on that check, because the host and the server do not trust each other (Section 1). The specification asks the client to validate the results that come back.
- **Resending after a broken stream.** The client re-issues the request with a new request ID. The server cannot redeliver the result, because streams cannot be resumed. The resend happens entirely in the client, without the model.

Key points

- The official Python SDK generates an MCP tool definition from a typed function: the input schema from the parameter type hints, the output schema from the return type, and, unless the decorator sets them, the name from the function's name and the description from its docstring.
- In MCP, only the shapes of a tool's arguments and results have an enforcer: the server must validate all tool inputs and, when the tool declares an output schema, return structured content that matches it, which the client should validate.
- The description and the tool annotations have no enforcer and rest on trust in the server, and MCP has no field for execution constraints, which exist only in the code of the host and the server.
- Tool annotations are hints that a client must treat as untrusted unless the server is trusted, and `idempotentHint` is one flag for the whole tool although idempotency can depend on the arguments.
- MCP is stateless: every request carries its protocol version and client capabilities, a server may not rely on earlier requests on a connection, and state that spans calls travels as an explicit handle in the tool arguments.
- On stdio a newline ends each message, and on Streamable HTTP each message from the client is a new POST to one endpoint, whose server must validate the Origin header and may answer with an SSE stream that carries progress notifications and whose closing cancels the request.
- When a response stream breaks, the client must re-issue the request with a new request ID, and because MCP has no idempotency key, deduplication or deadline, the server cannot recognize the repeat, so a tool that is not idempotent can apply its effect twice.

3 The MCP Inspector and its published vulnerability

The previous section established which parts of an MCP tool definition have an enforcer and which rest on trust, and that no deadline travels with a request (Section 2). This section examines these findings through the MCP Inspector, the tool that developers use to test MCP servers, and asks what such a test can and cannot show. The question matters because the Inspector receives exactly what any host receives, so its limits are the limits of every host. We then study a published vulnerability in the Inspector itself, which shows that a component that starts processes on request must check who sends the request.

3.1 A host with no model

The **MCP Inspector** is the MCP project's reference tool for testing and debugging MCP servers, and in MCP's terms it is a host with no model [28]. A developer connects it to a server, reads the server's tool definitions and calls its tools by hand. The same package also offers a command-line mode and a terminal mode, which work without a browser.

The Inspector consists of a web client and a proxy. The **web client** is a page in the developer's browser, on which the developer reads tool definitions, fills in arguments and reads results. The **proxy** is the Inspector's local program on the developer's machine, and it holds every connection to the servers. It also starts, as a subprocess, each server that uses the stdio transport (Section 1.5).

The web client sends its requests to the proxy, and the proxy forwards them to the server. A page in a browser cannot start a process on its machine, so the proxy does this on the page's behalf.

In current versions, the proxy accepts connections only from the developer's own machine. When it starts, it generates a **session token**, a secret that the proxy requires on every request to its API. Version 0.14.1 added these protections to close the vulnerability described in Section 3.4.

As a host (Section 1), the Inspector creates one client for each server it connects to, and that client sends the same `tools/list` and `tools/call` requests as the client of any other host. The Inspector differs from other hosts in that its user works in a browser and it has no model. A person chooses each call and types its arguments, where another host would pass on the model's tool call.

The Inspector displays the full tool list that a host receives, with every field of each tool definition. This is more than a model sees, because a host passes the model only the name, the description and the input schema of each tool (Section 1.8).

Because the messages are the same, testing a server in the Inspector shows exactly what the server sends to any host. Since no model takes part, each result reflects the server alone.

3.2 Errors and timeouts in the Inspector

Connected to a real server, the Inspector makes several properties of MCP directly visible. The server here is the edit server of Section 1, which serves the `edit` tool of our running agent, `mini-swe-agent`, from a separate process. Calls to it show the following:

- **A successful call.** A call with valid arguments returns a result with `isError` false, its content and its structured content. The Inspector also displays the request and the response as raw JSON-RPC messages, so the developer sees exactly what crossed the connection.
- **A tool execution error.** A call whose `old` argument does not occur in the file returns a result with `isError` true and the server's reason. This is the tool execution error of Section 1, the failure channel that a host passes to the model so that the model can correct its next call.
- **A failed validation.** A call with a required argument missing also returns `isError` true, with the validation message. The failure travels on the same channel, because MCP classifies input validation errors as tool execution errors (Section 1). The server performed the check, as MCP requires every server to validate all tool inputs (Section 2).
- **A timeout.** A call to a tool whose code runs longer than the Inspector's request timeout makes the Inspector report a timeout. The server finishes the call anyway.

MCP's other failure channel, the protocol error, did not appear in these calls. A protocol error is a JSON-RPC error that the client's code receives in place of a result, for example when a request names a tool that does not exist (Section 1). The timeout belongs to neither channel. The client stopped waiting before any response arrived.

The timeout shows that no deadline travels with an MCP request. Each side sets its own timeout, and the request carries no time limit that the server could read (Section 2). The specification asks a client whose timeout expires to cancel the request and stop waiting for a response. It asks a server that receives a cancellation to stop processing the request, and it states both as recommendations [32]. The protocol has no means to force the tool's code to stop. A tool that ignores cancellation, such as one blocked in a long synchronous computation, therefore runs to the end.

A timeout thus tells the client only that it stopped waiting. It does not tell the client whether the tool acted. For `edit`, the patch may be applied after the client has given up on the call. The client is then in the position of the lost reply studied in Lecture 4: the outcome of the call is unknown, and sending the call again repeats its effect when the tool is not idempotent (Section 2).

3.3 What the Inspector cannot show

The Inspector displays a tool's definition and the results of its calls. What the tool does while it runs lies outside its view. The following changes to the edit server show this limit:

- **A poisoned description.** Suppose an attacker adds one sentence to the description of `edit`, telling the model to read the user's private key before editing and to include its contents in the patch. The Inspector displays the new sentence verbatim and flags nothing.
- **A changed implementation.** Suppose instead that an attacker leaves the description as it was and changes the tool's code to write outside the workspace. Nothing that the Inspector displays changes.

A description is free text that a host passes to the model in full, as part of the tool definition (Section 1). An instruction placed in a description therefore reaches the model before any call is made. The Inspector shows the developer the same text that the model would receive. It does not judge whether that text describes the tool or instructs the model. The protocol gives it no basis for such a judgment, because no party checks a description (Section 2).

A change to the implementation leaves no trace in what a host receives. The tool definition is the server's own statement about the tool, and the server sends the same definition whatever its code does. The only evidence of the change is the tool's effect, here a file written outside the workspace, and that effect happens on the server's side of the connection.


Both changes are forms of tool poisoning, the addition of malicious content or behavior to a tool (Section 5). The first poisons the tool's definition, and the second poisons its implementation.

These limits apply to every host, because every host receives the same messages as the Inspector. A test in the Inspector shows what a server declares and what it returns. It does not show what the server does. A server that passes such a test may still read or write anything that its own rights allow.


3.4 A vulnerability in the Inspector's proxy

In June 2025, a critical vulnerability in the Inspector itself was disclosed. Versions of the Inspector before 0.14.1 had no authentication between the web client and the proxy, so the proxy accepted requests from anyone who could reach it [5]. The proxy starts processes on request. An unauthenticated request could therefore make it start a command of the requester's choice on the developer's machine.

The vulnerability is identified as CVE-2025-49596. A **CVE** (Common Vulnerabilities and Exposures) identifier names one



(a) Before version 0.14.1. A malicious page in the developer's browser sends a cross-site request to the proxy, which checks nothing and starts the command that the page names.



(b) From version 0.14.1. The proxy checks the session token and the origin of each request and refuses the same request, and the binding to localhost keeps other machines on the network out.

Figure 5: The Inspector vulnerability CVE-2025-49596 on the developer's machine, before and after the fix. Magenta marks the attack, from the adversary's page to the command it starts, and the numbered circles give the order of its steps.

reported vulnerability in one product, so that advisories, scanners and patches can refer to the same flaw. A **CVSS score** rates the severity of a vulnerability from 0 to 10 under the Common Vulnerability Scoring System. The advisory for this flaw gives it 9.4 under version 4.0 of the system, a score that counts as critical. The advisory credits a researcher at the security company Tenable, and Oligo Security, another security company, published an analysis of the exploit [13].

The **CWE** (Common Weakness Enumeration) is a catalog of classes of weakness, each describing a kind of mistake that many products can make. A CVE names one instance of such a mistake in one product. The Inspector flaw belongs to the class CWE-306, Missing Authentication for Critical Function, which the catalog defines as follows.

> **Definition 3.1** (Missing Authentication for Critical Function, CWE-306)**.** "The product does not perform any authentication for functionality that requires a provable user identity or consumes a significant amount of resources." [18]

Starting a process is functionality of this kind, because whoever can invoke it can run code. The result is **remote code execution**: an attacker runs commands of their choice on another person's machine.

The attack required nothing from the developer except a visit to a web page. Figure 5a shows the developer's machine during the attack, with the browser's two tabs on the left, the proxy in the middle and the MCP server on the right. The numbered circles trace the attack from the malicious page to the command that it starts.

The attack began with the developer running the Inspector: the web client talked to the proxy, and the proxy started the MCP server over stdio. In the vulnerable versions, the proxy listened on 0.0.0.0 and asked for no authentication. A program that listens on 0.0.0.0 accepts connections on every network interface of the machine, so other machines on the same network can connect to it as well.

A public page could reach the proxy through the developer's browser. A **cross-site request** is a request that a page sends to a site other than its own. Browsers send such requests, because pages routinely load images from other sites and submit forms to them.

The browser lets the sending page read the response only when the receiving server allows it. An ordinary request, such as a GET request for an image, still arrives at the receiver and is processed. The attack needed no response, because starting the command was its whole effect.

The page addressed its request to 0.0.0.0. The browser delivered it to the developer's own machine because of the **0.0.0.0-day**, a browser flaw that let public web pages reach services on the visitor's machine by sending requests to the address 0.0.0.0. This use of the address is separate from the proxy's listening on 0.0.0.0, which exposed the proxy to other machines on the network.

A second route to the same proxy was **DNS rebinding**. In DNS rebinding, the attacker's domain name first resolves to the attacker's server, which delivers the page, and then to a local address. The browser still treats the page's later requests as requests to the page's own domain, so it lets them through, and they reach a service on the visitor's machine.

Along the 0.0.0.0 route, the attack proceeded as follows, with its steps numbered as in Figure 5a:

1. **The developer visits a malicious page.** The adversary controls a public web page, and its script runs in the developer's browser, in a tab beside the Inspector.
2. **The page sends a cross-site request to the proxy.** The request names a command for the proxy to start, and the 0.0.0.0 address carries it to the developer's own machine.
3. **The proxy accepts the request.** The proxy checks neither a token nor which page sent the request, so it starts the named command as if it were an MCP server to be run over stdio.
4. **The command runs as the developer.** The command runs with the developer's rights. A visit to one page has given the adversary remote code execution.

3.5 The fix and the trust boundary

Version 0.14.1 closed the vulnerability by making the proxy check who sends each request and by limiting which machines can reach it [28]. Figure 5b shows the same request stopped at the proxy. The protections are the following:

- **Session token.** The proxy requires its session token on every request to its API. The token reaches the developer's own web client through a URL that carries it, which the Inspector prints when it starts. A page from another site does not know the token, so its requests are refused.
- **Origin check.** An origin check examines the Origin header of a request, which names the origin of the page that sent it, the scheme, host and port of its address (Section 2.6). The proxy rejects a request whose Origin header names a page other than the Inspector's web client. The browser sets this header itself, and a script on the page cannot change it.
- **Binding to localhost.** The proxy listens only on localhost, the address through which a machine reaches its own services. Other machines on the network can no longer connect to it.

These protections close different routes. The session token stops the malicious page, because the page does not know it, and the origin check rejects any request whose Origin header names another site. Binding to localhost cannot stop the page, because the developer's browser runs on the developer's own machine. The 0.0.0.0 route worked even against a service that listened only on localhost [13], and DNS rebinding sends the page's requests to a local address by design.

Binding to localhost stops every other machine on the network. In the vulnerable versions, any such machine could have sent the same request directly, with no browser involved.

The MCP specification asks for similar protections in a server that uses Streamable HTTP. Such a server must validate the Origin header of every incoming connection to prevent DNS rebinding (Section 2), should bind only to localhost when it runs locally, and should authenticate all connections [32]. The Inspector's proxy offers no tools of its own. It accepts MCP messages from the web client over the same HTTP transports as a server, so it can be attacked in the same way, from pages in the developer's browser.

A similar flaw was later found in another product. MCPJam, a third-party inspector for MCP servers, listened on 0.0.0.0 by default, and a request to its server could make it start a command with no check of the caller. The flaw was assigned CVE-2026-23744, with a CVSS 3.1 score of 9.8 [33]. Because the server listened on every interface, an attacker on the network could reach it with a single HTTP request, without a browser.

Both flaws come from one missing check. A component that runs commands on request must check who sends the request. The same rule applies to an MCP server, which must check every call it receives even when the host has already checked it (Section 1). When the check is missing, anyone who can send the request can run code.

A **trust boundary** is the line between components that do not trust each other, at which every request must be checked. Every trust boundary is a boundary in the sense of Lecture 4, an interface that a request and its reply cross. A boundary is a trust boundary only when the components on its two sides do not trust each other.

The Inspector's proxy sits on a trust boundary. On one side are the pages open in the developer's browser, which may come from any site. On the other side are the developer's files and processes, which any process that the proxy starts can reach with the developer's rights. The vulnerable versions treated every request as if it came from the Inspector's own web client.

The debugging tool is therefore a host with a trust boundary of its own, and that boundary needs the same checks as any other. The Inspector flaw also illustrates the difference between a class of weakness, a reported vulnerability and an attacker's use of it (Section 4), and a missing origin check recurs in the attacks on OpenClaw (Section 7).

Key points

- The MCP Inspector is a host with no model: its client sends the same `tools/list` and `tools/call` requests as the client of any other host, and a person chooses each call.
- A call that the tool refuses, or whose arguments fail the server's validation, comes back in the Inspector as a result with `isError` true and the server's reason, which is the tool execution error that a host passes to the model.
- No deadline travels with an MCP request, so a client's timeout only ends its wait, and a tool that ignores cancellation may finish its work after the client has given up, which leaves the outcome of the call unknown.
- Like every host, the Inspector receives only a tool's definition and its results, so it shows a poisoned description without warning and cannot reveal a changed implementation.
- Before version 0.14.1, the Inspector's proxy required no authentication, so a cross-site request from a malicious page could make it run a command as the developer (CVE-2025-49596, weakness class CWE-306).
- The fix added a session token and an origin check, which stop requests from other sites' pages, and bound the proxy to localhost in place of every network interface, which stops requests from other machines.
- A component that runs commands on request, including a debugging tool such as the Inspector, sits on a trust boundary and must check who sends each request.

4 Threat catalogs: the OWASP MCP Top 10 and MITRE ATLAS

The flaw in the MCP Inspector (Section 3) let a web page run commands on a developer's machine because one component did not check its caller. This section first defines the terms that separate such a defect from an adversary's use of it. It then

Table 6: The terms for a flaw and its use, each with the catalog that records it and its instance in the MCP Inspector flaw. Smell, fault, weakness and vulnerability describe the defect, and threat describes the adversary's action.

Term	Meaning	Catalog	In the Inspector flaw
Smell	A symptom of weak design	None	A local proxy accepted a connection from any caller.
Fault	A defect that produces wrong behavior at run time	None	The proxy launched a server process for an unauthenticated request.
Weakness	A class of fault	CWE	CWE-306, missing authentication for a critical function.
Vulnerability	A reported instance in a product	CVE	CVE-2025-49596 in the MCP Inspector.
Threat	The action an adversary takes with it	ATLAS	A web page the developer visited could launch commands on the developer's machine.

introduces two public catalogs: the OWASP MCP Top 10, which lists the risks of MCP deployments so that an engineer can audit a deployment part by part, and MITRE ATLAS, which records the techniques that adversaries use against AI systems. The next two sections (Sections 5 and 6) are organized by ATLAS's techniques and mitigations, so its terms are needed to read them.

4.1 From a design smell to a threat

The terms smell, fault, weakness and vulnerability describe a defect in a design, and the term threat describes what an adversary does with such a defect. We define each term and illustrate it with the Inspector flaw of Section 3. In that flaw, the proxy, the Inspector's local process that starts MCP servers for its web client, accepted requests from any caller.

- **Smell.** A smell is a symptom of weak design: a property that makes a defect likely without being a defect itself. In the Inspector, a local proxy accepted a connection from any caller. Accepting a connection does no harm by itself, but it lets any caller reach the functions behind it.
- **Fault.** A fault is a defect that produces wrong behavior at run time. The proxy launched a server process, that is, ran a command, for a request that carried no authentication. This behavior is the defect, because a request from an unknown caller starts a program on the developer's machine.
- **Weakness.** A weakness is a class of fault: a kind of mistake that many products can make. CWE, the catalog of weakness classes, lists this one as CWE-306, Missing Authentication for Critical Function [18].
- **Vulnerability.** A vulnerability is a reported instance of a weakness in a particular product. A CVE identifier names one reported vulnerability, and this one is CVE-2025-49596 in the MCP Inspector. Its advisory rates its severity at 9.4 on the 0 to 10 CVSS 4.0 scale [5].
- **Threat.** A threat is the action an adversary takes with a vulnerability. In the Inspector flaw, a web page that the developer visited could launch commands on the developer's machine, as Oligo Security demonstrated [13]. MITRE ATLAS, a catalog of the methods that adversaries use against AI systems (Section 4.5), describes actions of this kind.

Table 6 sets the terms side by side, with the catalog that records each one. Its last column, read from top to bottom, follows the Inspector flaw from a proxy that trusted any caller to a web page that could launch commands on the developer's machine.

Each term calls for a different response. A smell is removed by changing the design. A fault is removed by correcting the code that misbehaves. A weakness class tells reviewers what to look for in any product. A vulnerability is fixed by releasing a corrected version, as version 0.14.1 of the Inspector did. A threat is countered by mitigations that stop or expose the adversary's action (Section 6). We use the word threat only in this sense, for an adversary's action.

The same terms apply to our own harness. The guarantees table of Lecture 4 (Table 1) records, for each guarantee of `mini-swe-agent`, the component that enforces it, and it leaves reads unenforced. A defender reads that table to find what is not yet enforced, and an attacker reads the same rows as openings. Each unenforced row marks a fault in our harness. For example, `search` can read files outside the workspace at run time, because it skips the path check. If such a fault were found in a released product and reported, it would be a vulnerability, and an adversary who used it would carry out a threat.

4.2 The OWASP MCP Top 10

The **OWASP MCP Top 10** is a list of ten risks of MCP deployments, written so that an engineer can audit a deployment against it. It is published by **OWASP**, the Open Worldwide Application Security Project, a nonprofit community that publishes security guidance. The list is at version 0.1, a beta [38].

The list is young and still changing. Its entries were first written in November 2025 and revised during 2026. Its sixth entry, Intent Flow Subversion, was earlier titled "Prompt Injection via Contextual Payloads", and some project pages still show that title.

Each risk has its own entry, a page that describes the risk and adds a checklist and prevention steps:

- **A "vulnerable if" checklist.** The checklist gives four to twelve conditions under which a deployment is exposed to the risk, such as components installed without any check of where they came from.
- **Prevention steps.** The prevention steps are measures that remove those conditions, such as pinning each component to a known version.

An entry therefore answers a defender's question about a deployment as it is configured: is it open to this risk? An entry does not describe an attack as a sequence of steps.

To read the list against a deployment, we group the risks by the part of the deployment that each one acts on (Figure 6). The grouping is the course's own: OWASP lists its ten risks without any grouping. The parts are those of Section 1. The host holds the model's context and the MCP client, the server runs the tools, and tool definitions and tool results pass between them.

- **Host and model context.** Tool Poisoning, Intent Flow Subversion, and Context Injection & Over-Sharing act on what the model reads: a tool definition, a tool result, and context shared between users or sessions.
- **Server side.** Software Supply Chain Attacks & Dependency Tampering acts on the package registry, a public store from which the server's package is installed and updated, and on the packages it delivers. Command Injection & Execution acts on the server's tool code. Shadow MCP Servers are servers that the organization's security team never reviewed or recorded.
- **Credentials and identity.** Token Mismanagement & Secret Exposure, Privilege Escalation via Scope Creep, and Insufficient Authentication & Authorization act on the tokens and keys that the host and the server use, and on their scopes. A




Figure 6: The ten risks of the OWASP MCP Top 10, each placed by the course on the part of an MCP deployment it acts on. The model box stands for the context that the host assembles for the model. The dashed box stands for a server that the security team never reviewed or recorded.

token's scope is the set of actions that the token permits, and scope creep is the gradual widening of that set.

- **Logging.** Lack of Audit and Telemetry acts on the record of what happened. Without logs, nobody can reconstruct an attack.

The server side includes the path by which a server reaches its users. One such public store is npm, the package registry for JavaScript. A package registry is unrelated to the dispatcher's registry of Lecture 4, which maps tool names to functions. The **software supply chain** of a component is the set of packages, package registries and updates through which the component reaches its users. An MCP server is often installed and updated from a package registry, so the registry and every update it delivers belong to the server's supply chain.

Figure 6 draws one deployment and attaches each risk to the part it acts on. The credentials bar runs under the whole exchange, because both the host and the server hold tokens and keys. The dashed box stands for a server that the security team never reviewed or recorded. No risk is attached to the user or to the MCP client. The risks sit where the model reads, where code runs and comes from, where credentials are held, and where events are recorded.

4.3 Documented cases of the risks

For each risk, we name the best-supported documented public case that we found, read at its primary source, so that the risk is tied to something that happened (Table 7). Lack of Audit and Telemetry is the one risk for which we found no case, as the end of this subsection explains. The table gives each risk with its OWASP identifier, a one-sentence summary of what goes wrong, and the case. The summaries are our own wording.

The cases differ in the kind of evidence they provide, and the kind decides what a case shows.

- **In the wild.** A case in the wild is an attack observed against real users, here a malicious package that users installed. The package postmark-mcp, which copied every email sent through it to its author, is the one case of this kind [4], and Section 4.4 reads it in detail. Such a case shows that adversaries carry out the attack against real users.
- **Vendor advisory.** A vendor advisory is a vendor's published notice of a flaw that it has fixed. Claude Code, Anthropic's coding agent, reads configuration files stored in a project, and a malicious project could make it leak the user's API key (CVE-2026-21852, January 2026) [7]. The same research by Check Point found an earlier flaw, CVE-2025-59536, in which a project's files ran commands before Claude Code asked the user whether to trust the project [14]. The Git MCP server ignored the repository it was configured to stay inside (advisories of December 2025) [6, 10]. The package mcp-remote, which lets hosts connect to remote MCP servers, ran operating-system commands chosen by an attacker when it connected to an untrusted server (CVE-2025-6514, July 2025) [39]. In this case, the commands came from a malicious server rather than from the model. The Inspector flaw of Section 3 is a case of the same kind. An advisory shows that a flaw existed in the named versions and was fixed. It does not show that anyone exploited it.
- **Proof of concept.** A proof of concept is a demonstration, by researchers, that an attack can be carried out. Invariant Labs hid instructions in a tool description and showed that the model followed them [2]. It also showed that a GitHub issue written by an attacker could make an agent leak the contents of private repositories [17]. Such a case shows that the attack works under the researchers' conditions.
- **Vendor scan.** A vendor scan is a measurement, by a security company, of many deployments at once. Knostic found 1,862 MCP servers open to the internet. It checked a sample of 119 by hand, and every one of them listed its tools to a caller that gave no credentials [8]. A scan measures exposure. It cannot tell whether the organization that runs a server had reviewed and recorded it, and only a server that was never reviewed or recorded is a shadow server.
- **Vendor bug.** A vendor bug is a flaw that the vendor itself found and disclosed, with no attack reported. Asana found in June 2025 that its MCP server had exposed one organization's data to another [40]. Such a case shows that the risk occurred, through the vendor's own mistake.

Lack of Audit and Telemetry has no case. For this risk, a short search on October 8, 2026 found guidance and survey statistics. It found no MCP-specific incident. An incident may exist that the search missed.

4.4 One incident read through both catalogs

The two catalogs answer different questions about the same incident. OWASP asks which conditions made a deployment vulnerable, and ATLAS records what the adversary did, step by step. We read the postmark-mcp incident of September 2025 through each.

Postmark is a service that sends email for organizations through an API, and its MCP server lets AI agents send email through it. An adversary impersonated Postmark on npm by publishing

Table 7: The risks of the OWASP MCP Top 10 in OWASP's order, with our summary of each and the documented case we chose for it, where we found one. The summaries and the choice of cases are the course's.

ID	Risk	What goes wrong	Documented case
MCP01	**Token Mismanagement & Secret Exposure**	A token stored in configuration, logs or model memory can be read and reused.	GitHub advisory, January 2026 (research by Check Point): Claude Code project files leaked an API key.
MCP02	**Privilege Escalation via Scope Creep**	An agent's permissions widen over time until one mistaken call can do serious damage.	GitHub advisories, December 2025: the Git MCP server ignored its repository boundary.
MCP03	**Tool Poisoning**	A tool's description hides an instruction, so the model obeys the tool's author.	Invariant Labs, April 2025: hidden instructions in a tool description.
MCP04	**Software Supply Chain Attacks & Dependency Tampering**	A server package the user installed, or later updated, carries the attacker's code.	Koi Security, September 2025: postmark-mcp copied every email to the attacker.
MCP05	**Command Injection & Execution**	A tool passes model-written text to a shell or database without checking it.	JFrog, July 2025: mcp-remote ran attacker commands.
MCP06	**Intent Flow Subversion**	Instructions hidden in a file or tool result redirect the agent's plan.	Invariant Labs, May 2025: a GitHub issue made an agent leak private repositories.
MCP07	**Insufficient Authentication & Authorization**	A server or client accepts any caller without checking identity or permission.	Oligo Security, June 2025: the Inspector proxy accepted unauthenticated requests.
MCP08	**Lack of Audit and Telemetry**	Tool calls and context changes go unrecorded, so nobody can reconstruct an attack.	No MCP-specific incident found.
MCP09	**Shadow MCP Servers**	A team runs an MCP server that the organization's security staff never reviewed or recorded.	Knostic, July 2025: a scan found 1,862 MCP servers open to the internet.
MCP10	**Context Injection & Over-Sharing**	Context shared between users or sessions leaks data or carries injected instructions forward.	BleepingComputer, June 2025: Asana's MCP server exposed one organization's data to another.

a package named postmark-mcp, a name that Postmark had not registered there. The first versions behaved like a legitimate server. Version 1.0.16 added one line of code, which made the adversary's address a blind-copy (BCC) recipient of every email sent through the package's tool [4, 9]. A BCC recipient receives a copy of a message, and the other recipients do not see the address.

In Figure 7, a strip across the top summarizes the incident. Below it, the left half lists the conditions of the deployment that OWASP's entry names, and the right half lists the adversary's steps in order, as ATLAS records them.

The OWASP view. OWASP's entry Software Supply Chain Attacks & Dependency Tampering fits the incident. Its first example scenario, "Trojanized Plugin", reads: "A popular open-source connector gains a malicious update. It silently exfiltrates customer support transcripts to an adversary-controlled endpoint" [38]. We propose that the following items of the entry's checklist applied to the incident:

- **No provenance check.** "The system installs MCP connectors or plugins without signing / provenance checks." Without such a check, nothing verifies that a package comes from the vendor it names.
- **Floating versions.** "Teams use 'latest' or floating version references." A deployment that follows the latest version receives an update such as 1.0.16 without anyone choosing it.
- **No integrity check.** "There is no dependency integrity verification (hash, signature, attestation)." Without it, nothing compares the installed code with a copy known to be good.
- **No sandbox.** "No sandboxing isolates third-party components." Without a sandbox, a package's code runs with whatever access its process has.

OWASP does not mention postmark-mcp, and its own summary of the Tool Poisoning entry lists rug pulls, a legitimate release followed by a malicious update, so the incident could also be filed there. Under either entry, the OWASP view gives an engineer a question to ask of a deployment: are its components signed, pinned to a version and sandboxed?

The ATLAS view. ATLAS records the same incident as a case study, a documented attack mapped to the techniques it used [25]. Each step names the method the adversary used, which ATLAS calls a technique, and the goal the step served, which ATLAS calls a tactic (Section 4.5 defines both terms). A name of the form "technique: sub-technique" names a narrower variant of a technique, which ATLAS calls a sub-technique. The case study lists nine ordered steps:

1. **Impersonation** (Defense Evasion). The adversary published a legitimate version under the name postmark-mcp, so users took the package for Postmark's own.
2. **Develop Capabilities** (Resource Development). The adversary modified the server to add the adversary's address to the BCC line of every email.
3. **Publish Poisoned AI Artifacts: AI Agent Tools** (Resource Development). The adversary published the malicious version to npm.
4. **AI Supply Chain Rug Pull** (Defense Evasion). Because users adopted a legitimate version first, the malicious one avoided the scrutiny that new tools receive.
5. **AI Supply Chain Compromise: AI Agent Tool** (Initial Access). Organizations that upgraded to version 1.0.16 received the malicious version through the package registry.
6. **AI Agent Tool Poisoning: Implementation** (Persistence). The malicious line sat in the tool's code, its implementation, which the model never reads (Section 5). Once configured with an organization's agents, the poisoned server stayed in place.
7. **User Execution: Poisoned AI Agent Tool** (Execution). When users asked their agents to use the server's tools, the malicious code ran.
8. **Exfiltration via AI Agent Tool Invocation** (Exfiltration).




Figure 7: The postmark-mcp incident read through both catalogs: on the left, the OWASP entry that fits and the checklist items that applied, and on the right, the nine steps of the ATLAS case study, each a technique (bold) above its tactic (grey). Where a step is a sub-technique, its box shows only the sub-technique's name, and the text gives the full names. The mapping to the OWASP entry and the ticked items are the course's proposal.

Every email sent through the tool was copied to the adversary.

9. **External Harms** (Impact). The copied emails could reveal private information about the organization's clients, and the list of its clients.

A tactic can serve more than one step: Defense Evasion serves the first and the fourth steps, and Resource Development the second and the third.

The case study limits the loss to users who upgraded to the malicious version and kept using the tool.

The two views compared. Each catalog supplies what the other lacks.

- **OWASP** gives a checklist of vulnerable conditions and steps that prevent them, which an engineer can apply to a deployment before any attack. It orders no steps of an attack, and it rates no evidence: an entry does not say whether its scenarios have been seen in real attacks.
- **ATLAS** records what an adversary did, in order, with the goal of each step, and it types each case study as a real attack or a demonstration. It gives no checklist of vulnerable conditions, and it maps no mitigation to several steps of this incident, among them AI Supply Chain Rug Pull and AI Agent Tool Poisoning (Section 6).

4.5 MITRE ATLAS and its terms

MITRE ATLAS describes each step of an attack on an AI system by its goal and its method. **MITRE ATLAS** (Adversarial Threat Landscape for AI Systems) is MITRE's knowledge base of adversary tactics and techniques against AI-enabled systems [19]. MITRE is a US nonprofit research organization. ATLAS is modeled on **MITRE ATT&CK**, MITRE's knowledge base of the same kind for ordinary computer systems. ATLAS is built from tactics, techniques, sub-techniques, mitigations and case studies:

- **Tactic.** A tactic is the adversary's goal at one stage of an attack, such as getting into the system, avoiding detection or stealing data.
- **Technique.** A technique is a method for reaching a tactic's goal. Exfiltration via AI Agent Tool Invocation, for example, reaches the goal of stealing data by having the agent call a tool that sends the data out.
- **Sub-technique.** A sub-technique refines a technique to a narrower method. AI Agent Tools refines Publish Poisoned AI Artifacts to the case in which the published artifact is a tool for an agent, and ATLAS writes the pair as "Publish Poisoned AI Artifacts: AI Agent Tools".
- **Mitigation.** A mitigation is a countermeasure mapped to the techniques it counters. Section 6 studies the mitigations mapped to the techniques of this lecture.
- **Case study.** A case study, such as the postmark-mcp one of Section 4.4, is a documented attack mapped, step by step, to the techniques it used. ATLAS types each one as an **incident**, a real attack, or an **exercise**, a demonstration by researchers or by testers whom the system's owner authorized to attack it. The postmark-mcp case study is an incident.

ATLAS is updated in numbered releases, and we use release 2026.09, of September 2026. Release 2026.09 holds 120 techniques and 88 sub-techniques, which together we call its 208 entries. The same release holds 16 tactics, 40 mitigations and 73 case studies, of which 23 are incidents and 50 are exercises.

The postmark-mcp case study uses the following tactics:

- **Resource Development.** The adversary builds resources for the attack, such as a modified package.
- **Defense Evasion.** The adversary avoids detection.
- **Initial Access.** The adversary gets into the target system.
- **Persistence.** The adversary keeps its access to the system over time.
- **Execution.** The adversary's code runs.
- **Exfiltration.** The adversary moves data out of the victim's systems.
- **Impact.** The adversary manipulates, interrupts or destroys the victim's systems and data.

ATLAS thus describes an attack by the goal and the method of each step. It connects methods to the countermeasures that address them, where ATLAS records any, and to the incidents and exercises that used them. A defender can therefore move from an observed step to known attacks and, where they exist, to known defenses.




Figure 8: The ATLAS matrix of release 2026.09. Each column is a tactic, in the order of the stages of an attack, and each cell is a technique. Blue cells carry the Agentic AI tag, which the legend reads as applying to agentic systems, and magenta cells are the techniques this lecture follows.

4.6 The ATLAS matrix

The ATLAS matrix arranges the techniques by the goals they serve (Figure 8). The **ATLAS matrix** is a table whose columns are the tactics, ordered as the stages of an attack, and whose cells are the techniques that serve each tactic. In release 2026.09, the matrix has sixteen columns, from Reconnaissance on the left to Impact on the right, and Figure 8 prints them all. Each cell is a technique, and sub-techniques are not drawn.

A technique that serves several tactics appears under each of them. For this reason, the 120 techniques of release 2026.09 fill 131 cells. AI Agent Tool Invocation, a technique that recurs throughout this lecture, sits under three tactics.

> **Definition 4.1** (AI Agent Tool Invocation)**.** "Adversaries may use their access to an AI agent to invoke tools the agent has access to." [19]

AI Agent Tool Invocation is the use of access to an agent to invoke the tools it can reach. It appears under three tactics:

- **Execution.** Invoking a tool runs an action, such as a command or an API call.
- **Privilege Escalation.** An agent may hold tools and permissions that the adversary does not, so acting through the agent gains rights the adversary lacks.
- **Lateral Movement.** The tools connect the agent to other applications and systems, and the adversary reaches those systems through them.

In our running example, an instruction planted in text that `mini-swe-agent` reads could lead the model to call `edit`. This is indirect prompt injection, introduced in Lecture 4: text from a source outside the application's control reaches the model's context as an observation and steers the next action. The adversary would then change code through the agent without holding any right to edit that code. The call serves Execution, because it runs an action, and Privilege Escalation, because it uses a right that the agent holds and the adversary lacks.

The colors of the matrix mark two sets of techniques. Blue cells mark techniques that carry the Agentic AI tag, which means that the platforms field of their ATLAS entry lists Agentic AI (Section 4.7 describes the field). In release 2026.09, 76 techniques carry the tag, and they fill 82 cells. A cell whose technique this lecture follows is drawn in magenta even when the technique carries the tag, so the figure shows 70 blue cells. The matrix draws no sub-techniques. In the same release, another 63 sub-techniques carry the tag, and with them the tag covers the 139 entries that Section 4.7 counts.

Magenta cells mark the techniques that Sections 5 and 6 follow, listed in Table 8 in the order in which an attack uses them. Where the lecture follows a sub-technique, the matrix marks its parent's cell. The lecture follows Agentic Resource Consumption, for example, and the matrix marks the cell of its parent, Cost Harvesting. Escape to Host is the only technique of the set without the Agentic AI tag, because ATLAS lists it only for the Enterprise platform, which covers ordinary computer systems (Section 4.7).

Table 8: The techniques this lecture follows, in the order an attack uses them, with the tactics under which the ATLAS matrix places them.

Technique	Tactic
AI Agent Tool Poisoning	Persistence
Publish Poisoned AI Artifacts: AI Agent Tools	Resource Development
AI Supply Chain Rug Pull	Defense Evasion
AI Supply Chain Compromise: AI Agent Tool	Initial Access
User Execution: Poisoned AI Agent Tool	Execution
AI Agent Tool Invocation	Execution, Privilege Escalation, Lateral Movement
Credentials from AI Agent Configuration	Credential Access
Exfiltration via AI Agent Tool Invocation	Exfiltration
Escape to Host	Privilege Escalation
AI Agent Context Poisoning	Persistence
Cost Harvesting: Agentic Resource Consumption	Impact

4.7 Agentic AI coverage in ATLAS

The Agentic AI tag marks the ATLAS entries in which an adversary may operate on an agent, and most tagged entries are general techniques that list other AI platforms as well. Every ATLAS entry has a platforms field, which ATLAS describes as denoting "the platform(s) the adversary is operating in" [19]. Its values are Predictive AI (models that classify or predict), Generative AI




Figure 9: ATLAS entries (techniques and sub-techniques) of release 2026.09, counted by the year in which each was created. Each bar is split by whether the entry carries the Agentic AI tag and whether Agentic AI is its only AI platform. In the legend, "other platforms" means other AI platforms, so an entry that lists only Agentic AI and Enterprise counts as having no other AI platform.

(models that generate text, images or code), Agentic AI (systems in which a model calls tools) and Enterprise (ordinary computer systems). We say that an entry carries the **Agentic AI tag** when its platforms field lists Agentic AI. Reading the tag as "this technique applies to agents" is our interpretation of the field.

In release 2026.09, 139 of the 208 entries carry the tag, about two thirds of the catalog. Figure 9 counts the entries by the year in which each was created, and splits each year's entries three ways: no tag, the tag with another AI platform, and the tag with no other AI platform.

The chart supports the following readings:

- **Old entries carry the tag.** In release 2026.09, the 38 tagged entries created in 2021 are general-purpose techniques, and each lists Predictive AI and Generative AI as well as Agentic AI. The platforms field did not exist when they were written. Release 2026.05 added it to every technique: "All techniques are updated to include one or more platforms (Predictive AI, Generative AI, Agentic AI, Enterprise)."
- **Few entries list no other AI platform.** In release 2026.09, only 33 entries list no other AI platform: 29 list Agentic AI alone, and 4 list Agentic AI with Enterprise. In the same release, the other 106 tagged entries also list Predictive AI or Generative AI, and 69 entries carry no tag.
- **Entries with no other AI platform are recent.** All 33 entries of release 2026.09 that list no other AI platform were created in 2023 or later: one in 2023, 13 in 2025 and 19 in 2026. The one from 2023 is AI Agent Tool Invocation, created in October 2023 and renamed in September 2025. Across release 2026.09, 125 of the 208 entries were created in 2025 or 2026.

On our reading, the tag therefore marks the techniques that apply to agents, and most of them were written for AI systems in general. The entries that list no other AI platform were all created in 2023 or later, and every one except AI Agent Tool Invocation was created in 2025 or 2026. The chart counts catalog entries. It does not count attacks. The year of an entry records when ATLAS added the technique, which need not be when adversaries began to use it.

Key points

- A smell is a symptom of weak design, a fault is a defect that misbehaves at run time, a weakness is a class of faults (cataloged in CWE), a vulnerability is a reported instance in a product (identified by a CVE), and a threat is the action an adversary takes with it (described in ATLAS).
- The OWASP MCP Top 10 (version 0.1, beta) lists ten risks of MCP deployments, each with a "vulnerable if" checklist and prevention steps, and the course groups them by the part of a deployment they act on: host and model context, server side, credentials and identity, and logging.
- A documented case shows only what its kind of evidence can show: an attack in the wild shows that adversaries use the attack against real users, an advisory shows a fixed flaw but not its exploitation, a proof of concept shows that an attack works under the researchers' conditions, and a scan measures exposure.
- OWASP gives a checklist of the conditions that make a deployment vulnerable but orders no attack steps and rates no evidence, while ATLAS records an attack's steps in order, each a technique under a tactic, but gives no checklist.
- In ATLAS, a tactic is the adversary's goal at one stage, a technique is a method for reaching it, a sub-technique refines a technique, a mitigation counters techniques, and a case study maps a documented incident or exercise to the techniques it used.
- The ATLAS matrix places each technique under every tactic it serves, so AI Agent Tool Invocation, the use of an agent's access to invoke its tools, appears under Execution, Privilege Escalation and Lateral Movement.
- Most ATLAS entries that carry the Agentic AI tag are general AI techniques that also list other AI platforms, and those that list no other AI platform were all created in 2023 or later (in release 2026.09, 139 of 208 entries carry the tag, and 33 list no other AI platform).

5 Attacks on tool-using agents

Section 4 introduced MITRE ATLAS and listed the techniques that this lecture traces through an attack on a tool-using agent. This section explains them in the order in which an attack uses them: poisoning a tool, delivering it through the software supply chain, and using it to reach the agent's credentials, the data in its calls, the host machine, its memory and its budget. For each technique, we ask what the adversary needs and what it reaches, because a defender must know both to decide where a control has to act. Section 6 then asks which mitigations protect these assets.

5.1 Tool poisoning: definition, implementation and response

Tool poisoning is the insertion of malicious content or behavior into a tool, so that the agent that uses the tool, or the tool itself, does something other than what the tool claims to do. The adversary can change what the model reads about the tool, what the tool's code does when it runs, or what the tool returns after

a call. ATLAS records these changes as one technique.

> **Definition 5.1** (AI Agent Tool Poisoning)**.** "Adversaries may poison tools used by AI agents by introducing or modifying malicious content or behavior in a tool's model-visible definition, executable implementation, or runtime responses." [19]

We use the name tool poisoning for this technique wherever the poison sits. A poisoned tool is still presented as doing something harmless. ATLAS files tool poisoning under the Persistence tactic. Once a poisoned tool is installed or connected, it can give the adversary lasting influence over the agent's actions. OWASP's list has a risk with the same name, OWASP's Tool Poisoning entry (Section 4), which covers instructions hidden in a tool's description. OWASP's summary of that entry also lists rug pulls [38].

Each place of poison enters one call to a tool at a different moment (Figure 10). The figure uses the edit server of Section 1, which serves the `edit` tool of our running agent from a separate process. The host's client first obtains the tool's definition with `tools/list`. Later the client sends `tools/call`, and the server runs the tool's code. The result then comes back, and the host adds it to the model's context. The poison can sit in any of these places:

- **Definition poisoning.** The adversary adds instructions to the tool's definition, which the model reads before any call. In the figure, one sentence added to the description of `edit` tells the model to read the user's private key, the secret file that proves the user's identity when logging in to other machines, and include its contents in the patch. The host passes the description to the model together with the tool's name and input schema (Section 1), and nothing flags the added sentence. The MCP Inspector, for example, displays it verbatim and without warning (Section 3).
- **Implementation poisoning.** The adversary changes the tool's code, which the model never reads. The description can stay honest. In the figure, the code does its stated job of replacing a string but also writes a file outside the workspace. No host sees the change, because a host receives only the definition and the results (Section 3).
- **Response poisoning.** The adversary makes the tool return instructions, deceptive data or a fabricated error, which the model reads after the call. In the figure, the result is a tool execution error, a result with `isError` true, whose message tells the model to read the user's private key and retry.

A poisoned definition can act even if its tool is never called. When the host passes the definitions of all connected tools to the model, an instruction in one tool's description can change how the model uses another tool [2].

Response poisoning arrives after an approved call. The user's consent covers the call that the host showed (Section 1). It says nothing about the content that the call returns. A tool execution error is a natural carrier for the poison, because the model is expected to read it and correct its next call.

Response poisoning also differs from the indirect prompt injection of Lecture 4, in which text from a source outside the application reaches the context as an observation. In response poisoning, the tool itself is malicious or compromised, and it returns the content on purpose. A harmless tool that faithfully returns a web page containing an instruction delivers an indirect prompt injection.

The places of poison differ in what the attack needs from the model. Definition poisoning and response poisoning act through content that the model reads, so they succeed only if the model follows the planted instruction. Implementation poisoning acts through code, which the model never reads. Its effect is produced when the agent or the user invokes the tool, and the model has no planted instruction to follow or to refuse. An inspection of the model's input therefore cannot detect it.

5.2 The sub-techniques and the tool contract

ATLAS records each place of poison as a sub-technique of tool poisoning: Definition and Instructions for definition poisoning, Implementation for implementation poisoning, and Runtime Response for response poisoning. In each sub-technique, the adversary alters a different part of the tool contract (Recap of Lecture 4). Table 9 lists, for each sub-technique, what the adversary alters, the part of the contract it affects and the ATLAS case studies that record it. Its column for the part of the contract shows that each place of poison in Figure 10 breaks a different part of the contract.

Each sub-technique affects its part of the contract in the following way:

- **Definition and Instructions.** The tool definition is the only part of the contract that the model receives (Lecture 4). Poison there changes the tool's purpose as the model understands it. The description no longer only describes the tool. It also instructs the model.
- **Implementation.** The code breaks the tool's execution constraints, for example the rule that every write stays inside the workspace. An MCP tool definition has no field for execution constraints (Section 2), so a host can neither state nor check the constraint that the poisoned code breaks.
- **Runtime Response.** The poison sits in the results and errors that the tool returns. MCP's tool execution errors, the results with `isError` true, are one route for it.

ATLAS records definition poisoning in case studies of a remote MCP tool and of a skill, an installable package of instructions that an agent loads. In the first, researchers at Invariant Labs hosted an MCP server whose tool description told the agent to read the user's credential files and to place their contents in an otherwise unneeded argument of the call [2, 26]. In the second, a researcher shared a poisoned skill for ClawdBot, an earlier name of the personal assistant OpenClaw (Section 7). The skill's instructions made the agent that loaded it run a shell command that contacted the researcher's server [22]. Implementation poisoning appears in the postmark-mcp incident [25], which Section 5.3 follows step by step.

No case study in ATLAS release 2026.09 uses response poisoning [19]. The same release maps no mitigation to tool poisoning or to any of its sub-techniques (Section 6).

5.3 A supply-chain attack on a tool

A poisoned tool reaches its victims through the software supply chain (Section 4.2). An attack on a tool through this chain proceeds in the following steps. In Figure 11, each column is one step, the bands show whether it happens at the adversary, the package registry or the victim's machine, and the bottom row names the ATLAS technique of the step.

1. **Publication.** The adversary releases a tool that works as advertised, through a source repository, a package registry or a remote service of the adversary's own.
2. **Adoption.** Users install the tool, connect it to their agents and come to trust it. Nothing is wrong yet.
3. **The update.** The adversary publishes a malicious version, which replaces the working one on the machines of users who upgrade.
4. **Connection.** When the host reconnects to the server, `tools/list` brings the poisoned tool into the agent's tool set, beside the agent's other tools.
5. **Invocation.** A user makes a request, the agent calls the tool, and the tool's code runs with the agent's **privileges**, the rights that a process has to read and write files, use the network and




Figure 10: Tool poisoning in the definition, the implementation and the response of one call to the `edit` tool of an MCP server. The middle column says whether the model reads each place: the definition before any call, the implementation never, and the response after the call. Magenta marks what the adversary controls, and the poisoned text is illustrative.

Table 9: The sub-techniques of tool poisoning in ATLAS release 2026.09. Each row names what the adversary alters, the part of the tool contract of Lecture 4 that it affects, and the ATLAS case studies that record it.

Sub-technique	ID	What is altered	Part of the contract	Seen in
Definition and Instructions	AML.T0110.000	Descriptions, docstrings, parameter names, help text, schemas, annotations, examples, manifests and skill files	Purpose	Data Exfiltration via Remote Poisoned MCP Tool (April 2025); Supply Chain Compromise via Poisoned ClawdBot Skill (January 2026)
Implementation	AML.T0110.001	Executable logic. The tool may still do its stated job while also doing something else.	Execution constraints	Poisoned Postmark MCP Server Email Exfiltration (September 2025)
Runtime Response	AML.T0110.002	Content returned after an approved call: instructions, deceptive data, fabricated errors, embedded resources	Results and errors	No case study in this release

start programs.

The update is a **rug pull**: the adversary publishes a legitimate component, gains users, and then pushes a malicious update. A dependency often receives more scrutiny when it is first considered for adoption than when it is updated. An update to a tool that users already trust can therefore evade the checks that would catch a new malicious tool [19].

A server that runs on the user's machine is a process like any other, so it holds the privileges of the user who started it, as the agent does.

The postmark-mcp incident of September 2025, described in Section 4.4, followed these steps [4, 9]:

- **Publication.** The adversary published postmark-mcp on npm under a name that impersonated Postmark's MCP server. Versions 1.0.0 to 1.0.15 worked as advertised.
- **Adoption.** Users installed the package and connected it to their agents.
- **The update.** Version 1.0.16, released on September 17, 2025, about two days after the package was created [35], added the line that sent a blind copy of every message to the adversary.
- **Connection.** Every host that upgraded ran the new version at its next connection.
- **Invocation.** Every email that an agent sent through the tool also reached the adversary.

The host connected the new version exactly as it had connected the old one. The tool kept its name and its stated job, and the change was in the implementation, which no host reads (Section 3). A tool that behaves well at first can therefore be replaced by a hostile version, and the trust that users gave the first version passes to the next one unless something checks the update.

5.4 The postmark-mcp attack in ATLAS

The steps of Section 5.3 are the course's model of a supply-chain attack, and the ATLAS case study of postmark-mcp records the same attack in nine steps of its own (Section 4.4). Table 10 places the case study's techniques for publication, the update, connection and invocation at the matching step of our model [25]. Adoption has no technique. For each technique, the table gives the tactic it serves, which is the adversary's goal at that stage, and what the adversary does. The tactic column shows what each step achieves for the adversary.

The tactics name the purpose of each step:

- **Resource Development.** Putting a tool on a public registry under the adversary's control prepares a resource for the attack. The table places this technique at publication, where the tool first appears. In the postmark-mcp case study, ATLAS attaches it to the release of the malicious version, the event that our model calls the update, because that version was the poisoned artifact.




Figure 11: A supply-chain attack on a tool, illustrated by the postmark-mcp incident of September 2025. The bands show where each step happens (the adversary, the package registry and the victim's machine), and the bottom row names the ATLAS technique of each step. Magenta marks what the adversary controls, and the agent's other tools are illustrative.

Table 10: The techniques of the ATLAS case study of postmark-mcp, placed at the steps of the course's model of a supply-chain attack, with the tactic each one serves. Names, tactics and descriptions follow ATLAS release 2026.09, and adoption has no technique.

Step	Technique	ID	Tactic	What the adversary does
Publication	Publish Poisoned AI Artifacts: AI Agent Tools	AML.T0115.002	Resource Development	Publishes a tool through repositories, registries or an adversary-controlled remote service
The update	AI Supply Chain Rug Pull	AML.T0109	Defense Evasion	Publishes a legitimate component, gains adoption, then pushes a malicious update
Connection	AI Supply Chain Compromise: AI Agent Tool	AML.T0010.005	Initial Access	Gets a poisoned tool into the victim's environment, from which the adversary can also act through the agent's other tools
Invocation	User Execution: Poisoned AI Agent Tool	AML.T0011.002	Execution	Waits for the victim or the agent to call the poisoned tool, and malicious logic runs
Invocation	Exfiltration via AI Agent Tool Invocation	AML.T0086	Exfiltration	Moves data out through a tool that writes, here through the blind copy of every email

- **Defense Evasion.** The rug pull hides the attack from the scrutiny that new tools receive.
- **Initial Access.** Connection places the poisoned tool in the victim's environment. From there, the adversary can also act through the agent's other tools.
- **Execution.** Invocation runs the adversary's code when the victim or the agent calls the tool.
- **Exfiltration.** Invocation also moves data out of the victim's systems to the adversary, which is called **exfiltration**. In this incident, it happened inside ordinary calls, because the poisoned tool sent each email both to its intended recipients and to the adversary.

The case study also maps techniques that fall outside the steps of a supply-chain attack, such as Impersonation, for the borrowed name, and External Harms, for the content of the stolen emails (Section 4.4).

The harm in this incident happened at invocation. Once a tool runs on the user's machine, whether the tool itself is hostile or an injected instruction steers an honest one, an adversary can reach the agent's credentials, the data in a call, the host machine beyond the sandbox, the agent's memory and its budget.


5.5 Credentials in the agent's configuration

A tool that runs on the user's machine can read the secrets in the agent's configuration, because it runs as the same user, with the same rights, as the agent. **Credentials** are secrets that prove a program's right to use a service, such as API keys, access tokens and the connection strings of databases. Agents and their hosts keep them in configuration files, often as **plaintext**, readable text with no encryption. Secret managers and encrypted vaults exist, but credentials are often placed in less protected locations for convenience [19].


The attack proceeds as follows (Figure 12a):

1. **The secrets sit in plain files.** The agent's configuration holds API keys, tokens and connection strings, and the host loads them when it starts.
2. **A tool reads them as the same user.** A local MCP server that the host starts over stdio (Section 1) runs as the same user as the host. File permissions are granted to users, so a file that only its owner may read is readable by every process of that owner. File permissions therefore cannot tell the agent from its tools.
3. **The adversary uses the credentials elsewhere.** The tool sends copies out. A copied credential works from anywhere, so the adversary can call the model API on the victim's account and reach whatever services the tokens allow.

ATLAS records this as Credentials from AI Agent Configuration, a technique of the Credential Access tactic. It appears in case studies of the Cursor code editor and of OpenClaw. In the first, a web page scraped by an MCP tool carried an instruction that made Cursor propose a shell command. Cursor asked the user before running it, which may mitigate the attack. Once approved, the command read configuration files holding credentials and sent them to the researchers' server [20]. In the second, a researcher reached OpenClaw control interfaces that were exposed to the internet and read the credentials of many connected services from its plaintext configuration [21]. ATLAS release 2026.09 maps no



(a) A tool on the user's machine reads the agent's credentials. The host reads the configuration files at start-up, a local MCP server that runs as the same user reads them too, and the attacker uses the copies elsewhere. The secret values, variable names, user name and permissions are illustrative.



(b) An authorized tool call carries data out. An instruction in untrusted content makes the model put a sensitive file into the arguments of a well-formed call to a tool that writes, and the server forwards it to the attacker. The instruction, the tool, the arguments and the address are illustrative.

Figure 12: Assets that a tool exposes on the user's machine: the credentials in the agent's configuration and the data in the arguments of a call. Magenta marks what the adversary controls, and the numbered circles give the order of the steps.

mitigation to the technique (Section 6).

A tool that runs as the same user as the agent can read every file that the agent can read. A secret in a plain file is therefore protected from a tool only if the tool runs with fewer rights than the agent, for example as another user or inside a sandbox.

5.6 Exfiltration through an authorized call

An agent can be made to carry data out through an ordinary, authorized call to a tool that writes. A call is **authorized** when the agent is allowed to call its tool and the call passes the checks applied before the tool runs. The attack needs sensitive data in the agent's context, for example the user's private key, which the agent read earlier. It also needs a tool that writes outward, such as a tool that sends messages. This outward channel exists before anything goes wrong.

The attack proceeds as follows (Figure 12b):


1. **An injected instruction enters the context.** An instruction hidden in a web page, an email or a ticket reaches the context as untrusted content, and the model reads it as a task. This is the indirect prompt injection of Lecture 4.
2. **The model builds a well-formed call.** The model calls the tool that sends messages, with arguments that carry an address the adversary controls and the contents of the private key. The arguments match the input schema, and the tool is one that the agent is allowed to call.
3. **The server forwards the data.** The server sends the message over its outbound connection, and the private key reaches the adversary.

The call is authorized because the agent may call the tool. The data that the call carries is not authorized. The checks met so far in this course, such as the registry lookup, the input schema and the path check, look at which tool is called, at the form of its arguments and at where a path points. None of them asks where the content of an argument came from, so the leak travels in the arguments of an ordinary tool call.


Where the data leaves depends on where the server runs. In the figure, the server runs on the user's machine, so the data leaves when the server forwards the message. If the server is hosted elsewhere, the arguments have already left the machine with the call itself.

ATLAS records this as Exfiltration via AI Agent Tool Invocation: sensitive data is encoded into the input of a tool that writes and sent to a location the adversary controls, as part of an action that looks legitimate [19]. The tool may be legitimate and steered by a prompt injection, or it may itself be poisoned. In release 2026.09, ATLAS maps eight mitigations to this technique (Section 6).

Asking the user to approve each call protects only if the user can see what the call carries. In a demonstration by Invariant Labs, an agent was connected to a trusted WhatsApp MCP server and to a malicious second server [3]. The second server's tool description steered the agent into sending the user's message history to the adversary's number through the WhatsApp server. The host asked the user to confirm the call, but its dialog showed only the start of the message body, and the message history sat



(a) An agent can leave its sandbox. The container runtime and the operating-system kernel enforce the boundary. The agent's code crosses it by exploiting a flaw or through a configuration change that turns the sandbox off, and it then reaches the host machine's files, credentials and other processes.



(b) A poisoned instruction outlives its session. In session one, the agent reads untrusted content and stores its instruction as if it were the user's preference. In session two, the store is loaded into the system prompt as trusted input, and the instruction makes the agent call a tool that the user never asked for. The text of the instruction is illustrative.

Figure 13: Assets beyond a single call: the host machine outside the sandbox and the agent's persistent memory. Magenta marks what the adversary controls.

off screen to the right. The user could therefore approve a call without seeing what its arguments carried. The consent that the host obtains (Section 1) covers only what the user is shown.

5.7 Escape from the sandbox

A sandbox protects the host machine only while its boundary holds, and an agent's code can cross that boundary through a flaw or through a setting. The **host machine** is the computer on which the sandbox runs. As in Lecture 4, a sandbox is an environment in which the operating system confines a process, such as a container. A microVM, a small virtual machine, serves the same purpose. The agent process and its tools run inside the sandbox, and the host machine's files, credentials and other processes lie outside it.

The boundary is enforced by the **container runtime**, the program that creates containers and starts processes in them, and by the **operating-system kernel**, the core of the operating system that controls every process's access to files, memory and devices (Figure 13a). This kernel is unrelated to the kernel of Lecture 4, the interpreter that runs the model's scripts.

A **sandbox escape** crosses this boundary and gives the agent's code access to the host machine's files, credentials and processes. ATLAS records it as Escape to Host, a technique of the Privilege Escalation tactic. Its entry lists only the Enterprise platform, so Escape to Host is the only technique that this lecture follows without the Agentic AI tag (Section 4.6). The boundary can be crossed in either of the following ways:

- **A flaw in the container runtime or the operating-system kernel.** The agent's code exploits a vulnerability in the software that enforces the boundary. In SandboxEscapeBench, a benchmark that tests whether models can break out of containers, the most capable current language models identified and exploited vulnerabilities that the researchers had added to containers [15].
- **A setting that turns the sandbox off.** The agent's own configuration decides whether its tools run in the sandbox. An adversary who can change that setting moves execution to the host machine, where the boundary no longer applies. Changing an agent's configuration to disable safety features or user confirmations can let an adversary run tools on the host machine rather than in the sandbox [19].

The second route was used against OpenClaw [23]. A request to the Gateway API, the interface through which OpenClaw's clients reach its Gateway, changed the setting that decides where its `exec` tool runs, from the sandbox to the host machine (Section 7). OpenClaw's sandbox was optional and off by default in early 2026, so this step mattered only on installations that had turned the sandbox on.

A flaw and a setting differ in what the adversary needs. A flaw breaks the boundary, so the adversary needs an exploitable vulnerability. A setting removes the boundary, so the adversary needs only the ability to change the agent's own configuration. Once outside, the agent's code reaches everything that the sandbox was protecting: the host machine's files, the credentials stored there and its other processes.




Figure 14: An agent can be made to spend its budget. An instruction planted in a tool result makes the model repeat its call. Every call is ordinary and billed, no data is stolen, and no limit outside the loop stops the run. All numbers are illustrative and not to scale, and the instruction is one of the examples in the ATLAS entry.

Table 11: The ATLAS techniques that expose an asset through a tool-using agent, with the tactic each one serves. Names, tactics and descriptions follow ATLAS release 2026.09, and the asset column is ours.

Technique	ID	Tactic	Asset	What the adversary does
Credentials from AI Agent Configuration	AML.T0083	Credential Access	The agent’s credentials	Reads API keys, tokens and connection strings from the agent’s configuration files
Exfiltration via AI Agent Tool Invocation	AML.T0086	Exfiltration	The data in a call	Encodes sensitive data into the input parameters of a tool that writes
Escape to Host	AML.T0105	Privilege Escalation	The host machine	Escapes a container to the host machine. One agent route disables the sandbox.
AI Agent Context Poisoning	AML.T0080	Persistence	The agent’s memory	Causes instructions to persist in the agent’s memory or in a long thread
Agentic Resource Consumption	AML.T0034.002	Impact	The budget	Coerces the agent into expensive tool calls, fan-outs or loops that consume its budget

5.8 Instructions in persistent memory

An instruction that an agent writes into its memory outlives the session in which it was planted, and it returns in later sessions as trusted input. A **session** is one period of use of the agent, which starts with a fresh conversation. It is unrelated to the protocol session that earlier MCP revisions opened (Section 2). **Persistent memory** is a store that the agent loads into later sessions, such as a memory file or a saved conversation thread. The application loads the store into the **system prompt**, the instructions that the application places at the start of every context, which the model treats as coming from the application or the user.

Context poisoning is the planting of instructions in that store. ATLAS records it as AI Agent Context Poisoning, a technique of the Persistence tactic. Its sub-techniques are Memory, for instructions stored in a memory that the agent keeps across sessions, and Thread, for instructions placed in the earlier messages of a conversation thread, which the model reads as part of its context for the rest of that thread. A thread may continue over several sessions.

The attack proceeds as follows (Figure 13b):

1. **The agent reads untrusted content.** In the first session, a web page, an email or a document carries an instruction, as in the indirect prompt injection of Lecture 4.
2. **It writes the instruction to memory.** The agent stores the instruction, phrased as the user’s own preference.
3. **A later session loads it.** Days later, a new session loads the store into the agent’s context, before the user types anything.
4. **The agent acts on it.** The user types only a greeting, the stored instruction applies, and the agent calls a tool that fetches tasks from the adversary’s server. The user never asked for this call.

Memory is trusted input because it arrives in the system prompt. The stored instruction therefore no longer looks like external content. An indirect prompt injection affects the run in which the text is read. A poisoned memory affects every later session that loads it, so one planting keeps steering the agent until someone removes it.

Researchers at the security company HiddenLayer used this route against OpenClaw. Its early-2026 versions loaded a prompt file named HEARTBEAT.md into the system prompt of every conversation thread. In their attack, an injected instruction was appended to that file, so every new thread started with it (Section 7.4). ATLAS files this effect under the Thread sub-technique, because the planted instruction entered the context of every new thread, although the store that held it was a file [24]. ATLAS maps Memory Hardening and AI Red Team to the Memory sub-technique, and AI Red Team alone to the Thread sub-technique (Section 6).

5.9 Spending the agent’s budget

An injected instruction can make an agent spend its budget, so the victim pays even though no data leaves. In Lecture 2, the budget was a limit on the number of model calls in a run. In this attack, the budget is the money available for calls to the model and to paid APIs, and every call is billed.

The attack turns a normal run into an expensive one (Figure 14):

1. **A normal run.** One request enters the reactive loop of Lecture 2, which makes a few model calls and tool calls and

then answers. The run costs a small part of the budget.
2. **A planted instruction.** The result of a tool call carries an instruction to repeat a task many times. At the next model call, the model calls the tool again instead of answering, and it keeps going. Every call looks like a normal one.
3. **The budget is spent.** The calls continue until the requested repetitions are done or the money runs out. No data is stolen, and the victim pays.

Agentic Resource Consumption is the ATLAS sub-technique in which an adversary coerces an agent into costly tool calls, fan-outs or loops that consume its budget. A **fan-out** is a step that launches many calls at once. Agentic Resource Consumption is a sub-technique of Cost Harvesting, which serves the Impact tactic, and the ATLAS matrix shows its parent's cell (Section 4). The examples in its entry include asking for the same summary many times, asking for a translation into dozens of languages and making the agent delegate tasks to itself in a loop [19]. No case study in release 2026.09 uses it.

Nothing in such a loop is malicious by itself. Each call is well formed and authorized, so a check that inspects one call at a time finds nothing to refuse. What stops the run is a limit on the total, such as the number of calls or the money spent, enforced outside the model's choices. The budget of Lecture 2 is such a limit: the harness checks it before every model call, whatever the model asks for. ATLAS maps AI Red Team and Limit AI Workload Resource Consumption to the technique (Section 6).

5.10 Assets exposed through tool access

Each technique that follows a tool's invocation (Sections 5.5 to 5.9) exposes a different asset and serves a different tactic. Table 11 collects them, with the asset that each one exposes and what the adversary does.

Credentials from AI Agent Configuration, Exfiltration via AI Agent Tool Invocation, AI Agent Context Poisoning and Agentic Resource Consumption use access that the agent legitimately has, to its files, its tools, its context or its budget. A tool that reads the configuration runs with the user's rights. An exfiltrating call is authorized. A poisoned memory is loaded as trusted input. Each call of an expensive loop is ordinary. A check that looks only at which tool is called, at the form of its arguments and at where a path points therefore finds nothing to refuse in them.

Escape to Host differs. The agent's code leaves the boundary that was meant to contain it, either by exploiting a flaw in the software that enforces the sandbox or through a changed setting in the agent's own configuration. Section 6 asks which mitigations address these techniques and where along a tool call each one acts.

Key points

- Definition and response poisoning work only if the model follows an instruction planted in what it reads, while implementation poisoning runs whenever the tool is invoked, in code that the model never reads.
- In a rug pull, an adversary publishes a working tool, waits for users to adopt it and then pushes a malicious update that hosts connect as before, as postmark-mcp did when version 1.0.16 added a blind copy of every email.
- A tool that runs as the same user as the agent can read every secret in the agent's configuration files, because file permissions cannot tell the agent from its tools.
- An injected instruction can make an authorized call to a tool that writes carry sensitive data to the adversary, and an approval dialog protects only if it shows the user what the arguments carry.
- A sandbox protects the host machine only while its boundary holds, and an agent's code can cross it through a flaw in the container runtime or the operating-system kernel, or through a setting that turns the sandbox off.
- An instruction written to persistent memory returns in later sessions as trusted input, so one planting keeps steering the agent in every session that loads it.
- An injected loop spends the budget through calls that are each well formed and authorized, so a check that inspects one call at a time finds nothing to refuse, and only a limit on the total, enforced outside the model's choices, stops it.

6 Mitigations and where they act

Section 5 followed eleven ATLAS techniques along the life of a hostile tool, from its publication to the harm it does once an agent calls it. This section studies the countermeasures that ATLAS records for those techniques: which techniques have them, where along one tool call each kind acts, and whether ATLAS says which process must enforce them. A defender needs these answers to see which steps of an attack have no control, and which controls an attacker who reaches the agent could switch off. The case study of Section 7 shows what happened when an agent's controls lived inside the agent's own process and configuration.

6.1 Mitigations in ATLAS

A mitigation, defined in Section 4, is a countermeasure that ATLAS maps to the techniques it counters, and each mitigation says what to restrict or check. Each mapping between a mitigation and a technique carries a sentence that explains how the mitigation counters that technique [19]. For example, the mapping from Human In-the-Loop for AI Agent Actions to AI Agent Tool Invocation explains that requiring the user to confirm each tool call can prevent an adversary from running tools automatically.

The mapping is many-to-many. Release 2026.09 holds 40 mitigations and 361 mappings, so the average mitigation is mapped to nine techniques. One technique can also have several mitigations. A defender who starts from a technique therefore finds a list of countermeasures, and one who starts from a countermeasure finds every technique it addresses.

ATLAS labels each mitigation with one or more categories, which say what kind of control it is:

- **Policy.** A policy mitigation is a rule or practice that an organization adopts, such as keeping a list of everything a system is built from.
- **Technical (AI).** A technical AI mitigation is a control specific to AI systems, such as screening what flows into and out of a model.
- **Technical (cyber).** A technical cyber mitigation is a conventional security control on software, access and infrastructure, such as permissions or isolation in containers.

Most mitigations carry a single category. AI Red Team carries all three, and AI Honeypots carries both technical categories.

In release 2026.09, nine mitigations carry the word "agent" in their names. ATLAS created all nine between October 2025 and August 2026, so in October 2026 all nine were less than a year old. Sections 6.4 to 6.6 describe each of them.

6.2 Which techniques have mitigations

ATLAS concentrates its mitigations on the moment an agent invokes a tool, and it maps none to tool poisoning itself. To show this distribution, we sort the 40 mitigations of release 2026.09 into six groups. A **mitigation family** is one of these groups, formed according to what each mitigation's description says it does, and each mitigation belongs to exactly one family.

The six families are *Check what gets installed*, *Limit agent authority*, *Check what flows*, *Contain execution and exposure*, *Record and human oversight* and *Harden the model itself*. Section 6.3 places

Table 12: The mitigations that ATLAS release 2026.09 maps to each technique of Section 5, by mitigation family. A cell counts the mitigations mapped to the technique's own entry, a blank cell means none, and the last row adds up each column.

Technique (in attack order)	Check what gets installed	Limit agent authority	Check what flows	Contain execution and exposure	Record and human oversight	Harden the model itself	Total
AI Agent Tool Poisoning			*no mitigation mapped*				0
Publish Poisoned AI Artifacts: AI Agent Tools	1						1
AI Supply Chain Rug Pull			*no mitigation mapped*				0
AI Supply Chain Compromise: AI Agent Tool					1		1
User Execution: Poisoned AI Agent Tool†			*no mitigation mapped*				0
AI Agent Tool Invocation		4	2	1	3	2	12
Credentials from AI Agent Configuration			*no mitigation mapped*				0
Exfiltration via AI Agent Tool Invocation		4	1	1	2		8
Escape to Host			*no mitigation mapped*				0
AI Agent Context Poisoning			1		1		2
Cost Harvesting: Agentic Resource Consumption		1			1		2
Total	1	9	4	2	8	2	26

† The parent technique, User Execution, has five mitigations mapped to its own entry.

each of them on a tool call. The families are the course's grouping. ATLAS itself labels mitigations only by category.

Table 12 shows how the mitigations fall across techniques and families [19]. Its rows are the eleven techniques of Section 5, in attack order, and each cell counts the mitigations that ATLAS maps to one technique within one family.

A cell counts only the mitigations mapped to the technique's own entry. Several of the techniques are sub-techniques, and the technique that a sub-technique refines is its **parent technique**. Mappings to a parent are left out of the table. In release 2026.09, the parent technique User Execution has five mitigations of its own, and AI Supply Chain Compromise has four, among them AI Red Team. In the table, compare the row of AI Agent Tool Invocation, which holds the most mappings, with the rows that read "no mitigation mapped".

The counts fall unevenly across the techniques. In release 2026.09, AI Agent Tool Invocation carries 12 of the table's 26 mappings, and Exfiltration via AI Agent Tool Invocation carries eight. Both techniques describe what happens at the tool call itself: an adversary who steers the agent invokes a tool, or encodes data into the arguments of an authorized call.

The rows that read "no mitigation mapped" are AI Agent Tool Poisoning, AI Supply Chain Rug Pull, User Execution: Poisoned AI Agent Tool, Credentials from AI Agent Configuration and Escape to Host. For User Execution: Poisoned AI Agent Tool, the gap lies only on the sub-technique's own entry, because its parent, User Execution, has five mitigations mapped.

Across the columns, most mappings fall in the families that limit authority and keep a record. In release 2026.09, the *Limit agent authority* family holds nine mappings and the *Record and human oversight* family holds eight. The *Check what gets installed* family holds a single mapping: Vulnerability Scanning, mapped to Publish Poisoned AI Artifacts: AI Agent Tools.

The table counts the mappings that ATLAS records. It does not measure how well any mitigation works. An empty row means that no mitigation is mapped to that technique's own entry. It does not mean that nothing helps against the technique. A control on a later step, such as narrow permissions on the tools an agent may call, can still limit what a poisoned tool achieves.

A team that follows ATLAS's mappings will find many controls for the call that a tool receives. It will find none mapped to tool poisoning itself, and few for the earlier question of whether a tool should be trusted at all. Among the techniques by which a hostile tool is published, distributed and installed, only Vulnerability Scanning and AI Red Team are mapped to a technique's own entry. The other vetting mitigations reach these techniques only through a parent technique (Section 6.6).

6.3 Where each family acts along a tool call

The six families act at different stages of one tool call: the installation of the tool, its discovery through `tools/list`, its invocation, its execution and the handling of its result. Figure 15 draws one tool call from end to end and marks where each family acts. Read it from left to right, following the tool from the package registry to the outbound network.

The base of the figure is an ordinary tool call over MCP (Section 1). A tool is published in a package registry (Section 4.2), such as the npm registry that distributed postmark-mcp, and installed into the host.

The figure draws the model inside the host because the host makes every model call (Section 1). The model's tool calls reach the server only through the MCP client. The client receives the tool definitions in reply to `tools/list`, sends `tools/call` and receives the result from the MCP server. The server runs the tool, and the tool can open connections that leave the machine, which the figure calls the outbound network.

Each family attaches to one part of this picture:

- **Check what gets installed.** This family acts on the install arrow, before a model, dataset, library or tool is trusted. Its members check an artifact's signature (Code Signing) or its **cryptographic checksum**, a short value computed from




Figure 15: One tool call, from the installation of a tool to the outbound network, with the place where each mitigation family acts. The families are the course's grouping of ATLAS's mitigations.

a file's bytes that changes whenever the file changes (Verify AI Artifacts). They also scan the artifact for known flaws and unsafe calls (Vulnerability Scanning) [19]. Others test models and their training data (Validate AI Model, Sanitize Training Data, Maintain AI Dataset Provenance). An **AI bill of materials** is a list of every artifact used to build a system. Keeping one (AI Bill of Materials) allows a rapid response when a vulnerability is reported in one of those artifacts.

- **Limit agent authority.** This family acts on the calls that cross from the client to the server, by bounding what the agent may request. Its members set permissions for the agent, for the user it acts for and for each shared tool. They block or confirm tool calls once untrusted data is in the model's context, and they cap the tokens, iterations, tool calls, time and spending of a run. **Least privilege** is the principle of granting a component only the rights its task needs, and it underlies all the permissions mitigations. One member, AI Agent Authority Expansion Controls, states that its control belongs outside the agent (Section 6.7). The family also holds three general limits on who may access a model and how often it may be queried.
- **Check what flows.** This family acts on the messages themselves: the tool definitions, the call and the result. A **guardrail** is a screen placed between users, tools and the model that evaluates prompts, retrieved context, model outputs and tool requests before they are accepted (Generative AI Guardrails). Input and Output Validation for AI Agent Components validates the inputs and outputs of tools, outside the agent. Memory Hardening checks what an agent writes to its persistent memory. The family's other members filter the inputs and outputs of predictive models, which classify or score an input rather than generate content, or they detect generated media.
- **Contain execution and exposure.** This family draws a boundary around the MCP server and its tool. **Segmentation** isolates an agent's tools, data, identities and execution in containers or virtual machines with restricted file and network access (Segmentation of AI Agent Components). With segmentation in place, the arrow from the tool to the outbound network crosses a boundary, where a connection can be refused. Restrict Library Loading also contains execution, by stopping software from loading untrusted code. The family also limits exposure, meaning what an adversary can learn about the system or reach in it. Encrypt Sensitive Information and three limits on what an organization releases about its models serve this purpose.
- **Record and human oversight.** This family watches the host, where the agent's steps take place. **Telemetry** is the record that a system keeps of its own activity, here each step of the agent, each data access and each tool call (AI Telemetry Logging). Human In-the-Loop for AI Agent Actions requires a person to approve agent actions before they run. A **red team** carries out recurring, authorized attack exercises against a system so that its flaws are found and fixed (AI Red Team). AI Agent Scope Drift Detection, AI Honeypots and User Training complete the family. A honeypot is a decoy, such as a fake AI service, agent or credential, that legitimate users have no reason to use, so any use of it signals an adversary.
- **Harden the model itself.** This family acts on the model. Generative AI Guidelines give the model instructions and constraints, for example to treat retrieved content as untrusted. Generative AI Model Alignment trains or fine-tunes the model toward safe behavior that stays within its task. Both change the model, its training or its instructions so that it is harder to fool. ATLAS maps both to AI Agent Tool Invocation, and they are the two mappings in this family's column of Table 12. They are not in the tables that follow, and Lecture 6 discusses them. Three measures for predictive models complete the family.

The families differ in what they act on. The *Harden the model itself* family is the only one that works by changing the model. The others act on something around it: an artifact before it runs, the authority of a call, the content of messages, the place where a tool runs, or a record and a person. The difference matters for enforcement, because a control that acts outside the model still holds when an attack changes what the model does (Section 6.7).

6.4 Controls on agent authority

The mitigations of the *Limit agent authority* family restrict an agent's identity, its permissions, the authority it may acquire and the resources it may use [19]. Tables 13 to 15 list the individual mitigations. Each table gives a mitigation's category, a condensed statement of what it does, and the techniques of Section 5 that ATLAS maps it to, under these short names:

- **Tool invocation** is AI Agent Tool Invocation, and **exfiltration** is Exfiltration via AI Agent Tool Invocation.
- **Context poisoning** is AI Agent Context Poisoning, and **resource consumption** is Agentic Resource Consumption.
- **Publishing a poisoned tool** is Publish Poisoned AI Artifacts: AI Agent Tools.
- **Supply-chain compromise** is AI Supply Chain Compromise: AI Agent Tool, and **user execution** is User Execution: Poisoned AI Agent Tool.

An asterisk marks a mapping to the parent technique. A subtechnique is one form of its parent, so a countermeasure mapped to the parent applies to it as well.

The tables are a selection. They hold every mitigation that ATLAS maps to one of these techniques on the technique's own entry, except Generative AI Guidelines and Generative AI Model Alignment, which harden the model. They add Verify AI Artifacts and AI Bill of Materials, which reach the techniques only through a parent technique. They also add AI Agent Authority Expansion

Table 13: Mitigations that restrict an agent's identity, permissions, authority and resource use, with the techniques of this lecture that ATLAS maps each one to.

Mitigation	Category	What it does	Lecture techniques it maps to
Privileged AI Agent Permissions Configuration	Technical (cyber)	Applies role-based, attribute-based and least-privilege controls to an agent that holds elevated rights	tool invocation, exfiltration
Single-User AI Agent Permissions Configuration	Technical (cyber)	Gives an agent acting for one user no more rights than that user	tool invocation, exfiltration
AI Agent Tools Permissions Configuration	Technical (cyber)	Gives shared tools the permissions and restrictions of the agent that calls them	tool invocation, exfiltration
Restrict AI Agent Tool Invocation on Untrusted Data	Technical (AI)	Blocks or confirms tool calls once untrusted content has entered the model's context	tool invocation, exfiltration
Limit AI Workload Resource Consumption	Technical (AI)	Bounds the tokens, iterations, tool calls, time and spending of one agent run	resource consumption
AI Agent Authority Expansion Controls	Technical (AI)	Stops an agent from acquiring new permissions, tokens or targets during a run, enforced outside the agent	none of this lecture's techniques

Controls and AI Agent Scope Drift Detection, which map to none of them. Other mitigations that are mapped only to a parent technique are left out.

In Table 13, notice that every permissions mitigation maps to the same two techniques, tool invocation and exfiltration.

The permissions mitigations apply least privilege to different holders of rights:

- **A privileged agent.** Privileged AI Agent Permissions Configuration concerns an agent granted rights above those of a normal user, or one that serves many users. It calls for role-based and attribute-based access control, which grant rights according to the role a party holds or according to attributes of the party, the resource and the request.
- **An agent acting for one user.** Single-User AI Agent Permissions Configuration requires that such an agent never hold a permission that the user would not be granted. The agent receives its own identity, and it is decommissioned when its role ends. It works through **delegated access**, acting with rights handed down from the party on whose behalf it works, here the user's account.
- **A shared tool.** AI Agent Tools Permissions Configuration concerns a tool that several agents call. Through delegated access, the tool receives the permissions, identity and restrictions of the agent that calls it.

These mitigations map to tool invocation and exfiltration because they bound what a steered agent can do. An adversary who controls an agent's next action can invoke only the tools, and reach only the resources, that the agent's permissions allow. Delegated access extends the bound to shared tools, which cannot do for one agent what that agent could not do itself. Lecture 4's harness applied the same principle to a single tool: the path check confined `edit` to the workspace root.

Restrict AI Agent Tool Invocation on Untrusted Data responds to indirect prompt injection (Section 4.6). Once text from a source outside the application's control has entered the model's context, the mitigation blocks the automatic invocation of tools or asks the user to confirm each call. The strictness depends on the consequences of the action, and for high-consequence actions the mitigation recommends confirmation every time. The mitigation does not try to recognize an injection. It reduces what an injection can cause.

Limit AI Workload Resource Consumption bounds the tokens, iterations, retries, tool calls, time and spending of one agent run. It counters Agentic Resource Consumption, in which an adversary coerces an agent into costly calls, fan-outs or loops (Section 5). One request can set off many model calls and actions, so the limits apply to the whole run. The budget on model calls from Lecture 2 and the resource limits on scripts from Lecture 4 are instances of this mitigation.

AI Agent Authority Expansion Controls stops an agent from acquiring new permissions, tokens or targets during a run. The agent's maximum authority is granted before the run starts. Anything the agent discovers during the run, such as a new resource, identity, service or target, stays outside its scope until it is independently validated and added. ATLAS maps this mitigation to none of this lecture's techniques. It matters here because it is one of the mitigations that say where a control must sit (Section 6.7).

6.5 Validation and containment controls

These mitigations inspect what passes through a tool, a model or a memory, and they isolate where code runs [19]. Input and Output Validation for AI Agent Components, Generative AI Guardrails and Memory Hardening belong to the *Check what flows* family, and Segmentation of AI Agent Components belongs to the *Contain execution and exposure* family. In Table 14, notice that validation and segmentation map to the same two techniques as the permissions mitigations.

Input and Output Validation for AI Agent Components checks the format and the content of what tools receive and return. A format check includes schema validation. The MCP specification requires a server to validate all tool inputs (Section 2), and checking the arguments against the input schema is one way to meet that requirement. A content check looks for sensitive information leaving in the data, and it removes injected instructions or unsafe code. Exfiltration calls for content checks. The stolen data travels in the arguments of a call that is well formed and authorized (Section 5), so a check of the format alone lets it pass. The mitigation adds that validation should be performed outside the agent, a requirement that Section 6.7 examines.

Generative AI Guardrails puts the guardrails of Section 6.3 in the path of every prompt, retrieved passage, model output and tool request. A guardrail can be a fixed rule, such as an allowlist or a schema, or a model that classifies content. A guardrail differs from a guideline of the *Harden the model itself* family. A guideline asks the model to behave in a certain way, whereas a guardrail checks what actually passes. ATLAS maps guardrails to tool invocation,

Table 14: Mitigations that inspect what passes through a tool, a model or a memory, and that isolate where code runs, with the techniques of this lecture that ATLAS maps each one to. An asterisk marks a mapping to the parent technique.

Mitigation	Category	What it does	Lecture techniques it maps to
Input and Output Validation for AI Agent Components	Technical (AI)	Validates the format and content of tool inputs and outputs, performed outside the agent	tool invocation, exfiltration
Generative AI Guardrails	Technical (AI)	Screens prompts, retrieved context, outputs and tool requests between users, tools and the model	supply-chain compromise*, tool invocation
Memory Hardening	Technical (AI)	Checks and constrains what is written to and read from an agent's persistent memory	context poisoning
Segmentation of AI Agent Components	Technical (cyber)	Isolates agent tools, data, identities and execution in containers or virtual machines with restricted file and network access	tool invocation, exfiltration

and through the parent technique to supply-chain compromise.

Memory Hardening checks and constrains what is written to and read from an agent's persistent memory, the files or stored conversations that later sessions load. It counters context poisoning, in which an instruction planted in memory fires in a later session as trusted input (Section 5.8). Its controls include access control on memory operations, a record of the source of every update, and rollback to a known good version. In the second attack on OpenClaw (Section 7.4), an instruction appended to the prompt file `HEARTBEAT.md` reached every new conversation thread. ATLAS records the append as a change to the agent's configuration [24]. It records the effect as AI Agent Context Poisoning, through the Thread sub-technique. ATLAS maps Memory Hardening to AI Agent Context Poisoning and to its Memory sub-technique, and it maps only AI Red Team to the Thread sub-technique.

Segmentation of AI Agent Components applies the sandbox of Lecture 4 (Section 5.7) to every component of an agent. It maps to tool invocation and exfiltration: a tool whose network access is restricted can send data only where its restrictions allow, whatever its arguments. ATLAS maps no mitigation to Escape to Host, the technique that crosses this boundary (Table 12).

6.6 Tool vetting, logging and human approval

These mitigations vet what is installed, keep a record of what the agent does, and put a person in the path of consequential actions (Table 15). Verify AI Artifacts, Vulnerability Scanning and AI Bill of Materials belong to the *Check what gets installed* family, and the other mitigations in the table belong to the *Record and human oversight* family. In the table, notice that the vetting mitigations reach the supply-chain techniques mostly through parent techniques, while the record and approval mitigations map to the tool call.

Verify AI Artifacts compares an artifact's cryptographic checksum with the expected value [19]. A match shows that the artifact has not been modified since it was published. It cannot show that the published artifact is benign. In the rug pull of postmark-mcp (Section 5), the malicious version was itself the published version, so verifying its checksum would only have confirmed the malicious code.

Vulnerability Scanning examines model files, products and dependencies for unsafe calls and known flaws before they are used. A known flaw is one already reported, for example under a CVE identifier (Section 3). Scanning maps to the publication of a poisoned tool on that technique's own entry, the single mapping in the *Check what gets installed* column of Table 12.

AI Bill of Materials is a policy: the organization keeps an AI bill of materials for each system. Its value comes after a report. When a component is found to be vulnerable or malicious, the list shows which systems include it, so that they can be found and repaired quickly. After postmark-mcp was exposed, such a list would have shown which deployments had installed the malicious version.

AI Telemetry Logging records each step, data access, tool call and identity of an agent. The trace that the course's harness writes, introduced in Lecture 2 as the log of a run's events, is telemetry of this kind. A log prevents nothing by itself. It allows someone to detect an attack, reconstruct what happened and respond.

Human In-the-Loop for AI Agent Actions requires a person to approve an agent's actions before they run. It corresponds to consent in MCP: hosts must obtain the user's consent before invoking a tool, and the protocol cannot enforce this requirement itself (Section 1.9). It is also Lecture 2's human-in-the-loop pattern, in which a run stops at points fixed at design time and waits for a person to decide. Approvals cost time, so the mitigation scales them to the consequences of the action. Minor, repetitive actions need little oversight, and actions with significant consequences may need several approvers.

A person can refuse a harmful call only if the approval request shows the part of the call that causes the harm. In the WhatsApp case (Section 5.6), the confirmation dialog for a message showed only its beginning, and the exfiltrated data lay out of view [3]. The user approved a call whose arguments were not shown in full.

AI Red Team maps to more of this lecture's techniques than any other mitigation: supply-chain compromise, tool invocation, context poisoning and resource consumption. ATLAS advises the red team to choose the adversary behaviors it tests from ATLAS's own tactics and techniques.

AI Agent Scope Drift Detection watches whether an agent's planned actions remain consistent with its authorized objective, and it can pause the agent when they do not. Its signals include tool use that does not fit the task and attempts to reach resources outside the agent's scope. ATLAS maps it to none of this lecture's techniques.

6.7 Where a control is enforced

ATLAS places some controls outside the agent, and it leaves unnamed the process that should enforce any of them. Every mitigation says what to restrict or check. Permissions name what an agent may access, validation names what to inspect, segmentation names what to isolate, and logging names what to record.

Where a control sits determines whether the agent can get around it. AI Agent Authority Expansion Controls and Input and Output Validation for AI Agent Components both state where their control must sit: authority expansion controls "should be implemented outside the AI agent", and validation "should be performed external to the AI agent" [19]. A check that runs inside the agent's own process shares that process and its permissions with the agent

Table 15: Mitigations that vet what is installed, keep a record of what the agent does and put a person in the path of consequential actions, with the techniques of this lecture that ATLAS maps each one to. An asterisk marks a mapping to the parent technique.

Mitigation	Category	What it does	Lecture techniques it maps to
Verify AI Artifacts	Technical (cyber)	Compares a cryptographic checksum to confirm an artifact was not modified	supply-chain compromise*, user execution*
Vulnerability Scanning	Technical (cyber)	Scans model files, products and dependencies for unsafe calls and known flaws before use	publishing a poisoned tool, user execution*
AI Bill of Materials	Policy	Lists every artifact used to build the system, which enables a rapid response to reported vulnerabilities	supply-chain compromise*, user execution*
AI Telemetry Logging	Technical (cyber)	Records each step, data access, tool call and identity of an agent	tool invocation, exfiltration
Human In-the-Loop for AI Agent Actions	Technical (AI)	Requires a person to approve agent actions before they run	tool invocation, exfiltration
AI Red Team	Policy, technical (AI) and technical (cyber)	Runs recurring authorized attack exercises to find and fix flaws	supply-chain compromise, tool invocation, context poisoning, resource consumption
AI Agent Scope Drift Detection	Technical (AI)	Watches whether an agent's planned actions still match its authorized objective, and can pause it if not	none of this lecture's techniques

(Section 1.1). An attacker who controls the agent, or who reaches its configuration, can then switch the check off or route around it.

The authority expansion mitigation also rules out the model as the only enforcer. Authority expansion controls "should not rely solely on system prompts, model alignment, or the agent recognizing that an action is out of scope". A system prompt is text in the model's context, and other text in the same context, such as an injected instruction (Lecture 4), can steer the model. Alignment makes safe behavior more likely. It gives no guarantee for any particular input. A control that depends on the model's behavior fails exactly when an attack succeeds in changing that behavior.

No mitigation names the process that enforces it, and none names a feature of the operating-system kernel or a hardware component. Some mitigations come close. AI Agent Authority Expansion Controls lists kinds of mechanism, such as policy engines, target allowlists and approval gates. AI Agent Tools Permissions Configuration says that its configurations may live in the MCP servers that connect agents to tools, or in a tool's own configuration files. These name a kind of mechanism or a place where a setting is written. They leave open which process must check the setting.

The harness, the operating-system kernel (Section 5.7) and the network are all candidates for enforcing a rule outside the model:

- **The harness.** A check in the program that runs the agent, such as the dispatcher of Lecture 4, sees every tool call with its name and arguments. When the check runs in the agent's own process, it shares that process's permissions, and an attacker who controls the process can switch it off. Such a check is outside the model. It is still inside the agent, and the two quotations above ask for these controls to sit outside the agent.
- **The operating-system kernel.** The operating system confines a process in a sandbox and checks every file that the process actually opens, whatever path string the tool was given. A read that slips past the harness's path check, as reads through `search` did in Lecture 4, still reaches only the files that the sandbox allows.
- **The network.** A component on the network path can allow or refuse each connection that a tool opens, such as the outbound connection in Figure 15.

Each place sees different events. The harness sees tool calls, the operating-system kernel sees the file and process operations of a process, and the network sees connections. Which place enforces which rule is a design decision that ATLAS leaves to the builder of the system. Lecture 6 takes up this decision, starting with the two mitigations that put the rule in the model itself.

The case study that follows shows a real agent whose controls lived in its own configuration, and what attackers did once they reached that configuration (Section 7).

Key points

- In ATLAS, a mitigation is a countermeasure mapped to the techniques it counters and labeled as a policy, a technical control for AI or a technical control for cyber security, and release 2026.09 holds 40 of them.
- In release 2026.09, ATLAS maps most mitigations of the lecture's techniques to the tool call and none to tool poisoning, the rug pull, User Execution: Poisoned AI Agent Tool, Credentials from AI Agent Configuration or Escape to Host, although controls on later steps can still limit these attacks.
- The six mitigation families are the course's grouping of ATLAS's mitigations, and each acts at a different point of a tool call: on installation, on the agent's authority, on the messages, around the tool's execution, by recording activity and asking a person to approve, or on the model.
- The permissions mitigations apply least privilege to a privileged agent, to an agent acting for one user and to shared tools, so that an adversary who steers the agent can do no more than the agent is allowed to do.
- A matching checksum shows only that an artifact is unchanged since publication, and an approval protects the user only from what the approval request shows.
- ATLAS states that authority controls and validation should sit outside the agent, and that authority controls should not rely solely on system prompts, alignment or the agent's own judgment, because a control inside the agent's process or behavior can be disabled or bypassed.
- No ATLAS mitigation names the process that enforces it, so whether the harness, the operating-system kernel or the network enforces a given rule remains a design decision.

7 Case study: attacks on OpenClaw

The previous section showed that ATLAS says which actions to restrict, and sometimes that a control must sit outside the agent, and that it leaves the choice of the enforcing process to the builder of the

system (Section 6). This section studies two documented attacks on OpenClaw, an open-source personal assistant, in which that choice decided the outcome. In both attacks, the controls lived inside the agent's own process and configuration, and an attacker who reached the agent's settings or controlled its inputs switched them off or got past them. The case makes concrete the limitation stated in Section 1, uses techniques of Section 5, and meets again the missing origin check of the MCP Inspector (Section 3).

7.1 OpenClaw and its Gateway

OpenClaw (formerly Clawdbot and Moltbot) is an open-source personal AI assistant that runs on the user's own devices [37]. The user talks to it through chat apps that the user already has, such as WhatsApp, Telegram, Slack, Discord and Signal. The assistant reads each message, calls tools on the user's machine and replies in the same chat. The attacks in this section targeted the versions of early 2026.

OpenClaw kept the part that manages the assistant apart from the part that runs the model. A **control plane** is the process that manages the other parts of a system: it holds their configuration, starts their work and routes their messages. OpenClaw's control plane was the **Gateway**, a long-running process that owned the connections to the chat apps, the conversations and the tools. The Gateway ran on the host machine (Section 5.7), the machine on which OpenClaw was installed, outside any sandbox. In this section, "the host" means that machine, a different sense from the MCP host of Section 1.6.

Figure 16 shows the Gateway among OpenClaw's other parts. In the figure, look at the box labeled "agent's own configuration", which holds the two controls described below, and at the box labeled "WebSocket API", the Gateway API through which a client of the Gateway could rewrite them. The parts were the following:

- **Channels.** A channel was the Gateway's connection to one chat app, and every message from that app reached the Gateway through it.
- **Gateway API.** Every client of the Gateway, such as the command line, the companion apps and the browser interface, connected to it through one API, the Gateway API. The API used **WebSocket**, a protocol for a two-way connection that stays open, so that either side can send a message at any time. By default it listened only on localhost, the address through which a machine reaches its own services (Section 3).
- **Control UI.** The **Control UI** was OpenClaw's browser interface to the Gateway. Through it, the user changed the configuration, the approvals and the channels.
- **Agent runtime.** The agent runtime held the model and its system prompt. OpenClaw built the system prompt of every run from **prompt files**, Markdown files in the agent's workspace. Examples were SOUL.md, which describes the assistant's persona, and HEARTBEAT.md, a checklist for the assistant's periodic runs.
- **Tools.** The model acted through built-in tools such as `exec`, which ran shell commands, and `web_fetch`, which fetched a web page and returned its text.
- **Sandbox.** Tools could run in a Docker container, a sandbox in the sense of Lecture 4. The sandbox was optional and off by default, so tools normally ran on the host.

ATLAS calls `exec` and `web_fetch` the bash skill and the web_fetch skill. In OpenClaw, as in Section 5, a skill is an installable package of instructions built around a SKILL.md file. We therefore call `exec` and `web_fetch` tools and keep the word skill for such packages.

The approval prompt and the sandbox setting limited what the model's commands could do:

- **Approval prompt.** The **approval prompt** asked the user to approve a command before it ran on the host. It applied the human-in-the-loop pattern of Lecture 2, in which a run pauses for a person's decision. Its policy was a file whose fields said when to ask and which commands were allowed. An install could also have no approval prompt. In the install that the second attack used, `exec` ran commands on the host with no approval prompt and no sandbox (Section 7.4).
- **Sandbox setting.** The **sandbox setting** decided whether `exec` ran its commands in the Docker container or on the host. It was a key in a configuration file that the Gateway owned.

Both settings lived in files that the Gateway owned, which we call the agent's own configuration, and the Gateway API could rewrite both. The Control UI used the same API to change them, which is how the user adjusted them.

The Gateway API admitted a client that presented the **Gateway token**, the credential for the Gateway API. The Control UI held the token in the browser, so that it could connect without asking the user each time. OpenClaw treated every client that presented the token as an **operator**, a trusted administrator of that Gateway. The approval prompt protected the host from the model's commands. It did not check what each caller was allowed to do, so it did not separate one operator from another [36].

Holding the token was therefore what made a caller trusted, and any holder could rewrite the approval prompt and the sandbox setting through the Gateway API. A control that an API can rewrite holds only as long as no attacker reaches that API, and the Gateway that served the API ran outside any sandbox. Section 1 stated this limitation in general: a rule enforced inside the agent's own process can be disabled by whatever reaches that process.

7.2 OpenClaw's case studies in ATLAS

In ATLAS release 2026.09, every case study in which OpenClaw is the target is an exercise [19]. As in Section 4.5, an exercise documents a research or red-team demonstration, where an incident documents a real attack.

In the order of their dates, from late January to early February 2026, the case studies are the following:

- **Exposed control interfaces.** A researcher found hundreds of OpenClaw control interfaces open to the internet, read the agent's credentials from its plaintext configuration, and in one instance got the agent to run commands as root inside its container [21]. Some interfaces were open because of a **reverse proxy**, a server that forwards requests from the network to a service on the same machine. The reverse proxy made remote connections look local, and the Gateway trusted local connections.
- **A poisoned skill.** A researcher published a skill with a hidden instruction on ClawdHub, OpenClaw's public registry of skills, and used a script to inflate its download count [22]. In the first eight hours, 16 users downloaded and ran it in Claude Code, an agent that loads the same skill format.
- **One-click remote code execution.** A malicious link let a researcher run commands on the machine that ran OpenClaw. We call this attack the one-click chain, because it began with one click (Section 7.3). An attack **chain** is a sequence of steps in which each step gives the attacker what the next one needs.
- **Command and control through prompt injection.** A web page turned the assistant into a command channel for researchers, an attack we call the command-and-control chain (Section 7.4).

Both chains show where OpenClaw's controls lived and how the attackers reached them.




Figure 16: OpenClaw's parts as documented in January 2026. Chat apps reach the Gateway through channels, the Control UI reaches it through the Gateway API, a WebSocket API on localhost, and the agent runtime builds its system prompt from prompt files. The approval prompt and the sandbox setting sit in the agent's own configuration, which the Gateway API can rewrite. Magenta marks the settings that the attack of Section 7.3 turned off.

7.3 Remote code execution from one click

A malicious link gave a researcher remote code execution (Section 3.4) on the machine that ran OpenClaw. The vulnerability record of the attack, CVE-2026-25253, covers the step in which the Control UI leaked the Gateway token (step 2 below). The record gives a CVSS 3.1 score of 8.8 and lists the versions before 2026.1.29 as affected [34]. ATLAS records the attack as the exercise OpenClaw 1-Click Remote Code Execution [23].

The attack depended on how browsers treat WebSocket connections. The **same-origin policy** is the browser rule that stops a page from reading responses from any origin other than its own. An origin, as in Section 3, is the scheme, the host name and the port of a page's address. Browsers do not apply this policy to WebSocket.

A page may open a WebSocket to any server, and once the connection is open the page can send and read messages freely. A WebSocket server must therefore check the Origin header of each new connection itself. Only that check tells it whether the page that opened the connection belongs to a site it trusts.

The attack proceeded as follows, with the steps numbered as in Figure 17. Each step names the control that failed.

1. **The user opened a link.** The attacker's page ran a script in the user's browser. No control failed at this point, because a browser runs the scripts of every page it loads.
2. **The token went to the attacker.** The script opened the Control UI with a `gatewayUrl` parameter in its address, naming the attacker's server as the Gateway. The Control UI connected to that server without asking the user and sent the stored Gateway token. The control that failed was the secrecy of the token, because the UI treated a parameter in its own address as a trusted setting. The attacker now held the token, and the attacker's script in the user's browser used it in the next steps.
3. **A cross-site WebSocket reached the Gateway.** The script opened a WebSocket from the user's browser to the Gateway on localhost. The control that was missing was the origin check. The Gateway checked no Origin header, so it accepted a connection opened by a page from another site. Listening only on localhost did not help, because the connection came from the user's own browser on the same machine.
4. **The script signed in as the operator.** The script signed in with the stolen token. The token was genuine, so the Gateway treated the script as the operator. The control that failed was authentication. It worked as designed and still could not tell the user from a script that held the user's token.
5. **The approval prompt was turned off.** A call to `exec.approvals.set` turned off the approval prompt for host commands. The control that failed was the approval prompt itself, because its policy was a file that the Gateway API rewrote. Rewriting it required the administrative scope, the permission level for changing settings, and the stolen token carried that scope.
6. **Commands left the sandbox.** A call to `config.patch` set the host for `exec` to the Gateway's own machine, so commands ran on the host instead of in the Docker container. The control that failed was the sandbox, because the sandbox setting was a configuration key that the Gateway owned. Because the sandbox was off by default, this step mattered only on installs that had enabled it.
7. **A command ran on the host.** A call to `node.invoke` ran a shell command on the host. No control remained, because the approval prompt was off and commands no longer ran in the sandbox.

The researcher needed no flaw in the sandbox or in the approval logic, because "these protections are managed via the API itself" [12]. The API that let the user adjust the controls also let a script with the user's token switch them off.

ATLAS maps each step of the chain to a technique. The preparation steps used Develop Capabilities and Stage Capabilities. The numbered steps above then used User Execution: Malicious Link (step 1), Exploitation for Credential Access (step 2), Exploitation for Defense Evasion (step 3), Valid Accounts (step 4), Modify AI Agent Configuration (step 5), Escape to Host (step 6, Section 5) and Command and Scripting Interpreter (step 7).

> **Definition 7.1** (Modify AI Agent Configuration)**.** "Adversaries may modify the configuration files for AI agents on a system. This allows malicious changes to persist beyond the life of a single agent and affects any agents that share the configuration." [19]

ATLAS lists, among such changes, edits to the system prompt and the weakening of security controls that restrict the agent. Modify AI Agent Configuration is also the only technique of this chain whose platforms field lists Agentic AI alone. Develop Capabilities lists every platform, and the remaining techniques list only Enterprise.

In our reading, most of the chain used techniques that are not




Figure 17: The one-click chain on the user's machine (CVE-2026-25253). Magenta marks what the adversary controls, and the numbered circles give the order of the steps. The calls to the Gateway are drawn schematically, and the command in the host shell is the researchers' harmless example.

specific to AI systems: a stolen credential, a missing check in a WebSocket server and a shell command. The step specific to agents was the change to the agent's configuration.

A stolen Gateway token was enough to turn off the approval prompt, leave the sandbox and run a command on the host. The Inspector's proxy had the same missing origin check before its fix (Section 3). In both cases, a page from another site reached a service on the user's own machine. The Inspector's proxy also asked for no credential, whereas the Gateway required a token, which this chain had stolen first. A component that acts on requests arriving through a browser must check which page sent them.

7.4 Command and control through a web page

A web page that the user asked OpenClaw to summarize turned the assistant into a command channel for the researchers who wrote the page [16]. ATLAS records the attack as the exercise OpenClaw Command & Control via Prompt Injection [24]. Unlike the one-click chain, it stole no credential and changed no security setting.

The attack began with indirect prompt injection (Section 4.6), through the text of a web page that a tool returned. It then used a jailbreak. A **jailbreak** gets a model past the limits it was trained to respect. Those limits come from the model's safety alignment, the training that steers it toward safe behavior within its task (Section 6).

The jailbreak worked through control sequences. **Control sequences** are the markers of a prompt format that tell the model where each part of its input begins and ends. They mark, for example, the end of a tool result, the start of a user message, or a passage of the model's own reasoning. They are ordinary text, so a page can imitate them.

The goal of the attack was command and control. **Command and control** is a channel through which an attacker sends tasks to a compromised system, here a compromised agent, and the system carries them out.

The attack proceeded as follows, with the steps numbered as in Figure 18:

1. **Preparation.** The researchers read OpenClaw's public repository to learn its prompt format. They wrote the injection and hosted a web page, an install script and a to-do list on a look-alike site, whose name imitated an OpenClaw resource.
2. **The page entered the context.** The user took the look-alike site for a genuine OpenClaw resource and asked OpenClaw to summarize the page. `web_fetch` returned the page's text to the model as a tool result. The safeguard that failed was the user's judgment of which sites to trust, and the look-alike name was chosen to mislead it.
3. **Indirect prompt injection.** The model read the text of the page as instructions. The page told it to set up OpenClaw by running a script. The control that failed was the separation of data from instructions in the model's context.
4. **A jailbreak with spoofed control sequences.** The page imitated OpenClaw's control sequences for the end of a tool result, the start of a user message and the model's reasoning. The model therefore treated the page's text as the user's request and as its own reasoning. The control that failed was the model's safety alignment.
5. **A script ran through `exec`.** The model called `exec` with a command that downloaded the install script and passed it straight to the shell, in the form `curl ... | bash`. No control stopped the call. The install that the researchers used asked for no approval and had the sandbox off, and their report names no OpenClaw version.
6. **HEARTBEAT.md was changed.** The script appended the researchers' instructions to HEARTBEAT.md, a prompt file that stayed on disk. No control guarded it, because the prompt files were writable by the agent's own tools.
7. **Every new thread was poisoned.** In the early-2026 versions, HEARTBEAT.md went into the system prompt of every new thread, that is, every new conversation with the assistant. The instructions therefore arrived as trusted input, and the user only had to greet the assistant to trigger them. The current documentation of OpenClaw no longer lists HEARTBEAT.md as a prompt file.
8. **A command-and-control loop.** The agent fetched a to-do list from the researchers' server with `web_fetch` and ran each task with `exec`. From then on, the agent carried out the researchers' tasks with the user's tools and credentials.

The change to HEARTBEAT.md and its reload are the context poisoning of Section 5.8. An instruction planted in persistent memory takes effect later, in another thread, as trusted input. Because the prompt file outlived the thread in which it was changed, the attack also outlived it.

ATLAS maps the chain, after its preparation steps, to techniques that follow the numbered steps above: Masquerading and




Figure 18: The command-and-control chain. Magenta marks what the adversary controls, and the numbered circles give the order of the steps. The user's request is illustrative, and the text of the page and of HEARTBEAT.md is abbreviated.

Drive-by Compromise (step 2), LLM Prompt Injection: Indirect (step 3), LLM Jailbreak (step 4), AI Agent Tool Invocation (step 5), Modify AI Agent Configuration (step 6), and LLM Prompt Injection: Direct and AI Agent Context Poisoning: Thread (step 7). Step 8 maps to two separate techniques, AI Agent and Machine Compromise: Local AI Agent.

ATLAS records step 7 as a direct prompt injection. The planted instructions now reached the model through its own system prompt, with no tool result in between. AI Agent is a technique of the Command and Control tactic, in which an adversary uses an agent on the victim's system as its command channel. Modify AI Agent Configuration appears in both chains. In the one-click chain it switched off the approval prompt, and here it changed a prompt file.

With nothing switched off, a page that the agent read led it to add the researchers' instructions to its own system prompt. In the install that the researchers used, `exec` ran on the host with no approval prompt and no sandbox, and the files that define the agent were writable by the agent. The only remaining safeguard was the model's own behavior, and text in a page got past it.

7.5 The controls that failed

Every control that failed or was missing in the two chains was a setting or a file in the agent's own configuration, or the behavior of the model that the agent called. Table 16 lists these controls. For each one, it gives where the control lived, how the attack got past it, and the ATLAS mitigations mapped to the technique that the attack used at that point.

Each row follows from where OpenClaw placed the control. The approval policy was a file that the Gateway API rewrote, with the administrative scope that the stolen token carried. The sandbox setting was a key in the agent's own configuration, and the Gateway that owned this file was not itself sandboxed. The prompt files were writable by the same tools that the injection controlled. The control sequences were part of the prompt format, and untrusted text could repeat them.

ATLAS maps mitigations to techniques, and its case studies name no mitigation [19]. The last column therefore lists what ATLAS offers against each technique in general. It is not a record of what OpenClaw lacked.

For the changes to the configuration and the escape from the sandbox, ATLAS offers little. Against Modify AI Agent Configuration, it maps only AI Red Team (Section 6.6). None of its mappings restricts who may change an agent's configuration. Against Escape to Host, ATLAS maps no mitigation at all.

Against LLM Jailbreak, ATLAS maps AI Red Team together with mitigations that act on the model and its inputs. Generative AI Guardrails screen what passes between users, tools and the model. Generative AI Guidelines and Generative AI Model Alignment shape the model's behavior through its instructions and its training, and belong to the family *Harden the model itself* (Section 6.3). In the second attack, OpenClaw did not filter the control sequences out of the fetched page, and they got past the model's own safety alignment [16, 24].

Every row has the same cause. Each control could be changed or bypassed through a path that the agent itself offered: the Gateway API rewrote the settings, the agent's own tools wrote the prompt files, and text in a page steered the model. In the one-click chain, the script reached the settings through the Gateway API with a stolen token. In the command-and-control chain, the injected instructions led the agent's own tools to write the file.

The case illustrates the limitation stated in Section 1: a rule enforced inside the agent's own process and configuration can be disabled by whoever reaches the agent's settings or controls its inputs. ATLAS names what to restrict. It does not name the process that should enforce the restriction (Section 6). OpenClaw placed every one of these controls within reach of the Gateway API, the agent's own tools or the text that the agent read.

Key points

- OpenClaw's Gateway, its control plane, ran on the host outside any sandbox, and any caller holding the Gateway token was a trusted operator who could rewrite the approval prompt and the sandbox setting through the Gateway API.
- In the one-click chain (CVE-2026-25253), the Control UI sent its token to a server named in its own address, and the Gateway accepted a cross-site WebSocket because it checked no Origin header, so a page could sign in as the operator.
- With the stolen token, the script turned off the approval prompt for host commands, moved `exec` out of the sandbox and ran a command on the host, all through the Gateway API that the user also used to adjust these controls.
- In the command-and-control chain, a page that the agent summarized used indirect prompt injection and spoofed control sequences to make the agent run a script, which wrote the researchers' instructions into HEARTBEAT.md, a prompt file that the early-2026 versions loaded into every new thread.
- The command-and-control chain changed no security setting,

Table 16: Controls that failed or were missing in the two attacks on OpenClaw. The last column lists the mitigations that ATLAS maps to the technique the attack used, with the technique in parentheses.

Control	Where it lived	How the attack got past it	ATLAS mitigations mapped to the technique
The approval prompt for host commands	A policy file that the Gateway API could rewrite	One-click chain: a call with the stolen token set it to off	AI Red Team only (Modify AI Agent Configuration)
The sandbox	A configuration key that the Gateway API could patch	One-click chain: a call with the stolen token set the host for `exec` to the Gateway's machine	None (Escape to Host)
The prompt files	Workspace files that the agent's own tools could write	Command-and-control chain: no check existed, and a script that the agent ran appended the researchers' instructions	AI Red Team only (Modify AI Agent Configuration)
The model's alignment	The model and its prompt format	Command-and-control chain: spoofed control sequences in the page got past it	Generative AI Guardrails, Generative AI Guidelines, Generative AI Model Alignment and AI Red Team (LLM Jailbreak)

because in the install that the researchers used, `exec` ran on the host with no approval prompt and no sandbox, and the prompt files were writable by the agent's own tools.

- Modify AI Agent Configuration appears in both chains, and ATLAS maps only AI Red Team to it and no mitigation at all to Escape to Host.
- Every control that failed was a setting or a file in the agent's own configuration, or the behavior of the model that the agent called, and the attackers reached each one through the Gateway API, the agent's own tools or the text of a page.

References

[1] Anthropic. Introducing the Model Context Protocol. https://www.anthropic.com/news/model-context-protocol, November 2024. Published 2024-11-25. Accessed 2026-10-15.

[2] Luca Beurer-Kellner and Marc Fischer. MCP security notification: Tool poisoning attacks. Invariant Labs blog, https://invariantlabs.ai/blog/mcp-security-notification-tool-poisoning-attacks, April 2025. Published 2025-04-01. Accessed 2026-10-15.

[3] Luca Beurer-Kellner and Marc Fischer. WhatsApp MCP exploited: Exfiltrating your message history via MCP. Invariant Labs blog, https://invariantlabs.ai/blog/whatsapp-mcp-exploited, April 2025. Published 2025-04-07. The confirmation dialog for the send_message call showed a short message body and hid the exfiltrated history off screen to the right. Accessed 2026-10-15.

[4] Idan Dardikman. First malicious MCP in the wild: The Postmark backdoor that's stealing your emails. Koi Security blog, Internet Archive copy, https://web.archive.org/web/20250929094654/https://www.koi.security/blog/postmark-mcp-npm-malicious-backdoor-email-theft, September 2025. Published 2025-09-25; the original address now redirects. Accessed 2026-10-15.

[5] GitHub Security Advisory. Inspector proxy server vulnerabilities (GHSA-7f8r-222p-6f5g, CVE-2025-49596). https://github.com/modelcontextprotocol/inspector/security/advisories/GHSA-7f8r-222p-6f5g, June 2025. Published 2025-06-13. CVSS 4.0 base score 9.4 (critical). Affected: `@modelcontextprotocol/inspector` below 0.14.1; patched in 0.14.1. Credit: Rémy Marot (Tenable). Accessed 2026-10-15.

[6] GitHub Security Advisory. mcp-server-git has missing path validation when using –repository flag (GHSA-j22h-9j4x-23w5, CVE-2025-68145). https://github.com/advisories/GHSA-j22h-9j4x-23w5, December 2025. Published 2025-12-17. Accessed 2026-10-15.

[7] GitHub Security Advisory. Claude Code leaks data via malicious environment configuration before trust confirmation (GHSA-jh7p-qr78-84p7, CVE-2026-21852). https://github.com/anthropics/claude-code/security/advisories/GHSA-jh7p-qr78-84p7, January 2026. Published 2026-01-21. Fixed in Claude Code 2.0.65. Accessed 2026-10-15.

[8] Imri Goldberg. Exposing the unseen: Mapping MCP servers across the internet. Knostic blog, https://www.knostic.ai/blog/mapping-mcp-servers-study, July 2025. Published 2025-07-17. Accessed 2026-10-15.

[9] Ravie Lakshmanan. First malicious MCP server found stealing emails in rogue Postmark-MCP package. The Hacker News, https://thehackernews.com/2025/09/first-malicious-mcp-server-found.html, September 2025. Published 2025-09-29. Accessed 2026-10-15.

[10] Ravie Lakshmanan. Three flaws in Anthropic MCP Git server enable file access and code execution. The Hacker News, https://thehackernews.com/2026/01/three-flaws-in-anthropic-mcp-git-server.html, January 2026. Published 2026-01-20. CVE-2025-68143, CVE-2025-68144, CVE-2025-68145, reported by Cyata. Accessed 2026-10-15.

[11] LangChain. Tools. LangChain documentation, https://docs.langchain.com/oss/python/langchain/tools, 2026. Tool calling in LangChain and LangGraph. Accessed 2026-10-15.

[12] Mav Levin. 1-click RCE to steal your OpenClaw data and keys (CVE-2026-25253). depthfirst, https://depthfirst.com/post/1-click-rce-to-steal-your-moltbot-data-and-keys, February 2026. Published 2026-02-01. Accessed 2026-10-15.

[13] Avi Lumelsky. Critical RCE vulnerability in Anthropic MCP Inspector – CVE-2025-49596. Oligo Security blog, https://www.oligo.security/blog/critical-rce-vulnerability-in-anthropic-mcp-inspector-cve-2025-49596, June 2025. Published 2025-06-27. Accessed 2026-10-15.

[14] Jessica Lyons. Claude collaboration tools left the door wide open to remote code execution. The Register, https://www.theregister.com/2026/02/26/clade_code_cves/, February 2026. Published 2026-02-26. Reports research by Aviv Donenfeld and Oded Vanunu of Check Point (CVE-2025-59536 and CVE-2026-21852). Accessed 2026-10-15.

[15] Rahul Marchand, Art O Cathain, Jerome Wynne, Philippos Maximos Giavridis, Sam Deverett, John Wilkinson, Jason Gwartz, and Harry Coppock. Quantifying frontier LLM capabilities for container sandbox escape. In *Proceedings of the 43rd International Conference on Machine Learning (ICML)*, 2026. Authors as listed by ICML 2026 (icml.cc/virtual/2026/poster/66709); arXiv:2603.02277 v3 (2026-08-01) adds Stuart Jennings, Freddy Tuxworth and Tolga H. Dur. Introduces SandboxEscapeBench.

[16] Conor McCauley, Kasimir Schulz, Ryan Tracey, and Jason Martin. Exploring the security risks of AI assistants like OpenClaw. HiddenLayer, https://www.hiddenlayer.com/research/exploring-the-security-risks-of-ai-assistants-like-openclaw, February 2026. Published 2026-02-03. Accessed 2026-10-15.

[17] Marco Milanta and Luca Beurer-Kellner. GitHub MCP exploited: Accessing private repositories via MCP. Invariant Labs blog, https://invariantlabs.ai/blog/mcp-github-vulnerability, May 2025. Published 2025-05-26. Accessed 2026-10-15.

[18] MITRE. CWE-306: Missing authentication for critical function. Common Weakness Enumeration, version 4.20, https://cwe.mitre.org/data/definitions/306.html, 2026. Accessed 2026-10-15.

[19] MITRE. MITRE ATLAS (Adversarial Threat Landscape for AI Systems), release 2026.09. https://atlas.mitre.org; data: mitre-atlas/atlas-data, dist/v6/ATLAS-2026.09.yaml, September 2026. Released 2026-09-15. 208 technique entries (120 techniques, 88 sub-techniques), 16 tactics, 40 mitigations, 73 case studies. Accessed 2026-10-15.

[20] MITRE ATLAS. Data exfiltration via an MCP server used by Cursor (case study AML.CS0045). https://atlas.mitre.org/studies/AML.CS0045, 2026. In ATLAS release 2026.09. Accessed 2026-10-15.

[21] MITRE ATLAS. Exposed ClawdBot control interfaces leads to credential access and execution (case study AML.CS0048). https://atlas.mitre.org/studies/AML.CS0048, 2026. In ATLAS release 2026.09. Accessed 2026-10-15.

[22] MITRE ATLAS. Supply chain compromise via poisoned ClawdBot skill (case study AML.CS0049). https://atlas.mitre.org/studies/AML.CS0049, 2026. In ATLAS release 2026.09. Accessed 2026-10-15.

[23] MITRE ATLAS. OpenClaw 1-click remote code execution (case study AML.CS0050). https://atlas.mitre.org/studies/AML.CS0050, 2026. Exercise reported by depthfirst; nine steps. In ATLAS release 2026.09. Accessed 2026-10-15.

[24] MITRE ATLAS. OpenClaw command & control via prompt injection (case study AML.CS0051). https://atlas.mitre.org/studies/AML.CS0051, 2026. Exercise reported by HiddenLayer; eighteen steps. In ATLAS release 2026.09. Accessed 2026-10-15.

[25] MITRE ATLAS. Poisoned Postmark MCP server email exfiltration (case study AML.CS0053). https://atlas.mitre.org/studies/AML.CS0053, 2026. Incident, September 2025; nine steps. In ATLAS release 2026.09. Accessed 2026-10-15.

[26] MITRE ATLAS. Data exfiltration via remote poisoned MCP tool (case study AML.CS0054). https://atlas.mitre.org/studies/AML.CS0054, 2026. In ATLAS release 2026.09. Accessed 2026-10-15.

[27] Model Context Protocol. Connect to local MCP servers. https://modelcontextprotocol.io/docs/develop/connect-local-servers, 2026. Claude Desktop and the Filesystem server as the example. Accessed 2026-10-15.

[28] Model Context Protocol. MCP Inspector: visual testing tool for MCP servers. https://github.com/modelcontextprotocol/inspector, 2026. npm package `@modelcontextprotocol/inspector`. Accessed 2026-10-15.

[29] Model Context Protocol. What is the model context protocol (MCP)? https://modelcontextprotocol.io/docs/getting-started/intro, 2026. Accessed 2026-10-15.

[30] Model Context Protocol. MCP Python SDK: the official Python SDK for Model Context Protocol servers and clients. https://github.com/modelcontextprotocol/python-sdk, 2026. PyPI package `mcp`. Accessed 2026-10-15.

[31] Model Context Protocol. Model context protocol servers: reference implementations. https://github.com/modelcontextprotocol/servers, 2026. Reference servers maintained by the MCP steering group: Everything, Fetch, Filesystem, Git, Memory, Sequential Thinking, Time. Accessed 2026-10-15.

[32] Model Context Protocol. Model context protocol specification, revision 2026-07-28. https://modelcontextprotocol.io/specification/2026-07-28, 2026. Pages cited: overview, architecture, base protocol, transports (stdio, Streamable HTTP), cancellation, tools, schema reference, changelog. Accessed 2026-10-15.

[33] National Vulnerability Database. CVE-2026-23744: MCPJam inspector remote code execution. https://nvd.nist.gov/vuln/detail/CVE-2026-23744, January 2026. Published 2026-01-16. Versions 1.4.2 and earlier; fixed in 1.4.3. CVSS 3.1 base score 9.8 (critical). Accessed 2026-10-15.

[34] National Vulnerability Database. CVE-2026-25253: OpenClaw sends its gateway token to a gatewayUrl taken from a query string.

https://nvd.nist.gov/vuln/detail/CVE-2026-25253, February 2026. Published 2026-02-01. OpenClaw (also Clawdbot, Moltbot) before 2026.1.29. CVSS 3.1 base score 8.8 (high). Accessed 2026-10-15.

[35] npm. postmark-mcp: package metadata. npm registry, https://registry.npmjs.org/postmark-mcp, 2025. Created 2025-09-15T10:44Z; version 1.0.16 published 2025-09-17T08:59Z; all versions unpublished 2025-09-25. Accessed 2026-10-16.

[36] OpenClaw. Exec approvals. OpenClaw documentation, https://docs.openclaw.ai/tools/exec-approvals, 2026. Accessed 2026-10-16.

[37] OpenClaw. OpenClaw: an open-source personal AI assistant. https://github.com/openclaw/openclaw, 2026. Formerly Clawdbot and Moltbot; renamed OpenClaw on 2026-01-29. Accessed 2026-10-15.

[38] OWASP. OWASP MCP top 10, version 0.1 (beta). https://owasp.org/www-project-mcp-top-10/, 2026. Repository OWASP/www-project-mcp-top-10, commit 165fe0f of 2026-07-29; entry identifiers carry the year 2025 (MCP01:2025 to MCP10:2025). Project lead Vandana Verma Sehgal. Accessed 2026-10-15.

[39] Or Peles. Critical RCE vulnerability in mcp-remote: CVE-2025-6514 threatens LLM clients. JFrog blog, https://jfrog.com/blog/2025-6514-critical-mcp-remote-rce-vulnerability/, July 2025. Published 2025-07-09. Accessed 2026-10-15.

[40] Bill Toulas. Asana warns MCP AI feature exposed customer data to other orgs. BleepingComputer, https://www.bleepingcomputer.com/news/security/asana-warns-mcp-ai-feature-exposed-customer-data-to-other-orgs/, June 2025. Published 2025-06-18. Accessed 2026-10-15.