

GUÍA GRATUITA

¿QUÉ ES BITCOIN?

Todo lo que necesitás saber para entenderlo de verdad: quién lo creó, cómo funciona, cómo se compra, cómo se guarda y qué riesgos tiene. Incluye el whitepaper original.

Ezequiel Bagnato
Comunidad Inversores · @ezebagnato

CONTENIDO

LO QUE VAS A APRENDER

01 Bitcoin en una frase

02 Cómo nació: la historia en 6 fechas

03 Cómo funciona: la blockchain

04 La minería y el halving

05 Por qué solo habrá 21 millones

06 Cómo se compra (y se puede comprar poquito)

07 Cómo se guarda: billeteras y frase semilla

08 Los riesgos que nadie te cuenta

09 Glosario rápido

10 El whitepaper explicado + el original completo

ANTES DE EMPEZAR

Esta guía es educativa. No es una recomendación de inversión: Bitcoin puede subir y bajar mucho. Informate, entendé lo que comprás y nunca pongas dinero que no podés perder.

BITCOIN EN UNA FRASE

01

DINERO DIGITAL QUE NO TIENE DUEÑO

Bitcoin es una moneda que existe solo en internet y que **no la controla ningún banco, empresa ni gobierno**. Las personas se la mandan directamente entre ellas, desde el celular o la compu, a cualquier parte del mundo y a cualquier hora.

¿Quién lleva la cuenta de cuánto tiene cada uno? Nadie en particular y todos a la vez: miles de computadoras en el mundo guardan una copia del mismo registro y se controlan entre ellas.



Con un banco

El banco guarda tu dinero, aprueba cada pago y puede congelar tu cuenta. Los envíos al exterior tardan días y tienen comisiones altas.

Con Bitcoin

Vos guardás tus propias monedas. Un envío a otro país llega en minutos y nadie lo puede frenar ni revertir.

CÓMO NACIÓ

02

LA HISTORIA EN 6 FECHAS

2008 — **31 de octubre.** Alguien con el nombre de **Satoshi Nakamoto** publica el whitepaper: 9 páginas que explican cómo hacer dinero digital sin bancos. Fue en plena crisis financiera mundial. Hasta hoy nadie sabe quién es.

2009 — **3 de enero.** Nace el primer bloque de la blockchain. Satoshi le deja un mensaje: el titular de un diario británico sobre un nuevo rescate a los bancos.

2010 — **22 de mayo.** Primera compra conocida con bitcoin: **2 pizzas por 10.000 BTC**. Por eso cada 22 de mayo se festeja el "Bitcoin Pizza Day".

2012 — Primer **halving**: la emisión de bitcoins nuevos se corta a la mitad. Desde ahí se repite cada 4 años más o menos.

2024 — En EE.UU. se aprueban los **ETF de bitcoin**: fondos que se compran en la bolsa como una acción. En abril ocurre el cuarto halving.

Hoy — Lo usan millones de personas, empresas y hasta algunos gobiernos. Y sigue funcionando sin dueño, como el primer día.

CÓMO FUNCIONA

03

LA BLOCKCHAIN: UN CUADERNO QUE NADIE PUEDE BORRAR


Imaginá un cuaderno donde se anota cada movimiento de bitcoin: "Ana le mandó 0,01 a Juan". Ese cuaderno es la **blockchain** (cadena de bloques).

3 cosas que lo hacen especial

1. Es público. Cualquiera puede ver todos los movimientos (sin nombres: solo direcciones, que son como números de cuenta).

2. Está copiado en miles de computadoras (llamadas *nodos*). Si una se apaga o miente, las demás la ignoran.

3. Las hojas están encadenadas. Cada bloque nuevo lleva una "huella digital" (hash) del anterior. Cambiar un dato viejo rompería todas las huellas que siguen, y toda la red se daría cuenta.



DATO

Más o menos cada **10 minutos** se agrega un bloque nuevo con los últimos movimientos. Por eso, cuando mandás bitcoin, conviene esperar algunas confirmaciones (bloques) para darlo por firme.

MINERÍA Y HALVING

04

¿DE DÓNDE SALEN LOS BITCOINS NUEVOS?

Los **mineros** son computadoras especializadas que compiten para armar el próximo bloque. Para ganar tienen que resolver un problema matemático que solo se resuelve probando millones de veces por segundo. Eso gasta electricidad, y ese gasto es lo que protege a la red: hacer trampa costaría más que lo que se ganaría.

El que gana se lleva un **premio en bitcoins nuevos** más las comisiones de los movimientos del bloque. Así entran bitcoins a circular.

El halving: el premio se corta a la mitad

Cada 210.000 bloques (unos 4 años), el premio se reduce a la mitad:

2009	2012	2016	2020	2024
50 BTC	25 BTC	12,5	6,25	3,125

POR QUÉ IMPORTA

Cada halving hace que entren menos bitcoins nuevos al mercado. El próximo se espera para **2028**. Ojo: que históricamente el precio haya subido después de los halvings no garantiza que vuelva a pasar.

ESCASEZ

05

SOLO VAN A EXISTIR 21 MILLONES

A diferencia del peso o del dólar, que los bancos centrales pueden imprimir, el límite de Bitcoin está escrito en su código: **nunca habrá más de 21 millones**. Para cambiarlo, la mayoría de la red tendría que aceptarlo, y nadie tiene incentivos para hacerlo.

Ya se crearon **más del 94%**. Como el premio a los mineros se sigue cortando a la mitad, los que faltan van a ir saliendo cada vez más despacio: el último bitcoin se va a minar cerca del año **2140**.



¿Y si un bitcoin es muy caro?

No hace falta comprar uno entero. Cada bitcoin se divide en **100 millones de partes** llamadas **satoshis** (o "sats"). Podés comprar el equivalente a unos pocos dólares.

> **LA COMPARACIÓN**
>
> Por ser escaso y no depender de nadie, mucha gente lo compara con el **oro** y lo llama "oro digital". Es una comparación, no una garantía: su precio es mucho más volátil que el del oro.

CÓMO SE COMPRA

06

TUS PRIMEROS SATS, PASO A PASO

Yo uso Binance

Es el exchange con el que trabajo. En Argentina está registrado en la CNV como proveedor de servicios de activos virtuales (PSAV). Registrate con mi link: escaneá el código o tocá **acá**.

Link de referido.

1 **Creá tu cuenta con mi link** y verificá tu identidad: te piden DNI y una selfie. Es normal, lo exige la ley.

2 **Activá la verificación en dos pasos (2FA)** con una app como Google Authenticator. Es lo que más protege tu cuenta.

3 **Cargá pesos** por transferencia o comprá USDT (un dólar digital) por P2P, de persona a persona dentro del exchange.

4 **Activá la compra recurrente de BTC (DCA).** Binance te deja comprar todos los días desde **1 dólar**: con unos **$1.600 pesos** ya podés empezar a juntar bitcoin de a poco, sin depender del precio de un solo día.

▶ Mirá en mi video cómo activarla paso a paso

5 **Decidí dónde guardarlo.** Si juntaste un monto que te importa, pasalo a tu propia billetera (siguiente página).

OJO

Si alguien te escribe por privado prometiendo ganancias o pidiéndote bitcoin, es estafa. Siempre.

CÓMO SE GUARDA

07

BILLETERAS Y LA FRASE SEMILLA

Una billetera (wallet) no guarda las monedas: guarda la **llave** que te permite moverlas. Quien tiene la llave, tiene los bitcoins.

En el exchange

Cómodo para empezar, pero la llave la tiene la empresa. Si quiebra o te bloquea la cuenta, no podés mover tu dinero.

Billetera en el celu

"Caliente": una app donde la llave la tenés vos. Ideal para montos chicos y de uso diario.

Billetera física ("fría")

Un dispositivo tipo pendrive que guarda la llave sin conexión a internet. Es la opción más segura para ahorros de largo plazo.



La frase semilla

Al crear tu billetera te da **12 o 24 palabras**. Con ellas podés recuperar todo si perdés el celu. Por eso:

✔ Escribila en papel y guardala en un lugar seguro. ✘ Nunca le saques foto ni la guardes en la nube. ✘ **Nunca se la des a nadie**: ningún soporte técnico real te la va a pedir.

RIESGOS

08

LO QUE NADIE TE CUENTA

Sube y baja muchísimo

En 2022 bitcoin cayó más de 70% desde su máximo de fines de 2021. Puede pasar de nuevo. Si te desespera ver tu dinero a la mitad, invertí menos.

Si perdés la llave, lo perdés todo

No hay "olvidé mi contraseña". Sin la frase semilla, nadie puede devolverte tus bitcoins.

Los envíos no se pueden deshacer

Si mandás a una dirección equivocada, ese dinero no vuelve. Revisá siempre la dirección (y probá primero con un monto chico).

Estafas

Falsos "asesores", grupos que prometen ganancias fijas, apps truchas que copian a las reales. Si prometen ganar seguro, es mentira.

Apalancamiento

Algunas plataformas te dejan operar con más dinero del que tenés. Aumenta las ganancias y también las pérdidas: podés perder todo en minutos. No es para empezar.

LA REGLA DE ORO

Invertí solo lo que podés dejar quieto varios años sin necesitarlo.

GLOSARIO

09

LAS PALABRAS QUE VAS A ESCUCHAR

BTC
La abreviatura de bitcoin, como USD para el dólar.

Blockchain
El registro público donde quedan anotados todos los movimientos.

Minería
El proceso que agrega bloques nuevos y crea los bitcoins que faltan.

Exchange
Plataforma para comprar, vender y cambiar criptomonedas.

Frase semilla
Las 12 o 24 palabras que permiten recuperar tu billetera. Secreta siempre.

DCA
Comprar un monto fijo cada cierto tiempo, sin importar el precio del día.

Sats (satoshis)
La parte más chica de un bitcoin: 1 BTC = 100.000.000 sats.

Nodo
Una computadora que guarda una copia de la blockchain y controla que se cumplan las reglas.

Halving
El recorte a la mitad del premio de los mineros, cada unos 4 años.

Wallet
La billetera que guarda tu llave para mover tus bitcoins.

Stablecoin (USDT, USDC)
Cripto que copia el valor del dólar. Se usa mucho para entrar y salir de bitcoin.

HODL
Mantener a largo plazo sin vender por los movimientos del día.

EL WHITEPAPER

10

LAS 9 PÁGINAS QUE LO EMPEZARON TODO

El whitepaper se llama **"Bitcoin: A Peer-to-Peer Electronic Cash System"** ("Bitcoin: un sistema de dinero electrónico de persona a persona"). Está completo, en su idioma original (inglés), en las páginas que siguen. Acá lo tenés resumido:

1. **El problema:** los pagos por internet dependen de bancos e intermediarios que cobran, tardan y pueden revertir pagos.
2. **El "doble gasto":** el gran desafío del dinero digital es evitar que alguien gaste dos veces la misma moneda sin un banco que lo controle.
3. **La solución:** un registro público con fecha y hora de cada movimiento, compartido por toda la red.
4. **Prueba de trabajo:** para agregar movimientos hay que gastar poder de cómputo. Reescribir el pasado costaría rehacer todo ese trabajo.
5. **La red:** los nodos aceptan siempre la cadena más larga, la que tiene más trabajo acumulado.
6. **El incentivo:** quien agrega un bloque cobra monedas nuevas y comisiones, así le conviene más jugar limpio que atacar.
7. **Privacidad:** los movimientos son públicos, pero no figuran nombres, solo direcciones.
8. **Seguridad:** mientras la mayoría del poder de cómputo sea honesto, un atacante prácticamente no puede alcanzarla.

DOCUMENTO ORIGINAL

EL WHITEPAPER DE SATOSHI NAKAMOTO

Publicado el 31 de octubre de 2008. A continuación, las 9 páginas originales tal cual las escribió su autor, en inglés.

Tip: si no leés inglés, podés pedirle a una IA que te lo traduzca párrafo por párrafo mientras lo leés.

Bitcoin: A Peer-to-Peer Electronic Cash System

Satoshi Nakamoto
satoshin@gmx.com
www.bitcoin.org

Abstract. A purely peer-to-peer version of electronic cash would allow online payments to be sent directly from one party to another without going through a financial institution. Digital signatures provide part of the solution, but the main benefits are lost if a trusted third party is still required to prevent double-spending. We propose a solution to the double-spending problem using a peer-to-peer network. The network timestamps transactions by hashing them into an ongoing chain of hash-based proof-of-work, forming a record that cannot be changed without redoing the proof-of-work. The longest chain not only serves as proof of the sequence of events witnessed, but proof that it came from the largest pool of CPU power. As long as a majority of CPU power is controlled by nodes that are not cooperating to attack the network, they'll generate the longest chain and outpace attackers. The network itself requires minimal structure. Messages are broadcast on a best effort basis, and nodes can leave and rejoin the network at will, accepting the longest proof-of-work chain as proof of what happened while they were gone.


1. Introduction

Commerce on the Internet has come to rely almost exclusively on financial institutions serving as trusted third parties to process electronic payments. While the system works well enough for most transactions, it still suffers from the inherent weaknesses of the trust based model. Completely non-reversible transactions are not really possible, since financial institutions cannot avoid mediating disputes. The cost of mediation increases transaction costs, limiting the minimum practical transaction size and cutting off the possibility for small casual transactions, and there is a broader cost in the loss of ability to make non-reversible payments for non-reversible services. With the possibility of reversal, the need for trust spreads. Merchants must be wary of their customers, hassling them for more information than they would otherwise need. A certain percentage of fraud is accepted as unavoidable. These costs and payment uncertainties can be avoided in person by using physical currency, but no mechanism exists to make payments over a communications channel without a trusted party.

What is needed is an electronic payment system based on cryptographic proof instead of trust, allowing any two willing parties to transact directly with each other without the need for a trusted third party. Transactions that are computationally impractical to reverse would protect sellers from fraud, and routine escrow mechanisms could easily be implemented to protect buyers. In this paper, we propose a solution to the double-spending problem using a peer-to-peer distributed timestamp server to generate computational proof of the chronological order of transactions. The system is secure as long as honest nodes collectively control more CPU power than any cooperating group of attacker nodes.

2. Transactions

We define an electronic coin as a chain of digital signatures. Each owner transfers the coin to the next by digitally signing a hash of the previous transaction and the public key of the next owner and adding these to the end of the coin. A payee can verify the signatures to verify the chain of ownership.




The problem of course is the payee can't verify that one of the owners did not double-spend the coin. A common solution is to introduce a trusted central authority, or mint, that checks every transaction for double spending. After each transaction, the coin must be returned to the mint to issue a new coin, and only coins issued directly from the mint are trusted not to be double-spent. The problem with this solution is that the fate of the entire money system depends on the company running the mint, with every transaction having to go through them, just like a bank.

We need a way for the payee to know that the previous owners did not sign any earlier transactions. For our purposes, the earliest transaction is the one that counts, so we don't care about later attempts to double-spend. The only way to confirm the absence of a transaction is to be aware of all transactions. In the mint based model, the mint was aware of all transactions and decided which arrived first. To accomplish this without a trusted party, transactions must be publicly announced [1], and we need a system for participants to agree on a single history of the order in which they were received. The payee needs proof that at the time of each transaction, the majority of nodes agreed it was the first received.

3. Timestamp Server


The solution we propose begins with a timestamp server. A timestamp server works by taking a hash of a block of items to be timestamped and widely publishing the hash, such as in a newspaper or Usenet post [2-5]. The timestamp proves that the data must have existed at the time, obviously, in order to get into the hash. Each timestamp includes the previous timestamp in its hash, forming a chain, with each additional timestamp reinforcing the ones before it.



4. Proof-of-Work

To implement a distributed timestamp server on a peer-to-peer basis, we will need to use a proof-of-work system similar to Adam Back's Hashcash [6], rather than newspaper or Usenet posts. The proof-of-work involves scanning for a value that when hashed, such as with SHA-256, the hash begins with a number of zero bits. The average work required is exponential in the number of zero bits required and can be verified by executing a single hash.

For our timestamp network, we implement the proof-of-work by incrementing a nonce in the block until a value is found that gives the block's hash the required zero bits. Once the CPU effort has been expended to make it satisfy the proof-of-work, the block cannot be changed without redoing the work. As later blocks are chained after it, the work to change the block would include redoing all the blocks after it.



The proof-of-work also solves the problem of determining representation in majority decision making. If the majority were based on one-IP-address-one-vote, it could be subverted by anyone able to allocate many IPs. Proof-of-work is essentially one-CPU-one-vote. The majority decision is represented by the longest chain, which has the greatest proof-of-work effort invested in it. If a majority of CPU power is controlled by honest nodes, the honest chain will grow the fastest and outpace any competing chains. To modify a past block, an attacker would have to redo the proof-of-work of the block and all blocks after it and then catch up with and surpass the work of the honest nodes. We will show later that the probability of a slower attacker catching up diminishes exponentially as subsequent blocks are added.

To compensate for increasing hardware speed and varying interest in running nodes over time, the proof-of-work difficulty is determined by a moving average targeting an average number of blocks per hour. If they're generated too fast, the difficulty increases.

5. Network

The steps to run the network are as follows:

1) New transactions are broadcast to all nodes.
2) Each node collects new transactions into a block.
3) Each node works on finding a difficult proof-of-work for its block.
4) When a node finds a proof-of-work, it broadcasts the block to all nodes.
5) Nodes accept the block only if all transactions in it are valid and not already spent.
6) Nodes express their acceptance of the block by working on creating the next block in the chain, using the hash of the accepted block as the previous hash.

Nodes always consider the longest chain to be the correct one and will keep working on extending it. If two nodes broadcast different versions of the next block simultaneously, some nodes may receive one or the other first. In that case, they work on the first one they received, but save the other branch in case it becomes longer. The tie will be broken when the next proof-of-work is found and one branch becomes longer; the nodes that were working on the other branch will then switch to the longer one.

New transaction broadcasts do not necessarily need to reach all nodes. As long as they reach many nodes, they will get into a block before long. Block broadcasts are also tolerant of dropped messages. If a node does not receive a block, it will request it when it receives the next block and realizes it missed one.

6. Incentive


By convention, the first transaction in a block is a special transaction that starts a new coin owned by the creator of the block. This adds an incentive for nodes to support the network, and provides a way to initially distribute coins into circulation, since there is no central authority to issue them. The steady addition of a constant of amount of new coins is analogous to gold miners expending resources to add gold to circulation. In our case, it is CPU time and electricity that is expended.

The incentive can also be funded with transaction fees. If the output value of a transaction is less than its input value, the difference is a transaction fee that is added to the incentive value of the block containing the transaction. Once a predetermined number of coins have entered circulation, the incentive can transition entirely to transaction fees and be completely inflation free.

The incentive may help encourage nodes to stay honest. If a greedy attacker is able to assemble more CPU power than all the honest nodes, he would have to choose between using it to defraud people by stealing back his payments, or using it to generate new coins. He ought to find it more profitable to play by the rules, such rules that favour him with more new coins than everyone else combined, than to undermine the system and the validity of his own wealth.

7. Reclaiming Disk Space

Once the latest transaction in a coin is buried under enough blocks, the spent transactions before it can be discarded to save disk space. To facilitate this without breaking the block's hash, transactions are hashed in a Merkle Tree [7][2][5], with only the root included in the block's hash. Old blocks can then be compacted by stubbing off branches of the tree. The interior hashes do not need to be stored.




Transactions Hashed in a Merkle Tree

After Pruning Tx0-2 from the Block

A block header with no transactions would be about 80 bytes. If we suppose blocks are generated every 10 minutes, 80 bytes * 6 * 24 * 365 = 4.2MB per year. With computer systems typically selling with 2GB of RAM as of 2008, and Moore's Law predicting current growth of 1.2GB per year, storage should not be a problem even if the block headers must be kept in memory.

8. Simplified Payment Verification


It is possible to verify payments without running a full network node. A user only needs to keep a copy of the block headers of the longest proof-of-work chain, which he can get by querying network nodes until he's convinced he has the longest chain, and obtain the Merkle branch linking the transaction to the block it's timestamped in. He can't check the transaction for himself, but by linking it to a place in the chain, he can see that a network node has accepted it, and blocks added after it further confirm the network has accepted it.



As such, the verification is reliable as long as honest nodes control the network, but is more vulnerable if the network is overpowered by an attacker. While network nodes can verify transactions for themselves, the simplified method can be fooled by an attacker's fabricated transactions for as long as the attacker can continue to overpower the network. One strategy to protect against this would be to accept alerts from network nodes when they detect an invalid block, prompting the user's software to download the full block and alerted transactions to confirm the inconsistency. Businesses that receive frequent payments will probably still want to run their own nodes for more independent security and quicker verification.

9. Combining and Splitting Value


Although it would be possible to handle coins individually, it would be unwieldy to make a separate transaction for every cent in a transfer. To allow value to be split and combined, transactions contain multiple inputs and outputs. Normally there will be either a single input from a larger previous transaction or multiple inputs combining smaller amounts, and at most two outputs: one for the payment, and one returning the change, if any, back to the sender.



It should be noted that fan-out, where a transaction depends on several transactions, and those transactions depend on many more, is not a problem here. There is never the need to extract a complete standalone copy of a transaction's history.

10. Privacy

The traditional banking model achieves a level of privacy by limiting access to information to the parties involved and the trusted third party. The necessity to announce all transactions publicly precludes this method, but privacy can still be maintained by breaking the flow of information in another place: by keeping public keys anonymous. The public can see that someone is sending an amount to someone else, but without information linking the transaction to anyone. This is similar to the level of information released by stock exchanges, where the time and size of individual trades, the "tape", is made public, but without telling who the parties were.



As an additional firewall, a new key pair should be used for each transaction to keep them from being linked to a common owner. Some linking is still unavoidable with multi-input transactions, which necessarily reveal that their inputs were owned by the same owner. The risk is that if the owner of a key is revealed, linking could reveal other transactions that belonged to the same owner.

11. Calculations

We consider the scenario of an attacker trying to generate an alternate chain faster than the honest chain. Even if this is accomplished, it does not throw the system open to arbitrary changes, such as creating value out of thin air or taking money that never belonged to the attacker. Nodes are not going to accept an invalid transaction as payment, and honest nodes will never accept a block containing them. An attacker can only try to change one of his own transactions to take back money he recently spent.

The race between the honest chain and an attacker chain can be characterized as a Binomial Random Walk. The success event is the honest chain being extended by one block, increasing its lead by +1, and the failure event is the attacker's chain being extended by one block, reducing the gap by -1.

The probability of an attacker catching up from a given deficit is analogous to a Gambler's Ruin problem. Suppose a gambler with unlimited credit starts at a deficit and plays potentially an infinite number of trials to try to reach breakeven. We can calculate the probability he ever reaches breakeven, or that an attacker ever catches up with the honest chain, as follows [8]:

p = probability an honest node finds the next block
q = probability the attacker finds the next block
q_z = probability the attacker will ever catch up from z blocks behind

$$q_z = \begin{cases} 1 & \text{if } p \leq q \\ (q/p)^z & \text{if } p > q \end{cases}$$

Given our assumption that $p > q$, the probability drops exponentially as the number of blocks the attacker has to catch up with increases. With the odds against him, if he doesn't make a lucky lunge forward early on, his chances become vanishingly small as he falls further behind.

We now consider how long the recipient of a new transaction needs to wait before being sufficiently certain the sender can't change the transaction. We assume the sender is an attacker who wants to make the recipient believe he paid him for a while, then switch it to pay back to himself after some time has passed. The receiver will be alerted when that happens, but the sender hopes it will be too late.

The receiver generates a new key pair and gives the public key to the sender shortly before signing. This prevents the sender from preparing a chain of blocks ahead of time by working on it continuously until he is lucky enough to get far enough ahead, then executing the transaction at that moment. Once the transaction is sent, the dishonest sender starts working in secret on a parallel chain containing an alternate version of his transaction.

The recipient waits until the transaction has been added to a block and z blocks have been linked after it. He doesn't know the exact amount of progress the attacker has made, but assuming the honest blocks took the average expected time per block, the attacker's potential progress will be a Poisson distribution with expected value:

$$\lambda = z\frac{q}{p}$$

To get the probability the attacker could still catch up now, we multiply the Poisson density for each amount of progress he could have made by the probability he could catch up from that point:

$$\sum_{k=0}^{\infty} \frac{\lambda^k e^{-\lambda}}{k!} \cdot \begin{cases} (q/p)^{(z-k)} & \text{if } k \le z \\ 1 & \text{if } k > z \end{cases}$$

Rearranging to avoid summing the infinite tail of the distribution...

$$1 - \sum_{k=0}^{z} \frac{\lambda^k e^{-\lambda}}{k!} \left(1 - (q/p)^{(z-k)}\right)$$

Converting to C code...

```
#include <math.h>
double AttackerSuccessProbability(double q, int z)
{
    double p = 1.0 - q;
    double lambda = z * (q / p);
    double sum = 1.0;
    int i, k;
    for (k = 0; k <= z; k++)
    {
        double poisson = exp(-lambda);
        for (i = 1; i <= k; i++)
            poisson *= lambda / i;
        sum -= poisson * (1 - pow(q / p, z - k));
    }
    return sum;
}
```

Running some results, we can see the probability drop off exponentially with z.

```
q=0.1
z=0     P=1.0000000
z=1     P=0.2045873
z=2     P=0.0509779
z=3     P=0.0131722
z=4     P=0.0034552
z=5     P=0.0009137
z=6     P=0.0002428
z=7     P=0.0000647
z=8     P=0.0000173
z=9     P=0.0000046
z=10    P=0.0000012

q=0.3
z=0     P=1.0000000
z=5     P=0.1773523
z=10    P=0.0416605
z=15    P=0.0101008
z=20    P=0.0024804
z=25    P=0.0006132
z=30    P=0.0001522
z=35    P=0.0000379
z=40    P=0.0000095
z=45    P=0.0000024
z=50    P=0.0000006
```

Solving for P less than 0.1%...

```
P < 0.001
q=0.10   z=5
q=0.15   z=8
q=0.20   z=11
q=0.25   z=15
q=0.30   z=24
q=0.35   z=41
q=0.40   z=89
q=0.45   z=340
```

12. Conclusion

We have proposed a system for electronic transactions without relying on trust. We started with the usual framework of coins made from digital signatures, which provides strong control of ownership, but is incomplete without a way to prevent double-spending. To solve this, we proposed a peer-to-peer network using proof-of-work to record a public history of transactions that quickly becomes computationally impractical for an attacker to change if honest nodes control a majority of CPU power. The network is robust in its unstructured simplicity. Nodes work all at once with little coordination. They do not need to be identified, since messages are not routed to any particular place and only need to be delivered on a best effort basis. Nodes can leave and rejoin the network at will, accepting the proof-of-work chain as proof of what happened while they were gone. They vote with their CPU power, expressing their acceptance of valid blocks by working on extending them and rejecting invalid blocks by refusing to work on them. Any needed rules and incentives can be enforced with this consensus mechanism.

References

[1] W. Dai, "b-money," http://www.weidai.com/bmoney.txt, 1998.

[2] H. Massias, X.S. Avila, and J.-J. Quisquater, "Design of a secure timestamping service with minimal trust requirements," In *20th Symposium on Information Theory in the Benelux*, May 1999.

[3] S. Haber, W.S. Stornetta, "How to time-stamp a digital document," In *Journal of Cryptology*, vol 3, no 2, pages 99-111, 1991.

[4] D. Bayer, S. Haber, W.S. Stornetta, "Improving the efficiency and reliability of digital time-stamping," In *Sequences II: Methods in Communication, Security and Computer Science*, pages 329-334, 1993.

[5] S. Haber, W.S. Stornetta, "Secure names for bit-strings," In *Proceedings of the 4th ACM Conference on Computer and Communications Security*, pages 28-35, April 1997.

[6] A. Back, "Hashcash - a denial of service counter-measure," http://www.hashcash.org/papers/hashcash.pdf, 2002.

[7] R.C. Merkle, "Protocols for public key cryptosystems," In *Proc. 1980 Symposium on Security and Privacy*, IEEE Computer Society, pages 122-133, April 1980.

[8] W. Feller, "An introduction to probability theory and its applications," 1957.

SEGUÍ APRENDIENDO

¿TE SIRVIÓ? SEGUIME PARA MÁS

Todas las semanas subo contenido sobre trading, bots de IA, cripto y cómo cuidar tu dinero, explicado simple y sin vender humo. Escaneá o tocá cada uno:

Instagram
@ezebagnato

YouTube
Ezequiel Bagnato | Comunidad Inversores

Telegram
Canal de anuncios

X
@C_INVERSORES

Esta guía es solo educativa y no es una recomendación de inversión. Invertir en criptomonedas tiene riesgos, incluida la pérdida total del dinero. Fotos: Unsplash. Whitepaper: Satoshi Nakamoto (2008).