Case study 4: Bookcase

National 5 · Practical Woodworking · Answers and marking guidance

Award one mark per correct point unless stated. Other valid answers should be credited. Sketches can gain full marks if they show enough detail.

1 (a) Name the hand tool used to level the bottom of a housing. **(1 mark)**

- Hand router

1 (b) Describe the stages in cutting a through housing. Your answer can include sketches. **(3 marks)**

- Mark both sides of the housing across the board with a try square and marking knife, using the shelf for the width
- Gauge the depth (about one third of the thickness) on both edges
- Saw down to the depth lines with a tenon saw, remove waste with a chisel, then level with a hand router and test the fit

2 Name the plane used to cut the rebate. **(1 mark)**

- Rebate plane

3 Describe one advantage and one disadvantage of chipboard compared with pine. **(2 marks)**

- Advantage: cheaper / made from waste wood / available in wide boards that don't warp
- Disadvantage: edges crumble so traditional joints are hard to cut; heavier; damaged by water

4 Describe how to check the bookcase is square after it has been cramped. **(1 mark)**

- Measure both diagonals: they should be equal; adjust the cramps if not

4 State how to stop the sash cramps marking the bookcase. **(1 mark)**

- Place scrap blocks between the cramp jaws and the wood

4 Explain why excess glue should be wiped off. **(1 mark)**

- Dried glue stops stain or varnish soaking in, leaving light patches

Total: 10 marks