



Mobile IP

- · Support for mobile hosts in the Internet
- Discussion based on IPv4
- · Original work by John Ioannidis:
- Protocols for Mobile Internetworking, Ph.D. thesis, Columbia University, 1993
- First full implementation, Columbia University, 1991
- Many other implementations with slightly different approaches:
- Sony 1991
- IBM 1992
- Harvard 1994
- Linux Mobile IP 1996









The Problem

- The packet cannot be delivered
- Host 4 is no longer connected to Ethernet B
- It has moved to Ethernet C
- Keeps the same IP address (2.0.0.4), or
- Is assigned (somehow) a new IP address (4.0.0.23)
- Router B will send:
- An ICMP host unreachable message back to host 1
- Suggestions on how to solve this problem?

6

Solution 1: Host-specific Routes

- When host 4 keeps its old IP address (2.0.0.4)
- Enter host-specific routes into the routing tables of routers A, B and C:

Router A	Target/Prefix-Length	Next Hop	Interface
	2.0.0.4 / 32	3.0.0.252	с
Router B	Target/Prefix-Length	Next Hop	Interface
	2.0.0.4 / 32	3.0.0.252	c
Router C	Target/Prefix-Length	Next Hop	Interface
	2.0.0.4 / 32	"direct"	b


Solution 2: Change IP Address

- Simply change the IP address of host 4, as it moves from Ethernet B to Ethernet C
- New IP address: 4.0.0.23
- Assignment via some automated way, DHCP
- Change the IP address of a host whenever it changes its point of attachment

Solution 3: Mobile IP

- A standard proposed to address the problem of mobile internetworking
- It allows a mobile node to use two IP addresses:
- A fixed IP address, called home address
- An IP address that changes at each new point of attachment, called *care-of address*
- <u>Home address</u> is a permanent IP address assigned by the node's home network
- <u>Care-of address</u> is a temporary address assigned by the foreign network (the network that the host visits)

9



Home and Foreign Agent

- Home Agent:
- A router on a mobile node's home network
- Maintains current location information for the mobile node.
- Foreign Agent:
- Serves as a default router for the registered mobile nodes

Care-of Address: Foreign Agent CoA

- Two different conceptual types:
- Foreign agent care-of address:
 - * IP address of a foreign agent (FA) that has an interface on the foreign link
 - * The FA may have more than one IP address; So, the network prefix need not be the same as the network prefix of the foreign link
 - * The same FA CoA can be shared by many mobile nodes simultaneously

Care-of Address: Collocated CoA

- Collocated care-of address:
 - * An IP address temporarily assigned to a mobile
 - * Can be used by only one mobile node at a time
 - * The network prefix must be the same as the network prefix of the foreign link
 - * It might be used by a mobile node in situations where no foreign agents are available

13

Mobile IP Operation

- Three main mechanisms:
- Agent discovery
- Registration
- Routing

14

Mechanism 1: Agent Discovery

- Home Agents and Foreign Agents periodically broadcasts *Agent Advertisements*
- E.g. once every few seconds
- If the mobile node does not want to wait for the periodic advertisement, it can broadcast *Agent Solicitations* that will be answered by any foreign agent that receives it
- Mobile nodes determine whether they have moved from one link to another

15

Movement Detection

- Agent Advertisement has a Lifetime field
- Specifies how soon a mobile node should expect to hear another advertisement from that same agent
- If the mobile node fails to hear an advertisement from that agent within the specified *Lifetime*, then it assumes that it has moved to a different link
- Also movement detection based on network prefixes

Care-of Address

- A mobile node connected to a foreign link acquires a foreign agent care-of address from the *Agent Advertisements*
- If multiple care-of addresses are listed, any one of them can be used
- If a foreign agent is unavailable, the mobile node can obtain a collocated care-of address by DHCP
- Or a previously assigned collocated care-of address may be used

17

Agent Discovery Security

- No authentication is required by the Mobile IP specification
- MAY be authenticated using IPsec mechanisms
- We can have malicious mobile nodes or malicious foreign agents
- You can come up with your own ways of exploiting this


18


Mechanism 2: Registration

- Registration is the process by which a mobile node:
- Requests routing services from a foreign agent
- Informs its home agent of its current care-of address, which creates a *triple binding*:
 - * Home address | Care-of address | Lifetime
- Renews a registration which is due to expire, binding update
- Multiple triple bindings may be kept for the same MN (*almost* seamless handoff)
- Deregisters when it returns to its home link

19

Registering Foreign Agent Care-of Address The mobile node, with the assistance of a foreign agent, sends a Registration Request with the care-of address information 1 Mobile Node Visiting a foreign link When the home agent receives this request, it adds the necessary information to its routing table, and sends a Registration Reply back to the mobile node






Authentication


- The home agent must be certain that registration was originated by the mobile node and not by some other malicious node.
- Registration of the care-of address requires authentication
- The mobile node needs to prove its identity to its home agent
- It is done by making use of a secret key known only to the mobile node and its home agent
- Secret key is not sent as part of the communication
- Mobile IP standard requires keyed MD5


23


Mechanism 3: Routing


- Divided into different scenarios:
- Mobile node—Correspondent node
- Correspondent node→Mobile node
 - * With a foreign agent
 - * Without a foreign agent













Triangle Routing (2/2)

- Waste of network resources
- HA is a bottleneck
- What about network partitions?
- Why doesn't the mobile node inform the correspondent of its care-of address and have it tunnel directly to the mobile node?





On the Home Network

- If the HA is the gateway host then picking up packets destined for the MH is trivial
- If the HA is **not** the gateway host then:
- The HA pretends to be MH and responds to requests for MH's physical address (e.g. Ethernet address) with its own physical address
- ARP caches on all hosts have to be updated upon registration of the MH (ARP replies)

33

On the Foreign Network

- The care-of address used for encapsulation may belong to the FA or may be a temporary address acquired by the mobile host (e.g. via DHCP)
- The MH must never send ARP frames on a foreign network
- The MH can obtain the FA's link-layer address from the *agent advertisement* messages

34

Mobile IPv6

- There is no need for Foreign Agents since the MH can use the *Address Autoconfiguration* protocol to obtain a dynamic care-of address
- No triangular routing
- Binding updates are supplied by encoding them as destination options in the IP header
- IPv6 provides security protocols hence simplifying the authentication process

35

Further Reading

• C. E. Perkins, "Mobile networking through mobile IP," *IEEE Internet Computing*, pp. 58-69, Jan/Feb, 1998