
SBpipe documentation

Release 3.20.0

Piero Dalle Pezze and Nicolas Le Novère

Aug 21, 2017

CONTENTS

1	Source code	1
1.1	Python modules	1
1.1.1	sbpipe package	1
2	Indices	25
	Python Module Index	27
	Index	29

SOURCE CODE

1.1 Python modules

1.1.1 sbpipe package

Subpackages

sbpipe.R package

Subpackages

sbpipe.R.misc package

Module contents

Module contents

sbpipe.pl package

Subpackages

sbpipe.pl.create package

Submodules

sbpipe.pl.create.newproj module

```
class sbpipe.pl.create.newproj.NewProj (models_folder='Models',  
                                         ing_folder='Results')  
    Bases: sbpipe.pl.pipeline.Pipeline (page 7)
```

This module initialises the folder tree for a new project.

Parameters

- **models_folder** – the folder containing the models
- **working_folder** – the folder to store the results

```
run (project_name)
```

Create a project directory tree.

Parameters **project_name** – the name of the project

Returns 0

Module contents

sbpipe.pl.pe package

Submodules

sbpipe.pl.pe.parest module

```
class sbpipe.pl.pe.parest.ParEst (models_folder='Models',          working_folder='Results',
                                  sim_data_folder='param_estim_data',
                                  sim_plots_folder='param_estim_plots')
```

Bases: [sbpipe.pl.pipeline.Pipeline](#) (page 7)

This module provides the user with a complete pipeline of scripts for running model parameter estimations

```
classmethod analyse_data (simulator, model, inputdir, outputdir, fileout_final_estims,
                          fileout_all_estims, fileout_param_estim_details, file-
                          out_param_estim_summary, sim_plots_dir, best_fits_percent,
                          data_point_num, cluster='local', plot_2d_66cl_corr=False,
                          plot_2d_95cl_corr=False, plot_2d_99cl_corr=False,
                          logspace=True, scientific_notation=True)
```

The second pipeline step: data analysis.

Parameters

- **simulator** – the name of the simulator (e.g. Copasi)
- **model** – the model name
- **inputdir** – the directory containing the simulation data
- **outputdir** – the directory to store the results
- **fileout_final_estims** – the name of the file containing final parameter sets with the objective value
- **fileout_all_estims** – the name of the file containing all the parameter sets with the objective value
- **fileout_param_estim_details** – the name of the file containing the detailed statistics for the estimated parameters
- **fileout_param_estim_summary** – the name of the file containing the summary for the parameter estimation
- **sim_plots_dir** – the directory of the simulation plots
- **best_fits_percent** – the percent to consider for the best fits
- **data_point_num** – the number of data points
- **cluster** – local, lsf for Load Sharing Facility, sge for Sun Grid Engine.
- **plot_2d_66cl_corr** – True if 2 dim plots for the parameter sets within 66% should be plotted
- **plot_2d_95cl_corr** – True if 2 dim plots for the parameter sets within 95% should be plotted
- **plot_2d_99cl_corr** – True if 2 dim plots for the parameter sets within 99% should be plotted
- **logspace** – True if parameters should be plotted in log space
- **scientific_notation** – True if axis labels should be plotted in scientific notation

Returns True if the task was completed successfully, False otherwise.

classmethod generate_data (*simulator, model, inputdir, cluster, local_cpus, runs, outputdir, sim_data_dir*)

The first pipeline step: data generation.

Parameters

- **simulator** – the name of the simulator (e.g. Copasi)
- **model** – the model to process
- **inputdir** – the directory containing the model
- **cluster** – local, lsf for load sharing facility, sge for sun grid engine
- **local_cpus** – the number of cpu
- **runs** – the number of fits to perform
- **outputdir** – the directory to store the results
- **sim_data_dir** – the directory containing the simulation data sets

Returns True if the task was completed successfully, False otherwise.

classmethod generate_report (*model, outputdir, sim_plots_folder*)

The third pipeline step: report generation.

Parameters

- **model** – the model name
- **outputdir** – the directory to store the report
- **sim_plots_folder** – the folder containing the plots

Returns True if the task was completed successfully, False otherwise.

parse (*my_dict*)

run (*config_file*)

Module contents

sbpipe.pl.ps1 package

Submodules

sbpipe.pl.ps1.parscan1 module

class `sbpipe.pl.ps1.parscan1.ParScan1` (*models_folder='Models', working_folder='Results', sim_data_folder='single_param_scan_data', sim_plots_folder='single_param_scan_plots'*)

Bases: `sbpipe.pl.pipeline.Pipeline` (page 7)

This module provides the user with a complete pipeline of scripts for computing single parameter scans.

classmethod analyse_data (*model, knock_down_only, outputdir, sim_data_folder, sim_plots_folder, runs, local_cpus, percent_levels, min_level, max_level, levels_number, homogeneous_lines, cluster='local', xaxis_label='', yaxis_label=''*)

The second pipeline step: data analysis.

Parameters

- **model** – the model name
- **knock_down_only** – True for knock down simulation, false if also scanning over expression.

- **outputdir** – the directory containing the results
- **sim_data_folder** – the folder containing the simulated data sets
- **sim_plots_folder** – the folder containing the generated plots
- **runs** – the number of simulations
- **local_cpus** – the number of cpus
- **percent_levels** – True if the levels are percents.
- **min_level** – the minimum level
- **max_level** – the maximum level
- **levels_number** – the number of levels
- **homogeneous_lines** – True if generated line style should be homogeneous
- **cluster** – local, lsf for Load Sharing Facility, sge for Sun Grid Engine.
- **xaxis_label** – the name of the x axis (e.g. Time [min])
- **yaxis_label** – the name of the y axis (e.g. Level [a.u.])

Returns True if the task was completed successfully, False otherwise.

classmethod generate_data (*simulator, model, scanned_par, cluster, local_cpus, runs, simulate_intervals, single_param_scan_intervals, inputdir, outputdir*)

The first pipeline step: data generation.

Parameters

- **simulator** – the name of the simulator (e.g. Copasi)
- **model** – the model to process
- **scanned_par** – the scanned parameter
- **cluster** – local, lsf for Load Sharing Facility, sge for Sun Grid Engine.
- **local_cpus** – the number of CPU.
- **runs** – the number of model simulation
- **simulate_intervals** – the time step of each simulation
- **single_param_scan_intervals** – the number of scans to perform
- **inputdir** – the directory containing the model
- **outputdir** – the directory to store the results

Returns True if the task was completed successfully, False otherwise.

classmethod generate_report (*model, scanned_par, outputdir, sim_plots_folder*)

The third pipeline step: report generation.

Parameters

- **model** – the model name
- **scanned_par** – the scanned parameter
- **outputdir** – the directory containing the report
- **sim_plots_folder** – the folder containing the plots

Returns True if the task was completed successfully, False otherwise.

parse (*my_dict*)

run (*config_file*)

Module contents

sbpipe.pl.ps2 package

Submodules

sbpipe.pl.ps2.parscan2 module

```
class sbpipe.pl.ps2.parscan2.ParScan2(models_folder='Models', working_folder='Results',
                                       sim_data_folder='double_param_scan_data',
                                       sim_plots_folder='double_param_scan_plots')
```

Bases: *sbpipe.pl.pipeline.Pipeline* (page 7)

This module provides the user with a complete pipeline of scripts for computing double parameter scans.

```
classmethod analyse_data(model, scanned_par1, scanned_par2, inputdir, outputdir, cluster='local', local_cpus=1, runs=1)
```

The second pipeline step: data analysis.

Parameters

- **model** – the model name
- **scanned_par1** – the first scanned parameter
- **scanned_par2** – the second scanned parameter
- **inputdir** – the directory containing the simulated data sets to process
- **outputdir** – the directory to store the performed analysis
- **cluster** – local, lsf for Load Sharing Facility, sge for Sun Grid Engine.
- **local_cpus** – the number of CPU.
- **runs** – the number of model simulation

Returns True if the task was completed successfully, False otherwise.

```
classmethod generate_data(simulator, model, sim_length, inputdir, outputdir, cluster, local_cpus, runs)
```

The first pipeline step: data generation.

Parameters

- **simulator** – the name of the simulator (e.g. Copasi)
- **model** – the model to process
- **sim_length** – the length of the simulation
- **inputdir** – the directory containing the model
- **outputdir** – the directory to store the results
- **cluster** – local, lsf for Load Sharing Facility, sge for Sun Grid Engine.
- **local_cpus** – the number of CPU.
- **runs** – the number of model simulation

Returns True if the task was completed successfully, False otherwise.

```
classmethod generate_report(model, scanned_par1, scanned_par2, outputdir, sim_plots_folder)
```

The third pipeline step: report generation.

Parameters

- **model** – the model name

- **scanned_par1** – the first scanned parameter
- **scanned_par2** – the second scanned parameter
- **outputdir** – the directory containing the report
- **sim_plots_folder** – the folder containing the plots.

Returns True if the task was completed successfully, False otherwise.

parse (*my_dict*)

run (*config_file*)

Module contents

sbpipe.pl.sim package

Submodules

sbpipe.pl.sim.sim module

```
class sbpipe.pl.sim.sim.Sim(models_folder='Models', working_folder='Results',
                             sim_data_folder='simulate_data', sim_plots_folder='simulate_plots')
Bases: sbpipe.pl.pipeline.Pipeline (page 7)
```

This module provides the user with a complete pipeline of scripts for running model simulations

```
classmethod analyse_data(model, inputdir, outputdir, sim_plots_dir, exp_dataset,
                          plot_exp_dataset, cluster='local', xaxis_label='', yaxis_label='')
```

The second pipeline step: data analysis.

Parameters

- **model** – the model name
- **inputdir** – the directory containing the data to analyse
- **outputdir** – the output directory containing the results
- **sim_plots_dir** – the directory to save the plots
- **exp_dataset** – the full path of the experimental data set
- **plot_exp_dataset** – True if the experimental data set should also be plotted
- **cluster** – local, lsf for Load Sharing Facility, sge for Sun Grid Engine.
- **xaxis_label** – the label for the x axis (e.g. Time [min])
- **yaxis_label** – the label for the y axis (e.g. Level [a.u.])

Returns True if the task was completed successfully, False otherwise.

```
classmethod generate_data(simulator, model, inputdir, outputdir, cluster='local', local_cpus=2, runs=1)
```

The first pipeline step: data generation.

Parameters

- **simulator** – the name of the simulator (e.g. Copasi)
- **model** – the model to process
- **inputdir** – the directory containing the model
- **outputdir** – the directory containing the output files
- **cluster** – local, lsf for Load Sharing Facility, sge for Sun Grid Engine.

- **local_cpus** – the number of CPUs.
- **runs** – the number of model simulation

Returns True if the task was completed successfully, False otherwise.

classmethod generate_report (*model, outputdir, sim_plots_folder*)

The third pipeline step: report generation.

Parameters

- **model** – the model name
- **outputdir** – the output directory to store the report
- **sim_plots_folder** – the folder containing the plots

Returns True if the task was completed successfully, False otherwise.

parse (*my_dict*)

run (*config_file*)

Module contents

Submodules

sbpipe.pl.pipeline module

```
class sbpipe.pl.pipeline.Pipeline (models_folder='Models',
                                   ing_folder='Results',      work-
                                   sim_data_folder='sim_data',
                                   sim_plots_folder='sim_plots')
```

Bases: object

Generic pipeline.

Parameters

- **models_folder** – the folder containing the models
- **working_folder** – the folder to store the results
- **sim_data_folder** – the folder to store the simulation data
- **sim_plots_folder** – the folder to store the graphic results

get_models_folder ()

Return the folder containing the models.

Returns the models folder.

get_sim_data_folder ()

Return the folder containing the in-silico generated data sets.

Returns the folder of the simulated data sets.

get_sim_plots_folder ()

Return the folder containing the in-silico generated plots.

Returns the folder of the simulated plots.

classmethod get_simul_obj (*simulator*)

Return the simulator object if this exists. Otherwise throws an exception. The simulator name starts with an upper case letter. Each simulator is in a package within *sbpipe.simulator*.

Parameters **simulator** – the simulator name

Returns the simulator object.

get_working_folder()

Return the folder containing the results.

Returns the working folder.

classmethod load(*config*)

Safely load a YAML configuration file and return its structure as a dictionary object.

Parameters **config** – a YAML configuration file

Returns the dictionary structure of the configuration file

Raise `yaml.YAMLError` if the config cannot be loaded.

parse(*config_dict*)

Read a dictionary structure containing the pipeline configuration. This method is abstract.

Returns a tuple containing the configuration

run(*config_file*)

Run the pipeline.

Parameters **config_file** – a configuration file for this pipeline.

Returns True if the pipeline was executed correctly, False otherwise.

Module contents

sbpipe.report package

Submodules

sbpipe.report.latex_reports module

`sbpipe.report.latex_reports.get_latex_header` (*pdftitle*='SBpipe report', *title*='SBpipe report', *abstract*='Generic report.')

Initialize a Latex header with a title and an abstract.

Parameters

- **pdftitle** – the pdftitle for the LaTeX header
- **title** – the title for the LaTeX header
- **abstract** – the abstract for the LaTeX header

Returns the LaTeX header

`sbpipe.report.latex_reports.latex_report` (*outputdir*, *plots_folder*, *model_noext*, *filename_prefix*, *caption*=False)

Generate a generic report.

Parameters

- **outputdir** – the output directory
- **plots_folder** – the folder containing the simulated plots
- **model_noext** – the model name
- **filename_prefix** – the prefix for the LaTeX file
- **caption** – True if figure captions (=figure file name) should be added

`sbpipe.report.latex_reports.latex_report_pe` (*outputdir*, *plots_folder*, *model_noext*, *filename_prefix*)

Generate a report for a parameter estimation task.

Parameters

- **outputdir** – the output directory
- **plots_folder** – the folder containing the simulated plots
- **model_noext** – the model name
- **filename_prefix** – the prefix for the LaTeX file

```
sbpipe.report.latex_reports.latex_report_ps1 (outputdir,      plots_folder,      file-  
                                              name_prefix,      model_noext,  
                                              scanned_par)
```

Generate a report for a single parameter scan task.

Parameters

- **outputdir** – the output directory
- **plots_folder** – the folder containing the simulated plots
- **filename_prefix** – the prefix for the LaTeX file
- **model_noext** – the model name
- **scanned_par** – the scanned parameter

```
sbpipe.report.latex_reports.latex_report_ps2 (outputdir,      plots_folder,      file-  
                                              name_prefix,      model_noext,  
                                              scanned_par1, scanned_par2)
```

Generate a report for a double parameter scan task.

Parameters

- **outputdir** – the output directory
- **plots_folder** – the folder containing the simulated plots
- **filename_prefix** – the prefix for the LaTeX file
- **model_noext** – the model name
- **scanned_par1** – the 1st scanned parameter
- **scanned_par2** – the 2nd scanned parameter

```
sbpipe.report.latex_reports.latex_report_sim (outputdir, plots_folder, model_noext,  
                                              filename_prefix)
```

Generate a report for a time course task.

Parameters

- **outputdir** – the output directory
- **plots_folder** – the folder containing the simulated plots
- **model_noext** – the model name
- **filename_prefix** – the prefix for the LaTeX file

```
sbpipe.report.latex_reports.pdf_report (outputdir, filename)
```

Generate a PDF report from LaTeX report using pdflatex.

Parameters

- **outputdir** – the output directory
- **filename** – the LaTeX file name

Module contents

sbpipe.simul package

Subpackages

sbpipe.simul.copasi package

Submodules

sbpipe.simul.copasi.copasi module

```
class sbpipe.simul.copasi.copasi.Copasi
    Bases: sbpipe.simul.simul.Simul (page 11)
    Copasi simulator.

    pe (model, inputdir, cluster, local_cpus, runs, outputdir, sim_data_dir, output_msg=False)

    ps1 (model, scanned_par, simulate_intervals, single_param_scan_intervals, inputdir, outputdir,
        cluster='local', local_cpus=1, runs=1, output_msg=False)

    ps2 (model, sim_length, inputdir, outputdir, cluster='local', local_cpus=1, runs=1, out-
        put_msg=False)

    sim (model, inputdir, outputdir, cluster='local', local_cpus=1, runs=1, output_msg=False)
```

Module contents

sbpipe.simul.python package

Submodules

sbpipe.simul.python.python module

```
class sbpipe.simul.python.python.Python
    Bases: sbpipe.simul.pl_simul.PLSimul (page 10)
    Python Simulator.
```

Module contents

Submodules

sbpipe.simul.pl_simul module

```
class sbpipe.simul.pl_simul.PLSimul (lang, lang_err_msg, options)
    Bases: sbpipe.simul.simul.Simul (page 11)
    A generic simulator for models coded in a programming language.

    get_lang()
        Return the programming language name :return: the name

    get_lang_err_msg()
        Return the error if the programming language is not found :return: the error message
```

get_lang_options()

Return the options for the programming language command :return: the options. Return None, if no options are used.

pe (*model, inputdir, cluster, local_cpus, runs, outputdir, sim_data_dir, output_msg=False*)

ps1 (*model, scanned_par, simulate_intervals, single_param_scan_intervals, inputdir, outputdir, cluster='local', local_cpus=1, runs=1, output_msg=False*)

ps2 (*model, sim_length, inputdir, outputdir, cluster='local', local_cpus=1, runs=1, output_msg=False*)

replace_str_in_report (*report*)

sim (*model, inputdir, outputdir, cluster='local', local_cpus=1, runs=1, output_msg=False*)

sbpipe.simul.simul module

class sbpipe.simul.simul.Simul

Bases: object

Generic simulator.

get_all_fits (*path_in='.', path_out='.', filename_out='all_estimates.csv'*)

Collect all the parameter estimates. Results are stored in filename_out.

Parameters

- **path_in** – the path to the input files
- **path_out** – the path to the output files
- **filename_out** – a global file containing all fits from independent parameter estimations.

Returns the number of retrieved files

get_best_fits (*path_in='.', path_out='.', filename_out='final_estimates.csv'*)

Collect the final parameter estimates. Results are stored in filename_out.

Parameters

- **path_in** – the path to the input files
- **path_out** – the path to the output files
- **filename_out** – a global file containing the best fits from independent parameter estimations.

Returns the number of retrieved files

pe (*model, inputdir, cluster, local_cpus, runs, outputdir, sim_data_dir, output_msg=False*)
parameter estimation.

Parameters

- **model** – the model to process
- **inputdir** – the directory containing the model
- **cluster** – local, lsf for load sharing facility, sge for sun grid engine
- **local_cpus** – the number of cpu
- **runs** – the number of fits to perform
- **outputdir** – the directory to store the results
- **sim_data_dir** – the directory containing the simulation data sets

- **output_msg** – print the output messages on screen (available for cluster='local' only)

ps1 (*model, scanned_par, simulate_intervals, single_param_scan_intervals, inputdir, outputdir, cluster='local', local_cpus=1, runs=1, output_msg=False*)
Single parameter scan.

Parameters

- **model** – the model to process
- **scanned_par** – the scanned parameter
- **simulate_intervals** – the time step of each simulation
- **single_param_scan_intervals** – the number of scans to perform
- **inputdir** – the directory containing the model
- **outputdir** – the directory to store the results
- **cluster** – local, lsf for Load Sharing Facility, sge for Sun Grid Engine.
- **local_cpus** – the number of CPU used.
- **runs** – the number of model simulation
- **output_msg** – print the output messages on screen (available for cluster='local' only)

ps1_postproc (*model, scanned_par, simulate_intervals, single_param_scan_intervals, outputdir*)

Perform post processing organisation to single parameter scan report files.

Parameters

- **model** – the model to process
- **scanned_par** – the scanned parameter
- **simulate_intervals** – the time step of each simulation
- **single_param_scan_intervals** – the number of scans to perform
- **outputdir** – the directory to store the results

ps2 (*model, sim_length, inputdir, outputdir, cluster='local', local_cpus=1, runs=1, output_msg=False*)
Double parameter scan.

Parameters

- **model** – the model to process
- **sim_length** – the length of the simulation
- **inputdir** – the directory containing the model
- **outputdir** – the directory to store the results
- **cluster** – local, lsf for Load Sharing Facility, sge for Sun Grid Engine.
- **local_cpus** – the number of CPU.
- **runs** – the number of model simulation
- **output_msg** – print the output messages on screen (available for cluster='local' only)

ps2_postproc (*model, sim_length, outputdir*)

Perform post processing organisation to double parameter scan report files.

Parameters

- **model** – the model to process

- **sim_length** – the length of the simulation
- **outputdir** – the directory to store the results

replace_str_in_report (*report*)

Replaces strings in a report file.

Parameters **report** – a report file with its absolute path

sim (*model, inputdir, outputdir, cluster='local', local_cpus=1, runs=1, output_msg=False*)

Time course simulator.

Parameters

- **model** – the model to process
- **inputdir** – the directory containing the model
- **outputdir** – the directory containing the output files
- **cluster** – local, lsf for Load Sharing Facility, sge for Sun Grid Engine.
- **local_cpus** – the number of CPU.
- **runs** – the number of model simulation
- **output_msg** – print the output messages on screen (available for cluster='local' only)

Module contents

sbpipe.tasks package

Submodules

sbpipe.tasks.generate_data module

`sbpipe.tasks.generate_data.generate_data` (*infile, copasi=False*)

Replicate a copasi model and adds an id.

Parameters

- **infile** – the input file
- **copasi** – True if the model is a Copasi model

`sbpipe.tasks.generate_data.main` (*argv=None*)

`sbpipe.tasks.generate_data.run_copasi_model` (*infile*)

Run a Copasi model

Parameters **infile** – the input file

`sbpipe.tasks.generate_data.run_generic_model` (*infile*)

Run a generic model

Parameters **infile** – the input file

sbpipe.tasks.pe_analyse_data module

`sbpipe.tasks.pe_analyse_data.main` (*argv=None*)

```
sbpipe.tasks.pe_analyse_data.pe_analyse_data(model,          outputdir,          file-  
                                              out_final_estims,  fileout_all_estims,  
                                              fileout_param_estim_details, file-  
                                              out_param_estim_summary, plots_dir,  
                                              best_fits_percent,  data_point_num,  
                                              plot_2d_66cl_corr=False,  
                                              plot_2d_95cl_corr=False,  
                                              plot_2d_99cl_corr=False,  
                                              logspace=True,          scien-  
                                              tific_notation=True)
```

Plot parameter estimation results (Python wrapper).

param model the model name

param outputdir the directory to store the results

param fileout_final_estims the name of the file containing final parameter sets with the objective value

param fileout_all_estims the name of the file containing all the parameter sets with the objective value

param fileout_param_estim_details the name of the file containing the detailed statistics for the estimated parameters

param fileout_param_estim_summary the name of the file containing the summary for the parameter estimation

param plots_dir the directory of the simulation plots

param best_fits_percent the percent to consider for the best fits

param data_point_num the number of data points

param plot_2d_66cl_corr True if 2 dim plots for the parameter sets within 66% should be plotted

param plot_2d_95cl_corr True if 2 dim plots for the parameter sets within 95% should be plotted

param plot_2d_99cl_corr True if 2 dim plots for the parameter sets within 99% should be plotted

param logspace True if parameters should be plotted in log space

param scientific_notation True if axis labels should be plotted in scientific notation

return True if the task was completed successfully, False otherwise.

sbpipe.tasks.pe_analyse_data_all_fits module

```
sbpipe.tasks.pe_analyse_data_all_fits.main(argv=None)
```

```

sbpipe.tasks.pe_analyse_data_all_fits.pe_analyse_data_all_fits(model, out-
                                                                putdir, file-
                                                                out_all_estims,
                                                                file-
                                                                out_param_estim_details,
                                                                file-
                                                                out_param_estim_summary,
                                                                plots_dir,
                                                                data_point_num,
                                                                plot_2d_66cl_corr=False,
                                                                plot_2d_95cl_corr=False,
                                                                plot_2d_99cl_corr=False,
                                                                logspace=True,
                                                                scien-
                                                                tific_notation=True)

```

Plot parameter estimation results (Python wrapper).

param model the model name

param outputdir the directory to store the results

param fileout_all_estims the name of the file containing all the parameter sets with the objective value

param fileout_param_estim_details the name of the file containing the detailed statistics for the estimated parameters

param fileout_param_estim_summary the name of the file containing the summary for the parameter estimation

param plots_dir the directory of the simulation plots

param data_point_num the number of data points

param plot_2d_66cl_corr True if 2 dim plots for the parameter sets within 66% should be plotted

param plot_2d_95cl_corr True if 2 dim plots for the parameter sets within 95% should be plotted

param plot_2d_99cl_corr True if 2 dim plots for the parameter sets within 99% should be plotted

param logspace True if parameters should be plotted in log space

param scientific_notation True if axis labels should be plotted in scientific notation

return True if the task was completed successfully, False otherwise.

sbpipe.tasks.pe_analyse_data_best_fits module

```

sbpipe.tasks.pe_analyse_data_best_fits.main(argv=None)
sbpipe.tasks.pe_analyse_data_best_fits.pe_analyse_data_best_fits(model,
                                                                output-
                                                                dir, file-
                                                                out_final_estims,
                                                                plots_dir,
                                                                best_fits_percent,
                                                                logspace=True,
                                                                scien-
                                                                tific_notation=True)

```

Plot parameter estimation results (Python wrapper).

param model the model name

param outputdir the directory to store the results

param fileout_final_estims the name of the file containing final parameter sets with the objective value

param plots_dir the directory of the simulation plots

param best_fits_percent the percent to consider for the best fits

param logspace True if parameters should be plotted in log space

param scientific_notation True if axis labels should be plotted in scientific notation

return True if the task was completed successfully, False otherwise.

sbpipe.tasks.pe_collect module

`sbpipe.tasks.pe_collect.main` (*argv=None*)

`sbpipe.tasks.pe_collect.pe_collect` (*inputdir, outputdir, fileout_final_estims, fileout_all_estims, copasi=True*)

Collect the results so that they can be processed. :param inputdir: the input folder containing the data :param outputdir: the output folder to stored the collected results :param fileout_final_estims: the name of the file containing the best estimations :param fileout_all_estims: the name of the file containing all the estimations :param copasi: True if COPASI was used to generate the data.

sbpipe.tasks.pe_postproc module

`sbpipe.tasks.pe_postproc.generic_postproc` (*infile, outfile, copasi=True*)

Perform post processing file editing for the *pe* pipeline

Parameters

- **infile** – the model to process
- **outfile** – the directory to store the results
- **copasi** – True if the model is a Copasi model

`sbpipe.tasks.pe_postproc.main` (*argv=None*)

`sbpipe.tasks.pe_postproc.pe_postproc` (*infile, outfile, copasi=True*)

Perform post processing file editing for the *pe* pipeline

Parameters

- **infile** – the model to process
- **outfile** – the directory to store the results
- **copasi** – True if the model is a Copasi model

sbpipe.tasks.preproc module

`sbpipe.tasks.preproc.copasi_preproc` (*infile, outfile*)

Replicate a copasi model and adds an id.

Parameters

- **infile** – the input file
- **outfile** – the output file

`sbpipe.tasks.preproc.generic_preproc` (*infile, outfile*)

Copy the model file

Parameters

- **infile** – the input file
- **outfile** – the output file

`sbpipe.tasks.preproc.main (argv=None)`

`sbpipe.tasks.preproc.preproc (infile, outfile, copasi=False)`

Replicate a copasi model and adds an id.

Parameters

- **infile** – the input file
- **outfile** – the output file
- **copasi** – True if the model is a Copasi model

sbpipe.tasks.ps1_analyse_data module

`sbpipe.tasks.ps1_analyse_data.main (argv=None)`

`sbpipe.tasks.ps1_analyse_data.ps1_analyse_data (model_name, inhibition_only, outputdir, sim_data_folder, sim_plots_folder, repeat, percent_levels, min_level, max_level, levels_number, homogeneous_lines, xaxis_label, yaxis_label)`

Plot model single parameter scan time courses (Python wrapper).

Parameters

- **model_name** – the model name without extension
- **inhibition_only** – true if the scanning only decreases the variable amount (inhibition only)
- **outputdir** – the output directory
- **sim_data_folder** – the name of the folder containing the simulated data
- **sim_plots_folder** – the name of the folder containing the simulated plots
- **repeat** – the simulation number
- **percent_levels** – true if scanning levels are in percent
- **min_level** – the minimum level
- **max_level** – the maximum level
- **levels_number** – the number of levels
- **homogeneous_lines** – true if lines should be plotted homogeneously
- **xaxis_label** – the label for the x axis (e.g. Time [min])
- **yaxis_label** – the label for the y axis (e.g. Level [a.u.])

sbpipe.tasks.ps1_postproc module

`sbpipe.tasks.ps1_postproc.generic_postproc (infile, outfile, scanned_par, simulate_intervals, single_param_scan_intervals, copasi=True)`

Perform post processing organisation to single parameter scan report files.

Parameters

- **infile** – the model to process
- **outfile** – the directory to store the results
- **scanned_par** – the scanned parameter
- **simulate_intervals** – the time step of each simulation
- **single_param_scan_intervals** – the number of scans to perform
- **copasi** – True if the model is a Copasi model

`sbpipe.tasks.ps1_postproc.main (argv=None)`

`sbpipe.tasks.ps1_postproc.ps1_header_init (report, scanned_par)`
Header report initialisation for single parameter scan pipeline.

Parameters

- **report** – a report
- **scanned_par** – the scanned parameter

:return a list containing the header or an empty list if no header was created.

`sbpipe.tasks.ps1_postproc.ps1_postproc (infile, outfile, scanned_par, simulate_intervals, single_param_scan_intervals, copasi=True)`

Perform post processing organisation to single parameter scan report files.

Parameters

- **infile** – the model to process
- **outfile** – the directory to store the results
- **scanned_par** – the scanned parameter
- **simulate_intervals** – the time step of each simulation
- **single_param_scan_intervals** – the number of scans to perform
- **copasi** – True if the model is a Copasi model

sbpipe.tasks.ps2_analyse_data module

`sbpipe.tasks.ps2_analyse_data.main (argv=None)`

`sbpipe.tasks.ps2_analyse_data.ps2_analyse_data (model, scanned_par1, scanned_par2, inputdir, outputdir, id)`

Plot model double parameter scan time courses (Python wrapper).

Parameters

- **model** – the model name without extension
- **scanned_par1** – the 1st scanned parameter
- **scanned_par2** – the 2nd scanned parameter
- **inputdir** – the input directory
- **outputdir** – the output directory
- **run** – the simulation number

sbpipe.tasks.ps2_postproc module

`sbpipe.tasks.ps2_postproc.generic_postproc (infile, outfile, sim_length, copasi=True)`
 Perform post processing organisation to double parameter scan report files.

Parameters

- **infile** – the model to process
- **outfile** – the directory to store the results
- **sim_length** – the length of the simulation
- **copasi** – True if the model is a Copasi model

`sbpipe.tasks.ps2_postproc.main (argv=None)`

`sbpipe.tasks.ps2_postproc.ps2_postproc (infile, outfile, sim_length, copasi=True)`
 Perform post processing organisation to double parameter scan report files.

Parameters

- **infile** – the model to process
- **outfile** – the directory to store the results
- **sim_length** – the length of the simulation
- **copasi** – True if the model is a Copasi model

sbpipe.tasks.sim_analyse_data module

`sbpipe.tasks.sim_analyse_data.main (argv=None)`

`sbpipe.tasks.sim_analyse_data.sim_analyse_data (model, inputdir, outputdir, sim_plots_dir, exp_dataset, plot_exp_dataset, xaxis_label='', yaxis_label='')`

Plot model simulation time courses (Python wrapper).

Parameters

- **model** – the model name
- **inputdir** – the directory containing the data to analyse
- **outputdir** – the output directory containing the results
- **sim_plots_dir** – the directory to save the plots
- **exp_dataset** – the full path of the experimental data set
- **plot_exp_dataset** – True if the experimental data set should also be plotted
- **xaxis_label** – the label for the x axis (e.g. Time [min])
- **yaxis_label** – the label for the y axis (e.g. Level [a.u.])

sbpipe.tasks.sim_postproc module

`sbpipe.tasks.sim_postproc.generic_postproc (infile, outfile, copasi=True)`
 Perform post processing file editing for the *simulate* pipeline

Parameters

- **infile** – the model to process
- **outfile** – the directory to store the results

- **copasi** – True if the model is a Copasi model

`sbpipe.tasks.sim_postproc.main (argv=None)`

`sbpipe.tasks.sim_postproc.sim_postproc (infile, outfile, copasi=True)`

Perform post processing file editing for the *simulate* pipeline

Parameters

- **infile** – the model to process
- **outfile** – the directory to store the results
- **copasi** – True if the model is a Copasi model

sbpipe.tasks.utils module

Module contents

sbpipe.utils package

Submodules

sbpipe.utils.io module

`sbpipe.utils.io.files_with_pattern_recur (folder, pattern)`

Return all files with a certain pattern in folder+subdirectories

Parameters

- **folder** – the folder to search for
- **pattern** – the string to search for

Returns the files containing the pattern.

`sbpipe.utils.io.get_pattern_pos (pattern, filename)`

Return the line number (as string) of the first occurrence of a pattern in filename

Parameters

- **pattern** – the pattern of the string to find
- **filename** – the file name containing the pattern to search

Returns the line number containing the pattern or “-1” if the pattern was not found

`sbpipe.utils.io.refresh (path, file_pattern)`

Clean and create the folder if this does not exist.

Parameters

- **path** – the path containing the files to remove
- **file_pattern** – the string pattern of the files to remove

`sbpipe.utils.io.remove_file_silently (filename)`

Remove a filename silently, without reporting warnings or error messages. This is not really needed by Linux, but Windows sometimes fails to remove the file even if this exists.

Parameters **filename** – the file to remove

`sbpipe.utils.io.replace_str_in_file (filename_out, old_string, new_string)`

Replace a string with another in filename_out

Parameters

- **filename_out** – the output file

- **old_string** – the old string that should be replaced
- **new_string** – the new string replacing old_string

`sbpipe.utils.io.replace_str_in_report (report)`

Replace nasty strings in COPASI report file.

Parameters **report** – the report

`sbpipe.utils.io.write_mat_on_file (path, filename_out, data)`

Write the matrix results stored in data to filename_out

Parameters

- **path** – the path to filename_out
- **filename_out** – the output file
- **data** – the data to store in a file

sbpipe.utils.parcomp module

`sbpipe.utils.parcomp.call_proc (params)`

Run a command using Python subprocess.

Parameters **params** – A tuple containing (the string of the command to run, the command id)

`sbpipe.utils.parcomp.is_output_file_clean (filename, stream_type='standard output')`

Check whether a file contains the string 'error' or 'warning'. If so a message is printed.

Parameters

- **filename** – a file
- **stream_type** – 'stderr' for standard error, 'stdout' for standard output.

Returns True

`sbpipe.utils.parcomp.parcomp (cmd, cmd_iter_substr, output_dir, cluster='local', runs=1, local_cpus=1, output_msg=False)`

Generic function to run a command in parallel

Parameters

- **cmd** – the command string to run in parallel
- **cmd_iter_substr** – the substring of the iteration number. This will be replaced in a number automatically
- **output_dir** – the output directory
- **cluster** – the cluster type among local (Python multiprocessing), sge, or lsf
- **runs** – the number of runs
- **local_cpus** – the number of cpus to use at most
- **output_msg** – print the output messages on screen (available for cluster='local' only)

Returns True if the computation succeeded.

`sbpipe.utils.parcomp.quick_debug (cmd, out_dir, err_dir)`

Look up for *error* and *warning* in the standard output and error files. A simple debugging function checking the generated log files. We don't stop the computation because it happens that these messages are more *warnings* than real errors.

Parameters

- **cmd** – the executed command
- **out_dir** – the directory containing the standard output files

- **err_dir** – the directory containing the standard error files

Returns True

`sbpipe.utils.parcomp.run_cmd(cmd)`

Run a command using Python subprocess.

Parameters **cmd** – The string of the command to run

`sbpipe.utils.parcomp.run_cmd_block(cmd)`

Run a command using Python subprocess. Block the call until the command has finished.

Parameters **cmd** – A tuple containing the string of the command to run

`sbpipe.utils.parcomp.run_jobs_local(cmd, cmd_iter_substr, runs=1, local_cpus=1, output_msg=False)`

Run jobs using python multiprocessing locally.

Parameters

- **cmd** – the full command to run as a job
- **cmd_iter_substr** – the substring in command to be replaced with a number
- **runs** – the number of runs to execute
- **local_cpus** – The number of available cpus. If local_cpus <=0, only one core will be used.
- **output_msg** – print the output messages on screen (available for cluster_type='local' only)

Returns True

`sbpipe.utils.parcomp.run_jobs_lsf(cmd, cmd_iter_substr, out_dir, err_dir, runs=1)`

Run jobs using a Load Sharing Facility (LSF) cluster.

Parameters

- **cmd** – the full command to run as a job
- **cmd_iter_substr** – the substring in command to be replaced with a number
- **out_dir** – the directory containing the standard output from bsub
- **err_dir** – the directory containing the standard error from bsub
- **runs** – the number of runs to execute

Returns True if the computation succeeded.

`sbpipe.utils.parcomp.run_jobs_sge(cmd, cmd_iter_substr, out_dir, err_dir, runs=1)`

Run jobs using a Sun Grid Engine (SGE) cluster.

Parameters

- **cmd** – the full command to run as a job
- **cmd_iter_substr** – the substring in command to be replaced with a number
- **out_dir** – the directory containing the standard output from qsub
- **err_dir** – the directory containing the standard error from qsub
- **runs** – the number of runs to execute

Returns True if the computation succeeded.

sbpipe.utils.rand module

`sbpipe.utils.rand.get_rand_alphanum_str (length)`

Return a random alphanumeric string

Parameters `length` – the length of the string

Returns the generated string

`sbpipe.utils.rand.get_rand_num_str (length)`

Return a random numeric string

Parameters `length` – the length of the string

Returns the generated string

sbpipe.utils.re_utils module

`sbpipe.utils.re_utils.escape_special_chars (text)`

Escape ^,%, .[,.(, {, } from text :param text: the command to escape special characters inside :return: the command with escaped special characters

`sbpipe.utils.re_utils.nat_sort_key (str)`

The key to sort a list of strings alphanumerically (e.g. “file10” is correctly placed after “file2”)

Parameters `str` – the string to sort alphanumerically in a list of strings

Returns the key to sort strings alphanumerically

Module contents

Submodules

sbpipe.__main__ module

`sbpipe.__main__.main (argv=None)`

sbpipe.main module

`sbpipe.main.main (argv=None)`

SBpipe main function.

Returns 0 if OK, 1 if trouble

`sbpipe.main.read_file_header (filename)`

Read the first line of a file

Parameters `filename` – the file name to read

Returns the first line

`sbpipe.main.sbpipes (create_project='', simulate='', parameter_scan1='', parameter_scan2='',
parameter_estimation='', logo=False, license=False, nocolor=False,
log_level='', quiet=False, verbose=False)`

SBpipe function.

Parameters

- **create_project** – create a project with the name as argument
- **simulate** – model simulation using a configuration file as argument
- **parameter_scan1** – model one parameter scan using a configuration file as argument

- **parameter_scan2** – model two parameters scan using a configuration file as argument
- **parameter_estimation** – model parameter estimation using a configuration file as argument
- **logo** – True to print the logo
- **license** – True to print the license
- **nocolor** – True to print logging messages without colors
- **log_level** – Set the logging level
- **quiet** – True if quiet (CRITICAL+)
- **verbose** – True if verbose (DEBUG+)

Returns 0 if OK, 1 if trouble (e.g. a pipeline did not execute correctly).

`sbpipe.main.sbpipeline_logo()`
Return sbpipe logo.

Returns sbpipe logo

`sbpipe.main.set_basic_logger(level='INFO')`
Set a basic StreamHandler logger. :param level: the level for this console logger

`sbpipe.main.set_color_logger(level='INFO')`
Replace the current logging.StreamHandler with colorlog.StreamHandler. :param level: the level for this console logger

`sbpipe.main.set_console_logger(new_level='NOTSET', current_level='INFO', no-color=False)`
Set the console logger to a new level if this is different from NOTSET

Parameters

- **new_level** – the new level to set for the console logger
- **current_level** – the current level to set for the console logger
- **nocolor** – True if no colors should be used

`sbpipe.main.set_logger(level='NOTSET', nocolor=False)`
Set the logger :param level: the level for the console logger :param nocolor: True if no colors should be used

sbpipe.sbpipeline_config module

`sbpipe.sbpipeline_config.isPyPackageInstalled(package)`
Utility checking whether a Python package is installed.

Parameters `package` – a Python package name

Returns True if it is installed, false otherwise.

`sbpipe.sbpipeline_config.which(cmd_name)`
Utility equivalent to *which* in GNU/Linux OS.

Parameters `cmd_name` – a command name

Returns return the command name with absolute path if this exists, or None

Module contents

INDICES

- `genindex`
- `modindex`
- `search`

PYTHON MODULE INDEX

S

- sbpipe, 24
- sbpipe.__main__, 23
- sbpipe.main, 23
- sbpipe.pl, 8
 - sbpipe.pl.create, 2
 - sbpipe.pl.create.newproj, 1
 - sbpipe.pl.pe, 3
 - sbpipe.pl.pe.parest, 2
 - sbpipe.pl.pipeline, 7
 - sbpipe.pl.ps1, 5
 - sbpipe.pl.ps1.parscan1, 3
 - sbpipe.pl.ps2, 6
 - sbpipe.pl.ps2.parscan2, 5
 - sbpipe.pl.sim, 7
 - sbpipe.pl.sim.sim, 6
- sbpipe.R, 1
 - sbpipe.R.misc, 1
- sbpipe.report, 10
 - sbpipe.report.latex_reports, 8
- sbpipe.sbpipe_config, 24
- sbpipe.simul, 13
 - sbpipe.simul.copasi, 10
 - sbpipe.simul.copasi.copasi, 10
 - sbpipe.simul.pl_simul, 10
 - sbpipe.simul.python, 10
 - sbpipe.simul.python.python, 10
 - sbpipe.simul.simul, 11
- sbpipe.tasks, 20
 - sbpipe.tasks.generate_data, 13
 - sbpipe.tasks.pe_analyse_data, 13
 - sbpipe.tasks.pe_analyse_data_all_fits, 14
 - sbpipe.tasks.pe_analyse_data_best_fits, 15
 - sbpipe.tasks.pe_collect, 16
 - sbpipe.tasks.pe_postproc, 16
 - sbpipe.tasks.preproc, 16
 - sbpipe.tasks.ps1_analyse_data, 17
 - sbpipe.tasks.ps1_postproc, 17
 - sbpipe.tasks.ps2_analyse_data, 18
 - sbpipe.tasks.ps2_postproc, 19
 - sbpipe.tasks.sim_analyse_data, 19
 - sbpipe.tasks.sim_postproc, 19
 - sbpipe.tasks.utils, 20
- sbpipe.utils, 23
 - sbpipe.utils.io, 20
 - sbpipe.utils.parcomp, 21
 - sbpipe.utils.rand, 23
 - sbpipe.utils.re_utils, 23

A

analyse_data() (sbpipe.pl.pe.parest.ParEst class method), 2
 analyse_data() (sbpipe.pl.ps1.parscan1.ParScan1 class method), 3
 analyse_data() (sbpipe.pl.ps2.parscan2.ParScan2 class method), 5
 analyse_data() (sbpipe.pl.sim.sim.Sim class method), 6

C

call_proc() (in module sbpipe.utils.parcomp), 21
 Copasi (class in sbpipe.simul.copasi.copasi), 10
 copasi_preproc() (in module sbpipe.tasks.preproc), 16

E

escape_special_chars() (in module sbpipe.utils.re_utils), 23

F

files_with_pattern_recur() (in module sbpipe.utils.io), 20

G

generate_data() (in module sbpipe.tasks.generate_data), 13
 generate_data() (sbpipe.pl.pe.parest.ParEst class method), 3
 generate_data() (sbpipe.pl.ps1.parscan1.ParScan1 class method), 4
 generate_data() (sbpipe.pl.ps2.parscan2.ParScan2 class method), 5
 generate_data() (sbpipe.pl.sim.sim.Sim class method), 6
 generate_report() (sbpipe.pl.pe.parest.ParEst class method), 3
 generate_report() (sbpipe.pl.ps1.parscan1.ParScan1 class method), 4
 generate_report() (sbpipe.pl.ps2.parscan2.ParScan2 class method), 5
 generate_report() (sbpipe.pl.sim.sim.Sim class method), 7
 generic_postproc() (in module sbpipe.tasks.pe_postproc), 16
 generic_postproc() (in module sbpipe.tasks.ps1_postproc), 17

generic_postproc() (in module sbpipe.tasks.ps2_postproc), 19
 generic_postproc() (in module sbpipe.tasks.sim_postproc), 19
 generic_preproc() (in module sbpipe.tasks.preproc), 16
 get_all_fits() (sbpipe.simul.simul.Simul method), 11
 get_best_fits() (sbpipe.simul.simul.Simul method), 11
 get_lang() (sbpipe.simul.pl_simul.PLSimul method), 10
 get_lang_err_msg() (sbpipe.simul.pl_simul.PLSimul method), 10
 get_lang_options() (sbpipe.simul.pl_simul.PLSimul method), 10
 get_latex_header() (in module sbpipe.report.latex_reports), 8
 get_models_folder() (sbpipe.pl.pipeline.Pipeline method), 7
 get_pattern_pos() (in module sbpipe.utils.io), 20
 get_rand_alphanum_str() (in module sbpipe.utils.rand), 23
 get_rand_num_str() (in module sbpipe.utils.rand), 23
 get_sim_data_folder() (sbpipe.pl.pipeline.Pipeline method), 7
 get_sim_plots_folder() (sbpipe.pl.pipeline.Pipeline method), 7
 get_simul_obj() (sbpipe.pl.pipeline.Pipeline class method), 7
 get_working_folder() (sbpipe.pl.pipeline.Pipeline method), 7

I

is_output_file_clean() (in module sbpipe.utils.parcomp), 21
 isPyPackageInstalled() (in module sbpipe.sbpipe_config), 24

L

latex_report() (in module sbpipe.report.latex_reports), 8
 latex_report_pe() (in module sbpipe.report.latex_reports), 8
 latex_report_ps1() (in module sbpipe.report.latex_reports), 9
 latex_report_ps2() (in module sbpipe.report.latex_reports), 9
 latex_report_sim() (in module sbpipe.report.latex_reports), 9

load() (sbpipe.pl.pipeline.Pipeline class method), 8

M

main() (in module sbpipe.__main__), 23

main() (in module sbpipe.main), 23

main() (in module sbpipe.tasks.generate_data), 13

main() (in module sbpipe.tasks.pe_analyse_data), 13

main() (in module sbpipe.tasks.pe_analyse_data_all_fits),
14

main() (in module sbpipe.tasks.pe_analyse_data_best_fits),
15

main() (in module sbpipe.tasks.pe_collect), 16

main() (in module sbpipe.tasks.pe_postproc), 16

main() (in module sbpipe.tasks.preproc), 17

main() (in module sbpipe.tasks.ps1_analyse_data), 17

main() (in module sbpipe.tasks.ps1_postproc), 18

main() (in module sbpipe.tasks.ps2_analyse_data), 18

main() (in module sbpipe.tasks.ps2_postproc), 19

main() (in module sbpipe.tasks.sim_analyse_data), 19

main() (in module sbpipe.tasks.sim_postproc), 20

N

nat_sort_key() (in module sbpipe.utils.re_utils), 23

NewProj (class in sbpipe.pl.create.newproj), 1

P

parcomp() (in module sbpipe.utils.parcomp), 21

ParEst (class in sbpipe.pl.pe.parest), 2

ParScan1 (class in sbpipe.pl.ps1.parscan1), 3

ParScan2 (class in sbpipe.pl.ps2.parscan2), 5

parse() (sbpipe.pl.pe.parest.ParEst method), 3

parse() (sbpipe.pl.pipeline.Pipeline method), 8

parse() (sbpipe.pl.ps1.parscan1.ParScan1 method), 4

parse() (sbpipe.pl.ps2.parscan2.ParScan2 method), 6

parse() (sbpipe.pl.sim.sim.Sim method), 7

pdf_report() (in module sbpipe.report.latex_reports), 9

pe() (sbpipe.simul.copasi.copasi.Copasi method), 10

pe() (sbpipe.simul.pl_simul.PLSimul method), 11

pe() (sbpipe.simul.simul.Simul method), 11

pe_analyse_data() (in module
sbpipe.tasks.pe_analyse_data), 13

pe_analyse_data_all_fits() (in module
sbpipe.tasks.pe_analyse_data_all_fits),
14

pe_analyse_data_best_fits() (in module
sbpipe.tasks.pe_analyse_data_best_fits),
15

pe_collect() (in module sbpipe.tasks.pe_collect), 16

pe_postproc() (in module sbpipe.tasks.pe_postproc), 16

Pipeline (class in sbpipe.pl.pipeline), 7

PLSimul (class in sbpipe.simul.pl_simul), 10

preproc() (in module sbpipe.tasks.preproc), 17

ps1() (sbpipe.simul.copasi.copasi.Copasi method), 10

ps1() (sbpipe.simul.pl_simul.PLSimul method), 11

ps1() (sbpipe.simul.simul.Simul method), 12

ps1_analyse_data() (in module
sbpipe.tasks.ps1_analyse_data), 17

ps1_header_init() (in module
sbpipe.tasks.ps1_postproc), 18

ps1_postproc() (in module sbpipe.tasks.ps1_postproc),
18

ps1_postproc() (sbpipe.simul.simul.Simul method), 12

ps2() (sbpipe.simul.copasi.copasi.Copasi method), 10

ps2() (sbpipe.simul.pl_simul.PLSimul method), 11

ps2() (sbpipe.simul.simul.Simul method), 12

ps2_analyse_data() (in module
sbpipe.tasks.ps2_analyse_data), 18

ps2_postproc() (in module sbpipe.tasks.ps2_postproc),
19

ps2_postproc() (sbpipe.simul.simul.Simul method), 12

Python (class in sbpipe.simul.python.python), 10

Q

quick_debug() (in module sbpipe.utils.parcomp), 21

R

read_file_header() (in module sbpipe.main), 23

refresh() (in module sbpipe.utils.io), 20

remove_file_silently() (in module sbpipe.utils.io), 20

replace_str_in_file() (in module sbpipe.utils.io), 20

replace_str_in_report() (in module sbpipe.utils.io), 21

replace_str_in_report()
(sbpipe.simul.pl_simul.PLSimul method), 11

replace_str_in_report() (sbpipe.simul.simul.Simul
method), 13

run() (sbpipe.pl.create.newproj.NewProj method), 1

run() (sbpipe.pl.pe.parest.ParEst method), 3

run() (sbpipe.pl.pipeline.Pipeline method), 8

run() (sbpipe.pl.ps1.parscan1.ParScan1 method), 4

run() (sbpipe.pl.ps2.parscan2.ParScan2 method), 6

run() (sbpipe.pl.sim.sim.Sim method), 7

run_cmd() (in module sbpipe.utils.parcomp), 22

run_cmd_block() (in module sbpipe.utils.parcomp), 22

run_copasi_model() (in module
sbpipe.tasks.generate_data), 13

run_generic_model() (in module
sbpipe.tasks.generate_data), 13

run_jobs_local() (in module sbpipe.utils.parcomp), 22

run_jobs_lsf() (in module sbpipe.utils.parcomp), 22

run_jobs_sge() (in module sbpipe.utils.parcomp), 22

S

sbpipe (module), 24

sbpipe() (in module sbpipe.main), 23

sbpipe.__main__ (module), 23

sbpipe.main (module), 23

sbpipe.pl (module), 8

sbpipe.pl.create (module), 2

sbpipe.pl.create.newproj (module), 1

sbpipe.pl.pe (module), 3

sbpipe.pl.pe.parest (module), 2

sbpipe.pl.pipeline (module), 7

sbpipe.pl.ps1 (module), 5

sbpipe.pl.ps1.parscan1 (module), 3

sbpipe.pl.ps2 (module), 6

sbpipe.pl.ps2.parscan2 (module), 5
 sbpipe.pl.sim (module), 7
 sbpipe.pl.sim.sim (module), 6
 sbpipe.R (module), 1
 sbpipe.R.misc (module), 1
 sbpipe.report (module), 10
 sbpipe.report.latex_reports (module), 8
 sbpipe.sbpipes_config (module), 24
 sbpipe.simul (module), 13
 sbpipe.simul.copasi (module), 10
 sbpipe.simul.copasi.copasi (module), 10
 sbpipe.simul.pl_simul (module), 10
 sbpipe.simul.python (module), 10
 sbpipe.simul.python.python (module), 10
 sbpipe.simul.simul (module), 11
 sbpipe.tasks (module), 20
 sbpipe.tasks.generate_data (module), 13
 sbpipe.tasks.pe_analyse_data (module), 13
 sbpipe.tasks.pe_analyse_data_all_fits (module), 14
 sbpipe.tasks.pe_analyse_data_best_fits (module), 15
 sbpipe.tasks.pe_collect (module), 16
 sbpipe.tasks.pe_postproc (module), 16
 sbpipe.tasks.preproc (module), 16
 sbpipe.tasks.ps1_analyse_data (module), 17
 sbpipe.tasks.ps1_postproc (module), 17
 sbpipe.tasks.ps2_analyse_data (module), 18
 sbpipe.tasks.ps2_postproc (module), 19
 sbpipe.tasks.sim_analyse_data (module), 19
 sbpipe.tasks.sim_postproc (module), 19
 sbpipe.tasks.utils (module), 20
 sbpipe.utils (module), 23
 sbpipe.utils.io (module), 20
 sbpipe.utils.parcomp (module), 21
 sbpipe.utils.rand (module), 23
 sbpipe.utils.re_utils (module), 23
 sbpipe_logo() (in module sbpipe.main), 24
 set_basic_logger() (in module sbpipe.main), 24
 set_color_logger() (in module sbpipe.main), 24
 set_console_logger() (in module sbpipe.main), 24
 set_logger() (in module sbpipe.main), 24
 Sim (class in sbpipe.pl.sim.sim), 6
 sim() (sbpipe.simul.copasi.copasi.Copasi method), 10
 sim() (sbpipe.simul.pl_simul.PLSimul method), 11
 sim() (sbpipe.simul.simul.Simul method), 13
 sim_analyse_data() (in module
 sbpipe.tasks.sim_analyse_data), 19
 sim_postproc() (in module sbpipe.tasks.sim_postproc),
 20
 Simul (class in sbpipe.simul.simul), 11

W

which() (in module sbpipe.sbpipes_config), 24
 write_mat_on_file() (in module sbpipe.utils.io), 21