











Current Rating
1.5A/contact terminal
Voltage Rating
30V DC

Cnnector Mate and Unmate Force Mate force:3.75kgf(MAX) Unmate force:1.02kgf(MIN)

NO.1	
PART NO	NOTE
U-A-24D1-W-7	black
U-A-24D2-W-7	White

3	Base			1	NY66	White/black		
2	Terminal			8	Phosphor Bronze	Ag Plated		
1	Housing			1	SPCC/Phosphor Bronze	Ni Plated		
ITEM	PART NAME		TER'NO.	QTY.	MATERIAL	FINISHING		
APPROVALS DATE			Ξ	777.20\$\fix*\				
DRAWN JIANKUN.LU 2018.08.01		ELECTRONICS CO.,LTD						

											/	
					CHECKED				TITLE:	LE: USB CONNECTOR		
					APPROVALS				PART NO.			
А		NEW			 TOLERANCES AR	F 10~30			UNIT: mm	SCALE: 1:1	PROJ:	
REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.		5~10 ~ 5	±0.20 ±0.15	±2°	DRAWING NO.		SHEET 1 OF 1	
	A REV.	A ————————————————————————————————————				APPROVALS A NEW TOLERANCES AR	APPROVALS APPROVALS APPROVALS TOLERANCES ARE 10×30 5×10	APPROVALS APPROVALS APPROVALS NEW	APPROVALS APPROVALS APPROVALS APPROVALS TOLERANCES ARE TO	CHECKED	APPROVALS APPROVALS APPROVALS PART NO. OUR NEW — — — TOLERANCES ARE 10~30 ±0.25 ANGLE UNIT: mm SCALE: 1:1	