Making sense of the Marvel Universe

```
> characters %>% pull(Allies) %>% head
[[1]]
[1] "Rafael_Scarfe" "Claire_Temple" "Colleen_Wing"  "Karen_Page"     "Luke_Cage"      "Jessica_Jones" "Daredevil"      "Iron_Fist"


[[2]]
[1] "Iron_Man"       "Black_Widow"    "War_Machine"    "Vision"         "Black_Panther" "Happy_Hogan"


[[3]]
 [1] "Heimdall" "Volstagg" "Fandral"  "Hogun"     "Thor"       "Valkyrie" "Loki"      "Hulk"      "Korg"      "Miek"


[[4]]
 [1] "Captain_America" "Scarlet_Witch"   "Hawkeye"         "Iron_Man"        "Black_Widow"     "Vision"          "War_Machine"
 [8] "Nick_Fury"       "Maria_Hill"      "Ant-Man"         "Winter_Soldier"  "Sharon_Carter"


[[5]]
 [1] "Nick_Fury"       "Maria_Hill"      "Victoria_Hand"   "Jasper_Sitwell"  "Phil_Coulson"    "Melinda_May"     "Leo_Fitz"
 [8] "Jemma_Simmons"   "Grant_Ward"      "John_Garrett"    "Antoine_Triplett" "Watchdog_Alpha"  "Giyera"


[[6]]
[1] "Punisher"
```

Making sense of the Marvel Universe

```
> characters %>%
+     pull(Allies) %>%
+     set_names(characters$id) %>%
+     as_tbl_graph()
# A tbl_graph: 475 nodes and 1287 edges
#
# A directed multigraph with 149 components
#
# Node Data: 475 x 1 (active)
              name
              <chr>
1 A.I.M._President
2          Abilisk
3      Abomination
4    Absorbing_Man
5       Abu_Bakaar
6     Adolf_Hitler
# ... with 469 more rows
#
# Edge Data: 1,287 x 2
   from     to
  <int>  <int>
1     4    350
2     4    298
3     4     78
# ... with 1,284 more rows
```