

Frontend Guide

Site rename & HazCom updates

Two separate pieces of work shipped in the same release. The first renames the tenant concept across every module and changes JSON your code already reads. The second adds three things to HazCom. Ship the frontend with the backend — the rename is not backward compatible.

The whole release in four lines

- Global: every `subCompanyId` is now `siteId` — all 10 modules, every request and response.
- HazCom: chemicals and SDS gained an optional `disposeLocation` string.
- HazCom: training now returns a derived `attendeesCount` alongside the `attendees` string.
- HazCom: training's single `materialsLink` became a `materials` array supporting several files.

Old tokens stop working

The tenant is read from the `SiteId` JWT claim, which used to be `SubCompanyId`. A token issued before this deploy has no `SiteId`, so the API cannot resolve the tenant. Clear stored tokens on release and force a re-login rather than waiting for the first 401.

1 The Site rename — what it is

"Sub-company" is gone. The hierarchy is Organization → Site → User, where a site is one plant, depot or location inside the organization. The word changed everywhere at once: C# code, database columns, JWT claims and the JSON on the wire. The organization level was already named correctly and did not change.

Field renames

Before	After
<code>subCompanyId</code>	<code>siteId</code>
<code>subCompId</code>	<code>siteId</code>
<code>subCompanyName</code>	<code>siteName</code>
<code>companyName</code>	<code>siteName</code>
<code>companySize</code>	<code>siteSize</code>
<code>subcompany</code> (register body)	<code>sites</code>

`organizationId` and `organizationName` are untouched. So is `AllowSites` on audit and inspection templates — that field was already called `AllowSites` and still holds the same site ids.

JWT claims

```
SiteId           // was SubCompanyId
SiteName         // was SubCompanyName
OrganizationId   // unchanged
OrganizationName // unchanged
```

The duplicate `CompanyName` claim was removed — it always carried the same value as `SiteName`. If you read it, switch to `SiteName`.

Renamed routes

```
- GET /api/auth/GetCompaniesByOrganizationId/{organizationId}
+ GET /api/auth/GetSitesByOrganizationId/{organizationId}

- GET /api/auth/GetUsersBySubCompanyId/{subCompanyId}
+ GET /api/auth/GetUsersBySiteId/{siteId}
```

Both take `?search`, `?pageNumber` and `?pageSize` and return a paged envelope. The site picker rows that feed the template `AllowSites` control are now shaped:

```
{ "id": 1, "siteName": "Plant One", "industryType": "Manufacturing",
  "siteSize": "200-500", "location": "Houston", "organizationId": 1 }
```

Registration body

```
{
  "organizationName": "Acme",
  "activatedModules": "HazCom",
  "sites": [
    { "industryType": "Manufacturing", // was "subcompany"
      "siteName": "Plant One", // was "companyName"
      "siteSize": "200-500", // was "companySize"
      "location": "Houston" }
  ]
}
```

2 The Site rename — every module it touches

This is the part that is easy to under-scope. The rename is not a HazCom change: it landed in ten controllers and roughly forty DTOs. Any screen that displayed, filtered or grouped by sub-company needs updating.

Module	What carries <code>siteId</code> now
Auth & Users	Register, invite, accept-invitation, user lists, tenant context, the two renamed routes above.
Audit	Audit runs, findings, templates, sections, items, response sets, conditional logic.
Inspection	Inspection runs, findings, attachments, and the full template tree (sections, items, response sets, logic).
Documents	Documents, categories, departments, dashboard KPI payloads.
Incidents	Incident records and their nested collections.
Hazards	Hazard records, plus the leaderboard and grouped-count dashboards.
Near miss	Near miss records and the same pair of dashboards.
BBS / Walk & Talk	Observations, walk & talk records, behaviour categories.

Module	What carries siteld now
PPE	Inventory rows, assignments and the KPI cards.
HazCom	Chemicals, SDS, training, risk assessments — plus the three changes in part B.

siteld is never something you send

As before, the tenant comes from the token. siteld appears in responses so you can display or group by it, and it is never a query or body parameter on tenant-scoped endpoints. Another tenant's record still reads as not found, never forbidden.

3 HazCom · disposeLocation on chemicals and SDS

POST /api/hazcom/chemical and POST /api/hazcom/sds accept a new optional disposeLocation string (max 250 characters): where the chemical is disposed of once spent. It round-trips on create, on update and in every read of those records.

```
POST /api/hazcom/chemical
{
  "id": 0,
  "chemi_Name": "Toluene",
  "hazardClass": "Flammable",
  "location": "Store B",
  "disposeLocation": "Yard C skip",      // new, optional
  "currentQuantity": "5L"
}
```

It is nullable, so existing records return null until someone edits them. Render a missing value as "not recorded" rather than an empty field.

4 HazCom · training attendees

attendees was always a string and still is — a comma separated list of names. What is new is that the server normalises it on write and returns a derived count on read.

On write

The backend trims each name and drops blanks, so sloppy input is cleaned rather than rejected:

```
you send : " Ann Lee ,Bob Ray,, Cara Fox "
stored   : "Ann Lee, Bob Ray, Cara Fox"
```

On read

```
{
  "attendees": "Ann Lee, Bob Ray, Cara Fox",
  "attendeesCount": 3                      // new, read-only
}
```

attendeesCount is derived on each request and is read-only — sending it is ignored. An empty or whitespace-only list counts 0. Computing it client-side is fine; the rule is the same: split on commas, trim, drop blanks.

5 HazCom · training materials (breaking)

A training session can now carry several files — a briefing video and a PDF handout, say — so the single materialsLink string was replaced by a materials array backed by its own table.

```
- "materialsLink": "https://cdn.example.com/deck.pdf"
+ "materials": [
+   { "id": 12, "fileUrl": "https://cdn.example.com/intro.mp4",
+     "fileName": "intro.mp4", "fileType": "video/mp4",
+     "createdAt": "2026-08-03T09:00:00Z" }
+ ]
```

fileUrl and fileName are required on every entry; fileType is free text ("pdf", "video/mp4", whatever your uploader reports) and may be null. createdAt is returned on reads only. Existing single links were migrated into this array, so nothing was lost.

Creating a training

Omit id (or send 0) on each material. Send an empty array or omit materials entirely for a session with no files.

```
POST /api/hazcom/training
{
  "sessionDate": "2026-08-03T09:00:00Z",
  "trainer": "Jane Trainer",
  "attendees": "Ann Lee, Bob Ray",
  "materials": [
    { "fileUrl": "https://cdn.example.com/intro.mp4",
      "fileName": "intro.mp4", "fileType": "video/mp4" },
    { "fileUrl": "https://cdn.example.com/sheet.pdf",
      "fileName": "sheet.pdf", "fileType": "application/pdf" }
  ]
}
```

Updating a training — send the whole set

PUT /api/hazcom/training/{id} treats materials as the complete list, not a patch. Whatever you send becomes the new state:

- Entry with an existing id → that material is updated in place.
- Entry with id 0 or absent → a new material is added.
- Existing material you left out → soft deleted (it stops appearing in reads).
- Empty array → every material on the training is removed from view.

Always send the full array on update

If you send only the one file the user just added, the other files are dropped. Load the current materials into your form state, mutate that array, and send all of it back. Nothing is hard deleted, so a mistake is recoverable — but only by the backend.

An id belonging to a different training, or to another tenant, is rejected with 404 and the whole update is refused —

nothing is partially applied. Reads return only the live entries for your site, oldest first; soft-deleted files never appear.

6 Migration checklist

The response envelope is unchanged — keep checking success before reading dataModel:

```
{ "isError": false, "success": true, "statusCode": 200,  
  "message": "...", "dataModel": { }, "errorDetails": null }
```

- Search the whole frontend for subCompanyId, subCompld, subCompany, companyName and companySize. There is no module this misses.
- Update the two renamed auth routes, and anything reading the removed CompanyName JWT claim.
- Change the register payload key from subcompany to sites, and its two field names.
- Clear stored tokens on release so every user gets a token carrying SiteId.
- Add disposeLocation to the chemical and SDS forms; render null as "not recorded".
- Replace the single materials-link input with a multi-file list, and always PUT the full array.
- Optionally drop client-side attendee counting — attendeesCount matches it exactly.

Backend counterpart: docs/Backend-Organization-Sites-Rename-Guide.md. Note the Demo/lead module deliberately keeps its own Company field — that is a prospect's employer, not a tenant.