


NOTE: FACES MARKED 'A' ARE VISIBLE TO CUSTOMER, CONSIDERATIONS REGARDING GATE AND EJECTOR PIN

LETTER	FINISH	DESCRIPTION			
Α	SPI D-1	DULL FINISH			
В	SPI A-3	HIGH POLISH FINISH			
С	SPI D-2	VERY DULL FINISH			



## NOTES

SEE TABLE

- IF DIMENSION IS NOT SPECIFIED, ASSUME TOLERANCE: ±0.015" 3D FILE DIMENSIONS SUPERSEDE DIMENSIONS IN THIS DOCUMENT.
- TOLERANCE FOR NOTED DIMENSIONS ARE AS FOLLOWS: X.XX = ±0.010" X.XXX=±0.005"

- TOLERANCE FOR ALL ANGLES: ±0.5 DEGREES
  TOLERANCE FOR ALL RADII: ±0.005 OR 10%, WHICHEVER IS SMALLER.
  SURFACE IS CLEAN AND FREE OF BURRS AND ROUGH EDGES.
- REFER TO SOLID MODEL FOR DRAFT ANGLE ON SURFACES UNLESS OTHERWISE NOTED.
  REFER TO SOLID MODEL FOR CORNER AND FILLET RADII UNLESS OTHERWISE NOTED.
  UNLESS OTHERWISE NOTED, ALL SURFACES TO BE MINIMUM OF SPI C3 FINISH. ALL TOOL AND
- CUTTER MARKS TO BE REMOVED. GATE, PARTING LINE, EJECTOR PIN LOCATIONS, AND OTHER FEATURES FOR TOOLING CONSIDERATIONS SHALL BE APPROVED BY ECOVENT BEFORE TOOL CONSTRUCTION.
- PARTING LINE FLASH, GATES, RUNNER, AND RISER STUBS 0.005" MAXIMUM.
- EJECTOR PIN MARKS SHALL BE FLUSH TO .003 UNDERFLUSH WITH SURFACE. VISIBLE SINK MARKS TO BE .0005" DEEP MAX ON ALL COSMETIC SURFACES.
- [♦] CALLOUTS ARE APPLIED TO TOLERANCES THAT MAY REQUIRE SPECIAL QUALITY CONTROL PROCESSES. QUALITY CONTROL INSTRUCTIONS ARE OUTSIDE THE SCOPE OF THIS DRAWING AND ARE DEFINED BY EXTERNAL DOCUMENTATION TO BE AGREED TO WITH THE MANUFACTURER.
- NO REGRIND ACCEPTABLE.
- INTERIOR OF PART TO SHOW PART NUMBER, TOOL AND CAVITY NUMBER, TOOL REVISION (ON EJECTOR PIN), AND MATERIAL SYMBOL.
- UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS AND TOLERANCES ARE APPLICABLE AT 20
- DEGREES CELCIUS (68 DEGREES FAHRENHEIT) IN ACCORDANCE WITH ANSI/ASME B89.6.2. ALL HOMOGENOUS MATERIALS AND PROCESSES IN THIS DRAWING SHALL BE COMPLIANT TO THE EU ROHS DIRECTIVE 2011/65/EC.

REV	DESCRIPTION	ECO	DATE	BY	DO NOT SCALE DRAWING.	WORK TO D	IMENSIO	١
E INITIAL TOOLING RELEASE				IF PLATING IS SPECIFIED, ALL DIMENSIONS TO BE MET AFTER PLATING				
F	REDUCE MAGNET POCKET SIZE				UNLESS OTHERWISE SPECIFIED.  1. PERMISSIBLE TOLERANCES  DIMENSIONS=±0.015  ANGLES=±0.5°			5°
G	CHANGES TO BATTERY BOARD SNAPS				2. ALL RIGHT ANGLES=90° CHAMFER ANGLES=±5° 3. DIMENSIONS GIVEN IN INCHES CONCENTRICITY=0.010 T.I.R.			
	FIX LINE IN GEOMETRY AND UPDATE TEXTURE							
J	SCREW BOSSES, MAGNET POCKET FRICTION FIT	000078	02/24/16	TF	NOTICE: CHANGES TO MATERIAL, DESIGN, CONFIGURATION OR PROCESS MAY NOT BE	DESIGN	CTQ	CLASSIFICATION CHARACTERIST
					MADE WITHOUT NOTIFICATION TO ECOVENT. ALL MATERIALS AND PROCESSES MUST BE	*	**	(CRITICAL)
MATERIAL:				COMPLIANT WITH ENVIRONMENTAL LAWS AND	•	<b>*</b> *	(MAJOR)	
L2849UV LTL COLOR COMPOUNDERS FRPA100X BROWN				REULATIONS AS REFERENCED IN XXXXX	REVIEW:	DATE:		
(BROWN ABS/PC)-UV RESISTANT OR ECOVENT APPROVED EQUIVALENT				FACEPLATE 12X6 FLOOR	X6 FLOOR A2		œ e	
				PART NO. 602-00103	SHEET 1 OF 2			
FINISH DESCRIPTION			002-00103	леп				

SCALE: 1:2 THIS DOCUMENT IS THE PROPERTY OF ECOVENT. NEITHER THIS DOCUMENT NOR ANY INFORMATION CONTAINED HERIN MAY BE USED, REPRODUCED OR DISCLOSED TO THIRD PARTIES WITHOUT ECOVENT WRITTEN CONSENT.

